

Hunter Fan Company

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Ceiling Fan Remote Model: K6019-01, K6266-02

REPORT NUMBER

104058883MPK-002

ISSUE DATE

February 5, 2024

REVISED DATE

N/A

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK

© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)****Report Number:** 104058883MPK-002**Project Number:** G104058883**Report Issue Date:** February 5, 2024**Product Designation:** Ceiling Fan Remote**Model Tested:** K6019-01, K6266-02**FCC ID: IN2TX45****IC: 3558A-TX45****to****47CFR 2.1091****RSS-102 Issue 5****for****Hunter Fan Company****Tested by:**

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Hunter Fan Company
545 E. Algonquin Road
Arlington Heights, Illinois 60005 USA

Report prepared by:

Aaron Chang / EMC Team Lead

Report reviewed by:

Minh Ly / EMC Team Lead

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104058883MPK-002	
Equipment Under Test:	Ceiling Fan Remote
Trade Name:	Hunter Fan Company
Model(s) Tested:	K6019-01, K6266-02
Applicant:	Hunter Fan Company
Contact:	Julian Martin
Address:	Hunter Fan Company 545 E. Algonquin Road Arlington Heights, Illinois 60005
Country:	USA
Tel. Number:	(901) 248-2810
Email:	jmartin@hunterfan.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

<i>Hunter Fan Company</i>	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration)	7
4.0 Document History	10

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	F/300	6
1500 - 100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	F/1500	30
1500 - 100,000	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f 0.5	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10-4 f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
 * Based on nerve stimulation (NS).
 ** Based on specific absorption rate (SAR).

3.0 Test Results (Mobile Configuration)**3.1 Classification**

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Ceiling Fan Remote, Model: K6019-01, K6266-02 consists of a single radio.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Field Strength @3m (dBuV/m)	Note
433.9	62.64	Field strength measurements were taken from Report # 104058883MPK-001

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation

Calculations for this report are based on highest power measured.

Frequency Range (MHz)	Field Strength @3m (dBuV/m)	EIRP (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	Results
433.9	62.64	0.0006	0.0000012	1.6616042	Complies

Frequency Range (MHz)	Field Strength @3m (dBuV/m)	EIRP (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	Results
433.9	62.64	0.0006	0.0000001	0.2892667	Complies

Note: Antenna gains below 0 are considered as 0dBi.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
01/ G104058883	AC	ML	February 5, 2024	Original document