

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM141100656501
Page: 1 of 106

FCC REPORT

Application No:	SZEM1411006565CR
Applicant:	DEI Sales Inc. dba Definitive Technology
Manufacturer:	Definitive Technology
Factory:	Merry Electronics (Shenzhen) Co., Ltd.
Product Name:	Wireless Bluetooth over-ear headphone
Model No.(EUT):	HPNC
Trade mark:	Definitive Technology
FCC ID:	IPU-HPNC
Standards:	47 CFR Part 15, Subpart C (2014)
Date of Receipt:	2014-12-02
Date of Test:	2014-12-04 to 2015-01-08
Date of Issue:	2015-01-09

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-01-09		Original

Authorized for issue by:			
Tested By		 (Eric Fu) /Project Engineer	2015-01-08
Prepared By		 (Linlin Lv) /Clerk	2015-01-09
Checked By		 (Kevin Feng) /Reviewer	2015-01-15

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2009)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2009)	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2009)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2009)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2009)	PASS

4 Contents

	Page
1 COVER PAGE	1
2 VERSION.....	2
3 TEST SUMMARY.....	3
4 CONTENTS	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT	7
5.4 DESCRIPTION OF SUPPORT UNITS.....	7
5.5 TEST LOCATION	7
5.6 TEST FACILITY	8
5.7 DEVIATION FROM STANDARDS.....	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
5.10 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA	12
6.1 ANTENNA REQUIREMENT	12
6.2 CONDUCTED EMISSIONS	13
6.3 CONDUCTED PEAK OUTPUT POWER.....	17
6.4 20dB OCCUPY BANDWIDTH.....	24
6.5 CARRIER FREQUENCIES SEPARATION	30
6.6 HOPPING CHANNEL NUMBER	37
6.7 DWELL TIME	40
6.8 BAND-EDGE FOR RF CONDUCTED EMISSIONS	51
6.9 SPURIOUS RF CONDUCTED EMISSIONS	58
6.10 OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	82
6.11 RADIATED SPURIOUS EMISSION	84
6.11.1 Radiated Emission below 1GHz	87
6.11.2 Transmitter Emission above 1GHz	93
6.12 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	97-106

5 General Information

5.1 Client Information

Applicant:	DEI Sales Inc. dba Definitive Technology
Address of Applicant:	One Viper Way Vista, California 92081
Manufacturer:	Definitive Technology
Address of Manufacturer:	11433 Cronridge Drive Owings Mills, MD 21117
Factory:	Merry Electronics (Shenzhen) Co., Ltd.
Address of Factory:	Merry Industrial Park, #484 Hua Rong Rd., Da-Lang, Bao-An, Shenzhen 518109, China

5.2 General Description of EUT

Product Name:	Wireless Bluetooth over-ear headphone
Model No.:	HPNC
Trade mark:	Definitive Technology
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	3.0 with EDR
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
EUT Function:	Wireless bluetooth over-ear headphone
Test software of EUT:	Blue test 3 (manufacturer declare)
Test Power Grade:	100,30 (manufacturer declare)
Antenna Type:	Integral
Antenna Gain:	3dBi
Power Supply:	USB charge 5V 500mA
	Battery : DC 3.7V 900mAh (Li-ion Rechargeable Battery)
Test Voltage:	AC 120V 60Hz
Aux in Cable :	100cm (Unshielded)
USB Cable:	200cm (Unshielded)

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel	2402MHz
The Middle channel	2441MHz
The Highest channel	2480MHz

5.3 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar

5.4 Description of Support Units

The EUT has been tested independently.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-06-10
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-16
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2015-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2015-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2015-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-16
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-29
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-06-10
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-16
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-29
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
13	Band filter	Amindeon	82346	SEL0094	2015-05-16
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-16
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-16
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-06-04


RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-16
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-05-16
8	Band filter	amideon	82346	SEL0094	2015-05-16
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-05-16
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

Note: The calibration interval is one year, all the instruments are valid.



6 Test results and Measurement Data


6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3dBi.

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
5-30		60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none">1) The mains terminal disturbance voltage test was conducted in a shielded room.2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.		


Test Setup:	
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Charge + Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation at lowest channel is the worst case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live line:



Site : Shielding Room
Condition : 47 CFR PART15C AV CE LINE
Job No. : 6565CR
Test mode : Charge+TX mode

	Freq	Cable	LISN	Read	Limit	Over	Remark
		MHz	dB	dB	dBuV	dBuV	
1	0.21967	0.02	9.70	36.71	46.43	52.83	-6.40 Peak
2	0.37314	0.01	9.78	32.02	41.80	48.43	-6.63 Peak
3	0.68990	0.02	9.80	30.60	40.42	46.00	-5.58 Peak
4	0.88031	0.02	9.80	28.57	38.39	46.00	-7.61 Peak
5	2.273	0.02	9.81	28.90	38.73	46.00	-7.27 Peak
6	10.072	0.01	9.90	33.17	43.08	50.00	-6.92 Peak

Neutral line:




Site : Shielding Room
Condition : 47 CFR PART15C AV CE NEUTRAL
Job No. : 6565CR
Test mode : Charge+TX mode

Freq	Cable		LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB		dB	dBuV	dBuV	dBuV	dB
1	0.22083	0.02	9.70	34.71	44.43	52.79	-8.36	Peak
2	0.40187	0.01	9.80	31.49	41.30	47.81	-6.52	Peak
3	0.70096	0.02	9.80	30.43	40.25	46.00	-5.75	Peak
4	2.285	0.02	9.82	28.40	38.24	46.00	-7.76	Peak
5	5.535	0.01	9.93	30.08	40.02	50.00	-9.98	Peak
6	11.317	0.01	10.00	35.01	45.02	50.00	-4.98	Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2009
Test Setup:	 <p>The diagram illustrates the test setup. A 'Spectrum Analyzer' is connected to the 'E.U.T' (Equipment Under Test) via a cable. The 'E.U.T' is placed on a 'Non-Conducted Table'. The entire setup is positioned above a 'Ground Reference Plane'.</p>
	<p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Limit:	20dBm
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data


GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.78	20.00	Pass
Middle	2.05	20.00	Pass
Highest	1.56	20.00	Pass

π/4DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	0.79	20.00	Pass
Middle	-0.89	20.00	Pass
Highest	-1.43	20.00	Pass


8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	1.48	20.00	Pass
Middle	-0.17	20.00	Pass
Highest	-0.73	20.00	Pass

Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------




Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



6.4 20dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	NA
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type..
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data


Test channel	20dB Occupy Bandwidth (kHz)		
	GFSK	$\pi/4$ DQPSK	8DPSK
Lowest	884.615	1206.731	1221.154
Middle	894.231	1216.346	1230.769
Highest	889.423	1216.346	1230.769

Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------




Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



6.5 Carrier Frequencies Separation

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	2/3 of the 20dB bandwidth
	Remark: the transmission power is less than 0.125W.
Exploratory Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Measurement Data

GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	≥596	Pass
Middle	1002	≥596	Pass
Highest	1002	≥596	Pass

π/4DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	≥811	Pass
Middle	1002	≥811	Pass
Highest	1002	≥811	Pass

8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	≥821	Pass
Middle	1002	≥821	Pass
Highest	1002	≥821	Pass


Note: According to section 6.4,

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	894.231	596
π/4DQPSK	1216.346	811
8DPSK	1230.769	821




Test plot as follows:


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------




Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------




Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------




Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------



Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------



6.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (b)
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	At least 15 channels
Test Mode:	Hopping transmitting with all kind of modulation
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Measurement Data

Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15


Test plot as follows:

Test mode:

GFSK




Test mode:


 $\pi/4$ DQPSK


Test mode:

8DPSK



6.7 Dwell Time

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2009
Test Setup:	
Instruments Used:	Refer to section 5.10 for details
Test Mode:	Hopping transmitting with all kind of modulation and all kind of data type.
Limit:	0.4 Second
Test Results:	Pass

Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)
GFSK	DH1	0.09760	0.4
	DH3	0.26288	0.4
	DH5	0.31603	0.4
$\pi/4$ DQPSK	2-DH1	0.12704	0.4
	2-DH3	0.25968	0.4
	2-DH5	0.32043	0.4
8DPSK	3-DH1	0.12832	0.4
	3-DH3	0.26288	0.4
	3-DH5	0.31735	0.4

Remark:

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

On (ms)*total number=dwell time (ms)

The lowest channel (2402MHz), as below:

DH1 time slot=0.305 (ms)*total number=97.60 (ms)

DH3 time slot=1.643 (ms)* total number = 262.88 (ms)

DH5 time slot=2.873 (ms)* total number = 316.03 (ms)

2-DH1 time slot=0.397(ms)*total number=127.04 (ms)

2-DH3 time slot=1.623 (ms)* total number = 259.68 (ms)

2-DH5 time slot=2.913 (ms)* total number = 320.43 (ms)

3-DH1 time slot=0.401 (ms)*total number=128.32 (ms)



3-DH3 time slot=1.643 (ms)* total number = 262.88 (ms)

3-DH5 time slot=2.885 (ms)* total number = 317.35 (ms)





Test plot as follows:



Test Packet:	DH1
--------------	-----





Test Packet:	DH3
--------------	-----





Test Packet:	DH5
--------------	-----





Test Packet:	2-DH1
--------------	-------





Test Packet:	2-DH3
--------------	-------





Test Packet:	2-DH5
--------------	-------





Test Packet:	3-DH1
--------------	-------




Test Packet:	3-DH3
--------------	-------



Test Packet:	3-DH5
--------------	-------





6.8 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	 <p>Diagram illustrating the test setup for RF conducted emissions. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The setup is placed on a Non-Conducted Table, which sits above a Ground Reference Plane. The Spectrum Analyzer shows a signal spectrum.</p>
Remark:	Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass





Test plot as follows:



Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------





Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------





Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------





Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------





Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------






6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Test Setup:	
	<p>Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worse case of GFSK modulation type, 2-DH1 of data type is worse case of $\pi/4$ DQPSK modulation type, 3-DH1 of data type is worse case of 8DPSK modulation type.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass


Test mode:	GFSK	Test channel:	Lowest
------------	------	---------------	--------













Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------











Test mode:	GFSK	Test channel:	Highest
------------	------	---------------	---------













Test mode:	$\pi/4$ DQPSK	Test channel:	Lowest
------------	---------------	---------------	--------











Test mode:	$\pi/4$ DQPSK	Test channel:	Middle
------------	---------------	---------------	--------













Test mode:	$\pi/4$ DQPSK	Test channel:	Highest
------------	---------------	---------------	---------











Test mode:	8DPSK	Test channel:	Lowest
------------	-------	---------------	--------













Test mode:	8DPSK	Test channel:	Middle
------------	-------	---------------	--------










Test mode:	8DPSK	Test channel:	Highest
------------	-------	---------------	---------









**Remark:**

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.



6.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:								
	<p>The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.</p> <p>Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.</p> <p>The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.</p>								
Compliance for section 15.247(a)(1)									
<p>According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.</p> <ul style="list-style-type: none">• Number of shift register stages: 9• Length of pseudo-random sequence: $2^9 - 1 = 511$ bits• Longest sequence of zeros: 8 (non-inverted signal)									
									
<p><i>Linear Feedback Shift Register for Generation of the PRBS sequence</i></p> <p>An example of Pseudorandom Frequency Hopping Sequence as follow:</p> <table><tr><td>20 62 46 77</td><td>7 64</td><td>8 73</td><td>16 75 1</td></tr><tr><td></td><td></td><td></td><td></td></tr></table> <p>Each frequency used equally on the average by each transmitter.</p> <p>According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.</p>		20 62 46 77	7 64	8 73	16 75 1				
20 62 46 77	7 64	8 73	16 75 1						
									

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

6.11 Radiated Spurious Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz

Figure 3. Above 1GHz

The diagrams show the following test setup components and dimensions:

- Turntable:** A platform where the **EUT** (Equipment Under Test) and **AE** (Antenna Equipment) are placed. The distance between the **EUT** and the **Antenna Tower** is 3m. The height of the turntable from the **Ground Reference Plane** is 80cm.
- Antenna Tower:** A vertical structure with an **Antenna** at the top. The distance between the **Antenna Tower** and the **Ground Reference Plane** is 1m to 4m.
- Test Receiver:** A device connected to the **Antenna** and the **AE** via a blue line.
- Pre-Amplifier:** A component connected to the **Test Receiver**.
- Controller:** A component connected to the **Test Receiver**.
- Horn Antenna:** An alternative antenna type shown in Figure 3, positioned at the top of the **Antenna Tower**.


Test Procedure:	<ul style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB
-----------------	--

	<p>margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. Test the EUT in the lowest channel (2402MHz), the middle channel (2441MHz), the Highest channel (2480MHz)</p> <p>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</p> <p>i. Repeat above procedures until all frequencies measured was complete.</p>
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode and Charge + Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worse case. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)	Low Channel	
Test mode:	Charge + Transmitting mode	Vertical

Data: 71




Condition: 47 CFR PART 15.209 3m 3142C Vertical

Job No. : 6565CR

Test mode: Charge+TX mode

Freq	Cable Loss	Ant Factor	Preamp Factor	Read	Limit Line	Over Limit
				Level		
1	30.00	0.60	18.70	27.36	37.16	29.10 40.00 -10.90
2	50.59	0.80	8.61	27.29	39.79	21.91 40.00 -18.09
3	183.20	1.37	9.96	26.76	37.64	22.21 43.50 -21.29
4	222.17	1.53	11.35	26.62	36.16	22.42 46.00 -23.58
5	277.09	1.80	12.89	26.46	31.14	19.37 46.00 -26.63
6	866.09	3.47	22.79	26.96	27.54	26.84 46.00 -19.16

Test mode:	Charge + Transmitting mode	Horizontal
------------	----------------------------	------------

Data: 70

Condition: 47 CFR PART 15.209 3m 3142C Horizontal


Job No. : 6565CR

Test mode: Charge+TX mode

Freq	Cable Loss	Ant Factor	Preamp Factor	Read	Limit Level	Limit Line	Over Limit
				Level			
MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB
1	30.11	0.60	18.64	27.36	28.30	20.18	40.00 -19.82
2	82.36	1.10	7.94	27.23	36.29	18.10	40.00 -21.90
3	183.20	1.37	9.96	26.76	35.34	19.91	43.50 -23.59
4	271.32	1.77	12.73	26.47	34.80	22.83	46.00 -23.17
5	417.64	2.28	16.37	27.25	30.18	21.58	46.00 -24.42
6	958.79	3.66	23.30	26.51	23.19	23.64	46.00 -22.36

30MHz~1GHz (QP) Middle Channel		
Test mode:	Charge + Transmitting mode	Vertical

Data: 73




Condition: 47 CFR PART 15.209 3m 3142C Vertical

Job No. : 6565CR

Test mode: Charge+TX mode

	Cable	Ant	Preamp	Read	Limit	Over		
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	18.70	27.36	37.97	29.91	40.00	-10.09
2	50.98	0.80	8.55	27.29	39.99	22.05	40.00	-17.95
3	183.05	1.37	9.96	26.76	37.76	22.33	43.50	-21.17
4	222.80	1.53	11.39	26.62	36.68	22.98	46.00	-23.02
5	277.35	1.80	12.90	26.46	31.18	19.42	46.00	-26.58
6	866.79	3.47	22.80	26.96	27.01	26.32	46.00	-19.68

Test mode:	Charge + Transmitting mode	Horizontal
------------	----------------------------	------------

Data: 72

Condition: 47 CFR PART 15.209 3m 3142C Horizontal


Job No. : 6565CR

Test mode: Charge+TX mode

Freq	Cable Loss	Ant Factor	Preamp Factor	Read	Limit Level	Limit Line	Over Limit
				Level			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.11	0.60	18.64	27.36	28.28	20.16	40.00 -19.84
2	82.60	1.10	7.96	27.23	36.48	18.31	40.00 -21.69
3	183.05	1.37	9.96	26.76	35.47	20.04	43.50 -23.46
4	271.46	1.77	12.73	26.47	34.05	22.08	46.00 -23.92
5	417.11	2.28	16.37	27.23	30.41	21.83	46.00 -24.17
6	958.43	3.66	23.30	26.51	23.51	23.96	46.00 -22.04

30MHz~1GHz (QP) High Channel		
Test mode:	Charge + Transmitting mode	Vertical

Data: 75



Condition: 47 CFR PART 15.209 3m 3142C Vertical


Job No. : 6565CR

Test mode: Charge+TX mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.00	0.60	18.70	27.36	37.97	29.91	40.00	-10.09
2	50.98	0.80	8.55	27.29	39.99	22.05	40.00	-17.95
3	183.05	1.37	9.96	26.76	37.76	22.33	43.50	-21.17
4	222.98	1.53	11.39	26.62	36.69	22.99	46.00	-23.01
5	277.35	1.80	12.90	26.46	31.18	19.42	46.00	-26.58
6	866.79	3.47	22.80	26.96	25.05	24.36	46.00	-21.64



Test mode:	Charge + Transmitting mode	Horizontal
------------	----------------------------	------------

Data: 74

Condition: 47 CFR PART 15.209 3m 3142C Horizontal

Job No. : 6565CR

Test mode: Charge+TX mode

Freq	Cable	Ant	Preamp	Read	Limit	Over	Limit	
	Loss	Factor	Factor	Level	Level	Line		
1	30.00	0.60	18.70	27.36	28.28	20.22	40.00	-19.78
2	82.89	1.10	7.99	27.22	36.47	18.34	40.00	-21.66
3	183.05	1.37	9.96	26.76	35.47	20.04	43.50	-23.46
4	271.46	1.77	12.73	26.47	34.05	22.08	46.00	-23.92
5	417.11	2.28	16.37	27.23	30.14	21.56	46.00	-24.44
6	958.43	3.66	23.30	26.51	23.51	23.96	46.00	-22.04

6.11.2 Transmitter Emission above 1GHz

Lowest channel

Peak value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1329.151	54.7	74.0	19.3	24.8	34.2	6.0	V
4804.000	66.2	74.0	7.8	34.3	35.1	7.6	V
6635.020	55.8	74.0	18.2	35.4	33.7	9.1	V
7206.000	58.2	74.0	15.8	35.8	33.8	9.9	V
9608.000	60.6	74.0	13.4	37.2	32.5	12.0	V
12006.331	61.8	74.0	12.2	37.8	31.8	14.2	V
1327.692	46.1	74.0	27.9	24.7	34.2	6.0	H
4804.000	65.4	74.0	8.6	34.3	35.1	7.6	H
6505.529	56.2	74.0	17.8	35.2	33.7	8.9	H
7206.000	57.8	74.0	16.2	35.8	33.8	9.9	H
9608.000	60.5	74.0	13.5	37.2	32.5	12.0	H
11856.685	61.1	74.0	12.9	37.7	31.8	13.7	H

Average value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1329.151	26.5	54.0	27.5	24.8	34.2	6.0	V
4804.000	47.5	54.0	6.5	34.3	35.1	7.6	V
6635.020	43.0	54.0	11.0	35.4	33.7	9.1	V
7206.000	44.7	54.0	9.3	35.8	33.8	9.9	V
9608.000	48.3	54.0	5.7	37.2	32.5	12.0	V
12006.331	49.7	54.0	4.3	37.8	31.8	14.2	V
1327.692	26.4	54.0	27.6	24.7	34.2	6.0	H
4804.000	47.1	54.0	6.9	34.3	35.1	7.6	H
6505.529	43.2	54.0	10.8	35.2	33.7	8.9	H
7206.000	44.9	54.0	9.1	35.8	33.8	9.9	H
9608.000	48.8	54.0	5.2	37.2	32.5	12.0	H
11856.685	49.5	54.0	4.5	37.7	31.8	13.7	H

Middle channel

Peak value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1330.612	54.0	74.0	20.0	24.8	34.2	6.0	V
4882.000	65.4	74.0	8.6	34.6	35.2	7.6	V
6623.143	55.4	74.0	18.6	35.4	33.7	9.1	V
7323.000	57.3	74.0	16.7	35.7	33.8	10.0	V
9764.000	60.1	74.0	13.9	37.3	32.1	12.3	V
11500.976	61.1	74.0	12.9	37.7	31.6	13.5	V
1327.692	45.9	74.0	28.1	24.7	34.2	6.0	H
4882.000	62.5	74.0	11.5	34.6	35.2	7.6	H
6505.529	55.3	74.0	18.7	35.2	33.7	8.9	H
7323.000	57.2	74.0	16.8	35.7	33.8	10.0	H
9764.000	60.3	74.0	13.7	37.3	32.1	12.3	H
11521.601	61.2	74.0	12.8	37.7	31.6	13.5	H

Average value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1330.612	26.5	54.0	27.5	24.8	34.2	6.0	V
4882.000	47.09	54.0	6.9	34.6	35.2	7.6	V
6623.143	43.0	54.0	11.0	35.4	33.7	9.1	V
7323.000	43.7	54.0	10.3	35.7	33.8	10.0	V
9764.000	48.0	54.0	6.0	37.3	32.1	12.3	V
11500.976	49.4	54.0	4.6	37.7	31.6	13.5	V
1327.692	26.3	54.0	27.7	24.7	34.2	6.0	H
4882.000	45.7	54.0	8.3	34.6	35.2	7.6	H
6505.529	43.1	54.0	10.9	35.2	33.7	8.9	H
6505.529	43.1	54.0	10.9	35.2	33.7	8.9	H
7323.000	44.6	54.0	9.4	35.7	33.8	10.0	H
9764.000	47.9	54.0	6.1	37.3	32.1	12.3	H

Highest channel

Peak value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1330.612	54.2	74.0	19.8	24.8	34.2	6.0	V
4960.000	66.9	74.0	7.1	34.6	35.3	7.6	V
6587.637	55.9	74.0	18.1	35.4	33.7	9.0	V
7440.000	57.3	74.0	16.7	35.8	33.9	10.1	V
9920.000	60.5	74.0	13.5	37.3	32.1	12.3	V
11459.836	61.1	74.0	12.9	37.6	31.6	13.5	V
1327.692	47.4	74.0	26.6	24.7	34.2	6.0	H
4960.000	61.4	74.0	12.6	34.6	35.3	7.6	H
6482.258	55.2	74.0	18.8	35.2	33.7	8.9	H
7440.000	57.4	74.0	16.6	35.8	33.9	10.1	H
9920.000	60.5	74.0	13.5	37.3	32.1	12.3	H
11036.649	61.4	74.0	12.6	37.6	31.2	13.0	H

Average value:

Freq.(MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.F. (dB/m)	Amp.G. (dB)	Cbl.L. (dB)	Pol.
1330.612	26.4	54.0	27.6	24.8	34.2	6.0	V
4960.000	47.8	54.0	6.2	34.6	35.3	7.6	V
6587.637	43.1	54.0	10.9	35.4	33.7	9.0	V
7440.000	44.4	54.0	9.6	35.8	33.9	10.1	V
9920.000	47.7	54.0	6.3	37.3	32.1	12.3	V
11459.836	49.3	54.0	4.7	37.6	31.6	13.5	V
1327.692	26.3	54.0	27.7	24.7	34.2	6.0	H
4960.000	45.8	54.0	8.2	34.6	35.3	7.6	H
6482.258	42.7	54.0	11.3	35.2	33.7	8.9	H
7440.000	44.5	54.0	9.5	35.8	33.9	10.1	H
9920.000	48.6	54.0	5.4	37.3	32.1	12.3	H
11036.649	48.9	54.0	5.1	37.6	31.2	13.0	H

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2009		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			


Figure 1. 30MHz to 1GHz

Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channelg. Test the EUT in the lowest channel , the Highest channelh. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of data type Transmitting mode and Charge + Transmitting mode
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worse case. Pretest the EUT at Transmitting mode and Charge + Transmitting mode, found the Charge + Transmitting mode which it is worse case. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass

Test plot as follows:

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Vertical
------------------	------------	---------------	--------	---------	------	----------

Data: 3

Site : chamber


Condition: FCC PART C 247 PK 3m Vertical

Job No: : 6565CR

Mode: : 2402 Bandedge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		2390.00	4.90	32.35	38.46	47.09	45.88	74.00	-28.12
2 pp		2402.29	4.92	32.41	38.46	95.95	94.82	74.00	20.82

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------------	------------	---------------	--------	---------	------	------------

Data: 1

Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 6565CR

Mode: : 2402 Bandedge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	47.79	46.58	74.00	-27.42
2 pp	2402.29	4.92	32.41	38.46	94.77	93.64	74.00	19.64

Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Average	Vertical
------------------	------------	---------------	--------	---------	---------	----------

Data: 4



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical

Job No: 6565CR


Mode: 2402 Bandedge

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	35.16	33.95	54.00	-20.05
2 pp	2402.19	4.92	32.41	38.46	82.99	81.86	54.00	27.86



Worse case mode:	GFSK (DH5)	Test channel:	Lowest	Remark:	Average	Horizontal
------------------	------------	---------------	--------	---------	---------	------------

Data: 2



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 6565CR

Mode: : 2402 Bandedge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		2390.00	4.90	32.35	38.46	35.22	34.01	54.00	-19.99
2 pp		2402.19	4.92	32.41	38.46	82.03	80.90	54.00	26.90

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Vertical
------------------	------------	---------------	---------	---------	------	----------

Data: 7



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical


Job No: : 6565CR

Mode: : 2480 Bandedge

		Cable Freq	Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.81	5.02	32.44	38.47	94.32	93.31	74.00	19.31	
2	2483.50	5.03	32.44	38.47	50.23	49.23	74.00	-24.77	

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Peak	Horizontal
------------------	------------	---------------	---------	---------	------	------------

Data: 5



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 6565CR

Mode: : 2480 Bandedge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp		2479.86	5.02	32.44	38.47	94.14	93.13	74.00	19.13
2		2483.50	5.03	32.44	38.47	51.03	50.03	74.00	-23.97

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Average	Vertical
------------------	------------	---------------	---------	---------	---------	----------

Data: 8



Site : chamber


Condition: FCC PART C 247 AV 3m Vertical

Job No: : 6565CR

Mode: : 2480 Bandedge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2480.06	5.02	32.44	38.47	81.62	80.61	54.00	26.61	
2	2483.50	5.03	32.44	38.47	43.60	42.60	54.00	-11.40	

Worse case mode:	GFSK (DH5)	Test channel:	Highest	Remark:	Average	Horizontal
------------------	------------	---------------	---------	---------	---------	------------

Data: 6

Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 6565CR

Mode: : 2480 Bandedge

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1 pp	2480.06	5.02	32.44	38.47	81.47	80.46	54.00	26.46
2	2483.50	5.03	32.44	38.47	43.51	42.51	54.00	-11.49

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor