



A D T

FCC TEST REPORT

(PART 24)

REPORT NO.: RF130826C37-1

MODEL NO.: UNA-P3/UNA-L3

FCC ID: IXM-UNA-P3

RECEIVED: Aug. 26, 2013

TESTED: Sep. 04, 2013 ~ Sep. 05, 2013

ISSUED: Nov. 01, 2013

APPLICANT: Universal Scientific Industrial Co., Ltd.

ADDRESS: 141, Lane 351, Sec. 1, Taiping Road., TsaoTuen, Nantou 54261, Taiwan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION	5
2 SUMMARY OF TEST RESULTS.....	6
2.1 MEASUREMENT UNCERTAINTY	6
2.2 TEST SITE AND INSTRUMENTS.....	7
3 GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 CONFIGURATION OF SYSTEM UNDER TEST	9
3.3 DESCRIPTION OF SUPPORT UNITS.....	9
3.4 TEST ITEM AND TEST CONFIGURATION	10
3.5 EUT OPERATING CONDITIONS.....	11
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	11
4 TEST TYPES AND RESULTS.....	12
4.1 OUTPUT POWER MEASUREMENT	12
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT.....	12
4.1.2 TEST PROCEDURES	12
4.1.3 TEST SETUP	13
4.1.4 TEST RESULTS	14
4.2 FREQUENCY STABILITY MEASUREMENT	16
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	16
4.2.2 TEST PROCEDURE.....	16
4.2.3 TEST SETUP	16
4.2.4 TEST RESULTS	17
4.3 OCCUPIED BANDWIDTH MEASUREMENT.....	18
4.3.1 TEST PROCEDURES	18
4.3.2 TEST SETUP	18
4.3.3 TEST RESULTS	19
4.4 PEAK TO AVERAGE RATIO	20
4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	20
4.4.2 TEST SETUP	20
4.4.3 TEST PROCEDURES	20
4.4.4 TEST RESULTS	21
4.5 BAND EDGE MEASUREMENT	22
4.5.1 LIMITS OF BAND EDGE MEASUREMENT.....	22
4.5.2 TEST SETUP	22
4.5.3 TEST PROCEDURES	22
4.5.4 TEST RESULTS	23
4.6 CONDUCTED SPURIOUS EMISSIONS	25
4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	25
4.6.2 TEST PROCEDURE.....	25
4.6.3 TEST SETUP	25
4.6.4 TEST RESULTS	26
4.7 RADIATED EMISSION MEASUREMENT	27
4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	27
4.7.2 TEST PROCEDURES	27
4.7.3 DEVIATION FROM TEST STANDARD	27
4.7.4 TEST SETUP	28
4.7.5 TEST RESULTS	29
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	35



A D T

6	INFORMATION ON THE TESTING LABORATORIES	36
7	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	37



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF130826C37-1	Original release	Nov. 01, 2013



A D T

1 CERTIFICATION

PRODUCT: 3G Module

MODEL: UNA-P3/UNA-L3

BRAND: Universal Global Scientific Industrial Co., Ltd.

APPLICANT: Universal Scientific Industrial Co., Ltd.

TESTED: Sep. 04, 2013 ~ Sep. 05, 2013

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 24, Subpart E

The above equipment (model: UNA-P3/UNA-L3) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Evonne Liu , **DATE :** Nov. 01, 2013
Evonne Liu / Specialist

APPROVED BY : Sam Chen , **DATE :** Nov. 01, 2013
Sam Chen / Assistant Manager



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 24.232	Equivalent isotropically radiated power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -17.03dB at 3760.00MHz.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 15, 2013	Apr. 14, 2014
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2012	Dec. 16, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Mar. 25, 2013	Mar. 24, 2014
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Jan. 07, 2013	Jan. 06, 2014
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 25, 2012	Dec. 24, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier EMCI	EMC 012645	980115	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 184045	980116	Dec. 28, 2012	Dec. 27, 2013
Preamplifier EMCI	EMC 330H	980112	Dec. 28, 2012	Dec. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 19, 2012	Oct. 18, 2013
RF signal cable Worken	RG-213	NA	Dec. 29, 2012	Dec. 28, 2013
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 10.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 690701.
5. The IC Site Registration No. is IC 7450F-10.



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	3G Module	
MODEL NO.	UNA-P3/UNA-L3	
POWER SUPPLY	3.3Vdc	
MODULATION TYPE	GSM/GPRS	GMSK
	EDGE	8PSK
	WCDMA	BPSK
FREQUENCY RANGE	GSM/GPRS/EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
MAX. EIRP POWER	GSM	955.21mW
	EDGE	376.10mW
	WCDMA	299.43mW
EMISSION DESIGNATOR	GSM	244KGXW
	EDGE	257KG7W
	WCDMA	4M18F9W
MULTI-SLOTS CLASS	12	
WCDMA RELEASE VERSION	6	
ANTENNA TYPE	Fixed External Antenna	
I/O PORTS	Refer to users' manual	
DATA CABLE	Refer to NOTE as below	
ACCESSORY DEVICES	Refer to NOTE as below	


NOTE:

1. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 CONFIGURATION OF SYSTEM UNDER TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC Power Supply	TOP WARD	3303D	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Z-plane for EIRP and radiated emission. Following channel(s) was (were) selected for the final test as listed below:

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	EIRP	512 to 810	512, 661, 810	GSM, EDGE
-	FREQUENCY STABILITY	512 to 810	661	GSM, EDGE
-	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
-	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM, EDGE
-	BAND EDGE	512 to 810	512, 810	GSM, EDGE
-	CONDUCED EMISSION	512 to 810	661	GSM, EDGE
-	RADIATED EMISSION	512 to 810	661	GSM, EDGE

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
-	FREQUENCY STABILITY	9262 to 9538	9400	WCDMA
-	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
-	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
-	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
-	CONDUCED EMISSION	9262 to 9538	9400	WCDMA
-	RADIATED EMISSION	9262 to 9538	9400	WCDMA

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	26deg. C, 58%RH	3.3Vdc	Howard Kao
FREQUENCY STABILITY	26deg. C, 58%RH	3.3Vdc	Howard Kao
OCCUPIED BANDWIDTH	26deg. C, 58%RH	3.3Vdc	Howard Kao
BAND EDGE	26deg. C, 58%RH	3.3Vdc	Howard Kao
CONDUCED EMISSION	26deg. C, 58%RH	3.3Vdc	Howard Kao
RADIATED EMISSION	25deg. C, 65%RH	120Vac, 60Hz	David Huang



A D T

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



A D T

4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP

4.1.2 TEST PROCEDURES


EIRP MEASUREMENT:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE and 5MHz for WCDMA.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d.
$$\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn.}$$

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP



CONDUCTED POWER MEASUREMENT:



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM (1 Uplink)	28.99	28.57	28.08
GPRS 8 (GMSK, 1 slot)	28.97	28.54	28.07
GPRS 10 (GMSK, 2 slot)	28.44	28.01	27.54
GPRS 11 (GMSK, 3 slot)	26.84	26.41	25.94
GPRS 12 (GMSK, 4 slot)	26.29	25.86	25.39
EDGE 8 (GMSK, 1 Uplink)	28.95	28.52	28.05
EDGE 10 (GMSK, 2 Uplink)	28.44	28.01	27.54
EDGE 11 (GMSK, 3 Uplink)	26.83	26.40	25.93
EDGE 12 (GMSK, 4 Uplink)	26.28	25.87	25.40
EDGE 8 (8PSK, 1 Uplink)	24.49	24.06	23.59
EDGE 10 (8PSK, 2 Uplink)	23.40	22.97	22.50
EDGE 11 (8PSK, 3 Uplink)	21.56	21.13	20.66
EDGE 12 (8PSK, 4 Uplink)	20.56	20.13	19.66

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	23.69	23.71	23.58
HSDPA Subtest-1	22.75	22.73	22.86
HSDPA Subtest-2	22.78	22.76	22.89
HSDPA Subtest-3	22.33	22.31	22.44
HSDPA Subtest-4	22.30	22.28	22.41
HSUPA Subtest-1	20.20	20.18	20.31
HSUPA Subtest-2	20.83	20.81	20.94
HSUPA Subtest-3	21.58	21.56	21.69
HSUPA Subtest-4	21.05	21.03	21.16
HSUPA Subtest-5	22.83	22.81	22.94



A D T

EIRP POWER (dBm)

GSM

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	512	1850.2	-11.91	36.57	24.66	292.55	H
	661	1880.0	-12.72	37.22	24.50	282.10	H
	810	1909.8	-12.26	37.18	24.92	310.60	H
	512	1850.2	-7.85	37.65	29.80	955.21	V
	661	1880.0	-8.04	37.58	29.54	900.12	V
	810	1909.8	-7.71	37.48	29.77	948.42	V

EDGE

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	512	1850.2	-15.64	36.57	20.93	123.94	H
	661	1880.0	-17.16	37.22	20.06	101.48	H
	810	1909.8	-16.70	37.18	20.48	111.74	H
	512	1850.2	-12.41	37.65	25.24	334.27	V
	661	1880.0	-11.83	37.58	25.75	376.10	V
	810	1909.8	-11.88	37.48	25.60	363.08	V

WCDMA

Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
Z	9262	1852.4	-17.36	36.57	19.21	83.41	H
	9400	1880.0	-17.33	37.22	19.89	97.59	H
	9538	1907.6	-17.31	37.18	19.87	97.10	H
	9262	1852.4	-13.58	37.65	24.07	255.33	V
	9400	1880.0	-12.82	37.58	24.76	299.43	V
	9538	1907.6	-13.37	37.48	24.11	257.63	V

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





A D T

4.2.4 TEST RESULTS

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GSM	EDGE	WCDMA	
3.8	0.01	-0.01	0.01	2.5
3.4	0.01	-0.01	0.01	2.5
4.2	-0.01	-0.01	0.01	2.5

NOTE: The applicant defined the normal working voltage is from 3.4Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.


TEMP. (°C)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GSM	EDGE	WCDMA	
-30	0.01	-0.02	0.00	2.5
-20	0.01	-0.02	0.00	2.5
-10	-0.01	-0.02	0.00	2.5
0	-0.01	-0.02	0.00	2.5
10	-0.01	-0.02	-0.01	2.5
20	-0.01	-0.02	0.00	2.5
30	-0.01	-0.02	0.01	2.5
40	-0.01	-0.02	0.01	2.5
50	-0.01	-0.02	0.00	2.5
55	-0.01	-0.02	0.00	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 TEST SETUP






A D T

4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		26dB BANDWIDTH (kHz)	
		GSM	EDGE	GSM	EDGE
512	1850.2	236.67	253.63	295.4	322.9
661	1880.0	244.49	251.12	295.3	314.5
810	1909.8	240.62	255.91	295.3	327.8

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		26dB BANDWIDTH (MHz)	
		WCDMA	WCDMA	WCDMA	WCDMA
9262	1852.4	4.1769		4.731	
9400	1880.0	4.1740		4.718	
9538	1907.6	4.1732		4.725	




4.4 PEAK TO AVERAGE RATIO

4.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.4.4 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
		GSM	EDGE			
512	1850.2	0.10	2.68	9262	1852.4	2.57
661	1880.0	0.10	2.53	9400	1880.0	2.79
810	1909.8	0.10	2.34	9538	1907.6	2.58




4.5 BAND EDGE MEASUREMENT

4.5.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.5.2 TEST SETUP



4.5.3 TEST PROCEDURES


- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/GPRS/ EDGE).
- c. The center frequency of spectrum is the band edge frequency and span is 5MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA/LTE).
- d. Record the max trace plot into the test report.




A D T

4.5.4 TEST RESULTS


GSM



EDGE



WCDMA





A D T

Remark:

Band edge = measurement value + correction factor

GSM

For channel 512:

Correction factor = $10 \log (2.954/3) = -0.07$

For channel 810:

Correction factor = $10 \log (2.953/3) = -0.07$

EDGE

For channel 512:

Correction factor = $10 \log (3.229/3) = 0.32$

For channel 810:

Correction factor = $10 \log (3.278/3) = 0.38$

WCDMA

For channel 9262:

Correction factor = $10 \log (47.31/100) = -3.25$

For channel 9538:

Correction factor = $10 \log (47.25/100) = -3.26$

4.6 CONDUCTED SPURIOUS EMISSIONS


4.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .




4.6.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30 MHz to 19.1GHz. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.6.3 TEST SETUP



4.6.4 TEST RESULTS

GSM	EDGE
CHANNEL 661	CHANNEL 661
FREQUENCY RANGE : 30MHz~19.1GHz	FREQUENCY RANGE : 30MHz~19.1GHz
 <p>Ref 35 dBm Att 30 dB RBW 1 MHz Marker 1 [T1] -30.85 dBm VBW 3 MHz SWT 520 ms 3.759138500 GHz</p> <p>Offset 15 dB LVL 3dB</p> <p>Start 30 MHz 1.907 GHz/ Stop 19.1 GHz</p>	 <p>Ref 35 dBm Att 30 dB RBW 1 MHz Marker 1 [T1] -33.68 dBm VBW 3 MHz SWT 520 ms 3.654253500 GHz</p> <p>Offset 15 dB LVL 3dB</p> <p>Start 30 MHz 1.907 GHz/ Stop 19.1 GHz</p>
Date: 5.SEP.2013 14:41:01	Date: 5.SEP.2013 14:49:19
WCDMA	
CHANNEL 9400	
FREQUENCY RANGE : 30MHz~19.1GHz	
 <p>Ref 35 dBm Att 30 dB RBW 1 MHz Marker 1 [T1] -33.73 dBm VBW 3 MHz SWT 520 ms 3.629462500 GHz</p> <p>Offset 15 dB LVL 3dB</p> <p>Start 30 MHz 1.907 GHz/ Stop 19.1 GHz</p>	
Date: 5.SEP.2013 15:04:42	



A D T

4.7 RADIATED EMISSION MEASUREMENT

4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

4.7.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.7.3 DEVIATION FROM TEST STANDARD

No deviation

4.7.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).



A D T

4.7.5 TEST RESULTS

GSM:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 15

Level (dBm/m)

Date: 2013-09-04



Site : 966 Chamber 5
Condition : PART22/24 3m HORIZONTAL
Brand/Model: UNA-P3/L3
Remark : PCS1900 Link
Tested by : David Huang
Temperature : 25°C
Humidity : 65%
Plane : Z

	Freq	Read Level	Limit Level	Over Line	Limit	Over Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	44.31	-49.45	-48.26	-13.00	-36.45	-1.19	Peak
2	162.30	-71.18	-64.63	-13.00	-58.18	-6.55	Peak
3	267.06	-68.02	-62.11	-13.00	-55.02	-5.91	Peak
4	381.90	-69.65	-63.88	-13.00	-56.65	-5.77	Peak
5	668.20	-63.00	-63.87	-13.00	-50.00	0.87	Peak
6	974.10	-61.13	-65.28	-13.00	-48.13	4.15	Peak
7 pp	3760.00	-30.03	-21.73	-13.00	-17.03	-8.30	Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 16



Site : 966 Chamber 5
Condition : PART22/24 3m VERTICAL
Brand/Model: UNA-P3/L3
Remark : PCS1900 Link
Tested by : David Huang
Temperature : 25°C
Humidity : 65%
Plane : Z

Freq	Level	Read	Limit	Over	Factor	Remark
		Level	Line	Limit		
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	44.85	-51.04	-49.85	-13.00	-38.04	-1.19 Peak
2	168.51	-70.56	-63.88	-13.00	-57.56	-6.68 Peak
3	248.43	-69.95	-64.18	-13.00	-56.95	-5.77 Peak
4	324.50	-70.62	-64.43	-13.00	-57.62	-6.19 Peak
5	575.10	-64.13	-63.09	-13.00	-51.13	-1.04 Peak
6	948.90	-61.07	-64.73	-13.00	-48.07	3.66 Peak
7 pp	3760.00	-32.99	-24.69	-13.00	-19.99	-8.30 Peak



A D T


EDGE:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 11



Site : 966 Chamber 5
Condition : PART22/24 3m HORIZONTAL
Brand/Model: UNA-P3/L3
Remark : EDGE1900 Link
Tested by : David Huang
Temprature : 25°C
Humidity : 65%
Plane : Z

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	

1 pp 3760.00 -43.46 -35.16 -13.00 -30.46 -8.30 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 12



Site : 966 Chamber 5
Condition : PART22/24 3m VERTICAL
Brand/Model: UNA-P3/L3
Remark : EDGE1900 Link
Tested by : David Huang
Temperature : 25°C
Humidity : 65%
Plane : Z

Freq	Level	Read	Limit	Over	Factor	Remark	
		MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp	3760.00	-50.53	-42.23	-13.00	-37.53	-8.30	Peak



A D T


WCDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 11



Site : 966 Chamber 5
Condition : PART22/24 3m HORIZONTAL
Brand/Model: UNA-P3/L3
Remark : Band II Link
Tested by : David Huang
Temperature : 25°C
Humidity : 65%
Plane : Z

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m
1 pp	3760.00	-42.32	-34.02	-13.00	-29.32	-8.30 Peak
2	5640.00	-46.88	-44.98	-13.00	-33.88	-1.90 Peak




A D T



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 12



Site : 966 Chamber 5
Condition : PART22/24 3m VERTICAL
Brand/Model: UNA-P3/L3
Remark : Band II Link
Tested by : David Huang
Temperature : 25°C
Humidity : 65%
Plane : Z

		Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor
	MHz	dBm/m	dBm	dBm/m	dB	dB/m
1	3760.00	-45.84	-37.54	-13.00	-32.84	-8.30 Peak
2 pp	5640.00	-42.84	-40.94	-13.00	-29.84	-1.90 Peak



A D T

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---