



Lexmark International, Inc  
740 West New Circle Road  
Lexington, KY 40550  
U.S.A.  
Contact: Thomas Bugbee  
859-825-4432  
bugbee@lexmark.com

10/24/17

**RE FCC ID:YILLEXM07001**

**To the certification reviewer:**

We are hereby applying for full modular approval of the above-referenced FCC ID, based on compliance with all of the criteria as detailed below.

Sincerely,

Thomas Bugbee  
Regulatory Manager

**Part 15 Unlicensed Single Modular Transmitter Approval Justifications per  
15.212**

Requirement per 15.212	reference
(i) The radio elements of the modular transmitter must have their own RF shielding.	Shielding is provided by a metal cover over the circuitry.
(ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided).	Connect via USB 2.0 interface. All modulation and data inputs are buffered by circuitry on the transmitter chip.
(iii) The modular transmitter must have its own power supply regulation.	The Module contains its own Power supply regulation (see U2 on the schematic diagram).
(iv) The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c).	The transmitter module contains two separate PCB trace antennas and one chip antenna and thus is designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device per §§ 15.203 and 15.204(c). §§ 15.204(b) does not apply.
(v) The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with Part 15 parameters.	Testing was performed with the module extended outside of the host as shown in the test setup photos.
(vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. If the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	A sample of the host label is provided as an exhibit, showing the FCC identifier of the module.

(vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	The module complies fully with the operating requirements of Part 15 subpart B, C and E as demonstrated in the test report exhibits. The operating and installation instructions are also provided as exhibits.
(viii) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.	This module operates under Parts 15 B, C, and E and when installed in its final configuration in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. Based upon calculations provided, the MPE is well below the limits of general population/uncontrolled exposure.