Test Method:	FCC Part 15 Subpart C, Spurious Case Radiated Emissions, Paragraph 15.209(a)		
Customer:	NATS (KNOGO NA)	**Job No.**	R-8572-1
Test Sample:	Anti-theft device		
Model No.:	T-2280	**Serial No.**	N/A
Operating Mode:	Continuously transmitting at 1.97 and 8.2 MHz swept rf signal.		
Technician:	Peter Lananna	**Date:**	June 23, 2000

Notes: Test Distance: 3 Meters Temp:24C Humidity: 34%
Detector: Quasi-Peak Below 30 MHz to 1 GHz, Peak above 1 GHz

Test Freq.	Antenna Position	EUT Orientation	Meter Readings	Correction Factor	Corrected Reading	Converted Reading	**LIMIT**
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uV/m	uV/m
30.00							100
|							|
37.6	V/1.0	338	38	-4.3	33.7	48.4	|
|							|
88.00							100
88.00							150
|							|
198.8	V/1.5	090	40	-7.4	32.6	42.7	|
206.4	V/1.5	270	38	-7.2	30.8	34.7	|
226.4	V/1.5	135	38	-6.9	31.1	35.9	|
|							|
216.00							150
216.00							200
|							|
331.4	V/1.0	158	39	-3.2	35.8	61.7	|
333.8	V/1.0	158	42	-3.1	38.9	88.1	|
336.4	V/1.0	158	41	-3.0	38.0	79.4	|
338.4	V/1.0	180	42	-3.0	39.0	89.1	|
341.4	V/1.0	180	42	-2.8	39.2	91.2	|
343.9	V/1.0	158	40	-2.8	37.2	72.4	|
346.4	V/1.0	158	39	-2.6	36.4	66.1	|
348.9	V/1.0	158	39	-2.5	36.5	66.8	|
|							|
960.00							200
960.00							500
|							|
600.0	V/4.0	158	34	3.1	37.1	71.6	|
|							|
1000.0							500

The EUT was scanned from 30 MHz to 1 GHz

The emissions observed from the EUT do not exceed the specified limits. Emissions not recorded were more than 10dB under the specified limit

Retlif Testing Laboratories

Retlif Job Number R-8572-1