



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR 352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

## FCC PART 15.235 TEST REPORT

### LOW POWER UNLICENSED TRANSMITTER

|                      |  |
|----------------------|--|
| Applicant            | YICK SHUN ELECT. TOYS MFG. LTD   |
| Address              | UNIT 4, 15/F, CORNELL CENTRE<br>50 WING TAI ROAD CHAI WAN, HONG KONG   |
| FCC ID               | J7I-YS8005   |
| Product Description  | 49 MHZ WALKIE TALKIE   |
| Date Sample Received | 12/12/2007   |
| Date Tested          | 12/13/2007   |
| Tested By            | JOSEPH SCOGLIO   |
| Approved By          | S. S. SANDERS  |
| Timco Report No.     | 3808AUT7TestReport.doc   |
| Test Results         | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL  
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Certificate # 0955-01

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## TABLE OF CONTENTS

|                             |    |
|-----------------------------|----|
| GENERAL REMARKS .....       | 4  |
| REPORT SUMMARY .....        | 5  |
| TEST ENVIRONMENT.....       | 5  |
| TEST SETUP .....            | 5  |
| DUT SPECIFICATION .....     | 6  |
| TEST EQUIPMENT LIST .....   | 7  |
| TEST PROCEDURES .....       | 8  |
| RADIATION INTERFERENCE..... | 9  |
| OCCUPIED BANDWIDTH.....     | 10 |

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## **GENERAL REMARKS**

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

### **Summary**

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

### **Attestations**

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.



Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.  
849 NW State Road 45  
Newberry, FL 32669

**Authorized Signatory Name:** *S. S. SANDERS*

S. S. Sanders

**Date:** 12/17/2007

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## REPORT SUMMARY

|                                  |  |
|----------------------------------|--|
| Disclaimer                       | The test results only relate to the item tested. |
| Applicable Rule(s)               | FCC Pt 15.235, ANSI C63.4: 2003                  |
| Related Report(s) or Approval(s) | 3808BUT7TestReport.doc                           |

### Receiver

The receiver portion of this system has been tested and meets all of the FCC requirements per FCC rules Part 15.109. A report was issued and a copy of this report is available upon request.

## TEST ENVIRONMENT

|                 |   |
|-----------------|---|
| Test Facility   | The test sites are located at 849 NW State Road 45<br>Newberry, FL 32669 USA. |
| Test Condition: | Temperature: 26°C<br>Relative humidity: 50%                                   |

## TEST SETUP

|   |  |
|---|--|
| Test Exercise (e.g. software description, test signal, etc.): | The DUT was placed in continuous transmit mode of operation. |
| Deviation from the standard(s)                                | No deviation from the standard(s)                            |
| Modification to the DUT:                                      | No modification was made to the DUT.                         |
| Supporting Peripheral Equipment                               | Not applicable. The device is a stand-alone remote control.  |

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## DUT SPECIFICATION

|                   |  |  |  |
|-------------------|--|--|--|
| Applicant         | YICK SHUN ELECT. TOYS MFG. LTD                                   |  |  |
| Description       | 49 MHZ WALKIE TALKIE   |  |  |
| FCC ID            | J7I-YS8005   |  |  |
| Frequency Range   | 49.86-49.86 MHz  |  |  |
| DUT Power Source  | <input type="checkbox"/> 110-120Vac/50- 60Hz                     |  |  |
|                   | <input type="checkbox"/> DC Power                                |  |  |
|                   | <input checked="" type="checkbox"/> Battery Operated Exclusively |  |  |
| Test Item         | <input type="checkbox"/> Prototype                               | <input checked="" type="checkbox"/> Pre-Production | <input type="checkbox"/> Production          |
| Type of Equipment | <input type="checkbox"/> Fixed                                   | <input type="checkbox"/> Mobile                    | <input checked="" type="checkbox"/> Portable |

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

### TEST EQUIPMENT LIST

| Device                                 | Manufacturer    | Model    | Serial Number            | Cal/Char Date  | Due Date |
|--|-----------------|----------|--------------------------|----------------|----------|
| 3/10-Meter OATS                        | TEI             | N/A      | N/A                      | Listed 3/20/07 | 3/19/10  |
| 3-Meter OATS                           | TEI             | N/A      | N/A                      | Listed 1/11/06 | 1/10/09  |
| 3-Meter Semi-Anechoic Chamber          | Panashield      | N/A      | N/A                      | Listed 5/11/07 | 5/10/10  |
| Antenna: Biconnical                    | Eaton           | 94455-1  | 1057                     | CAL 12/12/05   | 12/12/07 |
| Antenna: Biconnical                    | Eaton           | 94455-1  | 1096                     | CAL 10/11/06   | 10/11/08 |
| Antenna: Biconnical                    | Electro-Metrics | BIA-25   | 1171                     | CAL 7/18/07    | 7/18/09  |
| Analyzer Blue Tower Quasi-Peak Adapter | HP              | 85650A   | 2811A01279               | CAL 5/17/07    | 5/17/09  |
| Analyzer Blue Tower RF Preselector     | HP              | 85685A   | 2926A00983               | CAL 5/17/07    | 5/17/09  |
| Analyzer Blue Tower Spectrum Analyzer  | HP              | 8568B    | 2928A04729<br>2848A18049 | CAL 5/17/07    | 5/17/09  |
| LISN                                   | Electro-Metrics | ANS-25/2 | 2604                     | CAL 10/5/06    | 10/5/08  |
| LISN                                   | Electro-Metrics | EM-7820  | 2682                     | CAL 7/23/07    | 7/23/09  |
| Antenna: Log-Periodic                  | Eaton           | 96005    | 1243                     | CAL 12/14/05   | 12/14/07 |

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
 FCC ID: J7I-YS8005  
 REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## TEST PROCEDURES

**Spurious Emissions:** The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was always greater than the RBW.

**Occupied Bandwidth:** A small sample of the transmitter output was fed into the spectrum analyzer and the following plot was generated. The vertical scale is set to 10 dB per division.

**Formula Of Conversion Factors:** The field strength at 3m was established by adding the meter reading of the spectrum analyzer to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB/m. The gain of the preselector was accounted for in the spectrum analyzer reading.

Example:

| Freq<br>MHz | Meter Reading<br>dBuV | ACF<br>dB/m | Cable Loss<br>dB | Field Strength<br>dBuV/m @ 3 m |
|-------------|-----------------------|-------------|------------------|--------------------------------|
| 33          | 20                    | +10.36      | +1.2             | = 31.56                        |

**ANSI C63.4-2003 Measurement:** The DUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The DUT was placed in the center of the table. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the 10th harmonic of the fundamental.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

## RADIATION INTERFERENCE

Rules Part No.: 15.235

### Requirements:

| Frequency MHz         | Limits                                |
|-----------------------|---------------------------------------|
| Fundamental Frequency | 80.0 dB $\mu$ V/m measured @ 3 meters |
| 30 – 88               | 40.0 dB $\mu$ V/m measured @ 3 meters |
| 80 – 216              | 43.5 dB $\mu$ V/m measured @ 3 meters |
| 216 – 960             | 46.0 dB $\mu$ V/m measured @ 3 meters |
| Above 960             | 54.0 dB $\mu$ V/m measured @ 3 meters |

### Test Data:

| Emission Frequency MHz | Meter Reading dBuV | Ant. Pol | Coax Loss dB | Correction Factor dB | Field Strength dBuV/m | Margin dB |
|------------------------|--------------------|----------|--------------|----------------------|-----------------------|-----------|
| 49.80                  | 41.6               | H        | 0.50         | 10.90                | 53.00                 | 27.00     |
| 49.80                  | 53.3               | V        | 0.50         | 10.78                | 64.58                 | 15.42     |
| 99.70                  | 3.3                | H        | 0.65         | 11.19                | 15.14                 | 28.36     |
| 99.70                  | 11.5               | V        | 0.65         | 11.63                | 23.78                 | 19.72     |
| 149.60                 | 11.8               | V        | 0.70         | 14.24                | 26.74                 | 16.76     |
| 149.60                 | 12.2               | H        | 0.70         | 13.87                | 26.77                 | 16.73     |
| 199.50                 | 3.6                | H        | 0.90         | 17.02                | 21.52                 | 21.98     |
| 199.50                 | 5.6                | V        | 0.90         | 17.04                | 23.54                 | 19.96     |
| 249.30                 | 10.8               | H        | 1.00         | 12.56                | 24.36                 | 21.64     |
| 249.30                 | 25.0               | V        | 1.00         | 12.37                | 38.37                 | 7.63      |
| 299.10                 | 15.1               | H        | 1.10         | 14.55                | 30.75                 | 15.25     |
| 299.10                 | 25.2               | V        | 1.10         | 14.55                | 40.85                 | 5.15      |
| 349.00                 | 12.7               | H        | 1.15         | 14.78                | 28.63                 | 17.37     |
| 349.00                 | 29.0               | V        | 1.15         | 14.58                | 44.73                 | 1.27      |
| 398.90                 | 3.5                | H        | 1.20         | 15.98                | 20.68                 | 25.32     |
| 398.90                 | 16.7               | V        | 1.20         | 15.78                | 33.68                 | 12.32     |
| 448.70                 | 4.0                | H        | 1.25         | 17.44                | 22.69                 | 23.31     |
| 448.70                 | 12.5               | V        | 1.25         | 16.94                | 30.69                 | 15.31     |
| 498.60                 | 4.5                | H        | 1.30         | 17.96                | 23.76                 | 22.24     |
| 498.60                 | 10.5               | V        | 1.30         | 17.90                | 29.70                 | 16.30     |

APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD

FCC ID: J7I-YS8005


REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc

## OCCUPIED BANDWIDTH

**Rules Part No.:** 15.235

**Requirements:** The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the un-modulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

**Test Data:** Please refer to the following plot.



APPLICANT: YICK SHUN ELECT. TOYS MFG. LTD  
FCC ID: J7I-YS8005  
REPORT: y\yick\3808AUT7\3808AUT7TestReport.doc