



A D T

# FCC TEST REPORT (15.407)

**REPORT NO.:** RF120406C16

**MODEL NO.:** GT-WS100RX

**FCC ID:** JCK28T0HWS1002

**RECEIVED:** Nov. 07, 2011

**TESTED:** Nov. 07 ~ Nov. 24, 2011

**ISSUED:** Apr. 19, 2012

**APPLICANT:** GIGA-BYTE TECHNOLOGY CO., LTD.

**ADDRESS:** No.6, Bao Chiang Road, Hsin-Tien Dist., New Taipei City 231, Taiwan

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C.)

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 45 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product, certification, approval or endorsement by TAF or any government agency. The test results in the report only apply to the tested sample.



Testing Laboratory  
2021



A D T

## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
1. CERTIFICATION .....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY .....	6
3. GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT.....	7
3.2 DESCRIPTION OF TEST MODES.....	8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	8
3.2.2 DESCRIPTION OF SUPPORT UNITS .....	9
3.2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	10
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	11
4. TEST TYPES AND RESULTS .....	12
4.1 RADIATED EMISSION AND BANDEdge MEASUREMENT.....	12
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT .....	12
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS.....	12
4.1.3 TEST INSTRUMENTS .....	13
4.1.4 TEST PROCEDURES .....	14
4.1.5 DEVIATION FROM TEST STANDARD .....	14
4.1.6 TEST SETUP .....	15
4.1.7 EUT OPERATING CONDITION .....	15
4.1.8 TEST RESULTS .....	16
4.2 CONDUCTED EMISSION MEASUREMENT .....	23
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	23
4.2.2 TEST INSTRUMENTS .....	23
4.2.3 TEST PROCEDURES .....	24
4.2.4 DEVIATION FROM TEST STANDARD .....	24
4.2.5 TEST SETUP .....	25
4.2.6 EUT OPERATING CONDITIONS .....	25
4.2.7 TEST RESULTS .....	26
4.3 MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT .....	30
4.3.1 LIMITS OF MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT .....	30
4.3.2 TEST SETUP .....	30
4.3.3 TEST INSTRUMENTS .....	30
4.3.4 TEST PROCEDURE .....	31
4.3.5 DEVIATION FROM TEST STANDARD .....	31
4.3.6 EUT OPERATING CONDITIONS .....	31
4.3.7 TEST RESULTS .....	32
4.4 PEAK POWER EXCURSION MEASUREMENT .....	33
4.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT.....	33



A D T

4.4.2 TEST SETUP .....	33
4.4.3 TEST INSTRUMENTS .....	33
4.4.4 TEST PROCEDURE .....	33
4.4.5 DEVIATION FROM TEST STANDARD .....	33
4.4.6 EUT OPERATING CONDITIONS .....	33
4.4.7 TEST RESULTS .....	34
4.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	38
4.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	38
4.5.2 TEST SETUP .....	38
4.5.3 TEST INSTRUMENTS .....	38
4.5.4 TEST PROCEDURES .....	38
4.5.5 DEVIATION FROM TEST STANDARD .....	38
4.5.6 EUT OPERATING CONDITIONS .....	38
4.5.7 TEST RESULTS .....	39
4.6 FREQUENCY STABILITY .....	40
4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT .....	40
4.6.2 TEST SETUP .....	40
4.6.3 TEST INSTRUMENTS .....	40
4.6.4 TEST PROCEDURE .....	41
4.6.5 DEVIATION FROM TEST STANDARD .....	41
4.6.6 EUT OPERATING CONDITION .....	41
4.6.7 TEST RESULTS .....	42
5. PHOTOGRAPHS OF THE TEST CONFIGURATION .....	43
6. INFORMATION ON THE TESTING LABORATORIES .....	44
7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	45



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120406C16-1	Original release	Apr. 19, 2012



A D T

## 1. CERTIFICATION

**PRODUCT:** SkyVision WS100

**MODEL:** GT-WS100RX

**BRAND:** Gigabyte

**APPLICANT:** GIGA-BYTE TECHNOLOGY CO., LTD.

**TESTED:** Nov. 07 ~ Nov. 24, 2011

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 15, Subpart E (Section 15.407)

ANSI C63.10-2009

The above equipment (Model: GT-WS100RX) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Polly Chien, DATE: Apr. 19, 2012  
Polly Chien / Specialist

**APPROVED BY** : Gary Chang, DATE: Apr. 19, 2012  
Gary Chang / Technical Manager



A D T

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.407(b)(5)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -11.09dB at 4.000MHz.
15.407(b/1/2/3) (b)(5)	Electric Field Strength Spurious Emissions, 30MHz ~ 40000MHz	PASS	Meet the requirement of limit. Minimum passing margin is -3.4dB at 319.60MHz
15.407(a/1/2/3)	Peak Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit.
15.407(a/1/2/3)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.19 dB
	200MHz ~1000MHz	3.21 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

EUT	SkyVision WS100
MODEL NO.	GT-WS100RX
POWER SUPPLY	5Vdc (adapter or host equipment)
MODULATION TYPE/ TECHNOLOGY	Downlink: OFDM 16-QAM Uplink: OOK
DATA RATE	100kbps
OPERATING FREQUENCY	5180.0 ~ 5240.0MHz
NUMBER OF CHANNEL	4 for channel bandwidth (18MHz) 2 for channel bandwidth (36MHz)
OUTPUT POWER	25.7mW
ANTENNA TYPE	Refer to note as below
ANTENNA CONNECTOR	NA
DATA CABLE	1.2m shielded HDMI cable with 2 cores
I/O PORTS	Refer to user's manual
ACCESSORY DEVICES	Adapter

#### NOTE:

1. The EUT consumes power from the following adapter:

BRAND:	DVE
MODEL:	DSA-12PFA-05 FUS
INPUT:	100-240Vac~, 50/60Hz, 0.5A
OUTPUT:	5Vdc, 2A
POWER LINE:	1.5m non-shielded cable without core

2. The EUT provides one completed transmitter and five receivers.

MODULATION MODE	TX FUNCTION
Channel bandwidth (18MHz)	1TX
Channel bandwidth (36MHz)	1TX

3. The frequency bands used in this EUT are listed as follows:

Frequency Band (MHz)	5180~5240	5745~5805
Channel bandwidth (18MHz)	√	√
Channel bandwidth (36MHz)	√	√

4. The EUT used the following antennas:

ITEM	ANTENNA TYPE	ANTENNA GAIN	ANTENNA CONNECTOR
Antenna 1 (RX)	Printed	2dBi	none
Antenna 2 (RX)	Printed	2dBi	none
Antenna 3 (RX)	Printed	2dBi	none
Antenna 4 (Tx/RX)	Printed	2dBi	none
Antenna 5 (RX)	Printed	2dBi	none

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 DESCRIPTION OF TEST MODES

4 channels are provided for channel bandwidth (18MHz):


<b>FREQUENCY</b>	<b>FREQUENCY</b>
5180MHz	5220MHz
5200MHz	5240MHz

2 channels are provided for channel bandwidth (36MHz):


<b>FREQUENCY</b>	<b>FREQUENCY</b>
5190MHz	5230MHz

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

##### Test Mode A



##### Test Mode B





A D T

### 3.2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	LED TV MONITOR	Panasonic	TH-L32E30W	12500043	FCC DoC Approved
2	NOTEBOOK	DELL	D531	CN-0XM006-48643-81U-2786	QDS-BRCM1020

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	0.2m shielded USB cable without core.

**NOTE:**

1. All power cords of the above support units are non shielded (1.8m).
2. The 0.2m USB cable was provided by the client.



A D T

### 3.2.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	PLC	APCM	
A	✓	✓	✓	✓	Power from adapter
B	-	✓	✓	-	Power from host equipment

Where

RE $\geq$ 1G: Radiated Emission above 1GHzRE $<$ 1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: “-” means no effect.

#### RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUR E MODE	MODE	AVAILABLE FREQUENCY	TESTED FREQUENCY	MODULATION TYPE	DATA RATE (Kbps)
A	Channel bandwidth (18MHz)	5180 to 5240	5180, 5200, 5240	OOK	100
A	Channel bandwidth (36MHz)	5190 to 5230	5190, 5230	OOK	100

#### RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUR E MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Kbps)
A, B	Channel bandwidth (18MHz)	5180 to 5240	5200	OOK	100

#### POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUR E MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Kbps)
A, B	Channel bandwidth (18MHz)	5180 to 5240	5200	OOK	100



A D T

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUR E MODE	MODE	AVAILABLE FREQUENCY	TESTED FREQUENCY	MODULATION TYPE	DATA RATE (Kbps)
A	Channel bandwidth (18MHz)	5180 to 5240	5180, 5200, 5240	OOK	100
A	Channel bandwidth (36MHz)	5190 to 5230	5190, 5230	OOK	100

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE≥1G	25deg. C, 68%RH	120Vac, 60Hz	Match Tsui
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Haru Yang, Antony Lee
PLC	25deg. C, 63%RH	120Vac, 60Hz	Scott Yang
	25deg. C, 65%RH	120Vac, 60Hz	Antony Lee
APCM	25deg. C, 68%RH	120Vac, 60Hz	Match Tsui

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)****ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

FREQUENCIES (MHz)	EIRP LIMIT (dBm)	EQUIVALENT FIELD STRENGTH AT 3m (dB <sub>u</sub> V/m) *NOTE 3
	PK	PK
5150 ~ 5250	-27	68.3

**NOTE:** The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m}, \text{ where } P \text{ is the eirp (Watts).}$$



A D T

#### 4.1.3 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Dec. 27, 2010	Dec. 26, 2011
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Feb. 23, 2011	Feb. 22, 2012
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Apr. 12, 2011	Apr. 11, 2012
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-408	Jan. 06, 2011	Jan. 05, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Dec. 27, 2010	Dec. 26, 2011
Preamplifier Agilent	8449B	3008A01961	Oct. 29, 2011	Oct. 28, 2012
Preamplifier Agilent	8447D	2944A10738	Oct. 29, 2011	Oct. 28, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250792/4	Aug. 19, 2011	Aug. 18, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	283397/4	Aug. 19, 2011	Aug. 18, 2012
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295012/4	Aug. 19, 2011	Aug. 18, 2012
Software ADT.	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA	NA
Turn Table ADT.	TT100.	TT93021704	NA	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 29, 2011	Oct. 28, 2012
High Speed Peak Power Meter	ML2495A	0842014	Apr. 26, 2011	Apr. 25, 2012
Power Sensor	MA2411B	0738404	Apr. 26, 2011	Apr. 25, 2012

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 4.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 460141.
5. The IC Site Registration No. is IC7450F-4.



A D T

#### 4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.1.6 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.7 EUT OPERATING CONDITION

- Set the EUT under transmitting condition continuously at specific channel frequency.



#### 4.1.8 TEST RESULTS

##### Channel bandwidth (18MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL		
TESTED FREQUENCY		5180MHz		FREQUENCY RANGE 1 ~ 40GHz
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 68%RH		TESTED BY Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	45.3 PK	74.0	-28.7	1.12 H	73	6.90	38.40
2	5150.00	35.0 AV	54.0	-19.0	1.12 H	73	-3.40	38.40
3	*5180.00	109.1 PK			1.12 H	73	70.70	38.40
4	*5180.00	95.9 AV			1.12 H	73	57.50	38.40
5	#10360.00	55.8 PK	68.3	-12.5	1.27 H	320	7.50	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	45.1 PK	74.0	-28.9	1.00 V	212	6.70	38.40
2	5150.00	33.6 AV	54.0	-20.4	1.00 V	212	-4.80	38.40
3	*5180.00	103.9 PK			1.00 V	212	65.50	38.40
4	*5180.00	91.3 AV			1.00 V	212	52.90	38.40
5	#10360.00	58.9 PK	68.3	-9.4	1.00 V	3	10.60	48.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



EUT TEST CONDITION		MEASUREMENT DETAIL	
TESTED FREQUENCY	5200MHz	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5190.00	45.1 PK	74.0	-28.9	1.10 H	84	6.70	38.40
2	5190.00	35.0 AV	54.0	-19.0	1.10 H	84	-3.40	38.40
3	*5200.00	108.6 PK			1.10 H	84	70.20	38.40
4	*5200.00	96.1 AV			1.10 H	84	57.70	38.40
5	#10400.00	56.0 PK	68.3	-12.3	1.16 H	316	7.60	48.40
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5190.00	44.9 PK	74.0	-29.1	1.00 V	226	6.50	38.40
2	5190.00	34.8 AV	54.0	-19.2	1.00 V	226	-3.60	38.40
3	*5200.00	104.0 PK			1.00 V	226	65.60	38.40
4	*5200.00	91.5 AV			1.00 V	226	53.10	38.40
5	#10400.00	57.7 PK	68.3	-10.6	1.00 V	179	9.30	48.40

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
TESTED FREQUENCY	5240MHz	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	108.8 PK			1.11 H	76	70.30	38.50
2	*5240.00	96.0 AV			1.11 H	76	57.50	38.50
3	5350.00	45.1 PK	74.0	-28.9	1.11 H	76	6.40	38.70
4	5350.00	34.6 AV	54.0	-19.4	1.11 H	76	-4.10	38.70
5	#10480.00	56.1 PK	68.3	-12.2	1.19 H	331	7.60	48.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	103.8 PK			1.00 V	250	65.30	38.50
2	*5240.00	91.1 AV			1.00 V	250	52.60	38.50
3	5350.00	45.0 PK	74.0	-29.0	1.00 V	250	6.30	38.70
4	5350.00	33.6 AV	54.0	-20.4	1.00 V	250	-5.10	38.70
5	#10480.00	57.8 PK	68.3	-10.5	1.00 V	181	9.30	48.50

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



A D T

## Channel bandwidth (36MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL		
TESTED FREQUENCY		5190MHz		FREQUENCY RANGE 1 ~ 40GHz
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		25deg. C, 68%RH		TESTED BY Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	56.0 PK	74.0	-18.0	1.04 H	33	17.60	38.40
2	5150.00	36.1 AV	54.0	-17.9	1.04 H	33	-2.30	38.40
3	*5190.00	105.6 PK			1.04 H	33	67.20	38.40
4	*5190.00	93.3 AV			1.04 H	33	54.90	38.40
5	#10380.00	58.2 PK	68.3	-10.1	1.30 H	250	9.90	48.30

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	52.0 PK	74.0	-22.0	1.00 V	212	13.60	38.40
2	5150.00	34.7 AV	54.0	-19.3	1.00 V	212	-3.70	38.40
3	*5190.00	100.7 PK			1.00 V	212	62.30	38.40
4	*5190.00	87.7 AV			1.00 V	212	49.30	38.40
5	#10380.00	59.4 PK	68.3	-8.9	1.35 V	120	11.10	48.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
TESTED FREQUENCY	5230MHz	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH	TESTED BY	Match Tsui

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	105.5 PK			1.03 H	33	67.00	38.50
2	*5230.00	92.7 AV			1.03 H	33	54.20	38.50
3	5350.00	45.2 PK	74.0	-28.8	1.03 H	33	6.50	38.70
4	5350.00	34.1 AV	54.0	-19.9	1.03 H	33	-4.60	38.70
5	#10460.00	57.8 PK	68.3	-10.5	1.32 H	253	9.30	48.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5230.00	100.2 PK			1.00 V	214	61.70	38.50
2	*5230.00	87.3 AV			1.00 V	214	48.80	38.50
3	5350.00	45.6 PK	74.0	-28.4	1.00 V	214	6.90	38.70
4	5350.00	33.7 AV	54.0	-20.3	1.00 V	214	-5.00	38.70
5	#10460.00	59.9 PK	68.3	-8.4	1.32 V	127	11.40	48.50

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency.
6. "#": The radiated frequency is out the restricted band.



A D T

## BELOW 1GHz WORST-CASE DATA : Channel bandwidth (18MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL			
TESTED FREQUENCY		5200MHz		FREQUENCY RANGE	
INPUT POWER		120Vac, 60 Hz		DETECTOR FUNCTION	
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	
TEST MODE		A			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	239.88	37.1 QP	46.0	-8.9	1.25 H	106	23.90	13.20
2	300.16	33.8 QP	46.0	-12.2	1.00 H	244	18.50	15.30
3	<b>319.60</b>	<b>42.6 QP</b>	<b>46.0</b>	<b>-3.4</b>	<b>1.00 H</b>	<b>244</b>	<b>26.70</b>	<b>15.90</b>
4	399.31	34.0 QP	46.0	-12.0	1.00 H	241	15.40	18.60
5	799.84	32.1 QP	46.0	-13.9	1.00 H	142	4.70	27.40
6	832.89	36.6 QP	46.0	-9.4	2.00 H	283	8.70	27.90
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	109.62	23.7 QP	43.5	-19.8	1.50 V	328	11.80	11.90
2	239.88	29.1 QP	46.0	-16.9	1.25 V	52	15.90	13.20
3	319.60	32.4 QP	46.0	-13.6	1.00 V	217	16.50	15.90
4	399.31	33.4 QP	46.0	-12.6	2.00 V	178	14.80	18.60
5	799.84	30.2 QP	46.0	-15.8	1.25 V	190	2.80	27.40
6	926.22	28.2 QP	46.0	-17.8	1.25 V	205	-0.70	28.90

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL			
TESTED FREQUENCY		5200MHz		FREQUENCY RANGE	
INPUT POWER (SYSTEM)		120Vac, 60 Hz		DETECTOR FUNCTION	
ENVIRONMENTAL CONDITIONS		25deg. C, 65%RH		TESTED BY	
TEST MODE		B			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	66.84	32.7 QP	40.0	-7.3	2.00 H	145	19.60	13.10
2	240.00	37.9 QP	46.0	-8.1	2.00 H	49	24.60	13.30
3	319.71	40.2 QP	46.0	-5.8	1.00 H	61	24.20	16.00
4	399.31	32.6 QP	46.0	-13.4	1.25 H	1	14.00	18.60
5	690.96	30.2 QP	46.0	-15.8	1.00 H	319	5.30	24.90
6	914.55	34.2 QP	46.0	-11.8	1.25 H	352	5.40	28.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.84	34.8 QP	40.0	-5.2	1.00 V	313	21.90	12.90
2	66.84	31.6 QP	40.0	-8.4	1.00 V	331	18.50	13.10
3	99.89	36.8 QP	43.5	-6.7	1.00 V	229	25.60	11.20
4	401.26	32.5 QP	46.0	-13.5	1.25 V	328	13.80	18.70
5	673.46	28.6 QP	46.0	-17.4	1.25 V	322	3.90	24.70
6	850.39	32.9 QP	46.0	-13.1	1.00 V	274	4.80	28.10

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 23, 2010	Nov. 22, 2011
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 30, 2010	Dec. 29, 2011
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 06, 2011	Jan. 05, 2012
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Jul. 07, 2011	Jul. 06, 2012
Software ADT	ADT_Cond_V7.3.7	NA	NA	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.



A D T

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.2.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

#### 4.2.7 TEST RESULTS


##### CONDUCTED WORST-CASE DATA : Channel bandwidth (18MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	Q.P.	AV.	Q.P.	AV.
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.150	0.16	43.45	28.75	43.61	28.91	66.00	56.00	-22.39	-27.09
2	0.271	0.18	41.30	34.68	41.48	34.86	61.08	51.08	-19.60	-16.22
3	0.474	0.20	32.69	21.77	32.89	21.97	56.44	46.44	-23.55	-24.47
4	0.834	0.22	31.89	21.11	32.11	21.33	56.00	46.00	-23.89	-24.67
5	4.184	0.38	31.89	21.19	32.27	21.57	56.00	46.00	-23.73	-24.43
6	7.125	0.50	33.42	23.30	33.92	23.80	60.00	50.00	-26.08	-26.20

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	A		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.150	0.19	43.25	26.19	43.44	26.38	66.00	56.00	-22.56	-29.62
2	0.271	0.19	41.50	35.18	41.69	35.37	61.08	51.08	-19.39	-15.71
3	0.455	0.21	31.41	21.08	31.62	21.29	56.79	46.79	-25.17	-25.50
4	0.861	0.21	29.12	18.94	29.33	19.15	56.00	46.00	-26.67	-26.85
5	1.887	0.24	27.31	17.11	27.55	17.35	56.00	46.00	-28.45	-28.65
6	6.203	0.44	28.17	17.62	28.61	18.06	60.00	50.00	-31.39	-31.94

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.




PHASE	Line 1	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	Q.P.	AV.
		[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.170	0.12	50.54	40.20	50.66	40.32	64.98	54.98	-14.33	-14.67
2	0.224	0.12	43.18	37.65	43.30	37.77	62.66	52.66	-19.36	-14.89
3	0.283	0.12	38.52	33.30	38.64	33.42	60.73	50.73	-22.09	-17.31
4	3.156	0.26	36.51	21.70	36.77	21.96	56.00	46.00	-19.23	-24.04
<b>5</b>	<b>4.000</b>	<b>0.31</b>	<b>44.60</b>	<b>30.43</b>	<b>44.91</b>	<b>30.74</b>	<b>56.00</b>	<b>46.00</b>	<b>-11.09</b>	<b>-15.26</b>
6	5.297	0.39	34.37	23.13	34.76	23.52	60.00	50.00	-25.24	-26.48

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




PHASE	Line 2	6dB BANDWIDTH	9kHz
TEST MODE	B		

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	Q.P.	AV.	Q.P.	AV.
		[MHz]	(dB)	Q.P.	AV.	Q.P.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.13	50.16	39.50	50.29	39.63	64.98	54.98	-14.70	-15.36
2	0.224	0.13	43.76	38.17	43.89	38.30	62.66	52.66	-18.77	-14.36
3	0.283	0.13	37.31	31.32	37.44	31.45	60.73	50.73	-23.29	-19.28
4	0.339	0.14	34.11	30.03	34.25	30.17	59.24	49.24	-24.99	-19.07
5	3.887	0.31	40.76	29.16	41.07	29.47	56.00	46.00	-14.93	-16.53
6	5.180	0.38	33.11	20.79	33.49	21.17	60.00	50.00	-26.51	-28.83

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



## 4.3 MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT


### 4.3.1 LIMITS OF MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

FREQUENCY BAND	LIMIT
5.15 ~ 5.25GHz	The lesser of 50mW (17dBm) or 4dBm + 10logB

**NOTE:** Where B is the 26dB emission bandwidth in MHz.

### 4.3.2 TEST SETUP

#### FOR POWER OUTPUT MEASUREMENT



#### FOR 26dB OCCUPIED BANDWIDTH



### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.



A D T

#### 4.3.4 TEST PROCEDURE

##### FOR AVERAGE POWER MEASUREMENT

A power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

##### FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

#### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually



A D T

#### 4.3.7 TEST RESULTS

##### POWER OUTPUT:

###### Channel bandwidth (18MHz)

CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
5180	25.1	14.0	17	PASS
5200	25.7	14.1	17	PASS
5240	25.7	14.1	17	PASS

###### Channel bandwidth (36MHz)

CHANNEL FREQUENCY (MHz)	POWER OUTPUT (mW)	POWER OUTPUT (dBm)	POWER LIMIT (dBm)	PASS/FAIL
5190	25.1	14.0	17	PASS
5230	25.7	14.1	17	PASS

##### 26dB BANDWIDTH:

###### Channel bandwidth (18MHz)

CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
5180	19.61	PASS
5210	19.68	PASS
5240	19.56	PASS

###### Channel bandwidth (36MHz)


FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)	PASS / FAIL
5190	40.27	PASS
5230	40.33	PASS

## 4.4 PEAK POWER EXCURSION MEASUREMENT

### 4.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Shall not exceed 13 dB

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.4.4 TEST PROCEDURE

- 1) Set RBW = 1 MHz, VBW  $\leq$  3 MHz, Detector = peak.
- 2) Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
- 3) Use the peak search function to find the peak of the spectrum.
- 4) Measure the PPSD.
- 5) Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.4.6 EUT OPERATING CONDITIONS

Same as 4.2.6



A D T



#### 4.4.7 TEST RESULTS

##### Channel bandwidth (18MHz)

CHANNEL FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD (dBm)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
5180	14.34	3.42	10.92	13	PASS
5200	14.62	3.69	10.93	13	PASS
5240	14.21	3.39	10.82	13	PASS



A D T







A D T

Channel bandwidth (36MHz)

CHANNEL FREQUENCY (MHz)	PEAK VALUE (dBm)	PPSD (dBm)	PEAK POWER EXCURSION (dB)	PEAK to AVERAGE EXCURSION LIMIT (dB)	PASS/FAIL
5190	10.67	0.20	10.47	13	PASS
5230	10.86	0.14	10.72	13	PASS



A D T




## 4.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

FREQUENCY BAND	LIMIT(dBm)
5.15 ~ 5.25GHz	4
5.25 ~ 5.35GHz and 5.470 ~ 5.725GHz	11
5.725~5825GHz	17

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.5.4 TEST PROCEDURES

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1 MHz, Set VBW  $\geq$  3 MHz, Detector = RMS
- 3) Sweep time = 26 second.
- 4) Perform a single sweep.
- 5) Record the max value

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6.



A D T

#### 4.5.7 TEST RESULTS

##### Channel bandwidth (18MHz)

FREQUENCY (MHz)	PSD (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
5180	3.42	4	PASS
5220	3.69	4	PASS
5240	3.39	4	PASS

##### Channel bandwidth (36MHz)


CHANNEL FREQUENCY (MHz)	PSD (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
5190	0.20	4	PASS
5230	0.14	4	PASS

## 4.6 FREQUENCY STABILITY

### 4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.



A D T

#### 4.6.4 TEST PROCEDURE

- a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.



A D T

#### 4.6.7 TEST RESULTS

FREQUEMCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5200MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (ppm)						
50	110.0	5199.987683	-2.369	5199.987997	-2.308	5199.987658	-2.373	5199.987870	-2.333
40	110.0	5199.988510	-2.210	5199.988733	-2.167	5199.988683	-2.176	5199.988868	-2.141
30	110.0	5199.989834	-1.955	5199.989554	-2.009	5199.990133	-1.897	5199.989672	-1.986
20	110.0	5199.991404	-1.653	5199.991343	-1.665	5199.991948	-1.548	5199.991285	-1.676
10	110.0	5199.992589	-1.425	5199.992887	-1.368	5199.992867	-1.372	5199.992496	-1.443
0	110.0	5199.991041	-1.723	5199.990984	-1.734	5199.991369	-1.660	5199.991276	-1.678
-10	110.0	5199.989568	-2.006	5199.989656	-1.989	5199.989656	-1.989	5199.990216	-1.882
-20	110.0	5199.989158	-2.085	5199.989613	-1.997	5199.989656	-1.989	5199.989292	-2.059
-30	110.0	5199.988198	-2.270	5199.988771	-2.159	5199.988063	-2.296	5199.988222	-2.265

FREQUEMCY STABILITY VERSUS VOLTAGE									
OPERATING FREQUENCY: 5200MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (ppm)						
20	93.5	5199.990288	-1.868	5199.989596	-2.001	5199.990026	-1.918	5199.989951	-1.932
	110.0	5199.991404	-1.653	5199.991343	-1.665	5199.991948	-1.548	5199.991285	-1.676
	126.5	5199.992558	-1.431	5199.992998	-1.347	5199.992584	-1.426	5199.992966	-1.353



A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation and authorization certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5.phtml](http://www.adt.com.tw/index.5.phtml). If you have any comments, please feel free to contact us at the following:

### **Linko EMC/RF Lab**

Tel: 886-2-26052180  
Fax: 886-2-26051924

### **Hsin Chu EMC/RF Lab**

Tel: 886-3-5935343  
Fax: 886-3-5935342

### **Hwa Ya EMC/RF/Safety/Telecom Lab**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## 7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---