



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	SMC Networks Inc.
Applicant Address	20 Mason, Irvine, CA 92618 USA
FCC ID	J15-AR9381DB24
Manufacturer's company	MAINTEK COMPUTER
Manufacturer Address	233 Jinfeng Rd., Suzhou, Jiangsu, PRC

Product Name	Wireless Data Gateway
Brand Name	SMC
Model No.	D3G2408WEXXXXXXX (X=0-9,A-Z or "-")
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Dec. 02, 2014
Final Test Date	Feb. 13, 2015
Submission Type	Original Equipment

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r02 and KDB 662911 D01 v02r01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	5
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	7
3.7. Table for Multiple Listing.....	7
3.8. Table for Supporting Units	7
3.9. Table for Parameters of Test Software Setting	8
3.10. EUT Operation during Test	8
3.11. Duty Cycle	8
3.12. Test Configurations	9
4. TEST RESULT	11
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Maximum Conducted Output Power Measurement.....	15
4.3. Power Spectral Density Measurement	17
4.4. 6dB Spectrum Bandwidth Measurement	28
4.5. Radiated Emissions Measurement	35
4.6. Emissions Measurement	53
4.7. Antenna Requirements	71
5. LIST OF MEASURING EQUIPMENTS	72
6. MEASUREMENT UNCERTAINTY.....	73
APPENDIX A. TEST PHOTOS	A1 ~ A5


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4N2724	Rev. 01	Initial issue of report	Mar. 17, 2015

1. VERIFICATION OF COMPLIANCE

Product Name : Wireless Data Gateway
Brand Name : SMC
Model No. : D3G2408WEXXXXXXX (X=0-9,A-Z or "-")
Applicant : SMC Networks Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 02, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	16.34 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.54 dB
4.3	15.247(e)	Power Spectral Density	Complies	1.2 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.16 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.03 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	IEEE 802.11b: 10.32 MHz IEEE 802.11g: 17.23 MHz IEEE 802.11n MCS0 (HT20): 18.00 MHz IEEE 802.11n MCS0 (HT40): 38.80 MHz
Maximum Conducted Output Power	IEEE 802.11b: 29.46 dBm IEEE 802.11g: 26.76 dBm IEEE 802.11n MCS0 (HT20): 27.52 dBm IEEE 802.11n MCS0 (HT40): 19.00 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Beamforming Function	☐ With beamforming ☒ Without beamforming

Antenna and Band width

Antenna	Three (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	X	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS 0-23
802.11n (HT40)	3	MCS 0-23
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n		

3.2. Accessories

Power	Brand	Model	Rating
Adapter	AtechOEM	A050112-T81	INPUT: 100-240V ~ 50-60Hz 1.4A OUTPUT: 12V, 4.17A

3.3. Table for Filed Antenna


Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	Airgain	N2420S-T-PK1-G45U	PCB Antenna	I-PEX	1.8
2	Airgain	N2420S-T-PK1-G135U	PCB Antenna	I-PEX	1.8
3	Airgain	N2420S-T-PK1-G60U	PCB Antenna	I-PEX	1.8

Note: The EUT has three antennas.

For IEEE 802.11b/g/n mode:

Chain 1, Chain 2 and Chain 3 can be used as transmitting/receiving antenna.

Chain 1, Chain 2 and Chain 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Power Spectral Density	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Radiated Emissions 9kHz~1GHz	CTX	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
Band Edge Emissions	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3

The following test modes were performed for all tests:

For all test items:

Mode 1. CTX.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Multiple Listing

D3G2408WEXXXXXXX

The X could be "0-9", "A-Z" or "-", only for marketing purpose. Marketing segmentation.

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	DoC

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E4300	DoC

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	DOS					
Mode	Test Frequency (MHz)					
	NCB: 20MHz			NCB: 40MHz		
	2412 MHz	2437 MHz	2462 MHz	2422 MHz	2437 MHz	2452 MHz
802.11b	19.5	25.5	19.5	-	-	-
802.11g	15	22.5	15.5	-	-	-
802.11n MCS0 HT20	14.5	23.5	14	-	-	-
802.11n MCS0 HT40	-	-	-	10	14.5	11

3.10. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.11. Duty Cycle

Mode	On Time (ms)	On+Off Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T Minimum VBW (kHz)
802.11b	1	1	100.00%	0.00	0.01
802.11g	2.024	2.068	97.87%	0.09	0.49
802.11n MCS0 HT20	2.02	2.060	98.06%	0.09	0.01
802.11n MCS0 HT40	0.880	0.947	92.93%	0.32	1.14


3.12. Test Configurations

3.12.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	3.5m
2	RJ-45 cable	No	10m

3.12.2. Radiation Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	3.5m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	52%
Test Engineer	Kane Liu	Phase	Line
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15485	31.66	-24.08	55.74	21.47	10.03	0.16	AVERAGE	LINE
2	0.15485	46.21	-19.53	65.74	36.02	10.03	0.16	QP	LINE
3	0.16155	44.31	-21.07	65.38	34.12	10.03	0.16	QP	LINE
4	0.16155	27.47	-27.91	55.38	17.28	10.03	0.16	AVERAGE	LINE
5	0.16944	43.33	-21.66	64.99	33.14	10.03	0.16	QP	LINE
6	0.16944	24.69	-30.30	54.99	14.50	10.03	0.16	AVERAGE	LINE
7	0.18056	25.97	-28.49	54.46	15.78	10.03	0.16	AVERAGE	LINE
8	0.18056	41.43	-23.03	64.46	31.24	10.03	0.16	QP	LINE
9	0.19654	39.41	-24.34	63.76	29.22	10.03	0.16	QP	LINE
10	0.19654	24.84	-28.91	53.76	14.65	10.03	0.16	AVERAGE	LINE
11	0.59164	39.03	-16.97	56.00	28.82	10.02	0.19	QP	LINE
12	0.59164	29.66	-16.34	46.00	19.45	10.02	0.19	AVERAGE	LINE

Temperature	25°C	Humidity	52%
Test Engineer	Kane Liu	Phase	Neutral
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15900	45.95	-19.57	65.52	35.84	9.95	0.16	QP	NEUTRAL
2	0.15900	27.24	-28.28	55.52	17.13	9.95	0.16	AVERAGE	NEUTRAL
3	0.17034	43.44	-21.50	64.94	33.32	9.96	0.16	QP	NEUTRAL
4	0.17034	20.83	-34.11	54.94	10.71	9.96	0.16	AVERAGE	NEUTRAL
5	0.17961	24.14	-30.37	54.50	14.01	9.96	0.16	AVERAGE	NEUTRAL
6	0.17961	42.15	-22.36	64.50	32.02	9.96	0.16	QP	NEUTRAL
7	0.59478	29.21	-16.79	46.00	19.14	9.88	0.19	AVERAGE	NEUTRAL
8	0.59478	36.69	-19.31	56.00	26.62	9.88	0.19	QP	NEUTRAL
9	3.681	34.06	-21.94	56.00	23.88	9.89	0.29	QP	NEUTRAL
10	3.681	23.61	-22.39	46.00	13.43	9.89	0.29	AVERAGE	NEUTRAL
11	3.943	35.61	-20.39	56.00	25.42	9.89	0.30	QP	NEUTRAL
12	3.943	25.30	-20.70	46.00	15.11	9.89	0.30	AVERAGE	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r02 section 9.2.3.2 Measurement using a power meter (PM).
2. Multiple antenna systems was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	26°C	Humidity	63%
Test Engineer	Jim Huang	Test Date	Feb. 12, 2015

Mode	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Chain 1	Chain 2	Chain 3	Total		
802.11b	2412 MHz	18.63	17.83	18.13	22.98	30.00	Complies
	2437 MHz	25.72	23.73	24.36	29.46	30.00	Complies
	2462 MHz	18.68	18.62	19.62	23.77	30.00	Complies
802.11g	2412 MHz	15.35	13.68	13.27	18.97	30.00	Complies
	2437 MHz	22.90	21.53	21.38	26.76	30.00	Complies
	2462 MHz	15.33	15.07	14.82	19.85	30.00	Complies
802.11n MCS0 HT20	2412 MHz	14.51	14.01	13.89	18.92	30.00	Complies
	2437 MHz	23.72	22.24	22.10	27.52	30.00	Complies
	2462 MHz	14.12	13.08	12.63	18.09	30.00	Complies
802.11n MCS0 HT40	2422 MHz	10.72	9.63	9.20	14.67	30.00	Complies
	2437 MHz	15.03	13.91	13.63	19.00	30.00	Complies
	2452 MHz	11.56	10.42	10.28	15.56	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	26°C	Humidity	63%
Test Engineer	Jim Huang		


Mode	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Chain 1	Chain 2	Chain 3	Total		
802.11b	2412 MHz	-2.67	-4.60	-4.13	1.05	7.43	Complies
	2437 MHz	2.24	1.09	0.94	6.23	7.43	Complies
	2462 MHz	-2.48	-4.75	-4.83	0.89	7.43	Complies
802.11g	2412 MHz	-8.57	-10.09	-9.09	-4.43	7.43	Complies
	2437 MHz	-0.57	-1.78	-2.30	3.28	7.43	Complies
	2462 MHz	-8.65	-9.72	-8.91	-4.30	7.43	Complies
802.11n MCS0 HT20	2412 MHz	-8.53	-9.84	-10.01	-4.64	7.43	Complies
	2437 MHz	0.06	-0.79	-0.98	4.23	7.43	Complies
	2462 MHz	-10.48	-10.61	-11.16	-5.97	7.43	Complies
802.11n MCS0 HT40	2422 MHz	-17.11	-17.26	-18.33	-12.76	7.43	Complies
	2437 MHz	-10.91	-13.76	-12.21	-7.37	7.43	Complies
	2452 MHz	-15.53	-17.63	-17.53	-12.01	7.43	Complies

Note 1: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left(\sum_{i=1}^{N_{CH}} g_{ij} \right)^2}{N_{ANT}} \right] = 6.57 \text{ dBi}$, so limit = 8 (6.57-6) = 7.43 dBm/3kHz

Note 2: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1




Date: 12.FEB.2015 00:10:51

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 2




Date: 12.FEB.2015 00:09:30

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 3




Date: 12.FEB.2015 00:10:07

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1




Date: 12.FEB.2015 00:17:26

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 2




Date: 12.FEB.2015 00:18:09

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 3




Date: 12.FEB.2015 00:18:58

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1




Date: 12.FEB.2015 00:26:07

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 2




Date: 12.FEB.2015 00:25:24

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 3




Date: 12.FEB.2015 00:24:45

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1




Date: 12.FEB.2015 00:32:24

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 2



Date: 12.FEB.2015 00:33:13

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 3



Date: 12.FEB.2015 00:33:49

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

6dB Spectrum Bandwidth	
Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth	
Spectrum Parameters	Setting
Span	1.5 times to 5.0 times the OBW
RBW	1 % to 5 % of the OBW
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) - section 8.0 DTS bandwidth= > 8.1 Option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth


Temperature	26°C	Humidity	63%
Test Engineer	Jim Huang		

Mode	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
802.11b	2412 MHz	11.12	10.32	500	Complies
	2437 MHz	10.08	10.20	500	Complies
	2462 MHz	11.04	10.32	500	Complies
802.11g	2412 MHz	16.24	17.28	500	Complies
	2437 MHz	16.40	17.28	500	Complies
	2462 MHz	16.40	17.28	500	Complies
802.11n MCS0 HT20	2412 MHz	16.08	17.76	500	Complies
	2437 MHz	15.76	18.00	500	Complies
	2462 MHz	16.08	18.00	500	Complies
802.11n MCS0 HT40	2422 MHz	30.72	38.40	500	Complies
	2437 MHz	30.72	38.60	500	Complies
	2452 MHz	36.48	38.80	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:41:30

99% Occupied Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:55:24

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:44:03

99% Occupied Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:56:41

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:46:50

99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Chain 1 + Chain 2 + Chain 3




Date: 12.FEB.2015 00:59:27

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Chain 1 + Chain 2 + Chain 3



Date: 12.FEB.2015 00:49:55

99% Occupied Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2452 MHz / Chain 1 + Chain 2 + Chain 3



Date: 12.FEB.2015 01:02:45

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	CTX
Test Date	Dec. 02, 2014		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	CTX

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	30.00	30.32	40.00	-9.68	38.75	0.61	18.76	27.80	QP	288	112	HORIZONTAL
2	125.06	38.09	43.50	-5.41	52.03	1.33	12.21	27.48	Peak	100	0	HORIZONTAL
3	250.19	33.40	46.00	-12.60	45.85	1.78	12.77	27.00	Peak	100	0	HORIZONTAL
4	375.32	42.21	46.00	-3.79	52.04	2.20	15.40	27.43	Peak	100	0	HORIZONTAL
5	467.47	35.49	46.00	-10.51	43.77	2.54	17.12	27.94	Peak	100	0	HORIZONTAL
6	625.58	37.99	46.00	-8.01	44.31	2.90	18.85	28.07	Peak	100	0	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	30.97	34.47	40.00	-5.53	43.42	0.63	18.22	27.80	QP	277	134	VERTICAL
2	36.79	36.09	40.00	-3.91	48.32	0.68	14.89	27.80	Peak	400	0	VERTICAL
3	47.46	35.93	40.00	-4.07	53.51	0.80	9.42	27.80	Peak	400	0	VERTICAL
4	54.25	36.49	40.00	-3.51	55.59	0.85	7.83	27.78	Peak	400	0	VERTICAL
5	59.10	36.12	40.00	-3.88	56.03	0.90	6.95	27.76	Peak	400	0	VERTICAL
6	62.98	36.02	40.00	-3.98	56.11	0.93	6.73	27.75	Peak	400	0	VERTICAL
7	375.32	39.50	46.00	-6.50	49.33	2.20	15.40	27.43	Peak	400	0	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11b CH 1 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
						dB	dB/m	dB			Pol/Phase
1	4824.15	41.58	54.00	-12.42	37.52	5.87	33.39	35.20	Average	231	290 HORIZONTAL
2	4824.21	48.06	74.00	-25.94	44.00	5.87	33.39	35.20	Peak	231	290 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
						dB	dB/m	dB			Pol/Phase
1	4824.14	46.73	74.00	-27.27	42.67	5.87	33.39	35.20	Peak	178	264 VERTICAL
2	4824.16	37.37	54.00	-16.63	33.31	5.87	33.39	35.20	Average	178	264 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11b CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4874.31	53.84	54.00	-0.16	49.64	5.92	33.48	35.20	Average	163	287 HORIZONTAL
2	4874.39	56.73	74.00	-17.27	52.53	5.92	33.48	35.20	Peak	163	287 HORIZONTAL
3	7312.24	46.57	54.00	-7.43	38.36	7.13	36.51	35.43	Average	168	47 HORIZONTAL
4	7313.04	62.22	74.00	-11.78	54.01	7.13	36.51	35.43	Peak	168	47 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4874.28	48.88	54.00	-5.12	44.68	5.92	33.48	35.20	Average	213	43 VERTICAL
2	4874.38	52.80	74.00	-21.20	48.60	5.92	33.48	35.20	Peak	213	43 VERTICAL
3	7308.60	48.32	54.00	-5.68	40.11	7.13	36.51	35.43	Average	155	280 VERTICAL
4	7308.78	55.30	74.00	-18.70	47.09	7.13	36.51	35.43	Peak	155	280 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11b CH 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4924.08	36.34	54.00	-17.66	31.99	5.97	33.58	35.20	Average	234	299 HORIZONTAL
2	4924.10	47.17	74.00	-26.83	42.82	5.97	33.58	35.20	Peak	234	299 HORIZONTAL
3	7382.82	50.48	74.00	-23.52	42.16	7.16	36.61	35.45	Peak	100	152 HORIZONTAL
4	7386.78	38.11	54.00	-15.89	29.79	7.17	36.61	35.46	Average	100	152 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4924.00	33.80	54.00	-20.20	29.45	5.97	33.58	35.20	Average	195	249 VERTICAL
2	4924.36	45.46	74.00	-28.54	41.11	5.97	33.58	35.20	Peak	195	249 VERTICAL
3	7386.78	39.59	54.00	-14.41	31.27	7.17	36.61	35.46	Average	190	284 VERTICAL
4	7387.18	50.74	74.00	-23.26	42.42	7.17	36.61	35.46	Peak	190	284 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11g CH 1 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4816.53	45.83	74.00	-28.17	41.80	5.87	33.36	35.20 Peak	100	199	HORIZONTAL
2	4826.66	33.22	54.00	-20.78	29.16	5.87	33.39	35.20 Average	100	199	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4815.38	32.79	54.00	-21.21	28.78	5.85	33.36	35.20 Average	100	26	VERTICAL
2	4824.42	45.85	74.00	-28.15	41.79	5.87	33.39	35.20 Peak	100	26	VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11g CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4871.18	52.53	74.00	-21.47	48.33	5.92	33.48	35.20	Peak	198	77 HORIZONTAL
2	4871.53	38.43	54.00	-15.57	34.23	5.92	33.48	35.20	Average	198	77 HORIZONTAL
3	7308.82	52.43	74.00	-21.57	44.22	7.13	36.51	35.43	Peak	230	326 HORIZONTAL
4	7310.10	39.87	54.00	-14.13	31.66	7.13	36.51	35.43	Average	230	326 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	4870.12	35.87	54.00	-18.13	31.70	5.92	33.45	35.20	Average	183	55 VERTICAL
2	4876.12	51.08	74.00	-22.92	46.88	5.92	33.48	35.20	Peak	183	55 VERTICAL
3	7314.85	40.51	54.00	-13.49	32.30	7.13	36.51	35.43	Average	225	324 VERTICAL
4	7315.74	53.62	74.00	-20.38	45.40	7.14	36.51	35.43	Peak	225	324 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11g CH 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4925.20	32.34	54.00	-21.66	27.99	5.97	33.58	35.20 Average	100	212	HORIZONTAL
2	4927.37	45.40	74.00	-28.60	41.05	5.97	33.58	35.20 Peak	100	212	HORIZONTAL
3	7389.48	36.90	54.00	-17.10	28.58	7.17	36.61	35.46 Average	100	340	HORIZONTAL
4	7389.69	50.70	74.00	-23.30	42.38	7.17	36.61	35.46 Peak	100	340	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4927.05	45.66	74.00	-28.34	41.31	5.97	33.58	35.20 Peak	100	323	VERTICAL
2	4927.17	32.27	54.00	-21.73	27.92	5.97	33.58	35.20 Average	100	323	VERTICAL
3	7385.41	37.02	54.00	-16.98	28.70	7.17	36.61	35.46 Average	100	30	VERTICAL
4	7388.23	50.47	74.00	-23.53	42.15	7.17	36.61	35.46 Peak	100	30	VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4824.61	46.05	74.00	-27.95	41.99	5.87	33.39	35.20	100	237	HORIZONTAL
2	4828.30	32.28	54.00	-21.72	28.22	5.87	33.39	35.20	100	237	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4824.64	32.30	54.00	-21.70	28.24	5.87	33.39	35.20	100	112	VERTICAL
2	4828.10	45.58	74.00	-28.42	41.52	5.87	33.39	35.20	100	112	VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	4873.30	52.64	74.00	-21.36	48.44	5.92	33.48	35.20	Peak	177	120 HORIZONTAL
2	4873.62	39.05	54.00	-14.95	34.85	5.92	33.48	35.20	Average	177	120 HORIZONTAL
3	7307.57	57.58	74.00	-16.42	49.37	7.13	36.51	35.43	Peak	151	31 HORIZONTAL
4	7313.69	39.68	54.00	-14.32	31.47	7.13	36.51	35.43	Average	151	31 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	4876.63	52.93	74.00	-21.07	48.73	5.92	33.48	35.20	Peak	198	60 VERTICAL
2	4876.69	37.23	54.00	-16.77	33.03	5.92	33.48	35.20	Average	198	60 VERTICAL
3	7319.01	54.54	74.00	-19.46	46.32	7.14	36.51	35.43	Peak	215	322 VERTICAL
4	7319.11	41.38	54.00	-12.62	33.16	7.14	36.51	35.43	Average	215	322 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4916.63	44.57	74.00	-29.43	40.28	5.95	33.54	35.20 Peak	101	118	HORIZONTAL
2	4933.68	31.84	54.00	-22.16	27.49	5.97	33.58	35.20 Average	101	118	HORIZONTAL
3	7378.12	49.86	74.00	-24.14	41.54	7.16	36.61	35.45 Peak	101	342	HORIZONTAL
4	7385.30	36.76	54.00	-17.24	28.44	7.17	36.61	35.46 Average	101	342	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4933.42	44.61	74.00	-29.39	40.26	5.97	33.58	35.20 Peak	101	75	VERTICAL
2	4934.00	31.68	54.00	-22.32	27.33	5.97	33.58	35.20 Average	101	75	VERTICAL
3	7378.15	49.55	74.00	-24.45	41.23	7.16	36.61	35.45 Peak	101	200	VERTICAL
4	7385.90	36.91	54.00	-17.09	28.59	7.17	36.61	35.46 Average	101	200	VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT40 CH 3 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	4841.95	46.48	74.00	-27.52	42.38	5.88	33.42	35.20	Peak	100	151 HORIZONTAL
2	4843.58	32.68	54.00	-21.32	28.58	5.88	33.42	35.20	Average	100	151 HORIZONTAL
3	7259.49	49.57	74.00	-24.43	41.45	7.10	36.43	35.41	Peak	100	220 HORIZONTAL
4	7262.67	36.42	54.00	-17.58	28.30	7.10	36.43	35.41	Average	100	220 HORIZONTAL

Vertical

: FSP40

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	4843.17	45.48	74.00	-28.52	41.38	5.88	33.42	35.20	Peak	100	348 VERTICAL
2	4843.87	32.30	54.00	-21.70	28.20	5.88	33.42	35.20	Average	100	348 VERTICAL
3	7263.98	36.48	54.00	-17.52	28.36	7.10	36.43	35.41	Average	100	108 VERTICAL
4	7264.21	49.28	74.00	-24.72	41.16	7.10	36.43	35.41	Peak	100	108 VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT40 CH 6 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4864.61	32.25	54.00	-21.75	28.10	5.90	33.45	35.20 Average	100	149	HORIZONTAL
2	4883.04	45.68	74.00	-28.32	41.48	5.92	33.48	35.20 Peak	100	149	HORIZONTAL
3	7319.65	49.89	74.00	-24.11	41.67	7.14	36.51	35.43 Peak	100	194	HORIZONTAL
4	7320.71	36.62	54.00	-17.38	28.40	7.14	36.51	35.43 Average	100	194	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4880.67	32.43	54.00	-21.57	28.23	5.92	33.48	35.20 Average	100	223	VERTICAL
2	4882.81	45.82	74.00	-28.18	41.62	5.92	33.48	35.20 Peak	100	223	VERTICAL
3	7312.60	49.60	74.00	-24.40	41.39	7.13	36.51	35.43 Peak	100	275	VERTICAL
4	7320.65	36.61	54.00	-17.39	28.39	7.14	36.51	35.43 Average	100	275	VERTICAL

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT40 CH 9 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4894.29	32.35	54.00	-21.65	28.11	5.93	33.51	35.20	Average	100	88	HORIZONTAL
2	4909.83	45.20	74.00	-28.80	40.91	5.95	33.54	35.20	Peak	100	88	HORIZONTAL
3	7364.14	50.69	74.00	-23.31	42.39	7.16	36.59	35.45	Peak	100	122	HORIZONTAL
4	7364.40	36.72	54.00	-17.28	28.42	7.16	36.59	35.45	Average	100	122	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4896.44	45.23	74.00	-28.77	40.99	5.93	33.51	35.20	Peak	100	145	VERTICAL
2	4903.07	32.45	54.00	-21.55	28.19	5.95	33.51	35.20	Average	100	145	VERTICAL
3	7356.32	49.44	74.00	-24.56	41.16	7.16	36.56	35.44	Peak	100	209	VERTICAL
4	7365.58	36.90	54.00	-17.10	28.60	7.16	36.59	35.45	Average	100	209	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (30dBc in any 100 kHz bandwidth emission)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 D01 v03r02 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11b CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 13, 2015		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2386.40	53.38	54.00	-0.62	21.24	4.09	28.05	0.00	Average	115	279 VERTICAL
2	2386.40	61.60	74.00	-12.40	29.46	4.09	28.05	0.00	Peak	115	279 VERTICAL
3	2413.60	112.06			79.86	4.11	28.09	0.00	Peak	115	279 VERTICAL
4	2414.00	108.48			76.28	4.11	28.09	0.00	Average	115	279 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2381.80	63.54	74.00	-10.46	31.45	4.08	28.01	0.00	Peak	172	246 VERTICAL
2	2389.00	53.06	54.00	-0.94	20.92	4.09	28.05	0.00	Average	172	246 VERTICAL
3	2434.20	115.89			83.59	4.12	28.18	0.00	Average	172	246 VERTICAL
4	2434.60	120.00			87.70	4.12	28.18	0.00	Peak	172	246 VERTICAL
5	2483.50	51.83	54.00	-2.17	19.41	4.16	28.26	0.00	Average	172	246 VERTICAL
6	2483.50	64.50	74.00	-9.50	32.08	4.16	28.26	0.00	Peak	172	246 VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2463.20	115.23			82.87	4.14	28.22	0.00	Peak	141	287 HORIZONTAL
2	2464.00	111.32			78.96	4.14	28.22	0.00	Average	141	287 HORIZONTAL
3	2483.50	52.64	54.00	-1.36	20.22	4.16	28.26	0.00	Average	141	287 HORIZONTAL
4	2484.00	62.44	74.00	-11.56	30.02	4.16	28.26	0.00	Peak	141	287 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11g CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2389.84	70.36	74.00	-3.64	38.22	4.09	28.05	0.00	Peak	210	252 HORIZONTAL
2	2390.00	53.92	54.00	-0.08	21.78	4.09	28.05	0.00	Average	210	252 HORIZONTAL
3	2410.24	111.62			79.42	4.11	28.09	0.00	Peak	210	252 HORIZONTAL
4	2410.40	100.91			68.71	4.11	28.09	0.00	Average	210	252 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2385.40	52.40	54.00	-1.60	20.27	4.08	28.05	0.00	Average	175	291 HORIZONTAL
2	2389.40	64.69	74.00	-9.31	32.55	4.09	28.05	0.00	Peak	175	291 HORIZONTAL
3	2441.00	120.44			88.13	4.13	28.18	0.00	Peak	175	291 HORIZONTAL
4	2441.40	111.26			78.95	4.13	28.18	0.00	Average	175	291 HORIZONTAL
5	2485.80	66.97	74.00	-7.03	34.51	4.16	28.30	0.00	Peak	175	291 HORIZONTAL
6	2508.20	53.85	54.00	-0.15	21.31	4.19	28.35	0.00	Average	175	291 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2456.00	104.51			72.15	4.14	28.22	0.00	Average	176	85 HORIZONTAL
2	2456.00	113.96			81.60	4.14	28.22	0.00	Peak	176	85 HORIZONTAL
3	2483.50	53.97	54.00	-0.03	21.55	4.16	28.26	0.00	Average	176	85 HORIZONTAL
4	2484.80	70.46	74.00	-3.54	38.04	4.16	28.26	0.00	Peak	176	85 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015, Jan. 16, 2015		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg
1	2389.20	70.70	74.00	-3.30	38.56	4.09	28.05	0.00	Peak	197	84 VERTICAL
2	2390.00	53.68	54.00	-0.32	21.54	4.09	28.05	0.00	Average	197	84 VERTICAL
3	2409.60	109.37			77.17	4.11	28.09	0.00	Peak	197	84 VERTICAL
4	2410.40	98.29			66.09	4.11	28.09	0.00	Average	197	84 VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg
1	2389.04	69.58	74.00	-4.42	37.44	4.09	28.05	0.00	Peak	211	260 HORIZONTAL
2	2390.00	53.78	54.00	-0.22	21.64	4.09	28.05	0.00	Average	211	260 HORIZONTAL
3	2431.55	110.26			78.01	4.12	28.13	0.00	Average	211	260 HORIZONTAL
4	2432.19	122.03			89.78	4.12	28.13	0.00	Peak	211	260 HORIZONTAL
5	2483.50	52.48	54.00	-1.52	20.06	4.16	28.26	0.00	Average	211	260 HORIZONTAL
6	2485.42	66.84	74.00	-7.16	34.38	4.16	28.30	0.00	Peak	211	260 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg
1	2457.60	99.81			67.45	4.14	28.22	0.00	Average	177	280 HORIZONTAL
2	2460.20	111.48			79.12	4.14	28.22	0.00	Peak	177	280 HORIZONTAL
3	2483.50	53.42	54.00	-0.58	21.00	4.16	28.26	0.00	Average	177	280 HORIZONTAL
4	2483.50	67.60	74.00	-6.40	35.18	4.16	28.26	0.00	Peak	177	280 HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	26°C	Humidity	68%
Test Engineer	Eddie Weang	Configurations	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Chain 1 + Chain 2 + Chain 3
Test Date	Jan. 15, 2015		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	2390.00	53.68	54.00	-0.32	21.54	4.09	28.05	0.00	Average	175	275	HORIZONTAL
2	2390.00	69.47	74.00	-4.53	37.33	4.09	28.05	0.00	Peak	175	275	HORIZONTAL
3	2428.00	96.33			64.08	4.12	28.13	0.00	Average	175	275	HORIZONTAL
4	2430.40	106.05			73.80	4.12	28.13	0.00	Peak	175	275	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2387.60	63.36	74.00	-10.64	31.22	4.09	28.05	0.00	Peak	171	95	HORIZONTAL
2	2390.00	49.98	54.00	-4.02	17.84	4.09	28.05	0.00	Average	171	95	HORIZONTAL
3	2441.00	101.06			68.75	4.13	28.18	0.00	Average	171	95	HORIZONTAL
4	2441.40	110.47			78.16	4.13	28.18	0.00	Peak	171	95	HORIZONTAL
5	2483.50	53.92	54.00	-0.08	21.50	4.16	28.26	0.00	Average	171	95	HORIZONTAL
6	2483.50	67.53	74.00	-6.47	35.11	4.16	28.26	0.00	Peak	171	95	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2444.80	96.19			63.88	4.13	28.18	0.00	Average	183	274	HORIZONTAL
2	2444.80	105.72			73.41	4.13	28.18	0.00	Peak	183	274	HORIZONTAL
3	2483.50	53.84	54.00	-0.16	21.42	4.16	28.26	0.00	Average	183	274	HORIZONTAL
4	2483.50	71.56	74.00	-2.44	39.14	4.16	28.26	0.00	Peak	183	274	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2452 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11b / Reference Level




Date: 15. JAN. 2015 23:23:19

Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:24:40

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 15. JAN. 2015 23:25:57

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:35:20

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 15. JAN. 2015 23:35:55

Plot on Configuration IEEE 802.11g / Reference Level




Date: 15. JAN. 2015 23:40:24

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:41:44

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 16. JAN. 2015 00:04:16

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 16. JAN. 2015 00:05:30

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 15.JAN.2015 23:43:43

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 15. JAN. 2015 23:50:05

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:51:35

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 15. JAN. 2015 23:52:13

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:52:56

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 15. JAN. 2015 23:53:38

Plot on Configuration IEEE 802.11n MCS0 HT40 / Reference Level




Date: 15. JAN. 2015 23:57:19

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 15. JAN. 2015 23:58:40

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 15. JAN. 2015 23:59:08

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)



Date: 16. JAN. 2015 00:00:05

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 2500MHz~26500MHz (down 30dBc)



Date: 16.JAN.2015 00:00:57

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 23, 2014	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 02, 2014	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 02, 2014	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	Dec. 04, 2014	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	May 26, 2014	Radiation (03CH01-CB)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02009	1GHz ~ 26.5GHz	Dec. 17, 2014	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Nov. 25, 2014	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSV40	101026	9kHz ~ 40GHz	Aug. 28, 2014	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESR26	101289	9kHz~26GHz	Aug. 22, 2014	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 15, 2014	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Dec.12, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz ~ 26.5 GHz	Nov. 15, 2014	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	1126203	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1210004	300MHz~40GHz	Oct. 06, 2014	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.4 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%