

TEST REPORT

Report Number: 100061439LEX-003
Project Number: G100061439


Report Issue Date: 8/23/2010

Product Name: Touchscreen
FCCID: J15-RB5701
ICID: 4137A-RB5701
Standards: Title 47 CFR Part 15 Subpart B and C, RSS-210
Issue 7 and RSS-Gen Issue 2

Tested by:
Intertek Testing Services NA, Inc.
731 Enterprise Drive
Lexington, KY 40510

Client:
SMC Networks
20 Mason Street
Irvine, CA 92618

Report prepared by


Jason Centers, Senior Project Engineer

Report reviewed by


Bryan Taylor, Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



TABLE OF CONTENTS

1	<i>Introduction and Conclusion</i>	3
2	<i>Test Summary</i>	3
3	<i>Description of Equipment Under Test</i>	4
4	<i>Peak Conducted Power</i>	6
5	<i>Occupied Bandwidth</i>	8
6	<i>Conducted Spurious Emissions</i>	17
7	<i>Power Spectral Density</i>	24
8	<i>Radiated Spurious Emissions (Transmitter)</i>	31
9	<i>Radiated Spurious Emissions (Receiver)</i>	42
10	<i>AC Powerline Conducted Emissions</i>	44
11	<i>Antenna Requirement per FCC Part 15.203</i>	48
12	<i>Measurement Uncertainty</i>	49
13	<i>Revision History</i>	50

1 Introduction and Conclusion

The tests indicated in section 2 were performed on the product constructed as described in section 3. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test method, a list of the actual test equipment used, documentation photos, results and raw data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested complied with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

The INTERTEK-Lexington is located at 731 Enterprise Drive, Lexington Kentucky, 40510. The radiated emission test site is a 10-meter semi-anechoic chamber. The chamber meets the characteristics of CISPR 16-1 and ANSI C63.4. For measurements, a remotely controlled flush-mount metal-top turntable is used to rotate the EUT a full 360 degrees. A remote controlled non-conductive antenna mast is used to scan the antenna height from one to four meters. The test site is listed with the FCC under registration number 485103. The test site is listed with Industry Canada under site number IC 2042M-1.

2 Test Summary

Page	Test full name	FCC Reference	IC Reference	Result
6	Peak Conducted Power	§ 15.247(b)(3)(4)	RSS210 A8.4 (4)	Pass
8	Occupied Bandwidth	§ 15.247(a)(2)	RSS210 A8.2(A)	Pass
17	Conducted Spurious Emissions	§ 15.247(d)	RSS210 (A8.5)	Pass
24	Power Spectral Density	§ 15.247(e)	RSS210 A8.2(B)	Pass
31	Radiated Spurious Emissions (Transmitter)	§ 15.247(d), § 15.209, and § 15.205	RSS-210 (2.2)	Pass
42	Radiated Spurious Emissions (Receiver)	§ 15.109	RSS-Gen (7.2.3)	Pass
44	AC Powerline Conducted Emissions	§ 15.207	RSS-Gen (7.2.2)	Pass
48	Antenna Requirement per FCC Part 15.203	§ 15.203	RSS-Gen (7.1.4)	Pass

3 Description of Equipment Under Test

Equipment Under Test	
Manufacturer	SMC Networks
Model Number	RB5701-Z
Serial Number	Test Sample 1
FCC Identifier	JI5-RB5701
IC Identifier	4137A-RB5701
Receive Date	8/2/2010
Test Start Date	8/3/2010
Test End Date	8/14/2010
Device Received Condition	Good
Test Sample Type	Production
Frequency Band	2412MHz – 2462MHz
Mode(s) of Operation	802.11b/g
Modulation Type	BPSK, QPSK, CCK, OFDM
Duty Cycle	100%
Transmission Control	Test Commands
Maximum Output Power	24.09 dBm (Conducted Measurement via U.FL Adapter)
Test Channels	1, 6, 11
Antenna Type (15.203)	Integral to PCB. Non-Detachable. Gain = 2.84dBi
Operating Voltage	120VAC

Description of Equipment Under Test


The test sample was a touch screen automation device manufactured by SMC Netowrks.

Operating modes of the EUT:

No.	Descriptions of EUT Exercising
1	Transmitting on channels 1, 6, or 11.
2	Receive / idle mode

3.1 System setup including cable interconnection details, support equipment and simplified block diagram

3.2 EUT Block Diagram:



3.3 Cables:

Cables					
Description	Length	Shielding	Ferrites	Connection	
				From	To
AC Power Cable	5 ft.	None	None	AC Power Source	AC Input
Serial Cable	6 ft.	Yes	None	Ethernet Switch	Laptop Computer

3.4 Support Equipment:

Support Equipment			
Description	Manufacturer	Model Number	Serial Number
Wireless Router	Linksys	WRT110	MSU00HB71513
Laptop Computer	HP	Nc6000	CNU4120T70

4 Peak Conducted Power

4.1 Test Limits

§ 15.247(b)(3): For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

§ 15.247(b)(4): The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247). The peak output power was measured using the channel power function of the spectrum analyzer.

4.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	8/17/2009	8/17/2010

4.4 Results:

Mode	Channel Number	Frequency (MHz)	Peak Conducted Power (dBm)	Peak Conducted Power Limit (dBm)	Margin (dB)	Result
802.11b – 1 Mbps	1	2412	19.14	30	-10.86	Pass
802.11b – 1 Mbps	6	2437	20.62	30	-9.38	Pass
802.11b – 1 Mbps	11	2462	21.44	30	-8.56	Pass
802.11b – 11 Mbps	1	2412	18.97	30	-11.03	Pass
802.11b – 11 Mbps	6	2437	22.1	30	-7.9	Pass
802.11b – 11 Mbps	11	2462	24.09	30	-5.91	Pass
802.11g – 6 Mbps	1	2412	20.79	30	-9.21	Pass
802.11g – 6 Mbps	6	2437	21.32	30	-8.68	Pass
802.11g – 6 Mbps	11	2462	22.40	30	-7.6	Pass
802.11g – 54 Mbps	1	2412	20.92	30	-9.08	Pass
802.11g – 54 Mbps	6	2437	21.49	30	-8.51	Pass
802.11g – 54 Mbps	11	2462	22.94	30	-7.06	Pass

5 Occupied Bandwidth

5.1 Test Limits

§ 15.247(a)(2): For digital modulation systems, the minimum 6dB bandwidth shall be at least 500kHz.

5.2 Test Procedure


ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

5.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	8/17/2009	8/17/2010


5.4 Results:

Mode	Channel Number	Frequency (MHz)	6dB Bandwidth	99% Power Bandwidth	Result
802.11b – 11 Mbps	1	2412	8.6 MHz	---	Pass
802.11b – 11 Mbps	6	2437	7.0 MHz	12.0 MHz	Pass
802.11b – 11 Mbps	11	2462	7.6 MHz	---	Pass
802.11g – 54 Mbps	1	2412	16.0 MHz	---	Pass
802.11g – 54 Mbps	6	2437	16.3 MHz	16.23 MHz	Pass
802.11g – 54 Mbps	11	2462	15.9 MHz	---	Pass




Date: 14.AUG.2010 10:04:43

6dB Bandwidth Plot (Channel 1) – 802.11b mode




Date: 14.AUG.2010 10:09:43

6dB Bandwidth Plot (Channel 6) – 802.11b mode




Date: 14.AUG.2010 10:26:48

6dB Bandwidth Plot (Channel 11) – 802.11b mode




Date: 14.AUG.2010 11:18:07

99% Power Bandwidth Plot (Channel 6) – 802.11b mode




Date: 14.AUG.2010 09:54:21

6dB Bandwidth Plot (Channel 1) – 802.11g mode




Date: 14.AUG.2010 10:14:07

6dB Bandwidth Plot (Channel 6) – 802.11g mode



Date: 14.AUG.2010 10:48:50

6dB Bandwidth Plot (Channel 11) – 802.11g mode



Date: 14.AUG.2010 11:22:37

99% Power Bandwidth Plot (Channel 6) – 802.11g mode

6 Conducted Spurious Emissions

6.1 Test Limits

§ 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

6.2 Test Procedure



ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

6.3 Test Equipment Used:



Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMC Analyzer	2142	HP	E7405	8/21/2009	8/21/2010

6.4 Results:



The following plots show that there are no conducted spurious emissions exceeding the 20dB down criteria.





Conducted Spurious Emissions - 802.11b Mode Low Channel





Conducted Spurious Emissions - 802.11b Mode Mid Channel





Conducted Spurious Emissions - 802.11b Mode High Channel



Conducted Spurious Emissions - 802.11g Mode Low Channel



Conducted Spurious Emissions - 802.11b Mode Mid Channel



Conducted Spurious Emissions - 802.11g Mode High Channel

7 Power Spectral Density

7.1 Test Limits

§ 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

7.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)


7.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	8/17/2009	8/17/2010

7.4 Results:


*PSD Option 1 Method

Channel Number	Frequency (MHz)	PSD in 3kHz BW (dBm)	Limit (dBm)	Margin (dBm)	Result
1	2412	-6.57	8.0	-14.57	Pass
6	2437	1.67	8.0	-6.33	Pass
11	2462	6.13	8.0	-1.87	Pass
1	2412	-12.3	8.0	-20.3	Pass
6	2437	-11.39	8.0	-19.39	Pass
11	2462	-11.57	8.0	-19.57	Pass




Date: 12.AUG.2010 15:39:17

Power Spectral Density – Channel 1 802.11b mode




Date: 12.AUG.2010 15:59:03

Power Spectral Density – Channel 6 802.11b mode




Date: 12.AUG.2010 16:18:30

Power Spectral Density – Channel 11 802.11b mode




Date: 12.AUG.2010 15:45:19

Power Spectral Density – Channel 1 802.11g mode



Date: 12.AUG.2010 16:08:41

Power Spectral Density – Channel 6 802.11g mode



Date: 12.AUG.2010 16:29:36

Power Spectral Density – Channel 11 802.11g mode

8 Radiated Spurious Emissions (Transmitter)

8.1 Test Limits

§ 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Part 15.205(a): Restricted Bands of Operations

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
10.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	(²)
13.36–13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz.

² Above 38.6

Part 15.209(a): Field Strength Limits for Restricted Bands of Operation

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2,400 / F (kHz)	300
0.490 - 1.705	24,000 / F (kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

8.2 Test Procedure

ANSI C63.10: 2009 and KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)

8.3 Example of Field Strength Calculation Method:

The measured field strength was calculated by summing the readings taken from the spectrum analyzer with the appropriate correction factors associated with the antenna losses and cable losses. The calculation formula and sample calculations are listed below:

Formula:

$$FS = RA + AF + CF$$

FS = Field Strength in dB μ V/m

RA = Receiver Amplitude in dB μ V

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB (Including preamplifier and filter attenuation)

Example Calculation:

RA = 19.48 dB μ V

AF = 18.52 dB

CF = 0.78 dB

FS = 19.48 + 18.52 + 0.78 = 38.78 dB μ V/m

Level in μ V/m = Common Antilogarithm [(38.78 dB μ V/m)/20] = 86.89 μ V/m

8.4 Test Equipment Used:


Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
Spectrum Analyzer	3099	Rohde & Schwarz	FSP7	8/17/2009	8/17/2010
Preamplifier	987410	Miteq	AFS44-00102000-30-10P-44	6/17/2010	6/17/2011
Preamplifier	SF456200904	Mini-Circuits	ZX60-3018G-S+	2/12/2010	2/12/2011
Biconnilog Antenna	00051864	ETS	3142C	12/21/2009	12/21/2010
Horn Antenna	6556	ETS	3115	8/4/2009	8/4/2010
System Controller	121701-1	Sunol Sciences	SC99V	Time of Use	Time of Use
High Pass Filter	3986-01 DC0408	Microwave Circuits, Inc.	H3G020G2	2/10/2010	2/10/2011

8.5 Results:


All spurious emissions were attenuated by at least 20dB below the level of the fundamental as required by Part 15.247(d). Additionally, all emissions falling within restricted bands of operation and at the band edges were found to be below the limit specified in Part 15.209(a). The spurious emissions listed in the following tables are the worst case emissions.

Worst Case Spurious Measurements

Mode	Channel	Frequency	Polarity	Corr. Peak Reading. (dBuV/m)	Corr. Avg Reading. (dBuV/m)	Peak Limit (dBuV/m)	Avg. Limit (dBuV/m)	Results
802.11b	1	4.8239 GHz	V	52.789	40.139	74	54	Compliant
802.11b	6	4.8737 GHz	V	52.032	39.532	74	54	Compliant
802.11b	11	4.924 GHz	V	50.033	37.493	74	54	Compliant
802.11b	6	7.3111 GHz	V	48.497	34.517	74	54	Compliant
802.11b	11	7.3859 GHz	V	48.423	34.303	74	54	Compliant
802.11b	1	4.8239 GHz	H	47.969	34.919	74	54	Compliant
802.11b	6	4.8738 GHz	H	51.023	38.273	74	54	Compliant
802.11b	11	4.9239 GHz	H	49.403	36.333	74	54	Compliant
802.11b	1	7.2362 GHz	H	49.545	35.705	74	54	Compliant
802.11b	6	7.3117 GHz	H	47.696	34.653	74	54	Compliant
802.11b	11	7.3859 GHz	H	46.463	32.743	74	54	Compliant
802.11g	1	4.8269 GHz	H	41.779	27.865	74	54	Compliant
802.11g	6	4.8704 GHz	H	40.783	27.755	74	54	Compliant
802.11g	11	4.9239 GHz	H	43.073	28.493	74	54	Compliant
802.11g	6	7.3102 GHz	H	58.45	32.91	74	54	Compliant
802.11g	11	7.3849 GHz	H	47.667	32.927	74	54	Compliant
802.11g	1	4.822 GHz	V	42.504	28.019	74	54	Compliant
802.11g	6	4.8742 GHz	V	53.738	29.564	74	54	Compliant
802.11g	11	4.9258 GHz	V	43.077	27.636	74	54	Compliant
802.11g	6	7.31 GHz	V	45.237	33.545	74	54	Compliant
802.11g	11	7.4085 GHz	V	46.233	33.028	74	54	Compliant





Page 34 of 50



Date: 6.AUG.2010 05:09:30


Low Channel Band Edge Emissions (Average Detection) - 802.11b Mode

**Low Channel Band Edge Emissions (Peak Detection) – 802.11g Mode**




Date: 6.AUG.2010 05:42:57

Low Channel Band Edge Emissions (Average Detection) - 802.11g Mode




Date: 6.AUG.2010 06:22:11

High Channel Band Edge Emissions (Peak Detection) – 802.11b Mode




Date: 6.AUG.2010 06:20:37

High Channel Band Edge Emissions (Average Detection) - 802.11b Mode



Date: 6.AUG.2010 07:23:29

High Channel Band Edge Emissions (Peak Detection) – 802.11g Mode



Date: 6.AUG.2010 07:00:59

High Channel Band Edge Emissions (Average Detection) – 802.11g Mode

9 Radiated Spurious Emissions (Receiver)

9.1 Test Limits

§ 15.109: Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of emission (MHz)	Field strength (microvolts/meter)	Field strength (dBuV/m)
30–88	100	40
88–216	150	43.5
216–960	200	46
Above 960	500	54

9.2 Test Procedure

ANSI C63.4: 2003

9.3 Example of Field Strength Calculation Method:

The measured field strength was calculated by summing the readings taken from the spectrum analyzer with the appropriate correction factors associated with the antenna losses and cable losses. The calculation formula and sample calculations are listed below:

Formula:

$$FS = RA + AF + CF$$

FS = Field Strength in dBμV/m

RA = Receiver Amplitude in dBμV

AF = Antenna Factor in dB

CF = Cable Attenuation Factor in dB (Including preamplifier and filter attenuation)

Example Calculation:

RA = 19.48 dBμV

AF = 18.52 dB

CF = 0.78 dB

$$FS = 19.48 + 18.52 + 0.78 = 38.78 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(38.78 \text{ dB}\mu\text{V/m})/20] = 86.89 \mu\text{V/m}$$

9.4 Test Equipment Used:


Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	10887490.26	Rohde & Schwarz	ESI26	9/14/2009	9/14/2010
Preamplifier	SF456200904	Mini-Circuits	ZX60-3018G-S+	2/12/2010	2/12/2011
Biconnilog Antenna	00051864	ETS	3142C	12/21/2009	12/21/2010
System Controller	121701-1	Sunol Sciences	SC99V	Time of Use	Time of Use

9.5 Results:

All spurious emissions with the test sample in receive mode were below the limits specified in Part 15.109 for a class B digital device.

Maximized Quasi Peak Emissions

Radiated Emissions										
Test Engineer:	Bryan Taylor	Start Date:	6/21/2010		End Date:	6/21/2010				
Temperature:	23.2C	Humidity:	43.80%		Pressure:	990.3mBar				
Specification:	FCC Part 15B	Test Limit:	Class B							
Notes:	Not Transmitting									
A	B	C	D	E	F	G	H	I	J	K
Frequency	Polarity (H/V)	Raw Reading (dBUV)	Cab. (dB)	Ant. (dB)	Corr. Reading. (dBUV/m)	Limit (dBUV/m)	Delta (dB)	RBW / Detector	Test Distance	Results
282.75 MHz	H	36.11	-14.36	13.16	34.91	46.02	-11.11	120kHz/QP	3m	Compliant
1.0001 GHz	H	28.04	-10.96	23.9	40.98	53.98	-13	120kHz/QP	3m	Compliant
47.258 MHz	V	37.92	-16.02	8.05	29.95	40	-10.05	120kHz/QP	3m	Compliant
50.263 MHz	V	44.54	-15.79	7.6	36.35	40	-3.65	120kHz/QP	3m	Compliant
53.295 MHz	V	38.86	-15.65	7.76	30.97	40	-9.03	120kHz/QP	3m	Compliant
58.645 MHz	V	40.97	-15.94	9.47	34.5	40	-5.5	120kHz/QP	3m	Compliant
Calculations:					F = C + D + E		H = F - G			



Peak Scan (Receive Mode)

10 AC Powerline Conducted Emissions

10.1 Test Limits

§ 15.107(e): Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

10.2 Test Procedure

ANSI C63.4: 2003


10.3 Test Equipment Used:

Description	Serial Number	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	10887490.26	Rohde & Schwarz	ESI26	9/14/2009	9/14/2010
LISN	3333	Teseq	NNB52	2/23/2010	2/23/2011

10.4 Results:

Conducted Voltage Emissions on Power Lines								
Test Engineer:	Jason Centers	Start Date:	8/14/2010		End Date:	8/14/2010		
Temperature:	23.1C	Humidity:	48.30%		Pressure:	987.7mBar		
Specification:	FCC Part 15	Test Limit:	Class B		RBW:	9kHz		
Notes:	802.11B Mode							
Line	Frequency (MHz)	Quasi-Peak (dBuV)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)	Average (dBuV)	Average Limit (dBuV)	Average Delta (dB)	Results
L1	150.0 KHz	49.12	66	-16.88	24.64	56	-31.36	Compliant
L1	159.0 KHz	48.37	65.52	-17.15	24.22	55.52	-31.3	Compliant
L1	7.5755 MHz	45.8	60	-14.2	37.17	50	-12.83	Compliant
L1	8.3006 MHz	47.18	60	-12.82	38.38	50	-11.62	Compliant
L2	150.0 KHz	47.3	66	-18.7	23.81	56	-32.19	Compliant
L2	159.0 KHz	46.11	65.52	-19.41	23.34	55.52	-32.18	Compliant
L2	7.5746 MHz	45.9	60	-14.1	37.04	50	-12.96	Compliant
L2	8.3025 MHz	45.94	60	-14.06	37.46	50	-12.54	Compliant


Quasi-Peak and Average Measurements – Tx B Mode



Peak Scan (Line 1 and 2) – Tx B Mode

Conducted Voltage Emissions on Power Lines								
Test Engineer: Jason Centers		Start Date: 8/14/2010		End Date: 8/14/2010				
Temperature: 23.1C		Humidity: 48.30%		Pressure: 987.7mBar				
Specification: FCC Part 15		Test Limit: Class B		RBW: 9kHz				
Notes: 802.11 G Mode								
Line	Frequency (MHz)	Quasi-Peak (dBuV)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)	Average (dBuV)	Average Limit (dBuV)	Average Delta (dB)	Results
L1	150.0 KHz	49.51	66	-16.49	24.83	56	-31.17	Compliant
L1	168.0 KHz	47.51	65.06	-17.55	23.98	55.06	-31.08	Compliant
L1	8.1555 MHz	47.89	60	-12.11	37.98	50	-12.02	Compliant
L2	150.0 KHz	47.65	66	-18.35	23.95	56	-32.05	Compliant
L2	168.0 KHz	45.23	65.06	-19.83	23.35	55.06	-31.71	Compliant
L2	8.1506 MHz	46.98	60	-13.02	37.1	50	-12.9	Compliant


Quasi-Peak and Average Measurements – Tx G Mode



Peak Scan (Line 1 and 2) – Tx G Mode

Conducted Voltage Emissions on Power Lines								
Test Engineer: Bryan Taylor Start Date: 6/27/2010 End Date: 6/27/2010 Temperature: 22.4C Humidity: 40.50% Pressure: 989.3mBar Specification: FCC Part 15B Test Limit: Class B RBW: 9kHz Notes: Not Transmitting								
Line	Frequency (MHz)	Quasi-Peak (dBuV)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)	Average (dBuV)	Average Limit (dBuV)	Average Delta (dB)	Results
L1	372.5 KHz	39.17	58.44	-19.27	30.03	48.44	-18.41	Compliant
L1	457.5 KHz	38.61	56.74	-18.13	28.27	46.74	-18.47	Compliant
L1	23.1 MHz	43	60	-17	37.61	50	-12.39	Compliant
L2	372.5 KHz	37.49	58.44	-20.95	27.86	48.44	-20.58	Compliant
L2	457.5 KHz	38.37	56.74	-18.37	27.07	46.74	-19.67	Compliant
L2	23.1 MHz	42.88	60	-17.12	37.94	50	-12.06	Compliant

Quasi-Peak and Average Measurements – Rx Mode



Peak Scan (Line 1 and 2) – Rx Mode

11 Antenna Requirement per FCC Part 15.203

11.1 Test Limits

§ 15.203: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

11.2 Results:

The sample tested met the antenna requirement. The antenna used was permanently attached and integral to the PCB.

12 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements.

The measurement uncertainty figures were calculated and correspond to a coverage factor of $k = 2$, providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Measurement uncertainty Table

Parameter	Uncertainty	Notes
Radiated emissions, 30 to 1000 MHz	+3.9dB	
Radiated emissions, 1 to 18 GHz	+4.2dB	
Radiated emissions, 18 to 40 GHz	+4.3dB	
Power Port Conducted emissions, 150kHz to 30 MHz	+2.8dB	

13 Revision History

Revision Level	Date	Report Number	Notes
0	8/23/2010	100061439LEX-003	Original Issue