Attachment

User's Manual

SERIAL & PS/2 MOUSE USERS MANUAL

Model No.: MUO1IA,MUO2IA,

Description: 3keys 420DPI Combo Mouse, Serial and PS2 Mouse integrated.

Cable: 5 feet in length with Mini-DIN 6 pin connector.

PS/2 Mode: Direct connect to PC's PS/2 mouse port.

MS Serial Mode: Use a Mini-DIN 6F to DB-9F adapter to connect PC's COM port.

- Oscillator frequency: 4MHz.
- Power Consumption:
  PS/2 mode: Maximum 17.5mW, 3.5mA at 5V DC.
  MS mode: Maximum 174mW, 14.5mA at 12V DC.
- Hardware Resolution up to 420 DPI.
  Optical/Mechanical Interrupt Wheel design for smooth tracking pickups.

WARNING

Note : This equipment has been tested and found to comply with the limits for a Class B device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However , there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures :

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver in connected.
- Consult the dealer or an experienced radio / TV technician for technician for help.

Notice:

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.