



RF EXPOSURE REPORT

REPORT NO.: SA980223H07

MODEL NO.: E-R0001

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : LOGITECH FAR EAST LTD.

ADDRESS : #2 Creation Rd. 4, Science-Based Ind. Park
Hsinchu Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

TEST LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan



No SAR Evaluation Required if power is below the following threshold:

Tunable Range		Center of Tunable Band (GHz)	60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High		
2.402	2.480	2.441	24.19

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
1.06	1.276	4.75	3.811

Threshold for no SAR evaluation is 24.19 mW

Maximum TX Power is 1.276 mW Conducted and 3.811 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold