



RF EXPOSURE REPORT

REPORT NO.: SA110624E07

MODEL NO.: Y-R0026

APPLICANT: LOGITECH FAR EAST LTD.

ADDRESS: #2 Creation Rd. 4, Science-Based Ind. Park Hsinchu
Taiwan, R.O.C.

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 5 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. EVALUATION RESULT	5



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110624E07	Original release	July 27, 2011

1. CERTIFICATION

PRODUCT: Bluetooth Keyboard

MODEL: Y-R0026

BRAND: Logitech

APPLICANT: LOGITECH FAR EAST LTD.

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: IEEE C95.1

The above equipment (Model: Y-R0026) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Phoenix Huang , **DATE:** July 27, 2011
(Phoenix Huang, Specialist)

APPROVED BY : May Chen , **DATE:** July 27, 2011
(May Chen, Deputy Manager)

2. EVALUATION RESULT

No SAR Evaluation Required if power is below the following threshold:

Tunable Range		60/f SAR Limitation (mW)
F(GHz) Low	F(GHz) High	
2.402	2.480	24.19

Maximum measured transmitter power:

Pout Conducted (dBm)	Pout Conducted (mW)	Maximum Antenna Gain (dBi)	Pout EIRP (mW)
0.89	1.23	-4.78	1.95

Threshold for no SAR evaluation is 24.19 mW

Maximum TX Power is 1.23 mW Conducted and 1.95 mW EIRP

Conclusion: No SAR evaluation required since maximum Transmitter Pout (both conducted and EIRP) is below FCC threshold

--- END ---