

## APPENDIX D: SAR SYSTEM VALIDATION

		Approved by:	
FCC ID: JNZYR0089	SAR EVALUATION REPORT	Technical Manager	
DUT Type: Bluetooth Keyboard Case Access	APPENDIX D: Page 1 of 2		



Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.

Table D-1
SAR System Validation Summary – 1g

SAR		Freq.		Probe		Cond.	Perm.	CW VALIDATION			MOD. VALIDATION			
	System	(MHz)	Date	SN	Probe Cal Point		(σ)		SENSITIVITY	PROBE	PROBE	MOD.	DUTY	PAR
	System	(IVIITIZ)		314			(0)	(Er)	SENSITIVITY	LINEARITY	ISOTROPY	TYPE	<b>FACTOR</b>	PAR
	AM8	2450	05/04/2022	7546	2450	Head	1.780	39.800	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
	AM1	3700	02/21/2022	7639	3700	Head	2.970	38.397	PASS	PASS	PASS	TDD	PASS	N/A

NOTE: The probes have been calibrated for both CW and modulated signals. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID: JNZYR0089	SAR EVALUATION REPORT	Approved by:  Technical Manager	
DUT Type:	APPENDIX D:		
Bluetooth Keyboard Case Access	Page 2 of 2		