

## Report on the RF Testing of:

KYOCERA Corporation  
Mobile Phone, Model: DB62  
FCC ID: JOYDB62

## In accordance with FCC Part15 Subpart C

Prepared for: KYOCERA Corporation  
Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku  
Yokohama-shi, Kanagawa, Japan  
Phone: +81-45-943-6253 Fax: +81-45-943-6314



Japan

**Add value.  
Inspire trust.**

## COMMERCIAL-IN-CONFIDENCE

Document Number: JPD-TR-19173-0

### SIGNATURE

| NAME           | JOB TITLE                  | RESPONSIBLE FOR    | ISSUE DATE  |
|----------------|----------------------------|--------------------|-------------|
| Hiroaki Suzuki | Deputy Manager of RF Group | Approved Signatory | 10 OCT 2019 |

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Japan Ltd. document control rules.

### EXECUTIVE SUMMARY

A sample(s) of this product was tested and found to be compliant with FCC Part15 Subpart C.



### DISCLAIMER AND COPYRIGHT

The results in this report are applicable only to the equipment tested.  
This report shall not be re-produced except in full without the written approval of TÜV SÜD Japan Ltd.

### ACCREDITATION

This test report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. government.

TÜV SÜD Japan Ltd.  
Yonezawa Testing Center  
5-4149-7 Hachimanpara,  
Yonezawa-shi, Yamagata,  
992-1128 Japan

Phone: +81 (0) 238 28 2881  
Fax: +81 (0) 238 28 2888  
[www.tuv-sud.jp](http://www.tuv-sud.jp)

## Contents

|                                        |                                                     |            |
|----------------------------------------|-----------------------------------------------------|------------|
| <b>1</b>                               | <b>Summary of Test .....</b>                        | <b>3</b>   |
| 1.1                                    | Modification history of the test report .....       | 3          |
| 1.2                                    | Standards .....                                     | 3          |
| 1.3                                    | Test methods.....                                   | 3          |
| 1.4                                    | Deviation from standards .....                      | 3          |
| 1.5                                    | List of applied test(s) of the EUT .....            | 3          |
| 1.6                                    | Test information.....                               | 3          |
| 1.7                                    | Test set up.....                                    | 3          |
| 1.8                                    | Test period .....                                   | 3          |
| <b>2</b>                               | <b>Equipment Under Test.....</b>                    | <b>4</b>   |
| 2.1                                    | EUT information .....                               | 4          |
| 2.2                                    | Modification to the EUT .....                       | 5          |
| 2.3                                    | Variation of family model(s).....                   | 5          |
| 2.4                                    | Operating channels and frequencies .....            | 5          |
| 2.5                                    | Description of test mode .....                      | 6          |
| 2.6                                    | Operating flow .....                                | 6          |
| <b>3</b>                               | <b>Configuration of Equipment.....</b>              | <b>7</b>   |
| 3.1                                    | Equipment used .....                                | 7          |
| 3.2                                    | Cable(s) used .....                                 | 7          |
| 3.3                                    | System configuration .....                          | 7          |
| <b>4</b>                               | <b>Test Result .....</b>                            | <b>8</b>   |
| 4.1                                    | DTS Bandwidth / Occupied Bandwidth (99%) .....      | 8          |
| 4.2                                    | Maximum Conducted Output Power .....                | 13         |
| 4.3                                    | Band Edge Compliance of RF Conducted Emissions..... | 15         |
| 4.4                                    | Spurious emissions - Conducted - .....              | 20         |
| 4.5                                    | Spurious Emissions - Radiated - .....               | 31         |
| 4.6                                    | Restricted Band of Operation .....                  | 76         |
| 4.7                                    | Transmitter Power Spectral Density.....             | 90         |
| 4.8                                    | AC Power Line Conducted Emissions .....             | 95         |
| <b>5</b>                               | <b>Antenna requirement .....</b>                    | <b>99</b>  |
| <b>6</b>                               | <b>Measurement Uncertainty .....</b>                | <b>100</b> |
| <b>7</b>                               | <b>Laboratory Information.....</b>                  | <b>101</b> |
| <b>Appendix A. Test Equipment.....</b> |                                                     | <b>102</b> |
| <b>Appendix B. Duty Cycle .....</b>    |                                                     | <b>103</b> |

## 1 Summary of Test

### 1.1 Modification history of the test report

| Document Number | Modification History | Issue Date              |
|-----------------|----------------------|-------------------------|
| JPD-TR-19173-0  | First Issue          | Refer to the cover page |

### 1.2 Standards

CFR47 FCC Part 15 Subpart C

### 1.3 Test methods

ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02

### 1.4 Deviation from standards

None

### 1.5 List of applied test(s) of the EUT

| Test item section             | Test item                                      | Condition             | Result | Remark |
|-------------------------------|------------------------------------------------|-----------------------|--------|--------|
| 15.247(a)(2)                  | DTS Bandwidth / Occupied Bandwidth (99%)       | Conducted             | PASS   | -      |
| 15.247(b)(3)                  | Maximum conducted (average) output power       | Conducted             | PASS   | -      |
| 15.247(d)                     | Band Edge Compliance of RF Conducted Emissions | Conducted             | PASS   | -      |
| 15.247(d)<br>15.205<br>15.209 | Spurious Emissions                             | Conducted<br>Radiated | PASS   | -      |
| 15.247(d)<br>15.205<br>15.209 | Restricted Bands of Operation                  | Radiated              | PASS   | -      |
| 15.247(e)                     | Transmitter Power Spectral Density             | Conducted             | PASS   | -      |
| 15.207                        | AC Power Line Conducted Emissions              | Conducted             | PASS   | -      |

### 1.6 Test information

None

### 1.7 Test set up

Table-top

### 1.8 Test period

6-August-2019 - 11-September-2019

## 2 Equipment Under Test

### 2.1 EUT information

|                            |                                                                                                                                                                                                                               |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant                  | KYOCERA Corporation<br>Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku Yokohama-shi,<br>Kanagawa, Japan<br>Phone: +81-45-943-6253 Fax: +81-45-943-6314                                                                             |
| Equipment Under Test (EUT) | Mobile Phone                                                                                                                                                                                                                  |
| Model number               | DB62                                                                                                                                                                                                                          |
| Serial number              | N/A                                                                                                                                                                                                                           |
| Trade name                 | Kyocera                                                                                                                                                                                                                       |
| Number of sample(s)        | 1                                                                                                                                                                                                                             |
| EUT condition              | Pre-Production                                                                                                                                                                                                                |
| Power rating               | Battery: DC 3.8 V                                                                                                                                                                                                             |
| Size                       | (W) 51.3 × (D) 17.9 × (H) 112.3 mm                                                                                                                                                                                            |
| Environment                | Indoor and Outdoor use                                                                                                                                                                                                        |
| Terminal limitation        | -20°C to 60°C                                                                                                                                                                                                                 |
| Hardware Version           | DMT1                                                                                                                                                                                                                          |
| Software Version           | V0.030AN.0015.a                                                                                                                                                                                                               |
| Firmware Version           | Not applicable                                                                                                                                                                                                                |
| RF Specification           |                                                                                                                                                                                                                               |
| Protocol                   | IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20),                                                                                                                                                                                 |
| Frequency range            | IEEE802.11b /11g/11n (HT20): 2412 MHz-2462 MHz                                                                                                                                                                                |
| Number of RF Channels      | 11 Channels                                                                                                                                                                                                                   |
| Modulation type            | IEEE802.11b: DSSS (DBPSK, DQPSK, CCK)<br>IEEE802.11g /11n (HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)                                                                                                                             |
| Data rate                  | IEEE802.11b: 1, 2, 5.5, 11Mbps<br>IEEE802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps<br>IEEE802.11n (HT20 LGI): 6.5, 13, 19.5, 26, 39, 52, 58.5, 65Mbps<br>IEEE802.11n (HT20 SGI): 7.2, 14.4, 21.7, 28.9, 43.3, 57.8, 65, 72.2Mbps |
| Channel separation         | 5 MHz                                                                                                                                                                                                                         |
| Output power               | 47.523 mW (IEEE802.11b)<br>81.846 mW (IEEE802.11g)<br>82.947 mW (IEEE802.11n: HT20)                                                                                                                                           |
| Antenna type               | Internal antenna                                                                                                                                                                                                              |
| Antenna gain               | 2.0 dBi                                                                                                                                                                                                                       |

## 2.2 Modification to the EUT

The table below details modifications made to the EUT during the test project.

| Modification State              | Description of Modification  | Modification fitted by | Date of Modification |
|---------------------------------|------------------------------|------------------------|----------------------|
| Model: DB62, Serial Number: N/A |                              |                        |                      |
| 0                               | As supplied by the applicant | Not Applicable         | Not Applicable       |

## 2.3 Variation of family model(s)

### 2.3.1 List of family model(s)

DB62 has model with camera and without camera.

### 2.3.2 Reason for selection of EUT

Not applicable

## 2.4 Operating channels and frequencies

| Channel | Frequency [MHz] |
|---------|-----------------|
| 1       | 2412            |
| 2       | 2417            |
| 3       | 2422            |
| 4       | 2427            |
| 5       | 2432            |
| 6       | 2437            |
| 7       | 2442            |
| 8       | 2447            |
| 9       | 2452            |
| 10      | 2457            |
| 11      | 2462            |

## 2.5 Description of test mode

The EUT had been tested under operating condition.

There are three channels have been tested as following:

| Tested Channel [11b, 11g, 11n(HT20)] | Frequency [MHz] |
|--------------------------------------|-----------------|
| Low                                  | 2412            |
| Middle                               | 2437            |
| High                                 | 2462            |

The pre-test has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

| Tested Channel    | Modulation Type              | Data Rate      |
|-------------------|------------------------------|----------------|
| Low, Middle, High | IEEE802.11b: DSSS            | 1Mbps          |
| Low, Middle, High | IEEE802.11g: OFDM            | 6Mbps          |
| Low, Middle, High | IEEE802.11n (HT20 LGI): OFDM | MCS0 (6.5Mbps) |

The field strength of spurious emissions was measured at each position of all three axis X, Y and Z to compare the level, and the maximum noise.

The worst emission was found in X-axis, open and the worst case recorded.

Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports.

## 2.6 Operating flow

### - Tx mode

- i) Test program setup to the Software
- ii) Select a Test mode  
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]  
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

### - Rx mode

- i) Test program setup to the Software
- ii) Select a Test mode  
[IEEE802.11b, IEEE802.11g, IEEE802.11n (HT20)]  
Operating frequency: Channel Low: 2412MHz, Channel Middle: 2437MHz, Channel High: 2462MHz
- iii) Start test mode

### 3 Configuration of Equipment

Numbers assigned to equipment on the diagram in “3.3 System configuration” correspond to the list in “3.1 Equipment used” and “3.2 Cable(s) used”.

Cabling and setup(s) were taken into consideration and test data was taken under worse case condition.

#### 3.1 Equipment used

| No. | Equipment    | Company | Model No. | Serial No. | FCC ID/DoC | Comment |
|-----|--------------|---------|-----------|------------|------------|---------|
| 1   | Mobile Phone | KYOCERA | DB62      | N/A        | JOYDB62    | EUT     |
| 2   | AC Adapter   | KDDI    | 0301PQA   | N/A        | N/A        | *       |


\*:AC power line Conducted Emission Test.

#### 3.2 Cable(s) used

| No. | Equipment                  | Length[m] | Shield | Connector | Comment |
|-----|----------------------------|-----------|--------|-----------|---------|
| a   | USB cable (for AC Adapter) | 1.0       | Yes    | Metal     | *       |

\*:AC power line Conducted Emission Test.

#### 3.3 System configuration



## 4 Test Result

### 4.1 DTS Bandwidth / Occupied Bandwidth (99%)

#### 4.1.1 Measurement procedure


[FCC 15.247(a)(2), KDB 558074 D01 v05r02, Section 8.2]

The bandwidth at 6dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) RBW = 100kHz.
- b) VBW  $\geq 3 \times$  RBW.
- c) Sweep time = auto-couple.
- d) Detector = peak.
- e) Trace mode = max hold.

- Test configuration



#### 4.1.2 Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

#### 4.1.3 Measurement result

Date : 23-August-2019

Temperature : 24.5 [°C]

Humidity : 56.0 [%]

Test place : Shielded room No.4

Test engineer :

Tadahiro Seino


| Channel | DTS Bandwidth [MHz] |             |                    |
|---------|---------------------|-------------|--------------------|
|         | IEEE802.11b         | IEEE802.11g | IEEE802.11n (HT20) |
| Low     | 7.601               | 16.424      | 17.625             |
| Middle  | 7.597               | 16.410      | 17.602             |
| High    | 7.603               | 16.399      | 17.612             |

| Channel | Occupied Bandwidth (99%) [MHz] |             |                    |
|---------|--------------------------------|-------------|--------------------|
|         | IEEE802.11b                    | IEEE802.11g | IEEE802.11n (HT20) |
| Low     | 12.100                         | 16.518      | 17.676             |
| Middle  | 12.174                         | 16.558      | 17.703             |
| High    | 12.148                         | 16.534      | 17.671             |


#### 4.1.4 Trace data

[IEEE802.11b]


##### Channel Low



##### Channel Middle




##### Channel High




[IEEE802.11g]


Channel Low



Channel Middle




Channel High




[IEEE802.11n (HT20)]


Channel Low



Channel Middle



Channel High



## 4.2 Maximum Conducted Output Power

### 4.2.1 Measurement procedure

[FCC 15.247(b)(3), KDB 558074 D01 v05r02, Section 8.3.1.3]

The peak power is measured with a power sensor connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

- Test configuration



### 4.2.2 Limit

1 W (1000 mW) or less

**4.2.3 Measurement result**

Date : 23-August-2019

Temperature : 24.5 [°C]

Humidity : 56.0 [%]

Test place : Shielded room No.4

Test engineer :

Tadahiro Seino**[IEEE802.11b]****Battery Full**

| Channel | Center Frequency (MHz) | Reading (dBm) | Factor (dB) | Level (dBm) | Output Power (mW) | Limit (mW) | Result |
|---------|------------------------|---------------|-------------|-------------|-------------------|------------|--------|
| Low     | 2412                   | 6.10          | 10.58       | 16.68       | 46.537            | ≤1000      | PASS   |
| Middle  | 2437                   | 5.33          | 10.58       | 15.91       | 39.012            | ≤1000      | PASS   |
| High    | 2462                   | 6.19          | 10.58       | 16.77       | 47.523            | ≤1000      | PASS   |

**[IEEE802.11g]****Battery Full**

| Channel | Center Frequency (MHz) | Reading (dBm) | Factor (dB) | Level (dBm) | Output Power (mW) | Limit (mW) | Result |
|---------|------------------------|---------------|-------------|-------------|-------------------|------------|--------|
| Low     | 2412                   | 8.42          | 10.58       | 19.00       | 79.341            | ≤1000      | PASS   |
| Middle  | 2437                   | 7.58          | 10.58       | 18.16       | 65.509            | ≤1000      | PASS   |
| High    | 2462                   | 8.55          | 10.58       | 19.13       | 81.846            | ≤1000      | PASS   |

**[IEEE802.11n (HT20)]****Battery Full**

| Channel | Center Frequency (MHz) | Reading (dBm) | Factor (dB) | Level (dBm) | Output Power (mW) | Limit (mW) | Result |
|---------|------------------------|---------------|-------------|-------------|-------------------|------------|--------|
| Low     | 2412                   | 8.61          | 10.58       | 19.19       | 82.947            | ≤1000      | PASS   |
| Middle  | 2437                   | 7.77          | 10.58       | 18.35       | 68.344            | ≤1000      | PASS   |
| High    | 2462                   | 8.26          | 10.58       | 18.84       | 76.507            | ≤1000      | PASS   |

Calculation;

Reading (dBm) + Factor (dB) = Level (dBm)

 $10\log P = \text{Level (dBm)}$  $P = 10^{(\text{Maximum Peak Output Power} / 10)} \text{ (mW)}$

### 4.3 Band Edge Compliance of RF Conducted Emissions

#### 4.3.1 Measurement procedure


##### [FCC 15.247(d), KDB 558074 D01 v05r02, Section 8.5]

The Band Edge is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = Arbitrary setting. (Setting suitable for measurement.)
- b) RBW = 100kHz.
- c) VBW  $\geq 3 \times$  RBW
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



#### 4.3.2 Limit

In any 100 kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

**4.3.3 Measurement result**

Date : 23-August-2019

Temperature : 24.5 [°C]

Humidity : 56.0 [%]

Test place : Shielded room No.4

Test engineer :

Tadahiro Seino**[IEEE802.11b]**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Band-edge Frequency (MHz) | Band-edge Level (dBm) | Difference Level (dBm) | Limit (dBm)                         | Result |
|---------|-----------------|----------------------|---------------------------|-----------------------|------------------------|-------------------------------------|--------|
| Low     | 2412.00         | -5.08                | 2398.48                   | -55.29                | 50.21                  | At least 20dB below from peak of RF | PASS   |
| High    | 2462.00         | -4.58                | 2483.82                   | -67.50                | 62.92                  | At least 20dB below from peak of RF | PASS   |

**[IEEE802.11g]**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Band-edge Frequency (MHz) | Band-edge Level (dBm) | Difference Level (dBm) | Limit (dBm)                         | Result |
|---------|-----------------|----------------------|---------------------------|-----------------------|------------------------|-------------------------------------|--------|
| Low     | 2412.00         | -12.31               | 2399.84                   | -49.21                | 36.90                  | At least 20dB below from peak of RF | PASS   |
| High    | 2462.00         | -11.76               | 2483.58                   | -60.11                | 48.35                  | At least 20dB below from peak of RF | PASS   |


**[IEEE802.11n (HT20)]**

| Channel | Frequency (MHz) | RF Power Level (dBm) | Band-edge Frequency (MHz) | Band-edge Level (dBm) | Difference Level (dBm) | Limit (dBm)                         | Result |
|---------|-----------------|----------------------|---------------------------|-----------------------|------------------------|-------------------------------------|--------|
| Low     | 2412.00         | -12.27               | 2399.92                   | -47.55                | 35.28                  | At least 20dB below from peak of RF | PASS   |
| High    | 2462.00         | -11.77               | 2483.58                   | -57.95                | 46.18                  | At least 20dB below from peak of RF | PASS   |


#### 4.3.4 Trace data

[IEEE802.11b]

##### Channel Low




##### Channel High




[IEEE802.11g]

Channel Low




Channel High




[IEEE802.11n (HT20)]

Channel Low



Channel High



#### 4.4 Spurious emissions - Conducted -

##### 4.4.1 Measurement procedure

###### [FCC 15.247(d), KDB 558074 D01 v05r02, Section 8.5]

The spurious emissions (Conducted) are measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- a) Span = wide enough to fully capture the emission being measured.
- b) RBW = 100 kHz.
- c) VBW  $\geq$  RBW.
- d) Sweep time = auto-couple.
- e) Detector = peak.
- f) Trace mode = max hold.

- Test configuration



##### 4.4.2 Limit

In any 100 kHz bandwidth outside the frequency band the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

**4.4.3 Measurement result**

Date : 23-August-2019

Temperature : 24.5 [°C]

Humidity : 56.0 [%]

Test place : Shielded room No.4

Test engineer :

Tadahiro Seino**[IEEE802.11b、IEEE802.11g、IEEE802.11n (HT20)]**


| Channel | Frequency<br>[MHz] | Limit<br>[dB]                       | Results Chart      | Result |
|---------|--------------------|-------------------------------------|--------------------|--------|
| Low     | 2412               | At least 20dB below from peak of RF | See the trace Data | PASS   |
| Middle  | 2437               | At least 20dB below from peak of RF | See the trace Data | PASS   |
| High    | 2462               | At least 20dB below from peak of RF | See the trace Data | PASS   |

#### 4.4.4 Trace data


[IEEE802.11b]

Channel Low


30MHz-1GHz




1GHz-5GHz




5GHz-10GHz




10GHz-15GHz




15GHz-20GHz




20GHz-25GHz




### Channel Middle 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz




### 15GHz-20GHz




### 20GHz-25GHz




### Channel High 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz




### 15GHz-20GHz




### 20GHz-25GHz




**[IEEE802.11g]  
Channel Low  
30MHz-1GHz**




**1GHz-5GHz**




**5GHz-10GHz**




**10GHz-15GHz**




**15GHz-20GHz**




**20GHz-25GHz**




### Channel Middle 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz




### 15GHz-20GHz




### 20GHz-25GHz




### Channel High 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz



### 15GHz-20GHz




### 20GHz-25GHz




## [IEEE802.11n (HT20)]

## Channel Low


## 30MHz-1GHz




## 1GHz-5GHz




## 5GHz-10GHz




## 10GHz-15GHz




## 15GHz-20GHz




## 20GHz-25GHz




### Channel Middle 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz




### 15GHz-20GHz




### 20GHz-25GHz




### Channel High 30MHz-1GHz




### 1GHz-5GHz




### 5GHz-10GHz




### 10GHz-15GHz



### 15GHz-20GHz



### 20GHz-25GHz



#### 4.5 Spurious Emissions - Radiated -

##### 4.5.1 Measurement procedure

##### [FCC 15.247(d), 15.205, 15.209, KDB 558074 D01 v05r02, Section 8.6]

Test was applied by following conditions.

|                           |                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Test method               | : ANSI C63.10                                                                                                                    |
| Frequency range           | : 9 kHz to 25 GHz                                                                                                                |
| Test place                | : 3m Semi-anechoic chamber                                                                                                       |
| EUT was placed on         | : Styrofoam table / (W) 1.0 × (D) 1.0 × (H) 0.8 m (below 1 GHz)<br>Styrofoam table / (W) 0.6 × (D) 0.6 × (H) 1.5 m (above 1 GHz) |
| Antenna distance          | : 3 m                                                                                                                            |
| Test receiver setting     | Below 1 GHz                                                                                                                      |
| - Detector                | : Average (9 kHz-90 kHz, 110 kHz-490 kHz), Quasi-peak                                                                            |
| - Bandwidth               | : 200 Hz, 120 kHz                                                                                                                |
| Spectrum analyzer setting | Above 1 GHz                                                                                                                      |
| - Peak                    | : RBW=1 MHz, VBW=3 MHz, Span=0 Hz, Sweep=auto                                                                                    |
| - Average                 | : RBW=1 MHz, VBW=10Hz, Span=0 Hz, Sweep=auto<br>Display mode=Linear                                                              |

##### Average Measurement Setting [VBW]

| Mode              | Duty Cycle (%) | T <sub>on</sub> (us) | T <sub>off</sub> (us) | Determined VBW Setting  |
|-------------------|----------------|----------------------|-----------------------|-------------------------|
| IEEE802.11b       | 99.22          | 1024                 | 8                     | 10Hz (Duty Cycle ≥ 98%) |
| IEEE802.11g       | 99.42          | 1364                 | 8                     | 10Hz (Duty Cycle ≥ 98%) |
| IEEE802.11n(HT20) | 99.22          | 1272                 | 10                    | 10Hz (Duty Cycle ≥ 98%) |

Although these tests were performed other than open area test site, adequate comparison measurements


were confirmed against 30 m open area test site.

Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

Radiated emission measurements are performed at 3m distance with the broadband antenna (Loop antenna, Biconical antenna, Log periodic antenna and Double ridged guide antenna). The antenna is positioned both the horizontal and vertical planes of polarization and height is varied 1m to 4m and stopped at height producing the maximum emission. As for the Loop antenna, it is positioned with its plane vertical, and the center of the Loop antenna is 1m above the ground plane.

The EUT is Placed on a turntable, which is 0.8m/1.5m above ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. The test results represent the worst case emission for each emission with manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation. Sufficient time for the EUT, support equipment, and test equipment are allowed in order for them to warm up to their normal operating condition.

#### - Test configuration



#### 4.5.2 Calculation method

[9 kHz to 150 kHz]

Emission level = Reading + (Ant factor + Cable system loss)

Margin = Limit – Emission level

[150 kHz to 25 GHz]

Emission level = Reading + (Ant factor + Cable system loss - Amp. Gain)

Margin = Limit – Emission level

Example:

Limit @ 4824.0 MHz : 74.0 dBuV/m (Peak Limit)

S.A Reading = 49.5 dBuV Cable system loss = 8.4 dB

Result = 49.5 + 8.4 = 45.1 dBuV/m

Margin = 74.0 - 45.1 = 16.1 dB

#### 4.5.3 Limit

| Frequency<br>[MHz] | Field strength  |               | Distance<br>[m] |
|--------------------|-----------------|---------------|-----------------|
|                    | [uV/m]          | [dBuV/m]      |                 |
| 0.009-0.490        | 2400 / F [kHz]  | 20logE [uV/m] | 300             |
| 0.490-1.705        | 24000 / F [kHz] | 20logE [uV/m] | 30              |
| 1.705-30           | 30              | 29.5          | 30              |
| 30-88              | 100             | 40.0          | 3               |
| 88-216             | 150             | 43.5          | 3               |
| 216-960            | 200             | 46.0          | 3               |
| Above 960          | 500             | 54.0          | 3               |

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level [dBuV/m] = 20log Emission [uV/m]
3. As shown in 15.35(b), for frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition modulation.

#### 4.5.4 Test data

Date : 6-August-2019  
Temperature : 21.1 [°C]  
Humidity : 63.7 [%]  
Test place : 3m Semi-anechoic chamber

Test engineer : Tadahiro Seino

Date : 7-August-2019  
Temperature : 21.4 [°C]  
Humidity : 50.3 [%]  
Test place : 3m Semi-anechoic chamber

Test engineer : Tadahiro Seino

Date : 10-September-2019  
Temperature : 22.8 [°C]  
Humidity : 58.1 [%]  
Test place : 3m Semi-anechoic chamber

Test engineer : Tadahiro Seino


Date : 11-September-2019  
Temperature : 22.8 [°C]  
Humidity : 58.1 [%]  
Test place : 3m Semi-anechoic chamber

Test engineer : Tadahiro Seino

#### 4.5.4.1 Transmission mode - With camera

[11b]

#### Channel Low BELOW 1GHz




#### Final Result

| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |

#### Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11b]**  
**Channel Low**  
**ABOVE 1GHz**




## Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4824.000        | H   | 48.7                | 35.9                | 10.1          | 58.8                 | 46.0                 | 74.0                | 54.0                | 15.2           | 8.0            | 163.0       | 168.0     |

## Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11b]  
Channel Middle  
BELOW 1GHz**




**Final Result**

| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11b]**  
**Channel Middle**  
**ABOVE 1GHz**



## Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4874.000        | H   | 49.1                | 35.9                | 10.3          | 59.4                 | 46.2                 | 74.0                | 54.0                | 14.6           | 7.8            | 211.0       | 165.0     |


## Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

[11b]  
Channel High  
BELOW 1GHz



Final Result


| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11b]  
Channel High  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4924.000        | H   | 48.8                | 35.1                | 10.4          | 59.2                 | 45.5                 | 74.0                | 54.0                | 14.8           | 8.5            | 187.0       | 169.0     |


Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

[11g]  
Channel Low  
BELOW 1GHz



Final Result


| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11g]  
Channel Low  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4824.000        | H   | 49.3                | 35.3                | 10.1          | 59.4                 | 45.4                 | 74.0                | 54.0                | 14.6           | 8.6            | 201.0       | 178.0     |


Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

**[11g]  
Channel Middle  
BELOW 1GHz**




**Final Result**

| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

**[11g]**  
**Channel Middle**  
**ABOVE 1GHz**




## Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4874.000        | H   | 49.5                | 35.4                | 10.3          | 59.8                 | 45.7                 | 74.0                | 54.0                | 14.2           | 8.3            | 185.0       | 167.0     |

## Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11g]  
Channel High  
BELOW 1GHz**



**Final Result**


| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11g]  
Channel High  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4924.000        | H   | 50.1                | 35.5                | 10.4          | 60.5                 | 45.9                 | 74.0                | 54.0                | 13.5           | 8.1            | 188.0       | 191.0     |


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

**[11n(HT20)]**  
**Channel Low**  
**BELOW 1GHz**



**Final Result**


| No. | Frequency (P) | c.f        | Height | Angle |
|-----|---------------|------------|--------|-------|
|     | [MHz]         | [dB (1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11n(HT20)]  
Channel Low  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4824.000        | H   | 48.6                | 35.3                | 10.1          | 58.7                 | 45.4                 | 74.0                | 54.0                | 15.3           | 8.6            | 179.0       | 180.0     |


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

**[11n(HT20)]**  
**Channel Middle**  
**BELOW 1GHz**



Final Result


| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

**[11n(HT20)]**  
**Channel Middle**  
**ABOVE 1GHz**




Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4874.000        | H   | 49.4                | 35.3                | 10.3          | 59.7                 | 45.6                 | 74.0                | 54.0                | 14.3           | 8.4            | 205.0       | 164.0     |

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11n(HT20)]**  
**Channel High**  
**BELOW 1GHz**



**Final Result**

| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |


**Note:**

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11n(HT20)]  
Channel High  
ABOVE 1GHz



Final Result


| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4924.000        | H   | 49.9                | 35.5                | 10.4          | 60.3                 | 45.9                 | 74.0                | 54.0                | 13.7           | 8.1            | 181.0       | 167.0     |

Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

4.5.4.2 Receive mode - With camera

Channel Low  
BELOW 1GHz



Final Result


| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |

- Note:
1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable - Amp)]
  2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.



Japan

**Channel Middle**  
**BELOW 1GHz**



**Final Result**


| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.



Japan

**Channel High  
BELOW 1GHz**




**Final Result**

| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 25GHz at the 3 meters distance.

4.5.4.3 Transmission mode - Without camera

[11b]  
Channel Low  
BELOW 1GHz



Final Result

| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11b]  
Channel Low  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4824.000        | H   | 49.0                | 35.7                | 10.1          | 59.1                 | 45.8                 | 74.0                | 54.0                | 14.9           | 8.2            | 200.0       | 165.0     |


Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

**[11b]  
Channel Middle  
BELOW 1GHz**



**Final Result**

| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [°]   |


**Note:**

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11b]  
Channel Middle  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4874.000        | H   | 48.9                | 34.2                | 10.3          | 59.2                 | 44.5                 | 74.0                | 54.0                | 14.8           | 9.5            | 201.0       | 168.0     |


Note:

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.



Japan

**[11b]  
Channel High  
BELOW 1GHz**



**Final Result**

| No. | Frequency (P) | c. f      | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |


**Note:**

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11b]  
Channel High  
ABOVE 1GHz




Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4924.000        | H   | 49.2                | 34.3                | 10.4          | 59.6                 | 44.7                 | 74.0                | 54.0                | 14.4           | 9.3            | 198.0       | 171.0     |

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.

**[11g]  
Channel Low  
BELOW 1GHz**



**Final Result**

| No. | Frequency (P) | c.f       | Height | Angle |
|-----|---------------|-----------|--------|-------|
|     | [MHz]         | [dB(1/m)] | [cm]   | [° ]  |


**Note:**

- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Japan

[11g]  
Channel Low  
ABOVE 1GHz



Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(μV)] | Reading AV [dB(μV)] | c.f [dB(1/m)] | Result PK [dB(μV/m)] | Result AV [dB(μV/m)] | Limit PK [dB(μV/m)] | Limit AV [dB(μV/m)] | Margin PK [dB] | Margin AV [dB] | Height [cm] | Angle [°] |
|-----|-----------------|-----|---------------------|---------------------|---------------|----------------------|----------------------|---------------------|---------------------|----------------|----------------|-------------|-----------|
| 1   | 4824.000        | H   | 48.7                | 34.2                | 10.1          | 58.8                 | 44.3                 | 74.0                | 54.0                | 15.2           | 9.7            | 198.0       | 165.0     |

- Note:
- Emission Level (Margin) = Limit - [Reading + Factor ( Antenna + Cable – Amp)]
  - No emission were detected in frequency range 18GHz to 25GHz at the 3 meters distance.