

Report on the EMC Testing of:

KYOCERA Corporation
Mobile Phone, Model: EB1065

In accordance with FCC Part 15 Subpart B Class B

Prepared for: KYOCERA Corporation
Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku,
Yokohama-shi, Kanagawa, 224-8502 Japan
Phone: +81-45-943-6253 Fax: +81-45-943-6314



Japan

Add value.
Inspire trust.

COMMERCIAL-IN-CONFIDENCE

Document Number: JPD-TR-20200-0

SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Hiroaki Suzuki	Deputy Manager of RF Group	Approved Signatory	

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Japan Ltd. document control rules.

EXECUTIVE SUMMARY – Result: Complied

A sample of this product was tested and the result above was confirmed in accordance with FCC Part 15 Subpart B (excluding the deviations mentioned in section 1.4 of this document).



Certificate #3686.03

DISCLAIMER AND COPYRIGHT

The results in this report are applicable only to the equipment tested.
This report shall not be re-produced except in full without the written approval of TÜV SÜD Japan Ltd.

ACCREDITATION

This test report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the federal government.

TÜV SÜD Japan Ltd.
Yonezawa Testing Center
5-4149-7 Hachimanpara,
Yonezawa-shi, Yamagata,
992-1128 Japan

Phone: +81 (0) 238 28 2881
Fax: +81 (0) 238 28 2888
www.tuv-sud.jp

Additional signatures required by FCC 47 CFR Part 2, § 2.938 (b) (10)**Signatures of the individuals responsible for testing the product****ENGINEERING STATEMENT**

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC Part 15 Subpart B. The sample tested was found Complied compliant with the requirements defined in the applied rules.

NAME	RESPONSIBLE FOR	SIGNATURE
Hiroomi Tsuchiya	Testing	
Tsuyoshi Okumura	Testing	
Satoshi Hosoya	Testing	

Contents

1	Summary of Test	4
1.1	Modification history of the test report.....	4
1.2	Standards	4
1.3	Measurement standards.....	4
1.4	Deviation from standards.....	4
1.5	List of applied test(s) of the EUT	4
1.6	Test information	4
1.7	Test set up.....	4
1.8	Test period.....	4
2	Equipment Under Test	5
2.1	EUT information.....	5
2.2	Modification to the EUT	5
2.3	Variation of family model(s).....	5
2.4	Operation mode.....	6
3	Configuration of Equipment	7
3.1	Equipment used.....	7
3.2	Cable(s) used	7
3.3	System configuration	8
4	Test Result	10
4.1	Conducted emission at mains port	10
4.2	Radiated emission (below 1 GHz).....	12
4.3	Radiated emission (above 1 GHz).....	18
5	Measurement Uncertainty.....	25
6	Laboratory Information	26
Appendix A. Test Equipment.....		27
Appendix B. Configuration Photographs		28

1 Summary of Test

1.1 Modification history of the test report

Document Number	Modification History	Issue Date
JPD-TR-20200-0	First Issue	Refer to the cover page

1.2 Standards

FCC Part 15 Subpart B

1.3 Measurement standards

ANSI C63.4 2014

1.4 Deviation from standards

None

1.5 List of applied test(s) of the EUT

Regarding judgment of conformance to Emission test, a value of measurement uncertainty was not taken in account.

Test Name	Classification of EUT	Test	Worst Point (Margin)	Result	Remarks
Conducted emission at mains port	Class B	Applied	MP4 (No earphone) USB read with PC L2 0.159 MHz QP 11.4 dB	Pass	-
Radiated emission (below 1 GHz)	Class B	Applied	Out camera with ADP V 30.556 MHz QP 3.3 dB	Pass	-
Radiated emission (above 1 GHz)	Class B	Applied	MP4 (No earphone) USB Read with PC V 2999.910 MHz AV 16.6 dB	Pass	-

1.6 Test information

None

1.7 Test set up

Table-top

1.8 Test period

10-December-2020 - 14-December-2020

2 Equipment Under Test

2.1 EUT information

Applicant	KYOCERA Corporation Yokohama Office 2-1-1 Kagahara, Tsuzuki-ku, Yokohama-shi, Kanagawa, 224-8502 Japan Phone: +81-45-943-6253 Fax: +81-45-943-6314
Equipment Under Test (EUT)	Mobile Phone
Model number	EB1065
Serial number	359787710020701
Trade name	KYOCERA
Authorization	JOYEB1065
Number of sample(s)	1
EUT condition	Pre-production
Maximum frequency	2300 MHz
Power rating	Battery: DC 3.8 V
Size	(W) 80 mm × (D) 20 mm × (H) 168 mm
Hardware version	DMT2
Software version	0.070VE
Firmware version	Not applicable

2.2 Modification to the EUT

The table below details modifications made to the EUT during the test project.

Modification State	Description of Modification	Modification fitted by	Date of Modification
EB1065, S/N: 359787710020701			
0	As supplied by the applicant	Not Applicable	Not Applicable

2.3 Variation of family model(s)

2.3.1 List of family model(s)

Not applicable

2.3.2 Reason for selection of EUT

Not applicable

2.4 Operation mode

1. In Camera with ADP mode

- i) Power ON
- ii) Record

2. Out Camera with ADP mode

- i) Power ON
- ii) Record

3. Wide Camera with ADP mode

- i) Power ON
- ii) Record

4. MP4 with Earphone mode

- i) Power ON
- ii) Execution of Color Bar moving picture data

5. MP4 (No earphone) USB Read with PC mode

- i) Power ON
- ii) EUT connects to PC via USB cable
- iii) Read / write of MP4 moving picture data
- iv) Execution of Color Bar moving picture data

3 Configuration of Equipment

Numbers assigned to equipment or cables in “3.1 Equipment(s) used” and “3.2 Cable(s) used” correspond to numbers in “3.3 System configuration”.

This test configuration is based on the manufacture’s instruction.

Cabling and setup(s) were taken into consideration and test data was taken under worse case condition.

3.1 Equipment used

No.	Equipment	Company	Model No.	Serial No.	FCC ID /DoC	Remarks
EUT1	Smart Phone	KYOCERA	EB1065	359787710020701	JOYEB1065	EUT
AE1	AC adapter	KDDI	0301PQA	HS-TFA	N/A	*1
AE2	Earphone	N/A	N/A	N/A	N/A	-
AE3	Personal Computer	Lenovo	TYPE 7854-CTO	LR-0GDNF	DoC	-
AE4	AC adapter	Lenovo	42T4418	11S42T4418ZGWWG21 2MKX REV:H	N/A	-


*1: AC adapter is connected to keep operating.

3.2 Cable(s) used


No.	Cable	Length (m)	Shield	EUT accessory Ferrite core	Remarks
a	USB type C cable	1.0	Yes	-	-
b	USB cable	0.1	Yes	-	-
c	Earphone cable	1.25	No	-	-
d	DC cable for PC AC adapter	1.8	No	-	-
e	AC power cord for PC AC adapter	0.8	No	-	-

3.3 System configuration

1. In Camera with ADP mode
2. Out Camera with ADP mode
3. Wide camera with ADP mode




4. MP4 with earphone mode



: Un-detachable cable

5. MP4 (No earphone) USB read with PC mode



4 Test Result

4.1 Conducted emission at mains port

4.1.1 Measurement condition

Frequency range	0.15 MHz-30 MHz
Test place	10 m Semi-Anechoic Chamber No. 2
EUT was placed on	FRP table (W) 2.0 × (D) 1.0 × (H) 0.8 m
Metal reference plane	Vertical
Test receiver setting	Detector: Quasi-peak, Average Bandwidth: 9 kHz
Line Impedance Stabilization Network (LISN)	Specification: 50 Ω/50 μH Distance from EUT: 0.8 m

EUT is placed on a non-conducting table for table-top equipment or on insulation material for a floor-standing equipment. In addition, a table-top equipment is located 0.4 m to a metal reference plane.

Line Impedance Stabilization Network (LISN) is placed 0.8 m away from the EUT. The power code of the EUT is connected to LISN and its excess part is bundled in the center. The length of bundling is 0.3-0.4 m.

A power code of a peripheral is connected to LISN and terminated into 50 Ω.

Excess cables between equipment are bundled in the center. The length of bundling is 0.3-0.4 m.

Where LISN cannot be applied, the test is performed using a voltage probe.

After overall frequency range is investigated with spectrum analyzer using peak detector, measurements are performed with test receiver in setting to the defined values.

4.1.2 Calculation method

Emission level = Reading + c.f. (correction factor)*

Margin = Limit – Emission level

*Note: c.f. = LISN factor + Cable system loss + Attenuator loss


Example)

Limit @ 6.770 MHz:	60.0 dBμV (Quasi-peak) 50.0 dBμV (Average)
Quasi-peak	Reading = 41.2 dBμV c.f. = 10.3 dB Emission level = 41.2 + 10.3 = 51.5 dBμV Margin = 60.0 - 51.5 = 8.5 dB
Average	Reading = 35.0 dBμV c.f. = 10.3 dB Emission level = 35.0 + 10.3 = 45.3 dBμV Margin = 50.0 - 45.3 = 4.7 dB

4.1.3 Test data and Configuration photographs

Operation mode	MP4 (No earphone) USB Read with PC mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 13-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz



4.2 Radiated emission (below 1 GHz)

4.2.1 Measurement condition

Frequency range	30 MHz-1000 MHz
Test place	10 m Semi-Anechoic Chamber No. 1
EUT was placed on	FRP table (W) 2.0 × (D) 1.0 × (H) 0.8 m
Axis	0°-360°
Antenna	Distance from EUT: 3 m Height: 1-4 m Polarity: Horizontal/Vertical
Test receiver setting	Detector: Quasi-peak Bandwidth: 120 kHz

EUT is placed on a non-conducting table for table-top equipment or on insulation material for a floor-standing equipment. The non-conducting table or the insulation material is placed on a rotating turn table.

Excess cables between equipment are bundled in the center. The length of bundling is 0.3-0.4 m.

An antenna is adjusted between 1-4 m in height and varied its polarization (horizontal and vertical), and the EUT azimuth is varied by the rotating turntable 0 to 360 degrees.

After overall frequency range is investigated with spectrum analyzer using peak detector, measurements are performed with test receiver in setting to the defined values.

4.2.2 Calculation method

Emission level = Reading + c.f. (correction factor)*

Margin = Limit - Emission level

*Note: c.f. = Antenna factor + Cable system loss + Attenuator loss - Amplifier Gain

Example)

Limit @ 350.0 MHz: 37.0 dBμV/m

Reading = 41.1 dBμV c.f. = -11.8 dB/m


Emission level = 41.1 - 11.8 = 29.3 dBμV/m

Margin = 37.0 - 29.3 = 7.7 dB

4.2.3 Test data and Configuration photographs


Operation mode	In Camera with ADP mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 12-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz




Operation mode	Out Camera with ADP mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 12-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz




Operation mode	Wide Camera with ADP mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 12-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz




Operation mode	MP4 with Earphone mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 10-December-2020 Supply voltage: DC 3.8 V



Operation mode	MP4 (No earphone) USB Read with PC mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 10-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz



4.3 Radiated emission (above 1 GHz)

4.3.1 Measurement condition

Frequency range	1000 MHz-115000 MHz
Test place	10 m Semi-Anechoic Chamber No. 2
EUT was placed on	Styrene foam table (W) 2.0 × (D) 1.0 × (H) 0.8 m
Axis	0°-360°
Antenna	Distance: 4.00 m, 3.95 m, 3.80 m Height: 1-4 m Polarity: Horizontal/Vertical
Test receiver setting	Detector: Peak, Average Bandwidth: 1 MHz

EUT is placed on a styrene form table for table-top equipment or on insulation material for a floor-standing equipment. The styrene form table or the insulation material is placed on a rotating turn table.

Excess cables between equipment are bundled in the center. The length of bundling is 0.3-0.4 m.

Absorbers are placed between the EUT and an antenna.

The antenna is adjusted between 1-4 m in height and varied its polarization (horizontal and vertical), and the EUT azimuth is varied by the rotating turntable 0 to 360 degrees. Where height of the antenna is changed, its angle is also adjusted to the position of the EUT.

After overall frequency range is investigated with spectrum analyzer using peak detector, measurements are performed with test receiver in setting to the defined values.

The antenna is positioned from the test volume that was predetermined by the site VSWR measurement. Since this predetermined test volume is different from maximum circumference where the EUT and the peripheral devices are actually placed, the measurement distance conversion factor is added to the measurement data.

Antenna 3 dB beamwidth (antenna used: 3117)

Antenna: 3115

Frequency (GHz)	θ3 dB (°)	3 dB beamwidth w (m)
1.0	63	3.68
2.0	47	2.61
3.0	38	2.07
4.0	36	1.95
5.0	40	2.18
6.0	44	2.42

Antenna: 3117

Frequency (GHz)	θ3 dB (°)	3 dB beamwidth w (m)
1.0	82	5.22
2.0	60	3.46
3.0	76	4.69
4.0	56	3.19
5.0	54	3.06
6.0	50	2.80

Measurement distance: $d = 3.0 \text{ m}$

$W = 2 \times d \times \tan(0.5 \times \theta_{3 \text{ dB}})$

4.3.2 Calculation method

Emission level = Reading + Measurement distance conversion factor + c.f. (correction factor)*

Margin = Limit - Emission level

*Note: c.f. = Antenna factor + Cable system loss + Attenuator loss - Amplifier Gain

Example)

Limit @ 1100.0 MHz: 70.0 dB μ V/m (Peak)
50.0 dB μ V/m (Average)

Measurement distance: 3.25 m

Measurement distance conversion factor: $20 \log (3.25\text{m}/3.0\text{m}) = 0.7 \text{ dB}$


Peak Reading = 50.2 dB μ V, Measurement distance conversion factor = 0.7 dB,
c.f. = 1.7 dB/m
Emission level = $50.2 + 0.7 + 1.7 = 52.6 \text{ dB}\mu\text{V/m}$
Margin = $70.0 - 52.6 = 17.4 \text{ dB}$

Average Reading = 32.0 dB μ V, Measurement distance conversion factor = 0.7 dB,
c.f. = 1.7 dB/m
Emission level = $32.0 + 0.7 + 1.7 = 34.4 \text{ dB}\mu\text{V/m}$
Margin = $50.0 - 34.4 = 15.6 \text{ dB}$

4.3.3 Test data and Configuration photographs


Operation mode	In Camera with ADP mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 13-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz



Operation mode	Out Camera with ADP mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 14-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz



Standard : FCC Class B


Operator : Satoshi Horoga
Temp, Hum, Atm : 18.1°C, 29.4(h) 977(hPa)
Note1 : Fixed height of antenna: 1.00-1.00m
Note2 : Measurement distance: 3.56m

<<EMI Data Sheet>>

No.	Frequency [MHz]	Reading PK [dB(μV)]	Reading AV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin AV [dB]	Height [cm]	Angle [°]
1	1139.061	54.4	39.4	-11.2	43.2	28.2	74.0	54.0	30.8	25.8	100.0	182.0
2	1166.258	54.3	39.5	-10.8	43.5	28.7	74.0	54.0	30.5	25.3	128.0	275.0
3	1193.237	54.8	39.6	-10.4	44.4	29.2	74.0	54.0	29.6	24.8	273.0	246.0
4	1370.435	54.6	39.4	-9.8	44.8	29.6	74.0	54.0	29.2	24.4	100.0	172.0
5	1434.782	54.1	39.1	-10.4	43.7	28.7	74.0	54.0	30.3	25.3	100.0	189.0
6	1560.041	53.7	38.8	-10.2	43.5	28.6	74.0	54.0	30.5	25.4	100.0	133.0
7	2127.774	53.1	38.0	-5.5	47.6	32.5	74.0	54.0	26.4	21.5	139.0	266.0


Operation mode	MP4 with Earphone mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0

Date of test: 12-December-2020 Supply voltage: DC 3.8 V



Operation mode	MP4 (No earphone) USB Read with PC mode
EUT	EB1065, S/N: 359787710020701 - Modification State 0




Date of test: 13-December-2020 Supply voltage: AC 120 V Supply frequency: 60 Hz



5 Measurement Uncertainty

The reported measurement uncertainty is based on a value obtained by multiplying standard uncertainty by coverage factor of $k=2$, and a level of confidence becomes 95 %.

Item	Parameter	U_{lab}	U_{cispr}
Conducted Emission, AMN	9kHz to 150kHz	± 3.8 dB	± 3.8 dB
Conducted Emission, AMN	150kHz to 30MHz	± 3.4 dB	± 3.4 dB
Conducted Emission, AN	150kHz to 30MHz	± 4.3 dB	-
Conducted Emission, Voltage Probe	9kHz to 30MHz	± 2.8 dB	± 2.9 dB
Conducted Emission, AAN	150kHz to 30MHz	± 4.9 dB	± 5.0 dB
Conducted Emission, Current Probe	150kHz to 30MHz	± 2.9 dB	± 2.9 dB
Disturbance Power	30MHz to 300MHz	± 4.3 dB	± 4.5 dB
Radiated Emission	30MHz to 1000MHz	± 4.9 dB	± 6.3 dB
Radiated Emission	1GHz to 6GHz	± 4.6 dB	± 5.2 dB
Radiated Emission	6GHz to 18GHz	± 4.9 dB	± 5.5 dB
Radiated Emission	9kHz to 30MHz	± 3.9 dB	-

Judge	Measured value and standard limit value	
PASS	Standard limit value  Even if it takes uncertainty into consideration, a standard limit value is fulfilled.	Case1
	 Although measured value is in a standard limit value, a limit value won't be fulfilled if uncertainty is taken into consideration.	Case2
FAIL	 Although measured value exceeds a standard limit value, a limit value will be fulfilled if uncertainty is taken into consideration.	Case3
	 Even if it takes uncertainty into consideration, a standard limit value isn't fulfilled.	Case4

6 Laboratory Information

Testing was performed and the report was issued at:

TÜV SÜD Japan Ltd. Yonezawa Testing Center

Address: 5-4149-7 Hachimanpara, Yonezawa-shi, Yamagata, 992-1128 Japan
Phone: +81-238-28-2881
Fax: +81-238-28-2888

Accreditation and Registration

A2LA
Certificate #3686.03

VLAC
Accreditation No.: VLAC-013

BSMI
Laboratory Code: SL2-IN-E-6018, SL2-A1-E-6018

Innovation, Science and Economic Development Canada
ISED#: 4224A

VCCI Council

Registration number	Expiration date
A-0166	03-July-2021

Appendix A. Test Equipment

Conducted emission at mains port

Equipment	Company	Model No.	Serial No.	Cal. due	Cal. Date
EMI receiver	ROHDE&SCHWARZ	ESR7	102352	31-Dec-2021	03-Dec-2020
Line impedance stabilization network	Kyoritsu Technology Corporation	TNW-407F2	12-17-110-1	31-May-2021	26-May-2020
Attenuator	TOYO Connector	BA-PJ-10	N/A(S509)	31-Dec-2020	18-Dec-2019
Coaxial cable	FUJIKURA	5D-2W/5m	N/A(S336)	31-Jan-2021	09-Jan-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX106/28m	501941/6	31-Jan-2021	09-Jan-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/2m	MY15570/4	31-Jan-2021	09-Jan-2020
Software	TOYO Corporation	EP5/CE-AJ	0611193/V5.4.11	N/A	N/A

Radiated emission (below 1 GHz)

Equipment	Company	Model No.	Serial No.	Cal. due	Cal. date
EMI Receiver	ROHDE&SCHWARZ	ESR7	101187	30-Apr-2021	28-Apr-2020
Biconical antenna	Schwarzbeck	VHBB9124/BBA9106	1333	31-Dec-2020	04-Dec-2019
Log-periodic antenna	Schwarzbeck	VUSLP9111B	346	30-Sep-2021	09-Sep-2020
Attenuator	TDC	TAT-43B-06	N/A(S209)	31-Jul-2021	20-Jul-2020
Attenuator	TAMAGAWA.ELEC	CFA-10/3dB	N/A(S504)	31-Jul-2021	20-Jul-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/9m	MY23758/4	31-Oct-2021	28-Oct-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/1m	MY24628/4	31-Oct-2021	28-Oct-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/2m	SN MY28398/4	31-Oct-2021	28-Oct-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX106/13m	MY1159/6	31-Oct-2021	28-Oct-2020
Preamplifier	ANRITSU	MH648A	M96057	31-Jan-2021	09-Jan-2020
10m Semi-anechoic Chamber	TOKIN	N/A	N/A(9001-NSA3m)	31-Oct-2021	29-Oct-2020
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.6.0	N/A	N/A

Radiated emission (above 1 GHz)

Equipment	Company	Model No.	Serial No.	Cal. due	Cal. date
Spectrum analyzer	ROHDE&SCHWARZ	FSV40	101732	28-Feb-2021	17-Feb-2020
Low Noise Pre Amplifier	tsj	MLA-0118-J02-40	19326	31-Dec-2020	17-Dec-2019
Double ridged guide antenna	ETS LINDGREN	3117	00143141	31-May-2021	27-May-2020
Attenuator	HUBER+SUHNER	6803.17.B	N/A(2341)	31-Dec-2020	18-Dec-2019
Microwave cable	HUBER+SUHNER	SUCOFLEX104/1m	MY38347/4	31-Jan-2021	09-Jan-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/9m	MY36274/4	31-Dec-2020	19-Dec-2019
Microwave cable	HUBER+SUHNER	SUCOFLEX106/10m	501942/6	31-Jan-2021	09-Jan-2020
Microwave cable	HUBER+SUHNER	SUCOFLEX104/2m	MY34424/4	31-Jan-2021	09-Jan-2020
Absorber	NEC TOKIN	TFA	N/A	N/A	N/A
10m Semi-anechoic Chamber	TOKIN	N/A	N/A(9005-SVSWR/TTφ3m)	31-Jan-2021	10-Jan-2020
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.6.0	N/A	N/A



Japan

Appendix B. Configuration Photographs

Abort Appendix B: Please refer to the JPD-TR-20200-0Annex