


[11n(HT40)]
W56 / Channel Low
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT40)]
W56 / Channel Low
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c. f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	5463.800	H	50.6		10.2	60.8		68.2	7.4		179.0	187.0	
2	5469.030	V	50.2		10.2	60.4		68.2	7.8		131.0	180.0	
3	11020.000	H	46.3	33.1	10.6	56.9	43.7	74.0	17.1	10.3	152.0	98.0	

Note:


- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT40)]
W56 / Channel Middle
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT40)]
W56 / Channel Middle
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	11100.000	H	45.4	33.4	10.8	56.2	44.2	74.0	17.8	9.8	171.0	59.0	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT40)]
W56 / Channel High
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT40)]
W56 / Channel High
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	11340.000	H	46.2	33.6	11.1	57.3	44.7	74.0	16.7	9.3	163.0	86.0	

Note:


- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT80)]
W52
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.



Zacta

[11n(HT80)]
W52
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Height [cm]	Angle [°]	Remark
1	10420.000	H	45.5	9.9	55.4	68.2	12.8	149.0	120.0	

Note:


- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT80)]
W53
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT80)]
W53
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency	(P)	Reading	c. f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		PK [dB(μV)]	[dB(1/m)]	PK [dB(μV/m)]	PK [dB(μV/m)]	PK [dB]	[cm]	[°]	
1	10580.000	H	46.2	10.1	56.3	68.2	11.9	145.0	130.0	

Note:


1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT80)]
W56 / Channel Low
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT80)]
W56 / Channel Low
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	5469.600	H	51.9	-----	10.2	62.1	-----	68.2	6.1	-----	197.0	133.0	
2	5467.610	V	50.6	-----	10.2	60.8	-----	68.2	7.4	-----	181.0	330.0	
3	11060.000	H	46.3	33.3	10.7	57.0	44.0	74.0	17.0	10.0	152.0	193.0	

Note:


- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.



Zacta

[11n(HT80)]
W56 / Channel High
BELOW 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result


No.	Frequency [MHz]	(P)	c.f [dB(1/m)]	Height [cm]	Angle [°]	Remark
-----	-----------------	-----	---------------	-------------	-----------	--------

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz at the 3 meters distance.

[11n(HT80)]
W56 / Channel High
ABOVE 1GHz

***** RADIATED EMISSION *****
 [3m Semi-anechoic chamber]



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [°]	Remark
1	11220.000	H	46.2	33.6	11.0	57.2	44.6	74.0	16.8	9.4	170.0	212.0	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 18GHz to 40GHz at the 3 meters distance.




Zacta

7.4.4.2 Receive mode

W52 / Channel Low BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W52 / Channel Middle BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W52 / Channel High BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W53 / Channel Low BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W53 / Channel Middle BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W53 / Channel High BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:


- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.



Zacta

W56 / Channel Low BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W56 / Channel Middle BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result


No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

- Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
- No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

W56 / Channel High BELOW 1GHz

***** RADIATED EMISSION *****
[3m Semi-anechoic chamber]



Final Result

No.	Frequency (P)	c.f	Height	Angle	Remark
	[MHz]	[dB(1/m)]	[cm]	[°]	

Note:

1. Emission Level (Margin) = Limit - [Reading + Factor (Antenna + Cable – Amp)]
2. No emission were detected in frequency range 9kHz to 1000MHz and 1GHz to 40GHz at the 3 meters distance.

8. Frequency Stability

8.1 Measurement procedure [FCC 15.407(g)]

The EUT was placed inside of a constant temperature chamber as the temperature in the chamber was varied between -30°C and $+60^{\circ}\text{C}$. The temperature was incremented by 10°C intervals and the unit was allowed to stabilize at each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.


The EUT was set to operate with the following conditions.

- 5.2GHz Band, 5.3GHz Band, 5.6GHz Band

The test mode of EUT is as follows.

- Tx mode

- Test configuration



8.2 Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified.

8.3 Measurement result

Date : November 10, 2017
 Temperature : 22.4 [°C]
 Humidity : 32.4 [%]
 Test place : Shielded room No.4

Test engineer :
 Chiaki Kanno

Date : November 14, 2017
 Temperature : 22.5 [°C]
 Humidity : 34.6 [%]
 Test place : Shielded room No.4

Test engineer :
 Chiaki Kanno

[Channel: 36 (5180MHz)]

Power Supply	Temperature	Measurements Frequency (startup)	Frequency Tolerance (startup)	Measurements Frequency (2mins)	Frequency Tolerance (2mins)	Measurements Frequency (5mins)	Frequency Tolerance (5mins)	Measurements Frequency (10mins)	Frequency Tolerance (10mins)
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]
3.80	25(Ref.)	5179993171	0.00000000	5179999737	1.26756924	5179994867	0.32741356	5179998074	0.94652634
	60	5179983845	-1.80038847	5179982322	-2.09440431	5179982110	-2.13533100	5179982914	-1.98011844
	50	5179962833	-5.85676448	5179993939	0.14826274	5179981502	-2.25270567	5179976794	-3.16158718
	40	5179969692	-4.53263146	5179984755	-1.62471257	5179972681	-3.95560367	5179989291	-0.74903574
	30	5179998726	1.07239524	5179997016	0.74227897	5179988428	-0.91563827	5179989983	-0.61544483
	20	5180010334	3.31332483	5179998381	1.00579283	5179991766	-0.27123588	5180005051	2.29343932
	10	5180017793	4.75328812	5180017575	4.71120312	5180010808	3.40483074	5180023313	5.81892659
	0	5180010877	3.41815122	5180020041	5.18726553	5180017229	4.64440767	5180025728	6.28514342
	-10	5180028007	6.72510539	5180039315	8.90811985	5180026414	6.41757603	5180027199	6.56912063
	-20	5180038463	8.74364087	5180013288	3.88359585	5180036381	8.34170984	5180049726	10.91796806
	-30	5180035200	8.11371726	5180038687	8.78688417	5180036922	8.44615013	5180019744	5.12992954
3.42	25	5179976160	-3.28398116	5179995753	0.49845626	5180000650	1.44382430	5179996271	0.59845639
4.18	25	5179975373	-3.43591187	5180007802	2.82452110	5179996032	0.55231733	5179981132	-2.32413434



Zacta

[Channel: 64 (5320MHz)]

Power Supply	Temperature	Measurements Frequency (startup)	Frequency Tolerance (startup)	Measurements Frequency (2mins)	Frequency Tolerance (2mins)	Measurements Frequency (5mins)	Frequency Tolerance (5mins)	Measurements Frequency (10mins)	Frequency Tolerance (10mins)
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]
3.80	25(Ref.)	5319977733	0.0000000	5319998457	3.89550503	5319987028	1.74718776	5320003072	4.76298986
	60	5319984385	1.25038117	5319974437	-0.61955147	5319984784	1.32538149	5319979098	0.25658002
	50	5319977153	-0.10902301	5319965976	-2.20997166	5319988025	1.93459456	5319979422	0.31748253
	40	5319969008	-1.64004446	5319971497	-1.17218536	5319980154	0.45507709	5319982676	0.92913923
	30	5320000803	4.33648432	5319975335	-0.45075377	5319985225	1.40827657	5320003474	4.83855409
	20	5320007019	5.50491026	5319994197	3.09474980	5320002797	4.71129791	5320021257	8.18123725
	10	5320026904	9.24270786	5320009014	5.87991183	5320007407	5.57784290	5320019612	7.87202543
	0	5320011849	6.41280880	5320010599	6.17784541	5320028159	9.47861110	5320029833	9.79327407
	-10	5320025489	8.97672930	5320028413	9.52635566	5320028645	9.56996487	5320039111	11.53726633
	-20	5320031224	10.05474133	5320040577	11.81283140	5320041759	12.03501278	5320053553	14.25193935
	-30	5320038266	11.37843108	5320023824	8.66375807	5320033979	10.57260064	5320038375	11.39891989
3.42	25	5319976702	-0.19379780	5319995994	3.43253316	5319995142	3.27238212	5320000341	4.24964185
4.18	25	5319997712	3.75546685	5319997433	3.70302302	5319991786	2.64155241	5320003040	4.75697480

[Channel: 140 (5700MHz)]

Power Supply	Temperature	Measurements Frequency (startup)	Frequency Tolerance (startup)	Measurements Frequency (2mins)	Frequency Tolerance (2mins)	Measurements Frequency (5mins)	Frequency Tolerance (5mins)	Measurements Frequency (10mins)	Frequency Tolerance (10mins)
[V]	[°C]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]	[Hz]	[ppm]
3.80	25(Ref.)	5699997537	0.0000000	5699995045	-0.43719317	5699983343	-2.49017651	5699995067	-0.43333352
	60	5699952513	-7.89895078	5699964748	-5.75245863	5699977664	-3.48649273	5699963729	-5.93123063
	50	5699978201	-3.39228217	5699973113	-4.28491413	5699961671	-6.29228342	5699989629	-1.38736902
	40	5699976483	-3.69368581	5699980150	-3.05035220	5699955363	-7.39895057	5699966320	-5.47666903
	30	5699973206	-4.26859834	5699979352	-3.19035226	5699999003	0.25719309	5699969495	-4.91965125
	20	5699982827	-2.58070287	5699990381	-1.25543914	5699976246	-3.73526477	5700004554	1.23105316
	10	5700007671	1.77789551	5700006256	1.52964978	5700017931	3.57789628	5700012188	2.57035199
	0	5700010234	2.22754482	5700006418	1.55807085	5700022738	4.42122998	5700024855	4.79263365
	-10	5700024492	4.72894941	5700023398	4.53701950	5700029899	5.67754631	5700034716	6.52263440
	-20	5700023925	4.62947568	5700033768	6.35631854	5700026454	5.07316009	5700028380	5.41105497
	-30	5700023225	4.50666861	5700014675	3.00666797	5700013113	2.73263276	5700018020	3.59351032
3.42	25	5699999138	0.28087731	5699995883	-0.29017556	5699981753	-2.76912400	5699994577	-0.51929847
4.18	25	5699984862	-2.22368517	5699980835	-2.93017670	5699996391	-0.20105272	5699974154	-4.10228247

9. AC Power Line Conducted Emissions

9.1 Measurement procedure [FCC 15.207]

Test was applied by following conditions.


Test method	: ANSI C63.10
Frequency range	: 0.15MHz to 30MHz
Test place	: 3m Semi-anechoic chamber
EUT was placed on	: FRP table / (W)2.0m × (D)1.0m × (H)0.8m
Vertical Metal Reference Plane	: (W)2.0m × (H)2.0m 0.4m away from EUT
Test receiver setting	
- Detector	: Quasi-peak, Average
- Bandwidth	: 9kHz

EUT and peripherals are connected to 50Ω/50μH Line Impedance Stabilization Network (LISN) which are connected to reference ground plane, and are placed 80cm away from EUT. Excess of AC power cable is bundled in center.

LISN for peripheral is terminated in 50Ω.

EUT operating mode is selected to emit the maximum noise. Overall frequency range is investigated with spectrum analyzer using peak detector. Maximum emission configuration is determined by manipulating the EUT, peripherals, interconnecting cables. Then, emission measurements are performed with test receiver in above setting to each current-carrying conductor of the mains port. Sufficient time for EUT, peripherals and test equipment is provided in order for them to warm up to their normal operating condition. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits.

- Test configuration



9.2 Calculation method

Emission level = Reading + (LISN. factor + Cable system loss)

Margin = Limit – Emission level


9.3 Limit

Frequency [MHz]	Limit	
	QP [dBuV]	AV [dBuV]
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50

*: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

9.4 Test data

***** CONDUCTED EMISSION at MAINS PORT *****
[3m Semi-anechoic chamber]



Final Result


--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.191	26.9	15.9	10.5	37.4	26.4	64.0	54.0	26.6	27.6
2	0.254	21.9	7.6	10.4	32.3	18.0	61.6	51.6	29.3	33.6
3	0.321	23.5	16.5	10.4	33.9	26.9	59.7	49.7	25.8	22.8
4	3.238	21.3	14.0	10.5	31.8	24.5	56.0	46.0	24.2	21.5
5	4.362	22.8	14.5	10.6	33.4	25.1	56.0	46.0	22.6	20.9
6	4.906	22.2	14.2	10.7	32.9	24.9	56.0	46.0	23.1	21.1

--- L2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.191	29.3	17.6	10.5	39.8	28.1	64.0	54.0	24.2	25.9
2	0.253	22.1	7.9	10.4	32.5	18.3	61.7	51.7	29.2	33.4
3	0.321	25.1	16.4	10.4	35.5	26.8	59.7	49.7	24.2	22.9
4	3.190	24.9	16.0	10.6	35.5	26.6	56.0	46.0	20.5	19.4
5	4.383	24.9	16.4	10.6	35.5	27.0	56.0	46.0	20.5	19.0
6	4.953	25.6	16.2	10.7	36.3	26.9	56.0	46.0	19.7	19.1

***** CONDUCTED EMISSION at MAINS PORT *****
[3m Semi-anechoic chamber]



Final Result


--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.189	25.1	15.0	10.5	35.6	25.5	64.1	54.1	28.5	28.6
2	0.321	24.0	16.4	10.4	34.4	26.8	59.7	49.7	25.3	22.9
3	3.743	23.4	15.0	10.6	34.0	25.6	56.0	46.0	22.0	20.4
4	4.115	23.6	15.4	10.6	34.2	26.0	56.0	46.0	21.8	20.0
5	4.758	23.0	15.0	10.7	33.7	25.7	56.0	46.0	22.3	20.3
6	4.944	23.5	15.0	10.7	34.2	25.7	56.0	46.0	21.8	20.3

--- L2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.190	27.8	17.2	10.5	38.3	27.7	64.0	54.0	25.7	26.3
2	0.319	25.5	17.6	10.4	35.9	28.0	59.7	49.7	23.8	21.7
3	3.658	26.5	17.0	10.6	37.1	27.6	56.0	46.0	18.9	18.4
4	4.135	25.5	17.0	10.6	36.1	27.6	56.0	46.0	19.9	18.4
5	4.768	26.3	16.6	10.7	37.0	27.3	56.0	46.0	19.0	18.7
6	4.950	25.9	16.4	10.7	36.6	27.1	56.0	46.0	19.4	18.9

***** CONDUCTED EMISSION at MAINS PORT *****
[3m Semi-anechoic chamber]



Final Result

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.191	25.2	15.1	10.5	35.7	25.6	64.0	54.0	28.3	28.4
2	0.320	23.5	16.7	10.4	33.9	27.1	59.7	49.7	25.8	22.6
3	3.433	22.3	14.4	10.6	32.9	25.0	56.0	46.0	23.1	21.0
4	4.628	22.2	14.6	10.6	32.8	25.2	56.0	46.0	23.2	20.8
5	5.887	21.8	14.0	10.7	32.5	24.7	60.0	50.0	27.5	25.3
6	9.495	22.0	13.9	11.0	33.0	24.9	60.0	50.0	27.0	25.1

--- L2 Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading AV [dB(μV)]	c. f [dB]	Result QP [dB(μV)]	Result AV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin AV [dB]
1	0.190	27.7	16.9	10.5	38.2	27.4	64.0	54.0	25.8	26.6
2	0.316	25.5	17.1	10.4	35.9	27.5	59.8	49.8	23.9	22.3
3	3.424	24.5	16.5	10.6	35.1	27.1	56.0	46.0	20.9	18.9
4	4.736	25.5	16.5	10.7	36.2	27.2	56.0	46.0	19.8	18.8
5	5.835	24.8	15.0	10.8	35.6	25.8	60.0	50.0	24.4	24.2
6	9.500	25.4	15.6	11.1	36.5	26.7	60.0	50.0	23.5	23.3

10. Duty Cycle

10.1 Measurement procedure

[KDB 789033 D02, Section B, Zero-Span Spectrum Analyzer Method]

The duty cycle is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

The spectrum analyzer is set to;

- RBW=8MHz, VBW=8MHz, Span=0Hz, Sweep=Auto, Detector=Peak, Trace mode=Single


The EUT was set to operate with following conditions.

- 5.2GHz Band, 5.3GHz Band, 5.6GHz Band

The test mode of EUT is as follows.

- Tx mode

- Test configuration



10.2 Limit

None

10.3 Measurement result

Date : November 9, 2017
Temperature : 22.9 [°C]
Humidity : 37.4 [%]
Test place : Shielded room No.4

Test engineer : Chiaki Kanno

Mode	Channel	Frequency (MHz)	Duty Cycle				DCF (dB) 10log(1/x)	DCF (dB) 20log(1/x)
			On Time(ms)	On+Off Time(ms)	X	1/T		
802.11a	36	5180	1.344	1.436	0.936	744.0	0.288	0.575
	40	5200						
	48	5240						
	52	5260	1.342	1.446	0.928	745.2	0.324	0.648
	56	5280						
	64	5320						
	100	5500	1.344	1.436	0.936	744.0	0.288	0.575
	116	5580						
	140	5700						

Note: X = On time / (On + Off time)

Mode	Channel	Frequency (MHz)	Duty Cycle				DCF (dB) 10log(1/x)	DCF (dB) 20log(1/x)
			On Time(ms)	On+Off Time(ms)	X	1/T		
802.11n (20MHz)	36	5180	1.260	1.362	0.925	793.7	0.338	0.676
	40	5200						
	48	5240						
	52	5260	1.260	1.366	0.922	793.7	0.351	0.702
	56	5280						
	64	5320						
	100	5500	1.260	1.350	0.933	793.7	0.300	0.599
	116	5580						
	140	5700						

Note: X = On time / (On + Off time)

Mode	Channel	Frequency (MHz)	Duty Cycle				DCF (dB) 10log(1/x)	DCF (dB) 20log(1/x)
			On Time(ms)	On+Off Time(ms)	X	1/T		
802.11n (40MHz)	38	5190	0.626	0.721	0.868	1597.4	0.614	1.227
	46	5230						
	54	5270	0.628	0.732	0.858	1592.4	0.666	1.331
	62	5310						
	102	5510	0.627	0.718	0.873	1594.9	0.589	1.177
	110	5550						
	134	5670						


Note: X = On time / (On + Off time)

Mode	Channel	Frequency (MHz)	Duty Cycle				DCF (dB) 10log(1/x)	DCF (dB) 20log(1/x)
			On Time(ms)	On+Off Time(ms)	X	1/T		
802.11ac (80MHz)	42	5210	0.3156	0.4056	0.778	3168.6	1.090	2.179
	58	5290	0.3151	0.4056	0.777	3173.6	1.096	2.193
	106	5530	0.3156	0.4046	0.780	3168.6	1.079	2.158
	122	5610	0.3151	0.4035	0.781	3173.6	1.074	2.148


Note: X = On time / (On + Off time)

10.4 Trace data [IEEE802.11a]


Channel: 40



Channel: 56




Channel: 116




[IEEE802.11n (HT20)]


Channel: 40



Channel: 56




Channel: 116




[IEEE802.11n (HT40)]


Channel: 38



Channel: 54




Channel: 110




[IEEE802.11ac (HT80)]

Channel: 42




Channel: 58




[IEEE802.11ac (HT80)]

Channel: 106



Channel: 122





Zacta

11. Antenna requirement

According to FCC section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The antenna is a special antenna mounted inside of the EUT. Therefore, the EUT complies with the antenna requirement of FCC section 15.203.

12. Uncertainty of measurement

Expanded uncertainties stated are calculated with a coverage Factor $k=2$.

Please note that these results are not taken into account when determining compliance or non-compliance with test result.

Test item	Measurement uncertainty
Conducted emission, AMN (9kHz – 150kHz)	$\pm 3.8\text{dB}$
Conducted emission, AMN (150kHz – 30MHz)	$\pm 3.3\text{dB}$
Radiated emission (9kHz – 30MHz)	$\pm 3.0\text{dB}$
Radiated emission (30MHz – 1000MHz)	$\pm 4.7\text{dB}$
Radiated emission (1GHz – 6GHz)	$\pm 4.9\text{dB}$
Radiated emission (6GHz – 18GHz)	$\pm 5.2\text{dB}$
Radiated emission (18GHz – 40GHz)	$\pm 5.8\text{dB}$



Zacta

13. Laboratory Information

1. Location

Name: Yonezawa Testing Center
 Address: 5-4149-7, Hachimanpara, Yonezawa-shi, Yamagata, 992-1128 Japan
 Phone: +81-238-28-2881
 Fax: +81-238-28-2888

2. Accreditation and Registration

- 1) VLAC
Accreditation No.: VLAC-013
- 2) NVLAP
LAB CODE: 200306-0
- 3) BSMI
Laboratory Code: SL2-IN-E-6018, SL2-A1-E-6018

4) Industry Canada

Site number	Facility	Expiration date
4224A-4	3m Semi-anechoic chamber	2020-11-27
4224A-5	10m Semi-anechoic chamber No.1	2020-11-27
4224A-6	10m Semi-anechoic chamber No.2	2019-12-14

5) VCCI Council

Registration number	Expiration date
A-0166	2019-07-03

Appendix A. Test equipment

Antenna port conducted test

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
Spectrum analyzer	Agilent Technologies	E4440A	US44302655	Jun. 30, 2018	Jun. 28, 2017
Attenuator	Weinschel	56-10	J4993	Nov. 30, 2017	Nov. 1, 2016
Temperature and humidity chamber	ESPEC	PL1KP	14007261	Jan. 31, 2018	Jan. 20, 2017

Radiated emission

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100765	Sep. 30, 2018	Sep. 13, 2017
Spectrum analyzer	Agilent Technologies	E4447A	MY46180188	Mar. 31, 2018	Mar. 15, 2017
Spectrum analyzer	Agilent Technologies	E4440A	US40420937	Oct. 31, 2018	Oct. 19, 2017
Preamplifier	ANRITSU	MH648A	M96057	Feb. 28, 2018	Feb. 1, 2017
Loop antenna	ROHDE&SCHWARZ	HFH2-Z2	100515	Feb. 28, 2018	Feb. 17, 2017
Attenuator	TDC	TAT-43B-06	N/A(S209)	May 31, 2018	May 23, 2017
Biconical antenna	Schwarzbeck	VHA9103/BBA9106	2155	Jul. 31, 2018	Jul. 18, 2017
Log periodic antenna	Schwarzbeck	UHALP9108A	0560	Jul. 31, 2018	Jul. 18, 2017
Attenuator	TME	CFA-01NPJ-6	N/A(S275)	Feb. 28, 2018	Feb. 3, 2017
Attenuator	TME	CFA-01NPJ-3	N/A(S272)	Feb. 28, 2018	Feb. 2, 2017
Preamplifier	TSJ	MLA-100M18-B02-40	1929118	Feb. 28, 2018	Feb. 3, 2017
Attenuator	AEROFLEX	26A-10	081217-08	May 31, 2018	May 24, 2017
Double ridged guide antenna	ETS LINDGREN	3117	00052315	Feb. 28, 2018	Feb. 23, 2017
Attenuator	Agilent Technologies	8491B	MY39268633	Feb. 28, 2018	Feb. 2, 2017
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	BBHA9170189	Jun. 30, 2018	Jun. 7, 2017
Double ridged guide antenna	A.H.Systems Inc.	SAS-574	469	Aug. 31, 2018	Aug. 8, 2017
Preamplifier	TSJ	MLA-1840-B03-35	1240332	Aug. 31, 2018	Aug. 8, 2017
Notch filter	Micro-Tronics	BRM50716	006	Jul. 31, 2018	Jul. 20, 2017
Microwave cable	HUBER+SUHNER	SUCOFLEX104/9m	MY30037/4	Feb. 28, 2018	Feb. 3, 2017
		SUCOFLEX104/1m	my24610/4	Feb. 28, 2018	Feb. 3, 2017
		SUCOFLEX104/8m	SN MY30031/4	Feb. 28, 2018	Feb. 2, 2017
		SUCOFLEX104/1.5m	MY32976/4	Dec. 31, 2017	Dec. 2, 2016
		SUCOFLEX104/1.5m	MY19309/4	Feb. 28, 2018	Feb. 3, 2017
		SUCOFLEX104/7m	41625/6	Feb. 28, 2018	Feb. 3, 2017
PC	DELL	DIMENSION E521	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/RE-AJ	0611193/V5.6.0	N/A	N/A
Absorber	RIKEN	PFP30	N/A	N/A	N/A
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-NSA)	May 31, 2018	May 30, 2017
3m Semi an-echoic Chamber	TOKIN	N/A	N/A(9002-SVSWR)	May 31, 2018	May 31, 2017

Conducted emission at mains port

Equipment	Company	Model No.	Serial No.	Cal. Due	Cal. Date
EMI Receiver	ROHDE&SCHWARZ	ESCI	100765	Sep. 30, 2018	Sep. 13, 2017
Attenuator	HUBER+SUHNER	6810.01.A	N/A (S411)	Feb. 28, 2018	Feb. 2, 2017
Line impedance stabilization network for EUT	Kyoritsu Electrical Works, Ltd.	KNW-407F2	12-17-110-2	Apr. 30, 2018	Apr. 25, 2017
Coaxial cable	FUJIKURA	5D-2W/4m	N/A (S350)	Feb. 28, 2018	Feb. 2, 2017
Coaxial cable	FUJIKURA	5D-2W/1m	N/A (S193)	Feb. 28, 2018	Feb. 3, 2017
Coaxial cable	HUBER+SUHNER	RG214/U/10m	N/A (S194)	Feb. 28, 2018	Feb. 3, 2017
PC	DELL	DIMENSION	75465BX	N/A	N/A
Software	TOYO Corporation	EP5/CE-AJ	0611193/V5.4.11	N/A	N/A

*: The calibrations of the above equipment are traceable to NIST or equivalent standards of the reference organizations.