

SAR EXCLUSION CALCULATION

FCC ID: JQ6-OK5427G2 / IC ID: 2236B-OK5427G2

RF Exposure Requirements: 47 CFR §1.1307(b)

RF Radiation Exposure Limits: 47 CFR §1.1310

RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65

EUT Frequency Band: 2402MHz-2480MHz

Equation:

According to the procedure in KDB447498 (v05r02) section 4.3, SAR testing is excluded if the following criteria is met.

$$(P/d)^* \sqrt{f} \leq 3.0 \text{ for 1-g SAR}$$

Where

P is the time averaged maximum conducted power in mW

d minimum separation distance in mm

f is the frequency in GHz

The distance between the antenna and human body is 5mm. the calculation was based on the distance of 5mm.

The highest power is 2.47dBm.

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-up Tolerance	Max Tune-up power (dBm)	Measurement Distance (mm)
Bluetooth LE	2480	2.47	3.86	±1	3.47	5

For BLE : $(P/d)^* \sqrt{f} = 0.1921 < 3$ for 1g SAR

Therefore, EUT is not require SAR Evaluation.



Completed By: Rachana Khanduri

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: May 18, 2017