



# **TEST REPORT**

**Report Number:** R15613923-E11e

**Applicant :** HID Global Corporation  
611 Center Ridge Dr  
Austin, TX USA

**Model :** 40TV2

**FCC ID :** JQ6-SIGNO40TV2

**IC :** 2236B-SIGNO40TV2

**EUT Description :** Signo V2 Reader

**Test Standard(s) :** FCC 47 CFR PART 1 SUBPART I  
FCC 47 CFR PART 2 SUBPART J  
OET BULLETIN NO. 65  
IEEE C95.3 – 2021  
ISED RSS-102 Issue 6

**Date Of Issue:**

2025-06-10

**Prepared by:**

UL LLC  
12 Laboratory Dr.  
Research Triangle Park, NC 27709 U.S.A.  
TEL: (919) 549-1400



Revision History

| Rev. | Issue Date | Revisions     | Revised By   |
|------|------------|---------------|--------------|
| V1   | 2025-06-10 | Initial Issue | Manish Baral |

## TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>1. ATTESTATION OF TEST RESULTS .....</b>                              | <b>4</b>  |
| <b>2. TEST METHODOLOGY .....</b>   | <b>6</b>  |
| <b>3. FACILITIES AND ACCREDITATION .....</b>                             | <b>6</b>  |
| <b>4. DECISION RULES AND MEASUREMENT UNCERTAINTY (RF EXPOSURE) .....</b> | <b>7</b>  |
| 4.1. <i>METROLOGICAL TRACEABILITY</i> .....                              | 7         |
| 4.2. <i>DECISION RULES</i> .....   | 7         |
| 4.3. <i>MEASUREMENT UNCERTAINTY</i> .....                                | 7         |
| <b>5. EQUIPMENT UNDER TEST .....</b>                                     | <b>8</b>  |
| 5.1. <i>DESCRIPTION OF EUT</i> .....                                     | 8         |
| 5.2. <i>SOFTWARE AND FIRMWARE</i> .....                                  | 8         |
| 5.3. <i>WORST-CASE CONFIGURATION AND MODE</i> .....                      | 8         |
| 5.4. <i>DESCRIPTION OF TEST SETUP</i> .....                              | 9         |
| 5.5. <i>MEASUREMENT SETUP</i> .....                                      | 10        |
| <b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>                           | <b>10</b> |
| <b>7. DUTY CYCLE .....</b>   | <b>11</b> |
| <b>8. MAXIMUM PERMISSIBLE RF EXPOSURE .....</b>                          | <b>13</b> |
| 8.1. <i>FCC LIMITS AND SUMMARY</i> .....                                 | 13        |
| 8.2. <i>IC LIMITS</i> .....  | 14        |
| 8.2.1. MAXIMUM RESULT SUMMARY RF EXPOSURE (FCC).....                     | 15        |
| 8.2.2. MAXIMUM RESULT SUMMARY RF EXPOSURE (RSS 102).....                 | 16        |
| 8.2.3. E- FIELD AND H- FIELD MEASUREMENTS (FCC) .....                    | 17        |
| 8.2.4. E- FIELD AND H- FIELD MEASUREMENTS (IC) .....                     | 18        |
| <b>9. RF EXPOSURE TEST SETUP AND SETUP PHOTO.....</b>                    | <b>19</b> |

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** HID Global Corporation  
611 Center Ridge Dr  
Austin, TX USA

**EUT DESCRIPTION:** Signo V2 Reader

**MODEL:** 40TV2

**SERIAL NUMBER:** 40TTKS-00-000000, 40TTKS-00-000000

**SAMPLE RECEIPT DATE:** 2025-03-10 and 2025-03-17

**DATE TESTED:** 2025-03-19 to 2025-04-22

| APPLICABLE STANDARDS                           |              |
|--|--------------|
| STANDARD                                       | TEST RESULTS |
| IEEE C95.3-2021                                | Complies     |
| OET BULLETIN NO. 65                            | Complies     |
| FCC 47 CFR PART 1 SUBPART I & PART 2 SUBPART J | Complies     |
| ISED RSS-102 Issue 6                           | Complies     |

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released For  
UL LLC. By:



---

Sarah Kuhaneck  
Engineer Project Associate  
Consumer, Medical and IT Segment.  
UL LLC.

Prepared By:



---

Manish Baral  
Engineer  
Consumer, Medical and IT Segment.  
UL LLC.

## 2. TEST METHODOLOGY

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for correctly integrating customer-provided data with measurements performed by UL LLC.

All testing / calculations were made in accordance with.

- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 447498 D03 Supplement C Cross-Reference v01
- FCC Parts 1.1310, 2.1091, 2.1093, IEEE Std C95.1-2005, IEEE Std C95.3-2021
- RSS-102 Issue 6
- IC Safety Code 6

## 3. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

|                                     | Address  | ISED CABID | ISED Company Number | FCC Registration |
|-------------------------------------|--|------------|---------------------|------------------|
| <input type="checkbox"/>            | Building:<br>12 Laboratory Dr<br>RTP, NC 27709, U.S.A                        |            | 2180C               |                  |
| <input checked="" type="checkbox"/> | Building:<br>2800 Perimeter Park Dr. Suite B<br>Morrisville, NC 27560, U.S.A | US0067     | 27265               | 825374           |

## 4. DECISION RULES AND MEASUREMENT UNCERTAINTY (RF EXPOSURE)

### 4.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

### 4.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| PARAMETER                    | $U_{Lab}$ |
|------------------------------|-----------|
| Magnetic Field Reading (A/m) | +/-0.3 dB |
| Electric Field Reading (V/m) | +/-0.3 dB |

Uncertainty figures are valid to a confidence level of 95.45%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

Signo Reader is a smartcard reader typically installed near doorway as part of physical access system, to control access to that door. A user will approach the door and present a BLE or RFID credentials to the reader with intention of entering the door. The reader will read the credential and send its data to a connected access control panel, which determine whether or not grant the user access to the door. Optionally, a personal identification number (PIN) may also be required, in which case the user will enter the PIN on the reader's keypad.

The EUT supports the following technologies:

| Wireless technologies | Frequency Band(s) | Operating mode(s)               |
|-----------------------|-------------------|---------------------------------|
| NFC                   | 13.56MHz          | Type A 106, 212, 424 & 848 Kbps |
|                       | 125KHz            | 4 Kbps                          |
| Bluetooth             | 2.4 GHz           | LE 1 & 2 Mbps                   |

Notes:

1. The EUT operated in a 1x1 SISO mode.
2. The EUT only supports 1 type(s) of NFC tag.

### 5.2. SOFTWARE AND FIRMWARE

The firmware version installed in the EUT during testing was:

The EUT firmware installed during testing was 10.1

The test utility software used during testing was Rev H

### 5.3. WORST-CASE CONFIGURATION AND MODE

The following configurations were tested as worst-case position:

| Config | Descriptions               | Frequency |
|--------|----------------------------|-----------|
| 1      | Tag Off                    | 13.56 MHz |
| 2      | Tag On (Centered)          |           |
| 3      | (Offset to WC Positioning) |           |

Additionally, testing in five orientations at each of the five configurations were performed. These include top, center, front, left, and right. Only the worst-case data per configuration is included in the report.

## 5.4. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

| Support Equipment List |              |                       |                         |               |
|------------------------|--------------|-----------------------|-------------------------|---------------|
| Description            | Manufacturer | Model                 | Serial Number           | FCC ID        |
| Laptop                 | Lenovo       | Yoga 7 16IAP7         | PF49WDF9                | -             |
| Laptop                 | Lenovo       | T14 Gen3              | PF4FKW01                | -             |
| Laptop Charger         | Lenovo       | ADLX65YLC2D           | 8ssa10R16920L1CZ35T1VXJ | -             |
| USB to Type C cable    | ANKER        | -                     | -                       | -             |
| Data Module            | HID          | -                     | PCB-00476               | -             |
| Laptop                 | Lenovo       | IdeaPad Flex 5 14IAU7 | PW0DWR8R                | TX2-RTL8852BE |

### I/O CABLES

| I/O Cable List |      |                      |                   |            |                  |   |
|----------------|------|----------------------|-------------------|------------|------------------|---|
| Cable No.      | Port | # of Identical Ports | Connector Type    | Cable Type | Cable Length (m) | Remarks                                 |
| 1              | DC   | 1                    | 10pin proprietary | Unshielded | <3m              | Used to connect EUT to DC Power Supply. |

## 5.5. MEASUREMENT SETUP

The measurements were taken using a probe placed 20 cm surrounding the device for all configurations.

20cm distance E-field and H-field are evaluated from the center of the Narda probe.

For measurement setup and all testing photos, refer to external photos exhibit R15701621-EP3e

## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was used for the tests documented in this report:

Test Equipment Used - Line-Conducted Emissions – Voltage (Morrisville – Conducted 1)

| Equipment ID                      | Description | Manufacturer | Model Number | Last Cal.  | Next Cal.  |
|-----------------------------------|-------------|--------------|--------------|------------|------------|
| Electric and Magnetic Field Probe | Narda       | EHP-200AC    | FA0001       | 2024-08-19 | 2025-08-19 |

## 7. DUTY CYCLE

### LIMITS

None; for reporting purposes only.

### PROCEDURE

Zero-Span Spectrum Analyzer Method.

### ON TIME AND DUTY CYCLE RESULTS

|                |              |
|----------------|--------------|
| Test Engineer: | 105900/84740 |
|----------------|--------------|

| Configuration     | Frequency (MHz) | ON Time B (msec) | Period (msec) | Duty Cycle x (linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) |
|-------------------|-----------------|------------------|---------------|-----------------------|----------------|-----------------------------------|
| Tag off           | 13.56           | 28.61            | 95.73         | 0.30                  | 29.89          | NA                                |
| Tag on (centered) | 13.56           | 24.61            | 403.70        | 0.06                  | 6.10           | NA                                |
| Tag on (offset)   | 13.56           | 22.61            | 405.70        | 0.06                  | 5.57           | NA                                |



## 8. MAXIMUM PERMISSIBLE RF EXPOSURE

### 8.1. FCC LIMITS AND SUMMARY

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)   | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(i) Limits for Occupational/Controlled Exposure</b>          |                               |                               |                                     |                          |
| 0.3-3.0   | 614                           | 1.63                          | *(100)                              | ≤6                       |
| 3.0-30  | 1842/f                        | 4.89/f                        | *(900/f <sup>2</sup> )              | <6                       |
| 30-300  | 61.4                          | 0.163                         | 1.0                                 | <6                       |
| 300-1,500   |                               |                               | f/300                               | <6                       |
| 1,500-100,000   |                               |                               | 5                                   | <6                       |
| <b>(ii) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34  | 614                           | 1.63                          | *(100)                              | <30                      |
| 1.34-30   | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | <30                      |
| 30-300  | 27.5                          | 0.073                         | 0.2                                 | <30                      |
| 300-1,500   |                               |                               | f/1500                              | <30                      |
| 1,500-100,000   |                               |                               | 1.0                                 | <30                      |

f = frequency in MHz. \* = Plane-wave equivalent power density.

Using the table above, the limits for uncontrolled exposure to 13.56 MHz RFID radio is 60.77 V/m and 0.16 A/m.

### RESULT:

|                |              |            |                          |
|----------------|--------------|------------|--------------------------|
| Test Engineer: | 105900/84740 | Test Date: | 2025-03-19 to 2025-04-22 |
|----------------|--------------|------------|--------------------------|

## 8.2. IC LIMITS

Radio Standards Specification 102, Issue 5 Radio Frequency (RF) Exposure Compliance of Radio communication Apparatus (All Frequency Bands), sets out the requirements and measurement techniques used to evaluate radio frequency (RF) exposure compliance of radio communication apparatus designed to be used within the vicinity of the human body

The electric and magnetic field strength reference levels, power density reference levels, and associated reference period for devices employed by the general public (uncontrolled environment) and controlled-use devices (controlled environment) are specified in table 7 and table 8. Note that the power density limits specified in these tables apply to whole body exposure conditions.

Table 7: RF field strength and power density limits for devices used by the general public (uncontrolled environment)

| Frequency range (MHz) | Electric field (V <sub>RMS</sub> /m) | Magnetic field (A <sub>RMS</sub> /m) | Power density (W/m <sup>2</sup> ) | Reference period (minutes) |
|-----------------------|--------------------------------------|--------------------------------------|-----------------------------------|----------------------------|
| 10-20                 | 27.46                                | 0.0728                               | 2                                 | 6                          |
| 20-48                 | 58.07 / $f^{0.25}$                   | 0.1540 / $f^{0.25}$                  | 8.944 / $f^{0.5}$                 | 6                          |
| 48-300                | 22.06                                | 0.05852                              | 1.291                             | 6                          |
| 300-6000              | 3.142 $f^{0.3417}$                   | 0.008335 $f^{0.3417}$                | 0.02619 $f^{0.6834}$              | 6                          |
| 6000-15000            | 61.4                                 | 0.163                                | 10                                | 6                          |
| 15000-150000          | 61.4                                 | 0.163                                | 10                                | 616000/ $f^{1.2}$          |
| 150000-300000         | 0.158 $f^{0.5}$                      | $4.21 \times 10^{-4} f^{0.5}$        | $6.67 \times 10^{-5} f$           | 616000/ $f^{1.2}$          |

**Note:**  $f$  is frequency in MHz.

### 8.2.1. MAXIMUM RESULT SUMMARY RF EXPOSURE (FCC)

#### CONFIGURATION 1: TAG OFF

| Electric Field Limit        |                       |                | Magnetic Field Limit  |                       |                |
|-----------------------------|-----------------------|----------------|-----------------------|-----------------------|----------------|
| FCC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | FCC RF Exposure (A/m) | Maximum Average (A/m) | Percentage (%) |
| 60.77                       | 8.360                 | 13.76%         | 0.16                  | 0.040785              | 25.49%         |

#### CONFIGURATION 2: TAG ON (CENTERED)

| Electric Field Limit        |                       |                | Magnetic Field Limit  |                       |                |
|-----------------------------|-----------------------|----------------|-----------------------|-----------------------|----------------|
| FCC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | FCC RF Exposure (A/m) | Maximum Average (A/m) | Percentage (%) |
| 60.77                       | 3.636                 | 5.983%         | 0.16                  | 0.028                 | 17.5%          |

#### CONFIGURATION 3: TAG ON (OFFSET)

| Electric Field Limit        |                       |                | Magnetic Field Limit  |                       |                |
|-----------------------------|-----------------------|----------------|-----------------------|-----------------------|----------------|
| FCC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | FCC RF Exposure (A/m) | Maximum Average (A/m) | Percentage (%) |
| 60.77                       | 3.348                 | 5.51%          | 0.16                  | 0.031                 | 19.38%         |

### 8.2.2. MAXIMUM RESULT SUMMARY RF EXPOSURE (RSS 102)

#### CONFIGURATION 1: TAG OFF

| Electric Field Limit       |                       |                | Magnetic Field Limit       |                       |                |
|----------------------------|-----------------------|----------------|----------------------------|-----------------------|----------------|
| IC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | IC RF Exposure Limit (A/m) | Maximum Average (A/m) | Percentage (%) |
| 27.46                      | 8.360                 | 30.44%         | 0.0728                     | 0.040785              | 56.02%         |

#### CONFIGURATION 2: TAG ON (CENTERED)

| Electric Field Limit       |                       |                | Magnetic Field Limit       |                       |                |
|----------------------------|-----------------------|----------------|----------------------------|-----------------------|----------------|
| IC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | IC RF Exposure Limit (A/m) | Maximum Average (A/m) | Percentage (%) |
| 27.46                      | 3.636                 | 13.2%          | 0.0728                     | 0.028                 | 38.5%          |

#### CONFIGURATION 3: TAG ON (OFFSET)

| Electric Field Limit       |                       |                | Magnetic Field Limit       |                       |                |
|----------------------------|-----------------------|----------------|----------------------------|-----------------------|----------------|
| IC RF Exposure Limit (V/m) | Maximum Average (V/m) | Percentage (%) | IC RF Exposure Limit (A/m) | Maximum Average (A/m) | Percentage (%) |
| 27.46                      | 3.348                 | 12.2%          | 0.0728                     | 0.031                 | 42.6%          |

### 8.2.3. E- FIELD AND H- FIELD MEASUREMENTS (FCC)

Note: Peak measurements were performed. RMS values were calculated from the peak measurement. Please refer to the formula for calculating the RMS values: [Field Strength x  $\sqrt{\text{Duty Cycle}}$ ].

#### CONFIGURATION 1: TAG OFF

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 1             | NA        | 20                      | 60.77                      | Bottom                       | 10.800   |      | 29.89        | 5.905                      | 0.16                         | Bottom   | 0.0296 | 29.86        | 0.016       |
|               |           |                         |                            | Center                       | 4.5890   |      |              | 2.50889                    |                              | Center   | 0.0746 |              | 0.040785    |
|               |           |                         |                            | Left                         | 15.291   |      |              | 8.360                      |                              | Left     | 0.0284 |              | 0.016       |
|               |           |                         |                            | Right                        | 13.652   |      |              | 7.464                      |                              | Right    | 0.0317 |              | 0.017       |
|               |           |                         |                            | Top                          | 11.536   |      |              | 3.069                      |                              | Top      | 0.0300 |              | 0.016       |
|               |           |                         |                            | Max                          | 15.291   |      |              | 8.360                      |                              | Max      | 0.0746 |              | 0.040785    |

#### CONFIGURATION 2: TAG ON (CENTERED)

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 2             | NA        | 20                      | 60.77                      | Bottom                       | 9.0218   |      | 6.10         | 2.228                      | 0.16                         | Bottom   | 0.0283 | 6.10         | 0.007       |
|               |           |                         |                            | Center                       | 14.720   |      |              | 3.636                      |                              | Center   | 0.1118 |              | 0.028       |
|               |           |                         |                            | Left                         | 12.261   |      |              | 3.028                      |                              | Left     | 0.0305 |              | 0.008       |
|               |           |                         |                            | Right                        | 14.256   |      |              | 3.521                      |                              | Right    | 0.0302 |              | 0.007       |
|               |           |                         |                            | Top                          | 12.121   |      |              | 2.994                      |                              | Top      | 0.0287 |              | 0.007       |
|               |           |                         |                            | Max                          | 14.720   |      |              | 3.636                      |                              | Max      | 0.1118 |              | 0.028       |

#### CONFIGURATION 3: TAG ON (OFFSET)

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 3             | NA        | 20                      | 60.77                      | Bottom                       | 7.5894   |      | 5.57         | 1.791                      | 0.16                         | Bottom   | 0.0273 | 5.57         | 0.006       |
|               |           |                         |                            | Center                       | 14.695   |      |              | 3.468                      |                              | Center   | 0.1332 |              | 0.031       |
|               |           |                         |                            | Left                         | 10.262   |      |              | 2.422                      |                              | Left     | 0.0292 |              | 0.007       |
|               |           |                         |                            | Right                        | 12.133   |      |              | 2.863                      |                              | Right    | 0.0294 |              | 0.007       |
|               |           |                         |                            | Top                          | 11.461   |      |              | 2.705                      |                              | Top      | 0.0278 |              | 0.007       |
|               |           |                         |                            | Max                          | 14.695   |      |              | 3.468                      |                              | Max      | 0.1332 |              | 0.031       |

### 8.2.4. E- FIELD AND H- FIELD MEASUREMENTS (IC)

Note: Peak measurements were performed. RMS values were calculated from the peak measurement. Please refer to the formula for calculating the RMS values: [Field Strength x  $\sqrt{\text{Duty Cycle}}$ ].

#### CONFIGURATION 1: TAG OFF

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 1             | NA        | 20                      | 27.46                      | Bottom                       | 10.800   |      | 29.89        | 5.905                      | 0.0728                       | Bottom   | 0.0296 | 29.86        | 0.016       |
|               |           |                         |                            | Center                       | 4.5890   |      |              | 2.50889                    |                              | Center   | 0.0746 |              | 0.040785    |
|               |           |                         |                            | Left                         | 15.291   |      |              | 8.360                      |                              | Left     | 0.0284 |              | 0.016       |
|               |           |                         |                            | Right                        | 13.652   |      |              | 7.464                      |                              | Right    | 0.0317 |              | 0.017       |
|               |           |                         |                            | Top                          | 11.536   |      |              | 3.069                      |                              | Top      | 0.0300 |              | 0.016       |
|               |           |                         |                            | Max                          | 15.291   |      |              | 8.360                      |                              | Max      | 0.0746 |              | 0.040785    |
|               |           |                         |                            |                              |          |      |              |                            |                              |          |        |              |             |

#### CONFIGURATION 2: TAG ON (CENTERED)

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 2             | NA        | 20                      | 27.46                      | Bottom                       | 9.0218   |      | 6.10         | 2.228                      | 0.16                         | Bottom   | 0.0283 | 6.10         | 0.007       |
|               |           |                         |                            | Center                       | 14.720   |      |              | 3.636                      |                              | Center   | 0.1118 |              | 0.028       |
|               |           |                         |                            | Left                         | 12.261   |      |              | 3.028                      |                              | Left     | 0.0305 |              | 0.008       |
|               |           |                         |                            | Right                        | 14.256   |      |              | 3.521                      |                              | Right    | 0.0302 |              | 0.007       |
|               |           |                         |                            | Top                          | 12.121   |      |              | 2.994                      |                              | Top      | 0.0287 |              | 0.007       |
|               |           |                         |                            | Max                          | 14.720   |      |              | 3.636                      |                              | Max      | 0.1118 |              | 0.028       |
|               |           |                         |                            |                              |          |      |              |                            |                              |          |        |              |             |

#### CONFIGURATION 3: TAG ON (OFFSET)

| Configuration | Test Mode | Measuring Distance (cm) | Electric Field Limit (V/m) | Electric Field Reading (V/m) |          |      |              | Magnetic Field Limit (A/m) | Magnetic Field Reading (A/m) |          |        |              |             |
|---------------|-----------|-------------------------|----------------------------|------------------------------|----------|------|--------------|----------------------------|------------------------------|----------|--------|--------------|-------------|
|               |           |                         |                            | FCC                          | Location | Peak | Duty Cycle % | FCC Average                | FCC                          | Location | Peak   | Duty Cycle % | FCC Average |
| 3             | NA        | 20                      | 27.46                      | Bottom                       | 7.5894   |      | 5.57         | 1.791                      | 0.0728                       | Bottom   | 0.0273 | 5.57         | 0.006       |
|               |           |                         |                            | Center                       | 14.695   |      |              | 3.468                      |                              | Center   | 0.1332 |              | 0.031       |
|               |           |                         |                            | Left                         | 10.262   |      |              | 2.422                      |                              | Left     | 0.0292 |              | 0.007       |
|               |           |                         |                            | Right                        | 12.133   |      |              | 2.863                      |                              | Right    | 0.0294 |              | 0.007       |
|               |           |                         |                            | Top                          | 11.461   |      |              | 2.705                      |                              | Top      | 0.0278 |              | 0.007       |
|               |           |                         |                            | Max                          | 14.695   |      |              | 3.468                      |                              | Max      | 0.1332 |              | 0.031       |
|               |           |                         |                            |                              |          |      |              |                            |                              |          |        |              |             |

## 9. RF EXPOSURE TEST SETUP AND SETUP PHOTO

For measurement setup and all testing photos, refer to external photos exhibit R15613923-EP3e

**END OF REPORT**