



FCC PART 15 SUBPART C

IC RSS-210 ISSUE 8, DEC 2010

TEST AND MEASUREMENT REPORT

For

Trimble Navigation Ltd.

935 Stewart Drive,

Sunnyvale, CA 94085, USA

FCC ID: JUP-76577WFBT
IC: 1756A-76577WFBT

Report Type: Original Report	Product Type: 802.11b/g and Bluetooth Combo Module
Test Engineer: <u>Ning Ma</u>	
Report Number: <u>R1201318-247BT</u>	
Report Date: <u>2012-04-09</u>	
Reviewed By: <u>Victor Zhang</u>	
Prepared By: <u>RF/EMC Lead</u>	
(84) Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732 9164	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk “*”

TABLE OF CONTENTS

1 GENERAL INFORMATION.....	6
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	6
1.2 MECHANICAL DESCRIPTION OF EUT	6
1.3 OBJECTIVE.....	6
1.4 RELATED SUBMITTAL(S)/GRANT(S)	6
1.5 TEST METHODOLOGY	6
1.6 MEASUREMENT UNCERTAINTY	6
1.7 TEST FACILITY	7
2 SYSTEM TEST CONFIGURATION.....	8
2.1 JUSTIFICATION	8
2.2 EUT EXERCISE SOFTWARE.....	8
2.3 SPECIAL ACCESSORIES	8
2.4 EQUIPMENT MODIFICATIONS	8
2.5 LOCAL SUPPORT EQUIPMENT	8
2.6 POWER SUPPLY AND LINE FILTERS.....	8
2.7 INTERFACE PORTS AND CABLING	8
2.8 INTERNAL PARTS LIST AND DETAILS.....	8
3 SUMMARY OF TEST RESULTS	9
4 FCC §15.203 & IC RSS-GEN §7.1.2 – ANTENNA REQUIREMENTS.....	10
4.1 APPLICABLE STANDARD	10
4.2 ANTENNAS LIST.....	10
5 FCC §15.207 & RSS-GEN §7.2.4 - AC LINE CONDUCTED EMISSIONS	11
5.1 APPLICABLE STANDARDS	11
5.2 TEST SETUP	11
5.3 TEST PROCEDURE	11
5.4 TEST SETUP BLOCK DIAGRAM.....	12
5.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	12
5.6 TEST EQUIPMENT LIST AND DETAILS	13
5.7 TEST ENVIRONMENTAL CONDITIONS.....	13
5.8 SUMMARY OF TEST RESULTS.....	13
5.9 CONDUCTED EMISSIONS TEST PLOTS AND DATA	14
6 FCC §15.205, §15.209, §15.247(D) & IC RSS-210 §2.2, §A8.5 – SPURIOUS RADIATED EMISSIONS ..	16
6.1 APPLICABLE STANDARD	16
6.2 TEST SETUP	17
6.3 TEST PROCEDURE	17
6.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	18
6.5 TEST EQUIPMENT LIST AND DETAILS	18
6.6 TEST ENVIRONMENTAL CONDITIONS.....	18
6.7 SUMMARY OF TEST RESULTS.....	19
6.8 RADIATED EMISSIONS TEST RESULT DATA	20
7 FCC §15.247(A) & IC RSS-210 §A8.1 – HOPPING CHANNEL BANDWIDTH.....	38
7.1 APPLICABLE STANDARD	38
7.2 MEASUREMENT PROCEDURE	38
7.3 TEST EQUIPMENT LIST AND DETAILS	38
7.4 TEST ENVIRONMENTAL CONDITIONS.....	38
7.5 TEST RESULTS	39
8 FCC §15.247(A) & IC RSS-210 §A8.1 – HOPPING CHANNEL SEPARATION.....	46

8.1	APPLICABLE STANDARD	46
8.2	MEASUREMENT PROCEDURE	46
8.3	TEST EQUIPMENT LIST AND DETAILS	46
8.4	TEST ENVIRONMENTAL CONDITIONS.....	46
8.5	TEST RESULTS	47
9	FCC §15.247(A) & IC RSS-210 §A8.1 - NUMBER OF HOPPING CHANNELS	49
9.1	APPLICABLE STANDARD	49
9.2	MEASUREMENT PROCEDURE	49
9.3	TEST EQUIPMENT LIST AND DETAILS	49
9.4	TEST ENVIRONMENTAL CONDITIONS.....	49
9.5	TEST RESULTS	49
10	FCC §15.247(A) & IC RSS-210 §A8.1 - DWELL TIME.....	52
10.1	APPLICABLE STANDARD	52
10.2	MEASUREMENT PROCEDURE	52
10.3	TEST EQUIPMENT LIST AND DETAILS	52
10.4	TEST ENVIRONMENTAL CONDITIONS.....	52
10.5	TEST RESULTS	53
11	FCC §15.247(B) & IC RSS-210 §A8.4 – MAXIMUM PEAK OUTPUT POWER.....	68
11.1	APPLICABLE STANDARD	68
11.2	MEASUREMENT PROCEDURE	68
11.3	TEST EQUIPMENT LIST AND DETAILS	68
11.4	TEST ENVIRONMENTAL CONDITIONS.....	68
11.5	TEST RESULTS	69
12	FCC §15.247(D) & IC RSS-210 §A 8.5 - BAND EDGES EMISSIONS	70
12.1	APPLICABLE STANDARD	70
12.2	MEASUREMENT PROCEDURE	70
12.3	TEST EQUIPMENT LIST AND DETAILS	70
12.4	TEST ENVIRONMENTAL CONDITIONS.....	70
12.5	TEST RESULTS	70
13	FCC §15.247(D) & IC RSS-210 §A8.5 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	74
13.1	APPLICABLE STANDARD	74
13.2	MEASUREMENT PROCEDURE	74
13.3	TEST EQUIPMENT LIST AND DETAILS	74
13.4	TEST ENVIRONMENTAL CONDITIONS.....	74
13.5	TEST RESULTS	74
14	IC RSS-GEN §6 - RECEIVER RADIATED SPURIOUS EMISSIONS.....	78
14.1	APPLICABLE STANDARDS	78
14.2	EUT SETUP.....	78
14.3	TEST PROCEDURE	78
14.4	CORRECTED AMPLITUDE & MARGIN CALCULATION	78
14.5	TEST EQUIPMENT LIST AND DETAILS	79
14.6	TEST ENVIRONMENTAL CONDITIONS.....	79
14.7	SUMMARY OF TEST RESULTS.....	79
14.8	TEST RESULTS	80
15	FCC §15.247(I), § 2.1091 & IC RSS-102 - RF EXPOSURE INFORMATION	83
15.1	APPLICABLE STANDARDS	83
15.2	MPE PREDICTION	84
15.3	MPE RESULTS	84
15.4	TEST RESULT	84
16	EXHIBIT A - FCC & IC EQUIPMENT LABELING REQUIREMENTS	85
16.1	FCC ID LABEL REQUIREMENTS	85
16.2	IC LABEL REQUIREMENTS	85

16.3	FCC & IC LABEL ON THE HOST UNIT.....	86
17	EXHIBIT B - TEST SETUP PHOTOGRAPHS	88
17.1	RADIATED EMISSION BELOW 1 GHZ (HOST: R10, ANTENNA: SWLP.12) FRONT VIEW.....	88
17.2	RADIATED EMISSION BELOW 1 GHZ (HOST: R10, ANTENNA: SWLP.12) REAR VIEW	88
17.3	RADIATED EMISSION BELOW 1 GHZ (HOST: SPS985, ANTENNA: MAF94432) FRONT VIEW.....	89
17.4	RADIATED EMISSION BELOW 1 GHZ (HOST: SPS985, ANTENNA: MAF94432) REAR VIEW.....	89
17.5	RADIATED EMISSION BELOW 1 GHZ (HOST: SPS985, ANTENNA: 1513151-1) FRONT VIEW	90
17.6	RADIATED EMISSION BELOW 1 GHZ (HOST: SPS985, ANTENNA: 1513151-1) REAR VIEW	90
17.7	RADIATED EMISSION ABOVE 1 GHZ (HOST: R10, ANTENNA: SWLP.12) FRONT VIEW	91
17.8	RADIATED EMISSION ABOVE 1 GHZ (HOST: R10, ANTENNA: SWLP.12) REAR VIEW	91
17.9	RADIATED EMISSION ABOVE 1 GHZ (HOST: SPS985, ANTENNA: MAF94432) FRONT VIEW	92
17.10	RADIATED EMISSION ABOVE 1 GHZ (HOST: SPS985, ANTENNA: MAF94432) REAR VIEW.....	92
17.11	RADIATED EMISSION ABOVE 1 GHZ (HOST: SPS985, ANTENNA: 1513151-1) FRONT VIEW	93
17.12	RADIATED EMISSION ABOVE 1 GHZ (HOST: SPS985, ANTENNA: 1513151-1) REAR VIEW	93
17.13	AC LINE CONDUCTED EMISSION (HOST: R10, ANTENNA: SWLP.12) FRONT VIEW	94
17.14	AC LINE CONDUCTED EMISSION (HOST: R10, ANTENNA: SWLP.12) SIDE VIEW	94
18	EXHIBIT C - EUT PHOTOGRAPHS.....	95
18.1	EUT - TOP VIEW	95
18.2	EUT - BOTTOM VIEW	95
18.3	TEST SUPPORTED BOARD TOP VIEW	96
18.4	TEST SUPPORTED BOARD BOTTOM VIEW	96
18.5	HOST MODEL: R10 (WITH ANTENNA MODEL: SWLP.12).....	97
18.6	HOST MODEL: SPS985 (WITH ANTENNA MODEL: MAF94432)	97
18.7	HOST MODEL: SPS985 (WITH ANTENNA MODEL: 1513151-1)	98
18.8	HOST AC/DC ADAPTER	98
18.9	ANTENNA MODEL: SWLP.12 – COMPONENT VIEW 1	99
18.10	ANTENNA MODEL: SWLP.12 – COMPONENT VIEW 2	99
18.11	ANTENNA MODEL: MAF94432.....	100
18.12	ANTENNA MODEL: 1513151-1 – COMPONENT VIEW 1	100
18.13	ANTENNA MODEL: 1513151-1 – COMPONENT VIEW 2.....	101
18.14	ANTENNA MODEL: SWLP.12 LOCATION IN EUT HOST	101
18.15	ANTENNA MODEL: MAF94432 LOCATION IN EUT HOST	102
18.16	ANTENNA MODEL: 1513151-1 LOCATION IN EUT Host.....	102

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	R1201318-247BT	Original Report	2012-04-09

1 General Information

1.1 Product Description for Equipment under Test (EUT)

This test and measurement report was prepared on behalf of *Trimble Navigation Ltd.* and their product, *model: LBEE19NJZC, FCC ID: JUP-76577WFBT, IC: 1756A-76577WFBT* or the “EUT” as referred to this report. The EUT is Bluetooth and 802.11a/b/g/n Wi-Fi combo module.

1.2 Mechanical Description of EUT

The EUT measures approximately 9.5mm (**L**) x 8.05mm (**W**) x 1.4mm (**H**) and weighs approximately 0.29 g.

The data gathered are from a typical production sample provided by the manufacturer with serial 112566 provide by the manufacturer.

1.3 Objective

This report is prepared on behalf of *Trimble Navigation Ltd* in accordance with Part 2, Subpart J, and Part 15, Subparts B and C of the Federal Communication Commissions rules and IC RSS-210 Issue 8, Dec 2010.

1.4 Related Submittal(s)/Grant(s)

N/A

1.5 Test Methodology

All measurements contained in this report were conducted in accordance with ANSI C63.4-2003.

1.6 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR16-4-2:2003, The Treatment of Uncertainty in EMC Measurements, the values ranging from ± 2.0 dB for Conducted Emissions tests and ± 4.0 dB for Radiated Emissions tests are the most accurate estimates pertaining to uncertainty of EMC measurements at BACL Corp.

1.7 Test Facility

The test site used by BACL Corp. to collect radiated and conducted emissions measurement data is located at its facility in Sunnyvale, California, USA.

The test site at BACL Corp. has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997, and Article 8 of the VCCI regulations on December 25, 1997. The test site also complies with the test methods and procedures set forth in CISPR 22:2008 §10.4 for measurements below 1 GHz and §10.6 for measurements above 1 GHz as well as ANSI C63.4-2003, ANSI C63.4-2009, TIA/EIA-603 & CISPR 24:2010.

The Federal Communications Commission and Voluntary Control Council for Interference have the reports on file and they are listed under FCC registration number: 90464 and VCCI Registration No.: R-3729, C-4176, G-469, and T-1206. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, BACL Corp. is a National Institute of Standards and Technology (NIST) accredited laboratory under the National Voluntary Laboratory Accredited Program (Lab Code 200167-0). The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2001670.htm>

2 System Test Configuration

2.1 Justification

The system was configured for testing in accordance with ANSI C63.4-2003. The EUT was tested in the testing mode to represent *worst-case* results during the final qualification test.

2.2 EUT Exercise Software

The software used, Marvel HCI Tool were provided by client and verified by Wei Sun to comply with the standard requirements being tested against.

2.3 Special Accessories

N/A.

2.4 Equipment Modifications

No modifications were made to the EUT.

2.5 Local Support Equipment

Manufacturer	Description	Model No.	Serial No.
DELL	Laptop	PP18L	-
Trimble Navigation Ltd	Connected Site	SPS985	-
Trimble Navigation Ltd	Connected Site	R10	-

2.6 Power Supply and Line Filters

Manufacturer	Description	Model	Serial Number
Delta Electronics Inc.	AC/DC Adapter	ADP-65JH AB	67JW1CG007P

2.7 Interface Ports and Cabling

Cable Description	Length (m)	From	To
RF Cable	< 1	EUT	Spectrum Analyzer

2.8 Internal Parts List and Details

Manufacturers	Descriptions	Models	Serial Numbers
Trimble Navigation	PCB Board	TYPE_JZ EVB	P2ML0127

3 Summary of Test Results

FCC & IC Rules	Description of Test	Result
FCC §15.247 (i), §2.1091 IC RSS-102	RF Exposure	Compliant
FCC §15.203 IC RSS-Gen §7.1.2	Antenna Requirements	Compliant
FCC §15.207 (a) IC RSS-Gen §7.2.4	AC Line Conducted Emissions	Compliant
FCC §15.247(d) IC RSS-210 §A8.5	Spurious Emissions at Antenna Port	Compliant
FCC §15.205, §15.209, §15.247(d) IC RSS-210 §2.2, §A8.5	Restricted Bands, Spurious Radiated Emissions	Compliant
FCC §15.247 (a)(1)(i) IC RSS-210 §A8.1(c)	20 dB Channel Bandwidth	Compliant
FCC §15.247 (a)(1) IC RSS-210 §A8.1(b)	Hopping Channel Separation	Compliant
FCC §15.247 (a)(1)(i) IC RSS-210 §A8.1(c)	Dwell Time	Compliant
FCC §15.247(a)(1)(i) IC RSS-210 §A8.1(c)	Number of Hopping Channels	Compliant
FCC §15.247(b)(2) IC RSS-210 §A8.4 (1)	Maximum Peak Output Power	Compliant
FCC §15.247(d) IC RSS-210 §A8.5	Band Edge	Compliant
FCC Part 15.109 IC RSS-Gen §6	Receiver Spurious Emission	Compliant

4 FCC §15.203 & IC RSS-Gen §7.1.2 – Antenna Requirements

4.1 Applicable Standard

For intentional device, according to FCC Part §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Per IC RSS-Gen §7.1.2, A transmitter can only be sold or operated with antennas with which it was certified. A transmitter maybe certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in IC RSS-210 or RSS-310 for devices of RF output powers of 10 milliwatts or less. For devices of output powers greater than 10 milliwatts, except devices subject to IC RSS-210 Annex 8 or RSS-210 Annex 9, the total antenna gain shall be added to the measured RF output power before using the specified power limits. For devices subject to IC RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

4.2 Antennas List

Model Number	Manufacturer	Antenna Type	Antenna Gain (dBi)
SWLP.12	Taoglas	Patch (Internal Antenna)	2.0
MAF94432	Laird	Dipole (Reversed TNC)	2.5
1513151-1	Tyco/Rangestar Wireless	IFA (Internal Antenna)	4.0

All antennas meet the requirements of FCC §15.203 and IC RSS-Gen §7.1.2. Please refer to the EUT photos.

5 FCC §15.207 & RSS-Gen §7.2.4 - AC Line Conducted Emissions

5.1 Applicable Standards

As per FCC §15.207 & IC RSS-Gen §7.2.4 Conducted limits:

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 ¹	56 to 46 ¹
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency.

5.2 Test Setup

The measurement was performed at shield room, using the setup per ANSI C63.4-2003 measurement procedure. The specification used was FCC Part15.207 and IC RSS-Gen limits.

External I/O cables were draped along the edge of the test table and bundle when necessary.

The AC/DC power adapter of the host was connected with LISN-1 which provided 120 V/60 Hz AC power.


5.3 Test Procedure

During the conducted emissions test, the power cord of the EUT host system was connected to the mains outlet of the LISN-2.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the peak detection mode, quasi-peak and average. Quasi-Peak readings are distinguished with a “QP.” Average readings are distinguished with an “Ave”.

5.4 Test Setup Block Diagram



5.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Cable Loss, and Attenuator Factor adding to the Indicated Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Cable Loss} + \text{Attenuator Factor}$$

For example, a Corrected Amplitude of 34.07 dBuV = Indicated Reading (23.85 dBuV) + Cable Factor (0.22 dB) + Attenuator Factor (10 dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

5.6 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100044	2011-04-14
Solar Electronics	LISN	9252-R-24-BNC	511205	2011-06-25
TTE	Filter, High Pass	H9962-150K-50-21378	K7133	2011-06-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

5.7 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	33 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-02-24 in 5 meters chamber #3.


5.8 Summary of Test Results

According to the recorded data in following table, the EUT complied with the FCC/IC standard's conducted emissions limits, with the margin reading of:

Connection: AC/DC adapter connected to 120 V/60 Hz, AC			
Margin (dB)	Frequency (MHz)	Conductor Mode (Line/Neutral)	Range (MHz)
-2.73	0.431358	Neutral	0.015-30 MHz

5.9 Conducted Emissions Test Plots and Data

120V/60 Hz Line:




Quasi-Peak Measurement

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (L/N)	Limit (dBuV)	Margin (dB)
0.427434	42.54	L	57.3	-14.76
1.845816	33.32	L	56	-22.68
3.16608	33.09	L	56	-22.91
1.512111	34.97	L	56	-21.03
1.22913	38.02	L	56	-17.98
2.305592	30.26	L	56	-25.74

Average Measurement

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (L/N)	Limit (dBuV)	Margin (dB)
0.427434	41.65	L	47.3	-5.66
1.845816	27.91	L	46	-18.09
3.16608	27.77	L	46	-18.23
1.512111	30.73	L	46	-15.27
1.22913	34.93	L	46	-11.07
2.305592	24.06	L	46	-21.94

120V/60 Hz Neutral:**Quasi-Peak Measurement**

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (L/N)	Limit (dBuV)	Margin (dB)
0.431358	44.41	N	57.23	-12.82
2.400558	30.9	N	56	-25.1
2.298913	30.05	N	56	-25.95
2.24106	31.95	N	56	-24.05
2.899917	32.82	N	56	-23.18
0.58434	32.05	N	56	-23.95

Average Measurement

Frequency (MHz)	Corrected Amplitude (dBuV)	Conductor (L/N)	Limit (dBuV)	Margin (dB)
0.431358	44.5	N	47.23	-2.73
2.400558	24.76	N	46	-21.24
2.298913	25.21	N	46	-20.79
2.24106	25.34	N	46	-20.66
2.899917	26.97	N	46	-19.03
0.58434	28.04	N	46	-17.96

6 FCC §15.205, §15.209, §15.247(d) & IC RSS-210 §2.2, §A8.5 – Spurious Radiated Emissions

6.1 Applicable Standard

As per FCC §15.35(d): Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz.

As per FCC §15.209(a) and RSS-210: Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

As Per FCC §15.205(a) except as show in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 – 0.110	16.42 – 16.423	960 – 1240	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	1300 – 1427	5.35 – 5.46
2.1735 – 2.1905	25.5 – 25.67	1435 – 1626.5	7.25 – 7.75
4.125 – 4.128	37.5 – 38.25	1645.5 – 1646.5	8.025 – 8.5
4.17725 – 4.17775	73 – 74.6	1660 – 1710	9.0 – 9.2
4.20725 – 4.20775	74.8 – 75.2	1718.8 – 1722.2	9.3 – 9.5
6.215 – 6.218	108 – 121.94	2200 – 2300	10.6 – 12.7
6.26775 – 6.26825	123 – 138	2310 – 2390	13.25 – 13.4
6.31175 – 6.31225	149.9 – 150.05	2483.5 – 2500	14.47 – 14.5
8.291 – 8.294	156.52475 – 156.52525	2690 – 2900	15.35 – 16.2
8.362 – 8.366	156.7 – 156.9	3260 – 3267	17.7 – 21.4
8.37625 – 8.38675	162.0125 – 167.17	3.332 – 3.339	22.01 – 23.12
8.41425 – 8.41475	167.72 – 173.2	3.3458 – 3.358	23.6 – 24.0
12.29 – 12.293	240 – 285	3.600 – 4.400	31.2 – 31.8
12.51975 – 12.52025	322 – 335.4		36.43 – 36.5
12.57675 – 12.57725	399.9 – 410		Above 38.6
13.36 – 13.41	608 – 614		

As per FCC §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

As per IC RSS-210 §A8.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

6.2 Test Setup

The radiated emissions tests were performed in the 5-meter Chamber, using the setup in accordance with ANSI C63.4-2003. The specification used was the FCC 15C and IC RSS-210 limits.

The spacing between the peripherals was 10 centimeters.

External I/O cables were draped along the edge of the test table and bundle when necessary.

6.3 Test Procedure

For the radiated emissions test, the EUT host, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to

find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

The spectrum analyzer or receiver is set as:

Below 1000 MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000 MHz:

- (1) Peak: $\text{RBW} = 1\text{MHz} / \text{VBW} = 1\text{MHz} / \text{Sweep} = \text{Auto}$
- (2) Average: $\text{RBW} = 1\text{MHz} / \text{VBW} = 10\text{Hz} / \text{Sweep} = \text{Auto}$

6.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Cable Loss, and Attenuator Factor adding to the Indicated Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Cable Loss} + \text{Attenuator Factor}$$

For example, a Corrected Amplitude of 34.08 dBuV/m = Indicated Reading (23.85 dBuV) + Cable Factor (0.22 dB) + Attenuator Factor (10dB)

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

6.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date
A.H Systems	Antenna, Horn	SAS-200/571	261	2012-01-18
Hewlett Packard	Pre-amplifier	8447D	2944A06639	2011-06-09
Sunol Science Corp	Combination Antenna	JB3	A020106-2	2011-08-10
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100337	2012-03-22
Sunol Science Corp	System Controller	SC99V	122303-1	N/R
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10
Mini-Circuits	Pre-amplifier	ZVA-183-S	667400960	2011-05-08

Statement of Traceability: BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

6.6 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	33 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-02-27 in 5 meter chamber #3.

6.7 Summary of Test Results

According to the data hereinafter, the EUT complied with the FCC Part 15C and IC RSS-210 standard's radiated emissions limits, and had the worst margin of:

30-1000 MHz:

Mode: Transmitting Worst mode (GFSK Mode with Antenna Model: MAF94432)			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Channel, Range
-14.78	66.60725	Horizontal	Low, 30 MHz – 1 GHz

Above 1 GHz:


Mode: Transmitting			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Channel, Range
-	-	-	Low, 1– 25 GHz
-	-	-	Mid, 1– 25 GHz
-	-	-	High, 1– 25 GHz

Please refer to the following table and plots for specific test result details

6.8 Radiated Emissions Test Result Data

1) 30 MHz – 1 GHz, Radiated Spurious Emissions Measured at 3 meters


Worst Case: GFSK Mode, Low Channel (Host: R10, Antenna Model: SWLP.12)



Quasi-Peak Measurement:

Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
33.157	20.63	254	H	27	40	-19.37
485.0105	30.43	101	V	41	46	-15.57
112.3505	22.86	118	V	149	43.5	-20.64
66.62075	24.86	98	H	64	40	-15.14
36.16775	10.77	211	H	129	40	-29.23
80.00825	21.12	109	H	36	40	-18.88


Worst Case: GFSK Mode, Low Channel (Host: SPS985, Antenna Model: MAF94432)



Quasi-Peak Measurement:

Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
30.9775	14.38	157	V	352	40	-25.62
108.077	19.36	98	V	12	43.5	-24.14
129.9413	8.88	264	V	308	43.5	-34.62
35.425	11.42	132	H	66	40	-28.58
109.453	10.32	148	V	300	43.5	-33.18
133.8083	8.4	199	V	28	43.5	-35.1

Worst Case: GFSK Mode, Low Channel (Host: SPS985, Antenna Model: 1513151-1)



Quasi-Peak Measurement:

Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
33.15625	21.45	H	206	7	40	-18.55
113.0858	16.26	V	132	151	43.5	-27.24
115.954	11.73	V	177	34	43.5	-31.77
66.60725	25.22	H	98	62	40	-14.78
35.1815	11.82	V	222	163	40	-28.18
79.987	23.41	H	109	85	40	-16.59

2) Above 1 GHz Radiated Spurious Emissions measured at 3 meters**8PSK Mode**

(Host: R10, Antenna Model: SWLP.12)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: MAF94432)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: 1513151-1)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

DQPSK Mode

(Host: R10, Antenna Model: SWLP.12)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: MAF94432)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: 1513151-1)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

GFSK Mode

(Host: R10, Antenna Model: SWLP.12)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: MAF94432)

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level

(Host: SPS985, Antenna Model: 1513151-1)


Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
Low Channel (2402 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
Middle Channel (2440 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹
High Channel (2480 MHz)											
-	-	-	-	-	-	-	-	-	-	-	- ¹

Note: All emissions are 20 dB below the limit and/or under the noise floor level


3) Spurious Emissions in Restricted Band

Worst Case: GFSK Mode, Host: R10, Antenna Model: SWLP.12


Low Channel (2402 MHz), Vertical, Peak




Low Channel (2402 MHz), Vertical, Average




Low Channel (2402 MHz), Horizontal, Peak




Low Channel (2402 MHz), Horizontal, Average




High Channel (2480 MHz), Vertical, Peak




High Channel (2480 MHz), Vertical, Average



High Channel (2480 MHz), Horizontal, Peak




High Channel (2480 MHz), Horizontal, Average




Worst Case: GFSK Mode, Host: SPS985, Antenna Model: MAF94432


Low Channel (2402 MHz), Vertical, Peak




Low Channel (2402 MHz), Vertical, Average




Low Channel (2402 MHz), Horizontal, Peak




Low Channel (2402 MHz), Horizontal, Average




High Channel (2480 MHz), Vertical, Peak




High Channel (2480 MHz), Vertical, Average



High Channel (2480 MHz), Horizontal, Peak




High Channel (2480 MHz), Horizontal, Average




Worst Case: GFSK Mode, Host: SPS985, Antenna Model: 1513151-1


Low Channel (2402 MHz), Vertical, Peak




Low Channel (2402 MHz), Vertical, Average




Low Channel (2402 MHz), Horizontal, Peak




Low Channel (2402 MHz), Horizontal, Average




High Channel (2480 MHz), Vertical, Peak




High Channel (2480 MHz), Vertical, Average



High Channel (2480 MHz), Horizontal, Peak



High Channel (2480 MHz), Horizontal, Average



7 FCC §15.247(a) & IC RSS-210 §A8.1 – Hopping Channel Bandwidth

7.1 Applicable Standard

According to FCC§15.247(a) (l)(i) & RSS-210 §A8.1 (c), the maximum 20 dB bandwidth of the hopping channel is 500 kHz.

7.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emissions bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

7.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

7.4 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa


The testing was performed by Ning Ma on 2012-03-01 at RF test site.

7.5 Test Results


Channel	Frequency (MHz)	20 dB Emission Bandwidth (kHz)
8PSK Mode		
Low	2402	1327
Mid	2440	1303
High	2480	1325
DQPSK Mode		
Low	2402	1299
Mid	2440	1299
High	2480	1266
GFSK Mode		
Low	2402	847.438
Mid	2440	846.062
High	2480	787.923

Please refer to the following plots.


8PSK Mode, Low Channel (2402 MHz)




8PSK Mode, Middle Channel (2440 MHz)




8PSK Mode, High Channel (2480 MHz)




DQPSK Mode, Low Channel (2402 MHz)




DQPSK Mode, Middle Channel (2440 MHz)




DQPSK Mode, High Channel (2480 MHz)




GFSK Mode, Low Channel (2402 MHz)



GFSK Mode, Middle Channel (2440 MHz)



GFSK Mode, High Channel (2480 MHz)



8 FCC §15.247(a) & IC RSS-210 §A8.1 – Hopping Channel Separation

8.1 Applicable Standard

According to FCC §15.247(a)(1) and IC RSS-210 §A8.1(b): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

8.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument Turn on the EUT and set it to any one convenient frequency within its operating range.
3. By using the Max-Hold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function, and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

8.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

8.4 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa


The testing was performed by Ning Ma on 2012-03-02 at RF test site.

8.5 Test Results


Channel	Frequency (MHz)	Channel Separation (kHz)	GFSK Limit > 2/3 20 dB BW (kHz)	QPSK Limit > 2/3 20 dB BW (kHz)	8PSK Limit > 2/3 20 dB BW (kHz)
Low	2402	1000	627.83	861.33	898.67
Mid	2440	1000	612.01	922.67	916.67
High	2480	1000	559.48	856.00	890.67

Please refer to the following plots.


Low Channel (2402 MHz)



Middle Channel (2440 MHz)



High Channel (2480 MHz)



9 FCC §15.247(a) & IC RSS-210 §A8.1 - Number of Hopping Channels

9.1 Applicable Standard

According to FCC §15.247(a)(1)(i) and IC RSS-210 §A8.1(c), for frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies

9.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the bench without connection to measurement instrument. Turn on the EUT and set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

9.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

9.4 Test Environmental Conditions


Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-03-04 at RF test site.


9.5 Test Results

Please refer to the following plots.


Hopping Channel Number: Total 79 Channels



39 Channels between 2400 to 2440.5 MHz



40 Channels between 2440.5 to 2483.5 MHz



10 FCC §15.247(a) & IC RSS-210 §A8.1 - Dwell Time

10.1 Applicable Standard

According to FCC §15.247(a)(1)(i) and IC RSS-210 §A8.1 (c), for frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period

10.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

10.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

10.4 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-03-07 at RF test site.


10.5 Test Results

8PSK Mode:


Channel	Pulse Width (ms)	Dwell time (sec)	Limit (sec)	Results
8PSK, DH1, Note: Dwell time = Pulse time*(1600/2/79)*31.6 S				
Low	0.416	0.133	0.4	Pass
Mid	0.416	0.133	0.4	Pass
High	0.415	0.132	0.4	Pass
8PSK, DH3, Note: Dwell time = Pulse time*(1600/4/79)*31.6 S				
Low	1.675	0.268	0.4	Pass
Mid	1.675	0.268	0.4	Pass
High	1.675	0.268	0.4	Pass
8PSK DH5, Note: Dwell time = Pulse time*(1600/6/79)*31.6 S				
Low	2.925	0.312	0.4	Pass
Mid	2.925	0.312	0.4	Pass
High	2.925	0.312	0.4	Pass

Please refer to following plots:


8PSK Mode, DH1, Low Channel




8PSK Mode, DH1, Middle Channel




8PSK Mode, DH1, High Channel




8PSK Mode, DH3, Low Channel




8PSK Mode, DH3, Middle Channel




8PSK Mode, DH3, High Channel




8PSK Mode, DH5, Low Channel



8PSK Mode, DH5, Middle Channel




8PSK Mode, DH5, High Channel




DQPSK Mode:

Channel	Pulse Width (ms)	Dwell time (sec)	Limit (sec)	Results
DQPSK, DH1, Note: Dwell time = Pulse time*(1600/2/79)*31.6 S				
Low	0.415	0.132	0.4	Pass
Mid	0.416	0.133	0.4	Pass
High	0.415	0.132	0.4	Pass
DQPSK, DH3, Note: Dwell time = Pulse time*(1600/4/79)*31.6 S				
Low	1.675	0.268	0.4	Pass
Mid	1.675	0.268	0.4	Pass
High	1.675	0.268	0.4	Pass
DQPSK, DH5, Note: Dwell time = Pulse time*(1600/6/79)*31.6 S				
Low	2.925	0.312	0.4	Pass
Mid	2.925	0.312	0.4	Pass
High	2.925	0.312	0.4	Pass


DQPSK Mode, DH1, Low Channel




DQPSK Mode, DH1, Middle Channel




DQPSK Mode, DH1, High Channel




DQPSK Mode, DH3, Low Channel




DQPSK Mode, DH3, Middle Channel




DQPSK Mode, DH3, High Channel




DQPSK Mode, DH5, Low Channel



DQPSK Mode, DH5, Middle Channel




DQPSK Mode, DH5, High Channel




GFSK Mode:

Channel	Pulse Width (ms)	Dwell time (sec)	Limit (sec)	Results
GFSK, DH1, Note: Dwell time = Pulse time*(1600/2/79)*31.6 S				
Low	0.415	0.132	0.4	Pass
Mid	0.406	0.130	0.4	Pass
High	0.413	0.132	0.4	Pass
GFSK, DH3, Note: Dwell time = Pulse time*(1600/4/79)*31.6 S				
Low	1.675	0.268	0.4	Pass
Mid	1.675	0.268	0.4	Pass
High	1.675	0.268	0.4	Pass
GFSK, DH5, Note: Dwell time = Pulse time*(1600/6/79)*31.6 S				
Low	2.917	0.311	0.4	Pass
Mid	2.917	0.311	0.4	Pass
High	2.925	0.312	0.4	Pass


GFSK Mode, DH1, Low Channel




GFSK Mode, DH1, Middle Channel




GFSK Mode, DH1, High Channel




GFSK Mode, DH3, Low Channel




GFSK Mode, DH3, Middle Channel




GFSK Mode, DH3, High Channel




GFSK Mode, DH5, Low Channel



GFSK Mode, DH5, Middle Channel



GFSK Mode, DH5, High Channel



11 FCC §15.247(b) & IC RSS-210 §A8.4 – Maximum Peak Output Power

11.1 Applicable Standard

According to FCC §15.247(b) (2), for frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels

According to IC RSS-210 §8.4(1), For frequency hopping systems operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W if the hopset uses 50 or more hopping channels;

11.2 Measurement Procedure

1. Place the EUT on the turntable and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

11.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

11.4 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-03-10 at RF test site.

11.5 Test Results

Channel	Frequency (MHz)	Max Peak Output Power		Limit (Watt)	Result
		(dBm)	(mw)		
8PSK Mode					
Low	2402	-2.59	0.55	1.0	Pass
Mid	2440	-2.62	0.547	1.0	Pass
High	2480	-2.94	0.51	1.0	Pass
DQPSK Mode					
Low	2402	-3.16	0.48	1.0	Pass
Mid	2440	-3.18	0.48	1.0	Pass
High	2480	-3.49	0.45	1.0	Pass
GFSK Mode					
Low	2402	-0.34	0.92	1.0	Pass
Mid	2440	-0.41	0.91	1.0	Pass
High	2480	-0.73	0.85	1.0	Pass

12 FCC §15.247(d) & IC RSS-210 §A 8.5 - Band Edges Emissions

12.1 Applicable Standard

According to FCC §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required.

According to IC RSS-210 §A 8.5. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required.

12.2 Measurement Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

12.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

12.4 Test Environmental Conditions


Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa

The testing was performed by Ning Ma on 2012-03-11 at RF test site.


12.5 Test Results

Please refer to the following plots.


8PSK Mode, Low band edge




8PSK Mode, High band edge




DQPSK Mode, Low band edge




DQPSK Mode, High band edge



GFSK Mode, Low band edge



GFSK Mode, High Band edge



13 FCC §15.247(d) & IC RSS-210 §A8.5 - Spurious Emissions at Antenna Terminals

13.1 Applicable Standard

As per FCC §15.247(d) and IC RSS-210 § A8.5, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

13.2 Measurement Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on a bench without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the SA on Max-Hold Mode, and then keep the EUT in transmitting mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

13.3 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10

Statement of Traceability: **BACL Corp.** attests that all calibrations have been performed per the NVLAP requirements, traceable to the NIST.

13.4 Test Environmental Conditions

Temperature:	21 °C
Relative Humidity:	32 %
ATM Pressure:	101.7kPa


The testing was performed by Ning Ma on 2012-03-13 at RF test site.

13.5 Test Results


Please refer to the following plots.

Worst Case: GFSK Mode**Low Channel (2402 MHz)**

30 MHz – 1 GHz




1 – 25 GHz




Middle Channel (2440 MHz)

30 MHz – 1 GHz




1 – 25 GHz




High Channel (2480 MHz)

30 MHz – 1 GHz



1 – 25 GHz



14 IC RSS-Gen §6 - Receiver Radiated Spurious Emissions

14.1 Applicable Standards

According to IC RSS-Gen §6, receiver spurious emission shall not exceed the radiated limits shown in the table below:

Frequency (MHz)	Field Strength (micro volts/meter)	Measurement Distance (meters)
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

14.2 EUT Setup

The radiated emissions tests were performed in the 3 meter chamber, using the setup in accordance with ANSI C63.4-2003.

14.3 Test Procedure

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations.

All data were recorded in the peak detection mode. Quasi-peak readings was performed only when an emissions was found to be marginal (within -4 dB of specification limits), and are distinguished with a "QP" in the data table.

14.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corrected Amplitude} - \text{Limit}$$

14.5 Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date
A.H Systems	Antenna, Horn	SAS-200/571	261	2012-01-18
Hewlett Packard	Pre-amplifier	8447D	2944A06639	2011-06-09
Sunol Science Corp	Combination Antenna	JB3	A020106-2	2011-08-10
Rohde & Schwarz	EMI Test Receiver	ESCI 1166.5950K03	100337	2011-03-21
Sunol Science Corp	System Controller	SC99V	122303-1	N/R
Agilent	PSA Spectrum Analyzer	E4440A	MY44303352	2011-05-10
Mini-Circuits	Pre-amplifier	ZVA-183-S	667400960	2011-05-08

Statement of Traceability: BACL attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

14.6 Test Environmental Conditions

Temperature:	22 °C
Relative Humidity:	33 %
ATM Pressure:	101.7kPa

The testing was performed by Wei Sun on 2012-03-27 in 5 meters chamber 3.

14.7 Summary of Test Results

According to the test data, the EUT complied with the FCC Part 15.109 and IC RSS-Gen, with the closest margins from the limit listed below:

Worst Case: Host: R10, Antenna Model: SWLP.12


Mode: Receiving			
Margin (dB)	Frequency (MHz)	Polarization (Horizontal/Vertical)	Range (MHz)
-5.56	33.156	Horizontal	30 MHz to 1000 MHz
-8.14	4173	Vertical	1 – 8 GHz

Please refer to the following table and plots for specific test result details

14.8 Test Results

Host: R10, Antenna Model: SWLP.12

1) 30 MHz -1 GHz, measured at 3 meters



Quasi-Peak Measurements


Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
33.156	34.34	249	H	140	40	-5.66
66.622	26.62	186	H	192	40	-13.38
114.3308	18.22	246	V	190	43.5	-25.28
485.0008	29.67	112	V	23	46	-16.33
35.97075	12.22	205	V	132	40	-27.78
50.25175	4.55	228	V	287	40	-35.45

2) Above 1 GHz, measured at 3 meters

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
4173	40.26	150	114	V	31.67	4.19	27.89	48.23	74	-25.77	Peak
4169	39.33	219	100	H	31.67	4.19	27.89	47.3	74	-26.7	Peak
4173	37.89	150	114	V	31.67	4.19	27.89	45.86	54	-8.14	Avg
4169	36.27	219	100	H	31.67	4.19	27.89	44.24	54	-9.76	Avg

Host: SPS985, Antenna Model: MAF94432

1) 30 MHz – 1 GHz, measured at 3 meters

**Quasi-Peak Measurements**

Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
33.159	20.24	242	V	110	40	-19.76
113.2143	19.08	217	V	127	43.5	-24.42
66.6145	24.59	110	H	83	40	-15.41
36.37125	10.65	170	H	185	40	-29.35
79.98975	13.99	98	H	357	40	-26.01
134.516	8.71	143	V	341	43.5	-34.79


2) Above 1 GHz, measured at 3 meters

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
-	-	-	-	-	-	-	-	-	-	-	-

Note: All emissions are 20 dB below the limit and/or under the noise floor level

Host: SPS985, Antenna Model: 1513151-1

1) 30 MHz – 1 GHz, measured at 3 meters



Quasi-Peak Measurements

Frequency (MHz)	Corrected Amplitude (dB)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB μ V/m)	Margin (dB)
33.15875	24.18	205	H	168	40	-15.82
113.79	25.34	108	V	191	43.5	-18.16
34.745	13.17	222	V	321	40	-26.83
268.233	21.7	108	H	296	46	-24.3
133.6623	8.19	272	V	229	43.5	-35.31
66.38475	31.04	98	V	182	40	-8.96

2) Above 1 GHz, measured at 3 meters

Frequency (MHz)	S.A. Reading (dB μ V)	Turntable Azimuth (degrees)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Reading (dB μ V/m)	FCC & IC		Comments
			Height (cm)	Polarity (H/V)	Factor (dB/m)				Limit (dB μ V/m)	Margin (dB)	
-	-	-	-	-	-	-	-	-	-	-	-

Note: All emissions are 20 dB below the limit and/or under the noise floor level

15 FCC §15.247(i), § 2.1091 & IC RSS-102 - RF Exposure Information

15.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Before equipment certification is granted, the procedure of IC RSS-102 must be followed concerning the exposure of humans to RF fields.

According to IC RSS-102 Issue 2 section 4.1, RF limits used for general public will be applied to the EUT.

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time (Minutes)
0.003-1	280	2.19	-	6
1-10	280/f	2.19/f	-	6
10-30	28	2.19/f	-	6
30-300	28	0.073	2*	6
300-1 500	1.585 f ^{0.5}	0.0042 f ^{0.5}	f/150	6
1 500-15 000	61.4	0.163	10	6
15 000-150 000	61.4	0.163	10	616000 / f ^{1.2}
150 000-300 000	0.158 f ^{0.5}	4.21 x 10 -4 f ^{0.5}	6.67 x 10 ⁻⁵ f	616000 / f ^{1.2}

Note: f is frequency in MHz

* Power density limit is applicable at frequencies greater than 100 MHz

15.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

15.3 MPE Results

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>-0.34</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>0.92</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>2402</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>4.0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>2.51</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.000459</u>
<u>Power density of prediction frequency at 20.0 cm (W/m²):</u>	<u>0.00459</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>1.0</u>
<u>MPE limit for uncontrolled exposure at prediction frequency (W/m²):</u>	<u>10</u>

15.4 Test Result

This device complies with the MPE limit at 20cm for uncontrolled exposure.