



# RF Exposure Evaluation Report

**APPLICANT** : Group Sense Limited  
**EQUIPMENT** : eBook Reader  
**MODEL NAME** : eBook Reader  
**FCC ID** : K2WSPJL10  
**FILING TYPE** : Certification  
**STANDARD** : OET Bulletin 65 Supplement C (Edition 01-01)

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with FCC OET Bulletin 65 Supplement C (Edition 01-01), and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager

**SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**



## **Table of Contents**

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>1. RF EXPOSURE INTRODUCTION .....</b>	<b>4</b>
<b>2. ADMINISTRATION DATA .....</b>	<b>6</b>
2.1 Testing Laboratory .....	6
2.2 Applicant .....	6
2.3 Manufacturer .....	6
<b>3. GENERAL INFORMATION .....</b>	<b>7</b>
3.1 Description of Device Under Test (DUT) .....	7
<b>4. RF EXPOSURE EVALUATION .....</b>	<b>8</b>
4.1 Radio Frequency Radiation Exposure Evaluation .....	8



## **Revision History**

<b>REPORT NO.</b>	<b>VERSION</b>	<b>DESCRIPTION</b>	<b>ISSUED DATE</b>
FA081921	Rev. 01	Initial issue of report	Oct. 25, 2010



## **1. RF Exposure Introduction**

### **Requirements**

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile and portable and are defined as follows:

#### **▪ Fixed installation:**

Fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

#### **▪ Mobile Devices:**

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR 2.1091.

#### **▪ Portable Devices:**

A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR 2.1093)



The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

▪ **Occupational/controlled Exposure:**

In general, occupational/controlled exposure limits are applicable to situation in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.

▪ **General Population/Uncontrolled Exposure:**

The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.



## **2. Administration Data**

### **2.1 Testing Laboratory**

<b>Test Site</b>	SPORTON INTERNATIONAL INC.
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  TEL: +886-3-327-3456 FAX: +886-3-328-4978

### **2.2 Applicant**

<b>Company Name</b>	Group SENSE LIMITED
<b>Address</b>	6/F., Enterprise Building, No. 5, Science Park West Avenue, Hong Kong Science Park, Shatin, N.T. Hong Kong

### **2.3 Manufacturer**

<b>Company Name</b>	Group SENSE LIMITED
<b>Address</b>	6/F., Enterprise Building, No. 5, Science Park West Avenue, Hong Kong Science Park, Shatin, N.T. Hong Kong

### **3. General Information**

#### **3.1 Description of Device Under Test (DUT)**

Product Feature & Specification	
DUT Type	eBook Reader
Model Name	eBook Reader
FCC ID	K2WSPJL10
Tx Frequency	2400 MHz ~ 2483.5 MHz
Rx Frequency	2400 MHz ~ 2483.5 MHz
Antenna Type	Chip Antenna with gain 0.2 dBi
HW Version	v1.0
SW Version	v0.9
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
DUT Stage	Identical Prototype

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



#### **4. RF Exposure Evaluation**

##### **4.1 Radio Frequency Radiation Exposure Evaluation**

For this device, the calculation is as follows:

No evaluation required if power is below this power threshold:

Frequency (GHz)	Power (mW)	Power (dBm)
2.48	24.19	13.84

Maximum measured transmitter power for the EUT:

Band	802.11b			802.11g		
Channel	1	6	11	1	6	11
Frequency (MHz)	2412	2437	2462	2412	2437	2462
Peak Power	15.64	16.03	16.17	21.87	21.96	21.01
Average Power	13.12	13.37	13.53	13.15	13.08	11.53

Threshold for no RF exposure evaluation is 13.84 dBm.

The maximum average power of this device is 13.53 dBm.

**Conclusion:** No RF exposure evaluation required since transmitter output power is below the power threshold.