



Maximum Permissible Exposure Evaluation

for

**HUGHES NETWORK SYSTEMS
HUGHES 9250**

FCC ID: K3YHNS9250

March 29, 2007

WLL PROJECT #: 9508

This report may not be reproduced, except in full, without the prior written consent of Washington Laboratories, Ltd.

Maximum Permissible Exposure Test Report

for

FCC ID: K3YHNS9250

1.0 Introduction

This report has been prepared on behalf of Hughes Network Systems HUGHES 9250. Transmitter to show compliance with the RF exposure requirements as defined in FCC §1.1307.

1.1 Requirements

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

For this test report the Hughes Network Systems HUGHES 9250 with the SpaceComm C10 antenna for the Part 25 LMES radio and a 0dB antenna for the WLAN antenna the MPE is evaluated at the 20cm test distance.

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Since there are no warnings or training associated with this unit and it can be used by anyone, the Hughes Network Systems HUGHES 9250 is evaluated to the General Population/Uncontrolled Exposure limits.

1.2 Radio Frequency Radiation Exposure Evaluation for the WLAN card.

The highest RF output power of the unit was measured is recorded. According to §1.1310 of the FCC rules, the power density limit for General Population/Uncontrolled Exposure is $1\text{mW}/\text{cm}^2$. The MPE shall be calculated at 20cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at the Antenna Terminals

G = Gain of Transmit Antenna (linear gain-isotropic)

R = Distance from Transmitting Antenna

Single Transmitter Frequency	2412	MHz
Limit	1.000	mW/cm ²
Distance (cm), R =	20	cm
Power (dBm), P =	13.72	dBm
TX Ant Gain (dB), G =	0	dB
MPE	0.00	mW/cm ² Separation<20 cm
Minimum Distance:	1.4	cm

1.3 *Radio Frequency Radiation Exposure Evaluation for the LMES antenna.*

The MPE for the LMES antenna was evaluated by testing the unit. The transmitter was turned on in a worst case mode, using a CW signal. Measurements were taken around the radome as well as 20 cm from the radom. The readings were taken with a Wandel and Goltermann EMR-20 field probe that has a readout in mW/cm²

The antenna was placed on a non-conductive surface and the probe was moved all around the antenna and the highest reading was recorded.

Frequency (MHz)	Modulation	20cm reading (mW/cm ²)	at radome cover (mW/cm ²)
1626.6	CW	0.24	0.54
1643.6	CW	0.3	0.57
1640.4	CW	0.24	0.62

Test Name: MPE measurements		Test Date: 03/29/2007	
Asset #	Manufacturer/Model	Description	Cal Due
561	Wandel and Goltermann EMR-20	Filed Strength Probe	2/8/2008

The measured reading show that the unit complies with the MPE requirements at 20cm.

The test setup is provided in the photograph below.

