To: Diane Poole

Diane.Poole@fcc.gov

From: Sae Hagino

Sae.hagino@intertek.com

Intertek Japan K.K.

Applicant: Kenwood Corporation

FCC ID: K44371300

Correspondence Reference Number: 38370 731 Confirmation Number: EA532633

Subject: Response to e-mail dated on Nov. 19

The applicable rule parts are: 22, 74, and 90.

Please add the following grant notes:

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

There is missing information on the equipment specifications. Please add the following Line Entries 10 through 18 (red text).

| Line | Lower | Upper | Power | Tolerance | Emission | Microprocessor | Rule | Grant |
|-------|-----------|-----------|-------|-----------|------------|----------------|---------------------------|--------|
| Entry | Frequency | Frequency | | | Designator | Number | Parts | Notes |
| 1 | 150 | 174 | 5 | 1 ppm | 16K0F3E | | 22, 74 , 90 | BC, EF |
| 2 | 150 | 174 | 5 | 1 ppm | 11K0F3E | | 22, 74 , 90 | BC, EF |
| 3 | 150 | 174 | 5 | 1 ppm | 8K30F1E | | 22, 74 , 90 | BC, EF |
| 4 | 150 | 174 | 5 | 1 ppm | 8K30F1D | | 22, 74 , 90 | BC, EF |
| 5 | 150 | 174 | 5 | 1 ppm | 8K30F7W | | 22, 74 , 90 | BC, EF |
| 6 | 150 | 174 | 5 | 1 ppm | 4K00F1E | | 22, 74 , 90 | BC, EF |
| 7 | 150 | 174 | 5 | 1 ppm | 4K00F1D | | 22, 74, 90 | BC, EF |

| 8 | 150 | 174 | 5 | 1 ppm | 4K00F7W | 22, 74 , 90 | BC, EF |
|----|-----|-----|---|---------|---------|--------------------|--------|
| 9 | 150 | 174 | 5 | 1 ppm | 4K00F2D | 22, 74, 90 | BC, EF |
| 10 | 150 | 174 | 5 | 0.5 ppm | 16K0F3E | 22, 74, 90 | BC, EF |
| 11 | 150 | 174 | 5 | 0.5 ppm | 11K0F3E | 22, 74, 90 | BC, EF |
| 12 | 150 | 174 | 5 | 0.5 ppm | 8K30F1E | 22, 74, 90 | BC, EF |
| 13 | 150 | 174 | 5 | 0.5 ppm | 8K30F1D | 22, 74, 90 | BC, EF |
| 14 | 150 | 174 | 5 | 0.5 ppm | 8K30F7W | 22, 74, 90 | BC, EF |
| 15 | 150 | 174 | 5 | 0.5 ppm | 4K00F1E | 22, 74, 90 | BC, EF |
| 16 | 150 | 174 | 5 | 0.5 ppm | 4K00F1D | 22, 74, 90 | BC, EF |
| 17 | 150 | 174 | 5 | 0.5 ppm | 4K00F7W | 22, 74, 90 | BC, EF |
| 18 | 150 | 174 | 5 | 0.5 ppm | 4K00F2D | 22, 74, 90 | BC, EF |