

TEST REPORT

REGULATION :

FCC Part 2, 24D, 90

RSS-134 Issue 2, RSS-119 Issue 12

Applicant	Testing Laboratory
JVC KENWOOD Corporation 1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan Tel.: +81 45 939 6254 Fax.: +81 45 939 6261	Intertek Japan K.K. Kashima Laboratory URL: http://www.japan.intertek-etlsemko.com (No.12 Test site) 298-6 Sada, Kashima, Ibaraki 314-0027 Japan Tel. +81 299 82 8464 (No.1 Test site) 3-2 Sunayama, Kamisu, Ibaraki 314-0255 Japan Tel. +81 479 40 1097

Equipment type	900MHz DIGITAL BASE-REPEATER
Trademark	KENWOOD
FCC Model(s)	NXR-5901-K
IC Model(s)	NXR-5901-K
Serial No.	B7390030
FCC ID	K44474701
IC CN and UPN	282F-474701
Test Result	Complied
Report Number	17080105JKA-002
Original Issue Date	September 29, 2017

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Approved by



Hideaki Kosemura

[Technical Manager]

Tested by



Koichi Wagatsuma

[Engineer]



VLAC accreditation are valid for FCC Part90,FCC Part24D and RSS-119.
RSS-134 is outside the scope.

In Accordance with FCC Rules and Regulations, Volume II, Part 2 and 90**Sub-part 2.1033**

Applicant and Manufacture Information	
APPLICANT	
Company	: JVC KENWOOD Corporation
Address	: 1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan
Contact Person	: Tamaki Shimamura Manager, Communications Systems Division
MANUFACTURER	
Company	: JVC KENWOOD Corporation
Address	: 1-16-2, Hakusan, Midori-ku, Yokohama-shi Kanagawa, 226-8525 Japan
(c)(2) FCC ID	
FCC ID	: K44474701
Model number	: NXR-5901-K
Serial number	: B7390030
Instruction Manual(S)	
Instruction manual(s)	: Please refer to attached Exhibits F
Type of Emission	
Emission Designation	: 11K0F3E(Narrow) 8K30F1E(Narrow) / 8K30F1D(Narrow) / 8K30F7W(Narrow) 4K00F1E(Very Narrow) / 4K00F1D(Very Narrow) / 4K00F7W(Very Narrow) 4K00F2D(Very Narrow)
Frequency range	
Frequency Range	: TX: 935 to 940 MHz (FCC90/RSS-119) TX: 940 to 941MHz (FCC24D/RSS-134) RX: 896 to 901 MHz and 901 to 902MHz
Power Rating	
Output Power	: 100m to 360m W
Type	: Continuously Variable
Maximum Power Rating	
Output Power	: 360m W
Voltages & currents in all elements in final RF stage, including final transistor or solid-state device	
Collector Current, A	: 5.0 A Maximum
Collector Voltage, Vdc	: 13.8 Vdc
Supply Voltage, Vdc	: 13.8 Vdc
Other Information	
Number of Channel	: 30 channels
Maximum Deviation	: ± 2.5 kHz (11K0F3E)
Frequency Stability	: 0.1 ppm : 935 to 940 MHz (FCC90/RSS-119)
	: 0.5 ppm : 940 to 941 MHz (FCC24D/RSS-134)
Antenna Impedance	: 50 Ω Nominal
Note	

TABLE OF CONTENTS

	Page
SECTION 1. GENERAL INFORMATION	4
SECTION 2. SUMMARY OF TEST RESULT	5
SECTION 3. TEST AND MEASUREMENT DATA	6
SECTION 4. INFORMATION ABOUT EUT AND SUPPORT EQUIPMENT(S)	7
SECTION 5. SUPPORT EQUIPMENT	8
SECTION 6. USED CABLE(S)	9
SECTION 7. TEST CONFIGURATION	10
SECTION 8. OPERATING CONDITION	11
SECTION 9. MEASUREMENT UNCERTAINTY	12
SECTION 10. TEST DATA	
10.1 Carrier Output Power (Conducted)	13
10.2 Unwanted Emissions (Transmitter Conducted)	16
10.3 Field Strength of Spurious Radiation	20
10.4 Emission Masks (Occupied Bandwidth)	26
10.5 Audio Frequency Response / Audio Low Pass Filter (Voice Input)	44
10.6 Modulation Limiting	48
10.7 Frequency Stability (Temperature Variation)	52
10.8 Frequency Stability (Voltage Variation)	56
10.9 Receiver Spurious Emissions(Radiated)	58
10.10 Necessary Bandwidth and Emission Bandwidth	62
10.11 99% Occupied Bandwidth	63
APPENDIX PHOTOGRAPHS	

SECTION 1. GENERAL INFORMATION

TEST PERFORMED

Location	Kashima No.1 Test Site and No.12 Test Site		
EUT Received	August 24, 2017		
Date of Test	August 24, 2017	to	September 21, 2017
Standard Applied	FCC Part 2, 24D, 90 RSS-134 Issue 2, RSS-119 Issue 12		
Measurement Method	ANSI/TIA-603-E-2016 / RSS-119 Issue 12(2015), RSS-Gen Issue 4(2014) RSS-134 Issue 2(2016)		
Deviation from Standard(s)	Not applicable		

QUALIFICATIONS OF TESTING LABORATORY (Kashima Lab.)

ACCREDITATION	SCOPE	LAB. CODE	Remarks
VLAC	EMC Testing	VLAC-008-1	JAPAN
FILING			
VCCI	EMC Testing	A-0126	JAPAN
FCC	EMC Testing	JP0008	
IC	EMC Testing	IC-2042Q-12	CANADA
CB-Scheme	EMC Testing	TL222	IECEE

ABBREVIATIONS

EUT	Equipment Under Test	DoC	Declaration of Conformity
AMN	Artificial Mains Network	ISN	Impedance Stabilization Network
LISN	Line Impedance Stabilization Network	Q-P	Quasi-peak
AMP	Amplifier	AVG	Average
ATT	Attenuator	PK	Peak
ANT	Antenna	Cal	Calibration
BBA	Broadband Antenna	N/A	Not applicable or Not available
DIP	Dipole Antenna	LCD	Liquid-Crystal Display
AE	Associated Equipment	4LEVEL FSK	4LEVEL Frequency Shift Key
GMSK	Gaussian Maximum Shift Key	CW ID	Continuously Repeating bit stream
FM	Frequency Modulation	C4FM	Constant envelope 4 Level FM
PTT	Push to Talk	AFC	Automatic frequency control

Revision Summary

Revised Date	Section	Description of Changes

SECTION 2. SUMMARY OF TEST RESULT

FCC Part2	Part24D	Part90	IC RSS-119	RSS-134	TEST ITEM	RESULTS	Comments
2.1046 (a)	24.132	-	5.4	4.3	Carrier Output Power (Conducted)	PASS	
2.1051	24.133	90.210	5.8	4.4	Unwanted Emissions (Transmitter Conducted)	PASS	
2.1053 (a)	24.133	90.210	5.8	4.4	Field Strength of Spurious Radiation	PASS	
2.1049 (c) (1)	24.133	90.210	5.5	4.4	Emission Masks (Occupied Bandwidth)	PASS	
2.1047 (a)	-	-	-	-	Audio Low Pass Filter (Voice Input)	PASS	
2.1047 (a)	-	-	-	-	Audio Frequency Response	PASS	
2.1047 (b)	-	-	-	-	Modulation Limiting	PASS	
2.1055 (a) (1)	24.135(a)	90.213 (a)	5.3	4.5	Frequency Stability (Temperature Variation)	PASS	
2.1055 (d) (1)	24.135(a)	90.213 (a)	5.3	4.5	Frequency Stability (Voltage Variation)	PASS	
-	-	-	RSS-Gen 7.1	RSS-Gen 7.1	Receiver Spurious Emissions	PASS	
-	-	90.203 (e)	-	-	Certification required (FCC Part 90.203(e))	Complied	
-	-	-	5.5	4.1	99% Occupied Bandwidth	PASS	

Limitation on Results

The test result of this report is effective equipment under test itself and under the test configuration described on the report.
This test report does not assure that whether the test result taken in other testing laboratory is compatible or reproducible to the test result on this report or not.

Note:

As for the FCC Part 15 Subpart B-Unintentional Radiators, the EUT has been measured and declared as Verification by JVC Kenwood Corporation.

SECTION 3. TEST AND MEASUREMENT DATA

All test and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J and Industry Canada as the following individual parts:

FCC Rule	Test Item	Tested
Part 24	Personal Communications Services	YES
Part 80	Stations in the Maritime Services	N.A.
Part 90	Private Land Mobile radio Services	YES

IC Rule	Test Item	Tested
RSS-119	Radio Transmitters and Receivers Operating in the Land Mobile and Fixed Services in the Frequency Range 27.4-960 MHz	YES
RSS-134	900MHz Narrowband Personal Communication Service	YES
RSS-Gen	General Requirements for Compliance of Radio Apparatus	YES

SECTION 4. INFORMATION ABOUT EUT AND SUPPORT EQUIPMENT(S)**4.1 List of System Configuration**

Symbol	Item	Model No.	Serial No.	Manufacture	Remarks
A1	900MHz DIGITAL BASE-REPEATER	NXR-5901-K	B7390030	JVC KENWOOD Corporation	EUT
A2	OCXO Unit	KXK-3M3	B7390030	JVC KENWOOD Corporation	EUT
Power Ratings of EUT :		DC 13.8 V (10.8 to 15.9V)		5.0 A Maximum	
Power Supply :		DC 13.8 V			
Condition of Equipment		Proto type			
Type		Rack Mount type			
Suppression Devices		No Modifications by the laboratory were made to the device			

4.2 Port(s)/Connector(s)

Port Name	Connector Type	Connector Pin	Remarks
RX	BNC	2pin	
REF OUT	BNC	2pin	
REF IN	BNC	2pin	
TX	BNC	2pin	
TEST/SPKR MOLEX	1625-15p	15pin	
Control I/O	D-sub	25pin	
SYNC 1	RJ-11	4pin	
SYNC 2	RJ-11	4pin	
LAN	RJ-45	8pin	
MICROPHONE	RJ-45	8pin	
USB	Type B	4pin	For maintenance

4.3 Highest Frequency Oscillator(s)/Crystal(s)

Operating Frequency	Board Name	Remarks
941 MHz	TXRX UNIT	

SECTION 5. SUPPORT EQUIPMENT

The EUT was supported by the following equipment during the test.

Symbol	Item	Model No.	Serial No.	Manufacture	FCC ID
B	Microphone	KMC-35	none	Kenwood	N/A
C	Hub	SD205	PSJ13420D34	CISCO	DoC
D	Controller	none	none	none	N/A
E	External Speaker	KES-5	none	Kenwood	N/A
F	Terminator	CT-03NP	4B336	TME	N/A
G	Terminator	3204-BNCM	No2	api technoogies	N/A
H	Terminator	3204-BNCM	No3	api technoogies	N/A
I	Terminator	3204-BNCM	No4	api technoogies	N/A
J	Terminator	3204-BNCM	No5	api technoogies	N/A
K	Terminator	3204-BNCM	No6	api technoogies	N/A
L	Base-Repeater (1)	NXR-JIG1	none	Kenwood	N/A
M	Base-Repeater (2)	NXR-JIG2	none	Kenwood	N/A
N	DC Power Supply (1)	PMC35-3A	LE000716	Kikusui	N/A
O	DC Power Supply (2)	PS-3020	301027	Daiwa	N/A
P	AC Adapter	GPSESU-12P50F-AM7BE	R090815002786	Bestec	DoC
Supplied Power:					
N, O, P	AC	100V,60Hz			

SECTION 6. USED CABLE(S)


The following cable(s) was used for the test.

No.	Name	Length (m)	Shield	Metal Connector	Ferrite core
1	Mic. cable	0.60	No	No	
2	LAN cable	1.00	No	No	
3	D-Sub	1.40	Yes	Yes	
4	Speaker cable	2.80	No	No	
5	Modular cable	0.20	No	No	
6	Modular cable	0.20	No	No	
7	Coaxial cable	1.00	Yes	Yes	
8	Coaxial cable	1.00	Yes	Yes	
9	I/O cable	0.80	No	No	
10	DC cable for EUT	4.00	No	No	Removable x 1
11	DC cable for Base-Repeater (1)	4.00	No	No	Removable x 1
12	DC cable for Base-Repeater (2)	4.00	No	No	Removable x 1
13	DC cable for HUB	2.00	No	No	Removable x 2
14	Power cable for DC Power Supply (1)	1.50	No	No	
15	Power cable for DC Power Supply (2)	1.30	No	No	

SECTION 7. TEST CONFIGURATION

Details of Configuration and Connection

Example: Case of Section 10.9Test



SECTION 8. OPERATING CONDITION

The EUT was operated under the following condition during the test.

8.1 Operating Condition

The test was carried out under Transmit mode.

(FCC:935.05MHz, 939.95MHz, 940.55MHz)

(RSS:935.05MHz, 939.95MHz, 940.55MHz)

(High Power : 360mW, Low Power : 100mW)


The test was carried out under Receive mode.

(896.05MHz, 900.95MHz, 901.55MHz)

EUT was examined in the operating conditions that had maximum emissions.


8.2 Operating Flow [Transmit mode]

Following operations were performed continuously.



8.3 Operating Flow [Receive mode]

Following operations were performed continuously.



SECTION 9. MEASUREMENT UNCERTAINTY

Carrier Output Power (Conducted)	U_{lab}	$U_{tia-603-d}$
	+/- 0.29dB ($k = 2$)	+/- 0.59 dB
Unwanted Emissions (Transmitter Conducted)		
	+/- 2.19 dB ($k = 2$)	+/- 1.1 dB
Field Strength of Spurious Radiation		
	+/- 2.78dB ($k = 2$)	+/- 3.3 dB
Emission Masks (Occupied Bandwidth)		
	+/- 0.5dB ($k = 2$)	+/- 2.1 dB
Transient Frequency Behavior		
	+/- 1.10% ($k = 2$)	+/- 21.6 %
Audio Low Pass Filter (Voice Input)		
	+/- 0.1dB ($k = 2$)	+/- 1.2 dB
Audio Frequency Response		
	+/- 0.1dB ($k = 2$)	+/- 1.2 dB
Modulation Limiting		
	+/- 1% ($k = 2$)	+/- 1.0 %
Frequency Stability (Temperature Variation)		
	+/- 10.1Hz ($k=2$)	+/-34.2 Hz
Frequency Stability (Voltage Variation)		
	+/- 10.1Hz ($k=2$)	+/-34.2 Hz
Receiver Spurious Emissions	U_{lab}	U_{cispr}
30-1000MHz	+/- 4.83dB ($k = 2$)	+/- 6.3 dB
abobe 1GHz	+/- 4.33dB ($k = 2$)	+/- 5.2 dB
Bandwidth		
	+/- 1.02% ($k = 2$)	-

SECTION 10. TEST DATA**10.1 Carrier Output Power (Conducted)**

REGULATIONS	: FCC Part 2 Section 1046 (a) / RSS-119 Section 5.4 FCC Part24 Section 132 / RSS-134 Section 4.3
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.1.2 / RSS-119 Section 4.1 RSS-134 Section 3.1

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 The EUT was conducted to a resistive coaxial attenuator of normal load impedance.
 $\text{RF Power (dBm)} = \text{Power Meter reading (dBm)} + \text{Attenuator Loss (dB)} + \text{Cable Loss (dB)}$
 $\text{RF Power (W)} = 10^{(\text{RF Power (dBm)}/10)/1000}$
- 3 Modulate the transmitter with a 2.5 kHz sine wave at an input Level of 16 dB greater than that necessary to produce 50 % of rated system deviation.(Only as for the test of RSS)


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Power Meter	Hewlett Packard	E4418B	GB38410265	1Y	Aug. 31, 18
2	Power Sensor	Hewlett Packard	8482A	US37292237	1Y	Aug. 31, 18
3	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
4	Modulation	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
5	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
6	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
7	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18

Measuring Cables

No.	Cable	Manufacturer	Model No.	Serial No.	Cal. Interval	Effective period
W2	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
W3	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18

Measuring Equipment Configuration



Note: Configuration of other Modulation test is composed without the Audio Generator.

Test Results

Test date	Aug. 24, 2017		
Location	Kashima No.12 Test Site		
temperature	26.1	[degree C]	
Humidity Variation	50.0	[%]	
Atmospheric Pressure	100.3	[kPa]	
Test Engineer	Koichi Wagatsuma		

Test was carried out for all the Authorized Bandwidth.
State the worst case (below).

No.	Frequency (MHz)	Band		Setting	RF Power (W)
1	935.05	Band 1	Low	11K0F3E	High Power 0.360
2	935.05	Band 1	Low	8K30F1E/F1D/F7W	High Power 0.360
3	935.05	Band 1	Low	4K00F1E/F1D/F7W	High Power 0.360
4	935.05	Band 1	Low	4K00F2D	High Power 0.360
5	939.95	Band 1	High	11K0F3E	High Power 0.360
6	939.95	Band 1	High	8K30F1E/F1D/F7W	High Power 0.360
7	939.95	Band 1	High	4K00F1E/F1D/F7W	High Power 0.360
8	939.95	Band 1	High	4K00F2D	High Power 0.360
9	940.55	Band 2	Middle	11K0F3E	High Power 0.360
10	940.55	Band 2	Middle	8K30F1E/F1D/F7W	High Power 0.360
11	940.55	Band 2	Middle	4K00F1E/F1D/F7W	High Power 0.360
12	940.55	Band 2	Middle	4K00F2D	High Power 0.360
1	935.05	Band 1	Low	11K0F3E	Low Power 0.100
2	935.05	Band 1	Low	8K30F1E/F1D/F7W	Low Power 0.100
3	935.05	Band 1	Low	4K00F1E/F1D/F7W	Low Power 0.100
4	935.05	Band 1	Low	4K00F2D	Low Power 0.100
5	939.95	Band 1	High	11K0F3E	Low Power 0.100
6	939.95	Band 1	High	8K30F1E/F1D/F7W	Low Power 0.100
7	939.95	Band 1	High	4K00F1E/F1D/F7W	Low Power 0.100
8	939.95	Band 1	High	4K00F2D	Low Power 0.100
9	940.55	Band 2	Middle	11K0F3E	Low Power 0.100
10	940.55	Band 2	Middle	8K30F1E/F1D/F7W	Low Power 0.100
11	940.55	Band 2	Middle	4K00F1E/F1D/F7W	Low Power 0.100
12	940.55	Band 2	Middle	4K00F2D	Low Power 0.100

RF Power: Peak reading

10.2 Unwanted Emissions (Transmitter Conducted)

REGULATIONS	: FCC Part 2 Section 1051, Part 90 Section 210 / RSS-119 Section 5.8 FCC Part24 Section133, RSS-134 Section 4.4
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.13.2 / RSS-119 Section 4.2 RSS-134 Section 3.2

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Modulate the transmitter with a 2.5 kHz sine wave at an input Level of 16 dB greater than that necessary to produce 50 % of rated system deviation.
- 3 Adjust the spectrum analyzer for the following setting:
 - a) RBW : 100 kHz (< 1 GHz), 1 MHz (> 1 GHz).
 - b) VBW : 300 kHz (< 1 GHz), 3 MHz (> 1 GHz).
 - c) Detector mode : Average power (FM Modulation) , Positive peak with peak hold (Digital Modulation)
- 4 The emissions were measured for the worst case as follows:
 - a) : within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - b) : from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Highpass Filter	TME	UHP-127	1511798E	1Y	Aug. 31, 18
3	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
4	Signal Generator	Rohde&Schwarz	SMP02	845275/007	1Y	Jul. 31, 18
5	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
6	Spectrum Analyzer	Agilent	N9030A	US51350220	1Y	Feb. 28, 18
7	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
8	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18

Measuring Cables

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W3	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
W4	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18
W2	Coaxial Cable	Suhner	SUCOFLEX104	F0000018	1Y	Jan. 31, 18

Measuring Equipment Configuration



Note: Configuration of other Modulation test is composed without the Audio Generator.

Test Results

Test date	Aug. 28, 2017
Location	Kashima No.12 Test Site
temperature	24 [degree C]
Humidity Variation	58 [%]
Atmospheric Pressure	100.1 [kPa]
Test Engineer	Koichi Wagatsuma

Test was carried out for all the frequency band of section 10.1

State the worst case (below).

State : High Power / Authorized Bandwidth 13.6 kHz (8K30F1E/F1D/F7W)

(Band 1)

No.	Tuned Frequency (MHz)	Band	Spurious Frequency (MHz)	Correct Level (dBm)	Emission Level (dBc)	Mask G Limit (dBc)	Mask J Limit (dBc)	Margin (Worst) (dB)
1	935.05	Low	1870.10	-51.02	-76.59	-38.6	-45.6	31.0
2	939.95	High	1879.90	-51.64	-77.20	-38.6	-45.6	31.6

There is the margin of 20dB over except for the above points.

Mask G Limit(dBc)=- (43+10Log(P))

Mask J Limit (dBc) = -(50+10Log(P))

Correct Level (dBm) = Substitute SG Level (dBm)

Emission Level (dBc) = Correct Level (dBm) - 10Log(P*1000)

P = Carrier Level (W)

" - " = Measurement Limit

State : Low Power / Authorized Bandwidth 13.6 kHz (8K30F1E/F1D/F7W)

(Band 1)

No.	Tuned Frequency (MHz)	Band	Spurious Frequency (MHz)	Correct Level (dBm)	Emission Level (dBc)	Mask G Limit (dBc)	Mask J Limit (dBc)	Margin (Worst) (dB)
1	935.05	Low	No Point detected	-	-	-33.0	-40.0	-
2	939.95	High	No Point detected	-	-	-33.0	-40.0	-

There is the margin of 20dB over except for the above points.

Mask G Limit(dBc)=- (43+10Log(P))

Mask J Limit (dBc) = -(50+10Log(P))

Correct Level (dBm) = Substitute SG Level (dBm)

Emission Level (dBc) = Correct Level (dBm) - 10Log(P*1000)

P = Carrier Level (W)

" - " = Measurement Limit

State : High Power / Authorized Bandwidth 45 kHz (8K30F1E/F1D/F7W)

(Band 2)

No.	Tuned Frequency (MHz)	Band	Spurious Frequency (MHz)	Correct Level (dBm)	Emission Level (dBc)	Mask133.(a)(1) Limit (dBc)	Margin (dB)
1	940.55	Middle	1881.10	-51.74	-77.30	-38.6	38.7

There is the margin of 20dB over except for the above points.

Mask133.(a)(1) Limit (dBc) = $-(43+10\log(P))$

Correct Level (dBm) = Substitute SG Level (dBm)

Emission Level (dBc) = Correct Level (dBm) - $10\log(P*1000)$

P = Carrier Level (W)

" - " = Measurement Limit

State : Low Power / Authorized Bandwidth 45 kHz (8K30F1E/F1D/F7W)

(Band 2)

No.	Tuned Frequency (MHz)	Band	Spurious Frequency (MHz)	Correct Level (dBm)	Emission Level (dBc)	Mask133.(a)(1) Limit (dBc)	Margin (dB)
1	940.55	Middle	No Point detected	-	-	-33.0	-

There is the margin of 20dB over except for the above points.

Mask133.(a)(1) Limit (dBc) = $-(43+10\log(P))$

Correct Level (dBm) = Substitute SG Level (dBm)

Emission Level (dBc) = Correct Level (dBm) - $10\log(P*1000)$

P = Carrier Level (W)

" - " = Measurement Limit

10.3 Field Strength of Spurious Radiation

REGULATIONS	:	FCC Part 2 Section 1053 (a), Part 90 Section 210 / RSS-119 Section 5.8 FCC Part 24 Section 133, RSS-134 Section 4.4
TEST METHOD/GUIDE	:	ANSI/TIA-603-E Section 2.2.12.2 / RSS-119 Section 4.2 RSS-134 Section 3.2

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Adjust the spectrum analyzer for the following setting:
 - a) RBW : 100 kHz (< 1 GHz), 1 MHz (> 1 GHz).
 - b) VBW : 300 kHz (< 1 GHz), 3 MHz (> 1 GHz).
 - c) Detector mode : Positive Peak
- 3 The transmitter was placed on a wooden turntable, and it was transmitting into non-radiating load which was also placed on the turntable.
- 4 The measurement antenna was placed at a distance of 3 meters from the EUT.
During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT.
The test was performed by placing the EUT on 3-orthogonal axis.
- 5 The frequency range up to tenth harmonic of the fundamental frequency was investigated.
- 6 Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable.
The absolute levels of the spurious emissions were measured by the substitution.
- 7 Spurious emissions in dB = 10 Log (TX power in Watts/0.001) – the absolute level


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator(10dB)	HUBER+SUHNER	6810.17B	5061	1Y	Feb. 28, 18
2	Dummy Load	TME	CT-03BP	4B336	1Y	Sep. 30, 18
3	Signal Generator	Rohde&Schwarz	SMP02	845275/007	1Y	Jul. 31, 18
4	Spectrum Analyzer	Agilent	N9030A	US51350220	1Y	Feb. 28, 18
5	D.R.G Antenna(RX)	Schwarzbeck	3115	5044	1Y	May. 31, 18
6	D.R.G Antenna(RX)	Schwarzbeck	3115	5045	1Y	Mar. 31, 18
7	Dipole Antenna(TX)	Schwarzbeck	UHA9105	AM0082002	1Y	Aug. 31, 18
8	Dipole Antenna(TX)	Schwarzbeck	VHA9103	C01082007	1Y	Aug. 31, 18
9	Tri-log Antenna(RX)	Schwarzbeck	VULB9168WP	126	1Y	Dec. 31, 17
10	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
11	DC Power Supply	Daiwa	PS-3020	301027	None	None
12	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18
13	Amplifier	TOYO	TPA0118-30	0402	1Y	Apr. 30, 18
14	Attenuator	HUBER + SUHNER	6803.17.B	5111	1Y	Apr. 30, 18
15	Amplifier	Intertek Japan	ZX60-3018G	005	1Y	Feb. 28, 18
16	Attenuator	TAMAGAWA	CFA-01	A00040805	1Y	Feb. 28, 18
17	RF Switch	Intertek Japan	ACX-150-1	A12301501	1Y	Feb. 28, 18

Measuring Cables

No.	Cable	Manufacturer	Model No.	Serial No.	Cal. Interval	Effective period
R11	Coaxial Cable	FUJIKURA	5D-2W	R11	1Y	Feb. 28, 18
R1	Coaxial Cable	FUJIKURA	5D-2W	R1	1Y	Feb. 28, 18
R3	Coaxial Cable	FUJIKURA	10D-2W	R3	1Y	Feb. 28, 18
R5	Coaxial Cable	FUJIKURA	RG-5A/U	R5	1Y	Feb. 28, 18
R7	Coaxial Cable	MIYAZAKI	5D-2W	R7	1Y	Feb. 28, 18
R10	Coaxial Cable	FUJIKURA	5D-2W	R10	1Y	Feb. 28, 18
R13	Coaxial Cable	SUHNER	SUCOFLEX 104	229603	1Y	Apr. 30, 18
R12	Coaxial Cable	Candox	5B-048-98-98-5000	111130	1Y	Apr. 30, 18
W13	Coaxial Cable	Suhner	SUCOFLEX106	KSR00207	1Y	Feb. 28, 18

Measuring Equipment Configuration



Test Results

Test date	Sep 20, 2017 to Sep 21, 2017
Location	Kashima No.12 Test Site
temperature	20.3 to 22.4 [degree C]
Humidity Variation	42 to 59 [%]
Atmospheric Pressure	99.9 to 100.9 [kPa]
Test Engineer	Koichi Wagatsuma

Test was carried out for all the frequency band of section 10.1
State the worst case (below).

State : High Power / Authorized Bandwidth 13.6 kHz / 939.95MHz(FCC /RSS) (Band 1)

No	Frequency (MHz)	Pol	Reading Level (dBm)	SG Out Level (dBm)	Antenna Gain (dBd)	Loss (dB)	Correct Level (dBm)	Emission Level (dBc)	Mask I / G Limit Level (dBc)	MASK J Limit Level (dBc)	Margin (Worst) (dB)
1	1879.90	Hor.	-58.45	-43.02	6.13	13.57	-50.5	-76.0	-38.6	-45.6	30.4
		Ver.	-56.68	-42.14	6.13	13.57	-49.6	-75.1	-38.6	-45.6	29.5
2	2819.85	Hor.	-58.13	-42.35	7.42	14.43	-49.4	-74.9	-38.6	-45.6	29.3
		Ver.	-51.61	-35.54	7.42	14.43	-42.6	-68.1	-38.6	-45.6	22.5
3	3759.80	Hor.	-49.57	-29.95	7.86	15.15	-37.2	-62.8	-38.6	-45.6	17.2
		Ver.	-41.40	-22.04	7.86	15.15	-29.3	-54.9	-38.6	-45.6	9.3
4	4699.75	Hor.	-54.90	-34.94	9.02	15.71	-41.6	-67.2	-38.6	-45.6	21.6
		Ver.	-50.93	-31.21	9.02	15.71	-37.9	-63.5	-38.6	-45.6	17.9
5	5639.70	Hor.	-60.78	-37.30	9.09	16.26	-44.5	-70.0	-38.6	-45.6	24.4
		Ver.	-57.93	-34.76	9.09	16.26	-41.9	-67.5	-38.6	-45.6	21.9
6	6579.65	Hor.	-	-	9.90	16.75	-	-	-38.6	-45.6	-
		Ver.	-	-	9.90	16.75	-	-	-38.6	-45.6	-
7	7519.60	Hor.	-	-	9.12	17.31	-	-	-38.6	-45.6	-
		Ver.	-	-	9.12	17.31	-	-	-38.6	-45.6	-
8	8459.55	Hor.	-	-	9.01	17.88	-	-	-38.6	-45.6	-
		Ver.	-	-	9.01	17.88	-	-	-38.6	-45.6	-
9	9399.50	Hor.	-	-	9.64	18.34	-	-	-38.6	-45.6	-
		Ver.	-	-	9.64	18.34	-	-	-38.6	-45.6	-

There is the margin of 20dB over except for the above points.

Mask I / G Limit (dBc) = $-(43+10\log(P))$

Mask J Limit (dBc) = $-(50+10\log(P))$

Correct Level (dBm) = Substitute SG Level (dBm) + ANT Gain (dBd) - Loss (Cable, Attenuator) (dB)

Emission Level (dBc) = Correct Level (dBm) - $10\log(P*1000)$

P = Carrier Level (W)

" - " = Measurement Limit

State : Low Power / Authorized Bandwidth 13.6 kHz / 935.05MHz(FCC /RSS) (Band 1)

Mask I / G											
No	Frequency (MHz)	Pol	Reading Level (dBm)	SG Out Level (dBm)	Antenna Gain (dBd)	Loss (dB)	Correct Level (dBm)	Emission Level (dBc)	Limit Level (dBc)	MASK J Limit Level (dBc)	Margin (Worst) (dB)
1	1870.10	Hor.	-61.98	-48.75	6.13	13.56	-56.2	-76.2	-33.0	-40.0	36.2
		Ver.	-58.48	-44.03	6.13	13.56	-51.5	-71.5	-33.0	-40.0	31.5
2	2805.15	Hor.	-62.60	-46.94	7.43	14.41	-53.9	-73.9	-33.0	-40.0	33.9
		Ver.	-57.57	-41.60	7.43	14.41	-48.6	-68.6	-33.0	-40.0	28.6
3	3740.20	Hor.	-	-	7.85	15.13	-	-	-33.0	-40.0	-
		Ver.	-	-	7.85	15.13	-	-	-33.0	-40.0	-
4	4675.25	Hor.	-	-	9.01	15.70	-	-	-33.0	-40.0	-
		Ver.	-	-	9.01	15.70	-	-	-33.0	-40.0	-
5	5610.30	Hor.	-	-	9.05	16.24	-	-	-33.0	-40.0	-
		Ver.	-	-	9.05	16.24	-	-	-33.0	-40.0	-
6	6545.35	Hor.	-	-	10.00	16.74	-	-	-33.0	-40.0	-
		Ver.	-	-	10.00	16.74	-	-	-33.0	-40.0	-
7	7480.40	Hor.	-	-	9.04	17.28	-	-	-33.0	-40.0	-
		Ver.	-	-	9.04	17.28	-	-	-33.0	-40.0	-
8	8415.45	Hor.	-	-	9.09	17.86	-	-	-33.0	-40.0	-
		Ver.	-	-	9.09	17.86	-	-	-33.0	-40.0	-
9	9350.50	Hor.	-	-	9.66	18.32	-	-	-33.0	-40.0	-
		Ver.	-	-	9.66	18.32	-	-	-33.0	-40.0	-
There is the margin of 20dB over except for the above points.											

Mask I / G Limit (dBc) = $-(43+10\log(P))$

Mask J Limit (dBc) = $-(50+10\log(P))$

Correct Level (dBm) = Substitute SG Level (dBm) + ANT Gain (dBd) - Loss (Cable, Attenuator) (dB)

Emission Level (dBc) = Correct Level (dBm) - $10\log(P*1000)$

P = Carrier Level (W)

" - " = Measurement Limit

State : High Power / Authorized Bandwidth 45kHz / 940.55MHz(FCC /RSS)

(Band 2)

No	Frequency (MHz)	Pol	Reading Level (dBm)	SG Out Level (dBm)	Antenna Gain (dBd)	Loss (dB)	Correct Level (dBm)	Emission Level (dBc)	Mask133.(a)(1) Limit Level (dBc)	Margin (dB)
1	1881.10	Hor.	-57.79	-44.28	6.13	13.57	-51.7	-77.3	-38.6	38.7
		Ver.	-55.90	-41.56	6.13	13.57	-49.0	-74.6	-38.6	36.0
2	2821.65	Hor.	-57.60	-41.85	7.42	14.43	-48.9	-74.4	-38.6	35.8
		Ver.	-50.67	-34.78	7.42	14.43	-41.8	-67.4	-38.6	28.8
3	3762.20	Hor.	-48.36	-28.83	7.86	15.15	-36.1	-61.7	-38.6	23.1
		Ver.	-40.52	-21.28	7.86	15.15	-28.6	-54.1	-38.6	15.5
4	4702.75	Hor.	-54.61	-34.65	9.02	15.71	-41.3	-66.9	-38.6	28.3
		Ver.	-49.55	-30.02	9.02	15.71	-36.7	-62.3	-38.6	23.7
5	5643.30	Hor.	-59.16	-35.70	9.10	16.26	-42.9	-68.4	-38.6	29.8
		Ver.	-55.46	-32.27	9.10	16.26	-39.4	-65.0	-38.6	26.4
6	6583.85	Hor.	-	-	9.88	16.75	-	-	-38.6	-
		Ver.	-	-	9.88	16.75	-	-	-38.6	-
7	7524.40	Hor.	-	-	9.13	17.31	-	-	-38.6	-
		Ver.	-	-	9.13	17.31	-	-	-38.6	-
8	8464.95	Hor.	-	-	9.00	17.89	-	-	-38.6	-
		Ver.	-	-	9.00	17.89	-	-	-38.6	-
9	9405.50	Hor.	-	-	9.65	18.35	-	-	-38.6	-
		Ver.	-	-	9.65	18.35	-	-	-38.6	-

There is the margin of 20dB over except for the above points.

Mask133.(a)(1) Limit (dBc) = -(43+10Log(P))

Correct Level (dBm) = Substitute SG Level (dBm) + ANT Gain (dB) - Loss (Cable, Attenuator) (dB)

Emission Level (dBc) = Correct Level (dBm) - 10Log(P*1000)

P = Carrier Level (W)

" - " = Measurement Limit

State : Low Power / Authorized Bandwidth 45kHz / 940.55MHz(FCC /RSS)

(Band 2)

No	Frequency (MHz)	Pol	Reading Level (dBm)	SG Out Level (dBm)	Antenna Gain (dBd)	Loss (dB)	Correct Level (dBm)	Emission Level (dBc)	Mask133.(a)(1) Limit Level (dBc)	Margin (dB)
1	1881.10	Hor.	-60.50	-46.99	6.13	13.57	-54.4	-74.4	-33.0	41.4
		Ver.	-57.45	-43.11	6.13	13.57	-50.5	-70.5	-33.0	37.5
2	2821.65	Hor.	-60.92	-45.18	7.42	14.43	-52.2	-72.2	-33.0	39.2
		Ver.	-57.29	-41.39	7.42	14.43	-48.4	-68.4	-33.0	35.4
3	3762.20	Hor.	-	-	7.86	15.15	-	-	-33.0	-
		Ver.	-	-	7.86	15.15	-	-	-33.0	-
4	4702.75	Hor.	-	-	9.02	15.71	-	-	-33.0	-
		Ver.	-	-	9.02	15.71	-	-	-33.0	-
5	5643.30	Hor.	-	-	9.10	16.26	-	-	-33.0	-
		Ver.	-	-	9.10	16.26	-	-	-33.0	-
6	6583.85	Hor.	-	-	9.88	16.75	-	-	-33.0	-
		Ver.	-	-	9.88	16.75	-	-	-33.0	-
7	7524.40	Hor.	-	-	9.13	17.31	-	-	-33.0	-
		Ver.	-	-	9.13	17.31	-	-	-33.0	-
8	8464.95	Hor.	-	-	9.00	17.89	-	-	-33.0	-
		Ver.	-	-	9.00	17.89	-	-	-33.0	-
9	9405.50	Hor.	-	-	9.65	18.35	-	-	-33.0	-
		Ver.	-	-	9.65	18.35	-	-	-33.0	-

There is the margin of 20dB over except for the above points.

Mask133.(a)(1) Limit (dBc) = -(43+10Log(P))

Correct Level (dBm) = Substitute SG Level (dBm) + ANT Gain (dB) - Loss (Cable, Attenuator) (dB)

Emission Level (dBc) = Correct Level (dBm) - 10Log(P*1000)

P = Carrier Level (W)

" - " = Measurement Limit

10.4 Emission Masks (Occupied Bandwidth)

REGULATIONS	: FCC Part 2 Section 1049 (c) (1), Part 90 Section 210 RSS-119 Section 5.5
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.11.2 / RSS-119 Section 5.8

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 For EUT supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for +/- 2.5 kHz deviation (or 50 % modulation). (FM modulation).
- 3 With level constant, the signal level was increased 16 dB.
- 4 For EUT supporting digital modulation, the digital modulation mode was operated to its maximum extent.
- 5 Adjust the spectrum analyzer for the following setting:
 - a) RBW : 300Hz (Non modulation , Modulation).
 - b) VBW : 10times the RBW (Non modulation , Modulation).
 - c) RBW and VBW : 30 kHz (Non modulation(Digital Modulation)).
- 6 The occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

The selection of Emission Mask

No.	Frequency		Authorized Bandwidth (kHz)		Selection of Emission Mask	
	(MHz)	Audio Filter	FCC	IC	FCC	IC
Emission Designation : 11K0F3E						
1	935.05	With	13.6	13.6	I	I
2	939.95	With	13.6	13.6	I	I
3	940.55	With	45	45	24.133(a)(1)	134 4.4.1
Emission Designation : 8K30F1E/F1D/F7W						
1	935.05	Without	13.6	13.6	J	J / G
2	939.95	Without	13.6	13.6	J	J / G
3	940.55	Without	45	45	24.133(a)(1)	134 4.4.1
Emission Designation : 4K00F1E / F1D / F7W						
1	935.05	Without	13.6	13.6	J	J / G
2	939.95	Without	13.6	13.6	J	J / G
3	940.55	Without	10	10	24.133(a)(2)	134 4.4.2
Emission Designation : 4K00F2D						
1	935.05	Without	13.6	13.6	J	J / G
2	939.95	Without	13.6	13.6	J	J / G
3	940.55	Without	10	10	24.133(a)(2)	134 4.4.2


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
4	Spectrum Analyzer	Agilent	N9030A	US51350220	1Y	Feb. 28, 18
5	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
6	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18
7	JIG	HP	EliteBook 2561p	CNU2262D0Q	None	None

Measuring Cables


No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W3	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
W4	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18
W2	Coaxial Cable	Suhner	SUCOFLEX104	F0000018	1Y	Jan. 31, 18

Measuring Equipment Configuration



FM Modulation test is with the the Audio Generator. : RF Output
Configuration of other Modulation test is composed without the Audio Generator.

<CWID Modulation Case>




Test Results


Test date	Aug. 28, 2017	
Location	Kashima No.12 Test Site	
temperature	23.2	[degree C]
Humidity Variation	61	[%]
Atmospheric Pressure	100.9	[kPa]
Test Engineer	Koichi Wagatsuma	

Test was carried out for all the frequency band of section 10.1
State the worst case (below).


State : High Power / Authorized Bandwidth 13.6 kHz/ 11K0F3E / 935.05 MHz(FCC/RSS)
Limit : Mask I




State : Low Power / Authorized Bandwidth 13.6 kHz/ 11K0F3E / 935.05 MHz(FCC/RSS)
Limit : Mask I




State : High Power / Authorized Bandwidth 45 kHz/ 11K0F3E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : Low Power / Authorized Bandwidth 45 kHz/ 11K0F3E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : High Power / Authorized Bandwidth 13.6 kHz/ 8K30F1E / 939.95 MHz(FCC/RSS)
Limit : Mask J / G




State : Low Power / Authorized Bandwidth 13.6 kHz/ 8K30F1E / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 13.6 kHz/ 8K30F1D / 939.95 MHz(FCC/RSS)
Limit : Mask J / G




State : Low Power / Authorized Bandwidth 13.6 kHz/ 8K30F1D / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 13.6 kHz/ 8K30F7W / 939.95 MHz(FCC/RSS)
Limit : Mask J / G




State : Low Power / Authorized Bandwidth 13.6 kHz/ 8K30F7W / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 45 kHz/ 8K30F1E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : Low Power / Authorized Bandwidth 45 kHz/ 8K30F1E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : High Power / Authorized Bandwidth 45 kHz/ 8K30F1D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : Low Power / Authorized Bandwidth 45 kHz/ 8K30F1D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : High Power / Authorized Bandwidth 45 kHz/ 8K30F7W / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : Low Power / Authorized Bandwidth 45 kHz/ 8K30F7W / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(1) /RSS-134 4.4.1




State : High Power / Authorized Bandwidth 13.6 kHz/ 4K00F1E / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : Low Power / Authorized Bandwidth 13.6 kHz/ 4K00F1E / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 13.6 kHz/ 4K00F1D / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : Low Power / Authorized Bandwidth 13.6 kHz/ 4K00F1D / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 13.6 kHz/ 4K00F7W / 935.05 MHz(FCC/RSS)
Limit : Mask J / G



State : Low Power / Authorized Bandwidth 13.6 kHz/ 4K00F7W / 935.05 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 10 kHz/ 4K00F1E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : Low Power / Authorized Bandwidth 10 kHz/ 4K00F1E / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : High Power / Authorized Bandwidth 10 kHz/ 4K00F1D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : Low Power / Authorized Bandwidth 10 kHz/ 4K00F1D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : High Power / Authorized Bandwidth 10 kHz/ 4K00F7W / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : Low Power / Authorized Bandwidth 10 kHz/ 4K00F7W / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2




Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$


State : High Power / Authorized Bandwidth 13.6 kHz/ 4K00F2D / 935.05 MHz(FCC/RSS)
Limit : Mask J / G



State : Low Power / Authorized Bandwidth 13.6 kHz/ 4K00F2D / 939.95 MHz(FCC/RSS)
Limit : Mask J / G




State : High Power / Authorized Bandwidth 10 kHz/ 4K00F2D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2



Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

State : Low Power / Authorized Bandwidth 10 kHz/ 4K00F2D / 940.55 MHz(FCC/RSS)
Limit : Mask FCC24.133(a)(2) /RSS-134 4.4.2



Regarding the frequency range of the 20kHz or more outside of the edge of authorized bandwidth,
the trace is adjusted according to the following formula. $10 \cdot \log(30\text{kHz}/300\text{Hz}) : 20 \text{ dB}$

10.5 Audio Frequency Response / Audio Low Pass Filter (Voice Input)

REGULATIONS : FCC Part 2 Section 1047 (a)

TEST METHOD/GUIDE : ANSI/TIA-603-E Section 2.2.6.2.2, 3.2.6.2

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Adjust the Modulation Analyzer for the following setting:
 - a) High-pass filter : 50 Hz
 - b) Low-pass filter : 15 kHz
 - c) Detector : positive peak
 - d) Function : FM
- 3 The audio signal input was adjusted to obtain 20 % modulation at 1 kHz, and this point was taken as the 0 dB reference level.
- 4 With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 5 kHz.
- 5 The response in dB relative to 1 kHz was then measured, using the Modulation Analyzer.


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
4	Audio Analyzer	Hewlett Packard	8903B	2948A07326	1Y	Sep. 30, 17
5	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
6	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18

Measuring Cables

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W2	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
W4	Coaxial Cable	Daiyu Densen	3D-2V	KSR00101	1Y	Feb. 28, 18
W3	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18

Measuring Equipment Configuration




Test Results

Test date	Aug 24, 2017	
Location	Kashima No.12 Test Site	
temperature	25	[degree C]
Humidity Variation	50	[%]
Atmospheric Pressure	100.1	[kPa]
Test Engineer	Koichi Wagatsuma	

Test was carried out for all the frequency band of section 10.1

State the worst case (below).

State : High Power / Authorized Bandwidth 13.6 kHz / 11K0F3E / 935.05 MHz(Band 1)(FCC / RSS)



Note:


Audio Filter of the above result is substituted with the same structure as Audio Frequency Response.

On the transmission condition below 3kHz,

Transceiver shows pre-emphasis condition of transmission function.

On the transmission condition above 3kHz, Transceiver shows Audio Low Pass Filter.

State : High Power / Authorized Bandwidth 45 kHz / 11K0F3E / 940.55 MHz(Band 2)(FCC / RSS)



Note:

Audio Filter of the above result is substituted with the same structure as Audio Frequency Response.

On the transmission condition below 3kHz,

Transceiver shows pre-emphasis condition of transmission function.

On the transmission condition above 3kHz, Transceiver shows Audio Low Pass Filter.

10.6 Modulation Limiting

REGULATIONS	: FCC Part 2 Section 1047 (b)
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.3.2, 1.3.4.4

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Adjust the Modulation Analyzer for the following setting:
 - a) High-pass filter : off
 - b) Low-pass filter : 15 kHz
 - c) Detector : positive peak
 - d) Function : FM
- 3 Apply a 1kHz modulation signal to the transmitter from the audio generator, and adjust the level to obtain 60% of full rated system deviation.
- 4 Measure the modulation frequency that was showed on the Modulation Analyzer when the output levels of the Audio Generator were changed from -20 dB to +50 dB by 10 dB.
- 5 Set the output frequencies of the Audio Generator 300 Hz and 3 kHz, and repeat test procedure 4.
- 6 Set the Detector of the Modulation Analyzer Negative Peak.
- 7 Repeat test procedure 4 and 5.


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
4	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
5	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18

Measuring Cables

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W2	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
W3	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18

Measuring Equipment Configuration




Test Results


Test date	Aug. 24, 2017	to	Aug. 25, 2017
Location	Kashima No.12 Test Site		
temperature	20.0 to 22.5	[degree C]	
Humidity Variation	50.0 to 55.0	[%]	
Atmospheric Pressure	99.9 to 100.1	[kPa]	
Test Engineer	Koichi Wagatsuma		

Test was carried out for all the frequency band of section 10.1
State the worst case (below).


State : High Power / Authorized Bandwidth 13.6 kHz / 11K0F3E / 935.05 MHz(Band 1)




State : High Power / Authorized Bandwidth 13.6 kHz / 11K0F3E / 935.05 MHz(Band 1)



State : High Power / Authorized Bandwidth 45 kHz / 11K0F3E / 940.55 MHz(Band 2)



State : High Power / Authorized Bandwidth 45 kHz / 11K0F3E / 940.55 MHz(Band 2)



10.7 Frequency Stability (Temperature Variation)

REGULATIONS	: FCC Part 2 Section 1055 (a) (1), Part 90 Section 213(a) RSS-119 Section 5.3 FCC Part24 Section 135(a) / RSS-134 Section 4.5
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.2.2 RSS-Gen Section 4.7(a)

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Set the temperature -30 degrees C.
- 3 Leave the EUT for 1 hour after it became the temperature that was set up.
- 4 Make the EUT the transmitting state.
measure the output frequency.
- 5 Make the EUT the receiving state.
- 6 Set the temperature 50 degrees C by 10 degrees C.
And repeat test procedure 4 to 6.


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	DC Power Supply	Takasago	GP035-20R	1014199060	None	None
4	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18
5	Temperature Chamber	Tabai	PL-3F	5103661	None	None
6	Temperature Meter	Sato	PC-5000TRH-II	A11999972	1Y	Feb. 28, 18
7	GPS Receiver	Hewlett Packard	HP Z3801A	3542A02414	None	None

Measuring Cables

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W2	Coaxial Cable	Pacific custom	RG-58 C/U	KSR00041	1Y	Feb. 28, 18
W1	Coaxial Cable	Suhner	SUCOFLEX104	KSR00042	1Y	Aug. 31, 18

Measuring Equipment Configuration



Test Results

Test date	Aug. 31, 2017
Location	Kashima No.1 Test Site
Test Engineer	Koichi Wagatsuma


Test was carried out for all the frequency band of section 10.1
State the worst case (below).

State : High Power / Authorized Bandwidth 13.6 kHz / 935.05 MHz (FCC / RSS)

Reference Frequency: 935.050000 MHz(FCC Stability)

935.050020 MHz(RSS Stability)

No.	Temperature (Degree C)	Frequency (MHz)	FCC Stability (ppm)	RSS Stability (ppm)	Limit (+/- ppm)	Min. Margin (ppm)
1	-30	935.050010	0.01	-0.01	0.1	0.09
2	-20	935.050010	0.01	-0.01	0.1	0.09
3	-10	935.050010	0.01	-0.01	0.1	0.09
4	0	935.050010	0.01	-0.01	0.1	0.09
5	10	935.050020	0.02	0.00	0.1	0.08
6	20	935.050020	0.02	0.00	0.1	0.08
7	30	935.050000	0.00	-0.02	0.1	0.08
8	40	935.050020	0.02	0.00	0.1	0.08
9	50	935.050010	0.01	-0.01	0.1	0.09




State : High Power / Authorized Bandwidth 45 kHz / 940.55 MHz (FCC / RSS)

Reference Frequency: 940.550000 MHz(FCC Stability)

Reference Frequency: 940.550020 MHz(RSS Stability)

No.	Temperature (Degree C)	Frequency (MHz)	FCC Stability (ppm)	RSS Stability (ppm)	Limit (+/- ppm)	Min. Margin (ppm)
1	-30	940.550030	0.03	0.01	0.5	0.47
2	-20	940.550020	0.02	0.00	0.5	0.48
3	-10	940.550020	0.02	0.00	0.5	0.48
4	0	940.550010	0.01	-0.01	0.5	0.49
5	10	940.550030	0.03	0.01	0.5	0.47
6	20	940.550020	0.02	0.00	0.5	0.48
7	30	940.550030	0.03	0.01	0.5	0.47
8	40	940.550040	0.04	0.02	0.5	0.46
9	50	940.550020	0.02	0.00	0.5	0.48



10.8 Frequency Stability (Voltage Variation)

REGULATIONS	: FCC Part 2 Section 1055 (a) (1), Part 90 Section 213(a) RSS-119 Section 5.3 FCC Part24 Section 135(a) / RSS-134 Section 4.5
TEST METHOD/GUIDE	: ANSI/TIA-603-E Section 2.2.2.2 RSS-Gen Section 4.7(a)

Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 The power supply voltage to the EUT was varied from 85 % to 115 % of the nominal value measured at the input to the EUT.


Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	DC Power Supply	Takasago	GP035-20R	1014199060	None	None
4	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18
5	Temperature Chamber	Tabai	PL-3F	5103661	None	None
6	Temperature Meter	Sato	PC-5000TRH-II	A11999972	1Y	Feb. 28, 18
7	GPS Receiver	Hewlett Packard	HP Z3801A	3542A02414	None	None

Measuring Cables

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
W2	Coaxial Cable	Pacific custom	RG-58 C/U	KSR00041	1Y	Feb. 28, 18
W1	Coaxial Cable	Suhner	SUCOFLEX104	KSR00042	1Y	Aug. 31, 18

Measuring Equipment Configuration



Test Results

Test date	Aug 31, 2017
Location	Kashima No.1 Test Site
Test Engineer	Koichi Wagatsuma

Test was carried out for all the frequency band of section 10.1

State the worst case (below).

State : High Power / Authorized Bandwidth 13.6 kHz / 939.95 MHz (FCC / RSS)

Reference Frequency: 939.950020 MHz

No.	Temperature (Degree C)	Diviation (%)	Voltage (V)	Frequency (MHz)	Stability (ppm)	Limit +/- (ppm)	Margin (ppm)
1	20+/-5	85	11.73	939.950040	0.02	0.1	0.08
2	20+/-5	100	13.80	939.950020	0.00	0.1	0.10
3	20+/-5	115	15.87	939.950030	0.01	0.1	0.09

State : High Power / Authorized Bandwidth 45 kHz / 940.55 MHz (FCC / RSS)

Reference Frequency: 940.550020 MHz

No.	Temperature (Degree C)	Diviation (%)	Voltage (V)	Frequency (MHz)	Stability (ppm)	Limit +/- (ppm)	Margin (ppm)
1	20+/-5	85	11.73	940.550030	0.01	0.5	0.49
2	20+/-5	100	13.80	940.550020	0.00	0.5	0.50
3	20+/-5	115	15.87	940.550020	0.00	0.5	0.50

10.9 Receiver Spurious Emissions(Radiated)

REGULATIONS : RSS-Gen Section 7

TEST METHOD/GUIDE : RSS-Gen Section 7

TEST PROCEDURE

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Tabletop Equipment
EUT is placed on the wooden table, the top of which is 0.8meter above the metal ground plane(turntable).
- 3 Interconnecting Cables
Excess part of the interconnecting cables longer than 1 meter are bundled in the center.
Cables that hang closer than 40 cm to the ground plane is folded back and forth forming bundle to 40 cm long, hanging approx, in the middle between ground plane and table.
- 4 Measuring Instruments
Measuring instruments list and their calibration schedule are shown on Measurement Equipment Configuration.
The brief description are as follows;
- 5 Antennas
The broadband Bi-cog antenna or Biconical and Log periodic antenna is used for measurement on the frequency range 30 – 1000 MHz.
The Double ridged guide antenna is used for frequency higher than 1000 MHz.
- 6 Pre-amplifier
The broadband pre-amplifier is used for radiated emission measurement.
The signal to noise ratio is improved by using pre-amplifier.
- 7 Spectrum Analyzer
The spectrum analyzer is used for preliminary measurement of frequency range 30 – 1000 MHz, and also used for final measurement of higher than 1000 MHz (RBW : 1 MHz).
- 8 EMI Test Receiver
The Quasi-peak detector (IF bandwidth : 120 kHz) built in test receiver is used for final measurement of the frequency 30 – 1000 MHz.
The test receiver is complied with the specification of the CISPR publication 16.
- 9 Turntable
The turntable is capable for EUT weight and rotatable 0 to 360 degree horizontally by remote control in the test room.
- 10 Antenna Mast
The antenna mast is attachable to all antennas described on antenna
height is adjustable 1 to 4 meters continuously by remote control at the test room, and antenna polarization is also changed by the remote control.
- 11 Preliminary Measurement
EUT is tested on all operating conditions.
The spectrum analyzer is set max-hold mode and swept during turntable was rotated 0 to 360 degree. Then spectrum chart are plotted out to find the worst emission conditions in configuration, operating mode, or ambient noise notation.

12 Final Measurement

The EUT operated in the condition where maximum emission is found in the preliminary test.

The turntable azimuth(EUT direction) and antenna height are adjusted the position so that maximum field strength is obtained for each frequency spectrum to be measured.

The equipment and cables are arranged or manipulated within the range of the test standard in the above condition.

When the uncertain result was obtained, the measurement is retried by using the half wave dipole antenna instead of the broadband antenna.


TEST EQUIPMENTS

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Broad Band antenna	Schwarzbeck	VULB9168WP	126	1Y	Dec. 31, 17
2	6 dB Attenuator	TAMAGAWA	UFA-01	A00040805	1Y	Feb. 28, 18
3	Amplifier	Intertek	ZX60-3018G	005	1Y	Feb. 28, 18
4	RF Switch	Intertek	ACX-150	A12301501	1Y	Feb. 28, 18
5	EMI Test receiver	Agilent	N9038A	MY51210201	1Y	Oct. 31, 17
6	Site Attenuation				1Y	Feb. 28, 18
7	Double Ridged antenna	Schwarzbeck	3115	5045	1Y	Mar. 31, 18
8	3 dB Attenuator	SUHNER	6803.17.B	KSR00089	1Y	Apr. 30, 18
9	Amplifier (1-18 GHz)	TOYO	TPA0118-30	0402	1Y	Apr. 30, 18
10	SVSWR				1Y	Oct. 31, 17
11	Testing Software	emiT (Version 3,0,0,0)			-	-

USED CABLES

No.	Cable	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
R11	Coaxial cable	FUJIKURA	5D-2W	R11	1Y	Feb. 28, 18
R1	Coaxial cable	FUJIKURA	5D-2W	R1	1Y	Feb. 28, 18
R3	Coaxial cable	FUJIKURA	10D-2W	R3	1Y	Feb. 28, 18
R5	Coaxial cable	FUJIKURA	RG-5A/U	R5	1Y	Feb. 28, 18
R7	Coaxial cable	FUJIKURA	RG-5A/U	R7	1Y	Feb. 28, 18
R10	Coaxial cable	FUJIKURA	5D-2W	R10	1Y	Feb. 28, 18
G1	Coaxial cable	SUHNER	SUCOFLEX 104	229603/4	1Y	Apr. 30, 18
G2	Coaxial cable	Candox	5B-048-98-98-5000	111130	1Y	Apr. 30, 18

MEASUREMENT EQUIPMENT CONFIGURATION



TEST RESULTS

Test date	Sep. 17, 2017
Location	Kashima No.12 Test Site
temperature	21.6 to 21.9 [degree C]
Humidity Variation	59 to 60 [%]
Atmospheric Pressure	100.1 to 101.2 [kPa]
Test Engineer	Koichi Wagatsuma

Test was carried out for the frequency band of section 10.1
State the worst case (below).

State : 896.05 MHz Receiver Condition (OCXO(Bult.))

No.	Frequency (MHz)	Pol	Mode	Reading Level (dBuv)	Factor* (dB)	Emission Level (dBuV/m)	Limit Level (dBuV/m)	Margin (dB)
1	81.24	Hor.		-	-5.2	-	40.0	-
		Ver.		39.4	-5.2	34.2	40.0	5.8
2	85.50	Hor.		-	-5.8	-	40.0	-
		Ver.		40.9	-5.8	35.1	40.0	4.9
3	87.47	Hor.		39.6	-6.1	33.5	40.0	6.5
		Ver.		41.0	-6.1	34.9	40.0	5.1
4	94.38	Hor.		42.0	-6.0	36.0	43.5	7.5
		Ver.		43.7	-6.0	37.7	43.5	5.8
5	98.75	Hor.		-	-5.6	-	43.5	-
		Ver.		42.3	-5.6	36.7	43.5	6.8
6	101.87	Hor.		39.9	-5.2	34.7	43.5	8.8
		Ver.		40.2	-5.2	35.0	43.5	8.5
7	625.03	Hor.		-	11.4	-	46.0	-
		Ver.		18.2	11.4	29.6	46.0	16.4
8	750.01	Hor.		-	13.7	-	46.0	-
		Ver.		15.5	13.7	29.2	46.0	16.8
9	823.00	Hor.		15.0	15.1	30.1	46.0	15.9
		Ver.		16.2	15.1	31.3	46.0	14.7
10	1125.00	Hor.	AVG	33.2	2.1	35.3	54.0	18.7
		Ver.	AVG	37.2	2.1	39.3	54.0	14.7
11	4938.00	Hor.	AVG	24.5	12.8	37.3	54.0	16.7
		Ver.	AVG	26.5	12.8	39.3	54.0	14.7

There is the margin of 20dB over except for the above points.
* Factor = Antenna,Antenna Pad,Cable,Preamp,(Dist. Conversion)
Emission Level = Reading Level + Factor

Note:

- 1 Measurement distance is 3 metres. (Above 1GHz is 6.3 metres)
- 2 Scanned frequency are 30 to 5000 MHz.
- 3 Highest frequency is 941 MHz.

10.1 Necessary Bandwidth and Emission Bandwidth

REGULATIONS : FCC Part 2 Section 202 (g) & Federal Register/ Vol.68, No236
TRC 43

Calculation Results

State : 11K0F3E (Authorized Bandwidth 11.25 kHz)

Item	Mark		
Maximum Modulation	(M)	3	kHz
Maximum Deviation	(D)	2.5	kHz
Constant Factor	(K)	1	
Necessary Bandwidth	(Bn)	11	kHz

$$B_n = (2 \times M) + (2 \times D \times K)$$

- 1.types of modulation of the main carrier : F= Frequency modulation
2.nature of signal(s) modulating the main carrier: 3= A single channel containing analog information
3.type of information to be transmitted: E= Telephony (including sound broadcasting)

State : 8K30F1E / 8K30F1D / 8K30F7W (4Level FSK / 9600bps, Authorized Bandwidth 11.25 kHz)

Item	Mark		
Digital information rate	(R)	9600	bps
Peak frequency deviation	(D)	3.391	kHz
Signaling states	(S)	4	
Numerical factor	(K)	0.516	
Necessary Bandwidth	(Bn)	8.3	kHz

$$B_n = (R / \log_2 S) + 2 \times D \times K$$

- 1.types of modulation of the main carrier : F= Frequency modulation
2.nature of signal(s) modulating the main carrier: 1= A single channel containing quantized or digital information without the use of a modulating sub-carrier
7= Two or more channels containing quantized or digital information
3.type of information to be transmitted: E= Telephony (including sound broadcasting)
D= Data transmission, telemetry, telecommand
W= Combination of the above

State : 4K00F1E / 4K00F1D / 4K00F7W (4Level FSK / 4800bps, Authorized Bandwidth 6 kHz)

Item	Mark		
Digital information rate	(R)	4800	bps
Peak frequency deviation	(D)	1.55	kHz
Signaling states	(S)	4	
Numerical factor	(K)	0.516	
Necessary Bandwidth	(Bn)	4	kHz

$$B_n = (R / \log_2 S) + 2 \times D \times K$$

- 1.types of modulation of the main carrier : F= Frequency modulation
2.nature of signal(s) modulating the main carrier: 1= A single channel containing quantized or digital information without the use of a modulating sub-carrier
7= Two or more channels containing quantized or digital information
3.type of information to be transmitted: E= Telephony (including sound broadcasting)
D= Data transmission, telemetry, telecommand
W= Combination of the above

State : 4K00F2D (CWID, Authorized Bandwidth 6 kHz)

Item	Mark		
Maximum Modulation	(M)	0.8	kHz
Maximum Deviation	(D)	1.2	kHz
Numerical factor	(K)	1	
Necessary Bandwidth	(Bn)	4	kHz

$$B_n = (2 \times M) + (2 \times D \times K)$$

- 1.types of modulation of the main carrier : F= Frequency modulation
2.nature of signal(s) modulating the main carrier: 2= A single channel containing quantized or digital information with the
3.type of information to be transmitted: D= Data transmission, telemetry, telecommand

10.11 99% Occupied Bandwidth

REGULATIONS	:	RSS-119 Section 5.5
		RSS-134 Section 4.1
TEST METHOD/GUIDE	:	RSS-Gen Section 6.6


Test Procedure

- 1 The EUT and test equipment were set up as shown on the following page.
- 2 Adjust the test instrument for the following setting:
 - RBW : 1 % to 5 % of the Necessary bandwidth
 - VBW : at least 3 times the RBW
 - Detector : Peak
 - Sweep Time : Auto
 - Trace mode : Max Hold
- 3 Allow trace to fully stabilize.
- 4 Use "Occupied Bandwidth Measurement" function to measure the 99% Occupied Bandwidth.
- 5 Modulate the transmitter with a 2.5 kHz sine wave at an input Level of 16 dB greater than that necessary to produce 50 % of rated system deviation.(Only 16K0F3E, 11K0F3E)

Measuring Equipments

No.	Equipment	Manufacture	Model No.	Serial No.	Cal. Interval	Effective period
1	Attenuator (30dB)	Weinschel	WA-29-30-34	8923	1Y	Aug. 31, 18
2	Modulation Analyzer	Hewlett Packard	8901B	3403A04852	1Y	Dec. 31, 17
3	Audio Generator	Anritsu	MG443B	M70150	1Y	Aug. 31, 18
4	Spectrum Analyzer	Agilent	N9030A	US51350220	1Y	Feb. 28, 18
5	DC Power Supply	Daiichi denpa kogyo	GZV4000	90290931	None	None
6	Digital Multi Meter	FLUKE	8846A	9642018	1Y	Jul. 31, 18
7	JIG	HP	EliteBook 2561p	CNU2262D0Q	None	None
8	Balance Cable	Nicoon	3D-2V	KSR00092	1Y	Mar. 31, 18
9	Coaxial Cable	Pacific custom	RG-58 C/U	AM90C04	1Y	Feb. 28, 18
10	Coaxial Cable	Suhner	SUCOFLEX104	F0000018	1Y	Jan. 31, 18


Measuring Equipment Configuration



FM Modulation test is with the the Audio Generator.

Configuration of other Modulation test is composed without the Audio Generator.







<CWID Modulation Case>









Test Results

Test date	Aug 29, 2017		
Location	Kashima No.12 Test Site		
temperature	23.9	[degree C]	
Humidity Variation	58.0	[%]	
Atmospheric Pressure	100.6	[kPa]	
Test Engineer	Koichi Wagatsuma		

Emission Designation	Frequency (MHz)	99% Occupied Bandwidth (kHz)	Authorized bandwidth (kHz)
11K0F3E	935.05	5.189	13.6
	939.95	5.189	
	940.55	5.189	45
8K30F1E/F1D/F7W	935.05	7.569	13.6
	939.95	7.673	
	940.55	7.614	45
4K00F1E / F1D / F7W	935.05	3.537	13.6
	939.95	3.562	
	940.55	3.514	10
4K00F2D	935.05	3.287	13.6
	939.95	3.288	
	940.55	3.285	10

Frequency (MHz)	Emission Designation	
	11K0F3E	8K30F1E/F1D/F7W
935.05	 Agilent Spectrum Analyzer - Occupied BW Center Freq 935.050000 MHz Center Freq 935.050000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 935.1 MHz #Res BW 110 Hz VBW 1.1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 5.189 kHz Transmit Freq Error 24 Hz x dB Bandwidth 5.232 kHz Total Power -4.10 dBm OBW Power 99.00 % x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 935.050000 MHz Center Freq 935.050000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 935.1 MHz #Res BW 100 Hz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 7.569 kHz Transmit Freq Error 57 Hz x dB Bandwidth 8.578 kHz Total Power 3.32 dBm OBW Power 99.00 % x dB -20.00 dB
939.95	 Agilent Spectrum Analyzer - Occupied BW Center Freq 939.950000 MHz Center Freq 939.950000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 940 MHz #Res BW 110 Hz VBW 1.1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 5.189 kHz Transmit Freq Error 24 Hz x dB Bandwidth 5.232 kHz Total Power -4.10 dBm OBW Power 99.00 % x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 939.950000 MHz Center Freq 939.950000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 940 MHz #Res BW 100 Hz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 7.673 kHz Transmit Freq Error 76 Hz x dB Bandwidth 8.321 kHz Total Power 3.31 dBm OBW Power 99.00 % x dB -20.00 dB
940.55	 Agilent Spectrum Analyzer - Occupied BW Center Freq 940.550000 MHz Center Freq 940.550000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 940.6 MHz #Res BW 110 Hz VBW 1.1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 5.189 kHz Transmit Freq Error 26 Hz x dB Bandwidth 5.232 kHz Total Power -4.09 dBm OBW Power 99.00 % x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 940.550000 MHz Center Freq 940.550000 MHz Trig: Free Run #Aver: 10 dB Radio Std: None Radio Device: BTS Ref 10.00 dBm Center 940.6 MHz #Res BW 100 Hz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 7.614 kHz Transmit Freq Error 46 Hz x dB Bandwidth 8.451 kHz Total Power 3.28 dBm OBW Power 99.00 % x dB -20.00 dB

Ferquency (MHz)	Emission Designation	
	4K00F1E / F1D / F7W	4K00F2D
935.05	 Agilent Spectrum Analyzer - Occupied BW Center Freq 935.050000 MHz Ref 10.00 dBm Center 935.1 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.537 kHz Total Power 3.10 dBm Transmit Freq Error 1 Hz OBW Power 99.00 % x dB Bandwidth 4.088 kHz x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 935.050000 MHz Ref 10.00 dBm Center 935.1 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.287 kHz Total Power -4.39 dBm Transmit Freq Error 18 Hz OBW Power 99.00 % x dB Bandwidth 3.372 kHz x dB -20.00 dB
939.95	 Agilent Spectrum Analyzer - Occupied BW Center Freq 939.950000 MHz Ref 10.00 dBm Center 940 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.562 kHz Total Power 3.27 dBm Transmit Freq Error 32 Hz OBW Power 99.00 % x dB Bandwidth 4.127 kHz x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 939.950000 MHz Ref 10.00 dBm Center 940 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.288 kHz Total Power -4.31 dBm Transmit Freq Error 17 Hz OBW Power 99.00 % x dB Bandwidth 3.373 kHz x dB -20.00 dB
940.55	 Agilent Spectrum Analyzer - Occupied BW Center Freq 940.550000 MHz Ref 10.00 dBm Center 940.6 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.514 kHz Total Power 3.20 dBm Transmit Freq Error 10 Hz OBW Power 99.00 % x dB Bandwidth 4.173 kHz x dB -20.00 dB	 Agilent Spectrum Analyzer - Occupied BW Center Freq 940.550000 MHz Ref 10.00 dBm Center 940.6 MHz VBW 1 kHz Span 50 kHz Sweep FFT Occupied Bandwidth 3.285 kHz Total Power -4.30 dBm Transmit Freq Error 20 Hz OBW Power 99.00 % x dB Bandwidth 3.369 kHz x dB -20.00 dB