



Test Report No.: RF2505WDG0050



TEST REPORT

Applicant	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA

Manufacturer or Supplier	Belkin International, Inc.
Address	555 S. Aviation Blvd., Suite 180, El Segundo, CA 90245, USA
Product	SoundForm™ Anywhere
Brand Name	belkin
Model	AUC014
Additional Model & Model Difference	N/A
Date of tests	Apr. 16, 2025 ~ Jun. 10, 2025

the tests have been carried out according to the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Eric Fang
Project Engineer / EMC Department

Approved by Glyn He
Assistant Manager / EMC Department

Date: Jun. 13, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT	6
3.2 DESCRIPTION OF TEST MODES	7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST.....	8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.4 DESCRIPTION OF SUPPORT UNITS	10
3.5 CONFIGURATION OF SYSTEM UNDER TEST	10
3.6 DUTY CYCLE OF TESET SIGNAL.....	11
4 TEST TYPES AND RESULTS.....	12
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	12
4.1.2 TEST INSTRUMENTS.....	13
4.1.3 TEST PROCEDURES	14
4.1.4 DEVIATION FROM TEST STANDARD	15
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	16
4.1.7 TEST RESULTS.....	17
4.2 NUMBER OF HOPPING FREQUENCY USED	33
4.2.1 LIMIT OF HOPPING FREQUENCY USED	33
4.2.2 TEST SETUP	33
4.2.3 TEST INSTRUMENTS.....	33
4.2.4 TEST PROCEDURES	34
4.2.5 DEVIATION FROM TEST STANDARD	34
4.2.6 TEST RESULTS.....	34
4.3 DWELL TIME ON EACH CHANNEL.....	39
4.3.1 LIMIT OF DWELL TIME USED	39
4.3.2 TEST SETUP	39
4.3.3 TEST INSTRUMENTS.....	39
4.3.4 TEST PROCEDURES	39



Test Report No.: RF2505WDG0050

4.3.5	DEVIATION FROM TEST STANDARD	40
4.3.6	TEST RESULTS.....	40
4.4	CHANNEL BANDWIDTH	46
4.4.1	LIMITS OF CHANNEL BANDWIDTH	46
4.4.2	TEST SETUP.....	46
4.4.3	TEST INSTRUMENTS.....	46
4.4.4	TEST PROCEDURE.....	46
4.4.5	DEVIATION FROM TEST STANDARD	46
4.4.6	EUT OPERATING CONDITION.....	46
4.4.7	TEST RESULTS.....	47
4.5	HOPPING CHANNEL SEPARATION.....	55
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION	55
4.5.2	TEST SETUP.....	55
4.5.3	TEST INSTRUMENTS.....	55
4.5.4	TEST PROCEDURES	55
4.5.5	DEVIATION FROM TEST STANDARD	55
4.5.6	TEST RESULTS.....	56
4.6	CONDUCTED OUTPUT POWER.....	64
4.6.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	64
4.6.2	TEST SETUP.....	64
4.6.3	TEST INSTRUMENTS.....	64
4.6.4	TEST PROCEDURES	64
4.6.5	DEVIATION FROM TEST STANDARD	64
4.6.6	EUT OPERATING CONDITION.....	65
4.6.7	TEST RESULTS.....	65
4.7	OUT OF BAND EMISSION MEASUREMENT	68
4.7.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	68
4.7.2	TEST INSTRUMENTS.....	68
4.7.3	TEST PROCEDURE.....	68
4.7.4	DEVIATION FROM TEST STANDARD	68
4.7.5	EUT OPERATING CONDITION.....	68
4.7.6	TEST RESULTS.....	68
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	77
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	78



Test Report No.: RF2505WDG0050

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2505WDG0050	Original release	Jun. 13, 2025

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Power by Battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.80dB
	30MHz ~ 1GMHz	4.65dB
	1GHz ~ 18GHz	5.01dB
	18GHz ~ 40GHz	4.10dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	SoundForm™ Anywhere
MODEL NO.	AUC014
ADDITIONAL MODELS	N/A
FCC ID	K7SAUC014
POWER SUPPLY	DC 5V from USB Host Unit or DC 3.7V from Li-ion Battery
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, $\pi/4$ DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	Left Earbuds: 1.811mW (Max. Measured) Right Earbuds: 1.871mW (Max. Measured)
ANTENNA TYPE	Ceramic Antenna, 2.7dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	See section 3.4

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2505WDG0050) for detailed product photo.
4. When earbuds in charging mode, BT function can't working.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, power supply voltage range and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered By Battery with BT function

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
A	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5



Test Report No.: RF2505WDG0050

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5
A	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 3.7V from Battery	Vincent
RE≥1G	25deg. C, 55%RH	DC 3.7V from Battery	Vincent
PLC	-	-	-
APCM	25deg. C, 60%RH	DC 3.7V from Battery	Vincent

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247
KDB 558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.


3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	Latitude 5280	77K2GH2	N/A
2	DC source	LONG WEI	PS-6403D	010934269	N/A

Description	Length (m)	Shielding (Y/N)	Remark
USB-A to USB-C cable	0.3	N	-
USB-A to USB-C cable	0.3	N	SHENZHEN TAI LIFENG ELECTRONIC TECHNOLOGY CO., LTD/ 116.14.02090
AC Line (Optional)	0.8	N	BV Lab.
DC Line (Optional)	1.8	N	BV Lab.

3.5 CONFIGURATION OF SYSTEM UNDER TEST




3.6 DUTY CYCLE OF TESET SIGNAL

Left Earbuds:

Test Mode	Packet Type	On Time (ms)	Period (ms)	Duty Cycle (%)	1/T Min. VBW (KHz)	VBW Setting (Hz)
BDR(GFSK)	DH5	2.855	3.75	76.13	0.350	500
EDR(8DPSK)	3DH5	2.893	3.753	77.08	0.346	500

GFSK: Duty Cycle= On Time/ Period=2.855/3.75=0.7613

8-DPSK: Duty Cycle= On Time/ Period=2.893/3.753=0.7708




Right Earbuds:

Test Mode	Packet Type	On Time (ms)	Period (ms)	Duty Cycle (%)	1/T Min. VBW (KHz)	VBW Setting (Hz)
BDR(GFSK)	DH5	2.877	3.752	76.68	0.348	500
EDR(8DPSK)	3DH5	2.893	3.75	77.15	0.346	500

GFSK: Duty Cycle= On Time/ Period=2.877/3.752=0.7668

8-DPSK: Duty Cycle= On Time/ Period=2.893/3.753=0.7715



4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Oct. 10, 25
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Apr. 07, 26
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	Apr. 13, 26
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Feb. 21, 26
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 25, 25
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	0085519	Oct. 19, 25
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Apr. 12, 26
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 17, 26
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Feb. 21, 26
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 28 25
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A

NOTE:

1. The test was performed in 966 Chamber.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation.
3. Test Lab Address: No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.
4. The FCC Site Registration No. is 749762.

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1.3m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be performed using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


Left Earbuds: GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	34.66	22.0 QP	40.0	-18.0	1.64 H	120	41.0	-19.0
2	76.63	13.7 QP	40.0	-26.3	1.78 H	133	35.0	-21.3
3	98.40	14.9 QP	43.5	-28.6	1.50 H	106	36.7	-21.8
4	154.36	13.5 QP	43.5	-30.0	1.30 H	86	30.1	-16.6
5	603.61	21.3 QP	46.0	-24.7	1.91 H	146	29.2	-7.9
6	819.68	25.0 QP	46.0	-21.0	2.04 H	158	29.3	-4.2

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value






Test Report No.: RF2505WDG0050

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.22	20.8 QP	40.0	-19.2	1.60 V	17	39.6	-18.8
2	47.10	17.3 QP	40.0	-22.7	1.83 V	39	35.1	-17.8
3	73.53	16.1 QP	40.0	-23.9	2.22 V	78	36.5	-20.4
4	141.92	13.0 QP	43.5	-30.5	2.36 V	92	30.0	-17.0
5	306.70	14.6 QP	46.0	-31.4	2.51 V	107	29.7	-15.1
6	718.64	23.6 QP	46.0	-22.4	2.68 V	124	29.4	-5.8

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com


Right Earbuds: GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	36.22	19.8 QP	40.0	-20.2	2.99 H	288	38.6	-18.8
2	110.83	13.7 QP	43.5	-29.9	2.68 H	258	34.1	-20.4
3	173.01	11.5 QP	43.5	-32.0	3.23 H	313	29.1	-17.6
4	305.14	13.8 QP	46.0	-32.2	3.40 H	329	28.9	-15.1
5	501.01	19.9 QP	46.0	-26.1	2.50 H	241	30.0	-10.1
6	743.51	23.6 QP	46.0	-22.4	3.54 H	343	28.8	-5.1

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value






Test Report No.: RF2505WDG0050

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.55	22.2 QP	40.0	-17.8	1.44 V	67	41.3	-19.1
2	64.20	17.7 QP	40.0	-22.3	1.58 V	81	35.9	-18.2
3	87.52	22.6 QP	40.0	-17.5	1.30 V	54	45.6	-23.0
4	157.47	13.1 QP	43.5	-30.4	1.72 V	94	29.7	-16.6
5	221.20	12.5 QP	46.0	-33.5	1.85 V	107	31.3	-18.7
6	672.00	22.7 QP	46.0	-23.3	2.01 V	124	29.4	-6.7

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.: RF2505WDG0050

ABOVE 1GHz DATA

Left Earbuds: BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	47.5 PK	74.0	-26.5	3.21 H	45	44.6	2.9
2	2390.00	34.2 AV	54.0	-19.8	3.21 H	45	31.3	2.9
3	*2402.00	91.3 PK			3.21 H	45	88.4	2.9
4	*2402.00	90.7 AV			3.21 H	45	87.8	2.9
5	4804.00	54.7 PK	74.0	-19.3	3.21 H	15	47.8	7.0
6	4804.00	47.9 AV	54.0	-6.1	3.21 H	15	41.0	7.0
7	7206.00	53.5 PK	74.0	-20.5	3.21 H	15	42.7	10.8
8	7206.00	40.5 AV	54.0	-13.5	3.21 H	15	29.7	10.8

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.5 PK	74.0	-21.5	3.21 V	15	49.7	2.9
2	2390.00	34.3 AV	54.0	-19.7	3.21 V	15	31.5	2.9
3	*2402.00	89.6 PK			3.21 V	45	86.7	2.9
4	*2402.00	86.8 AV			3.21 V	45	83.9	2.9
5	4804.00	54.9 PK	74.0	-19.1	3.21 V	15	48.0	7.0
6	4804.00	47.4 AV	54.0	-6.6	3.21 V	15	40.4	7.0
7	7206.00	53.4 PK	74.0	-20.6	3.94 V	7	42.6	10.8
8	7206.00	40.1 AV	54.0	-14.0	3.94 V	7	29.2	10.8

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	89.4 PK			3.21 H	15	86.4	3.0
2	*2441.00	88.6 AV			3.21 H	15	85.6	3.0
3	4882.00	55.3 PK	74.0	-18.7	1.54 H	45	48.1	7.2
4	4882.00	50.4 AV	54.0	-3.6	1.54 H	45	43.3	7.2
5	7323.00	54.6 PK	74.0	-19.4	3.64 H	360	43.4	11.2
6	7323.00	43.1 AV	54.0	-10.9	3.64 H	360	31.9	11.2

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	87.1 PK			3.21 V	15	84.1	3.0
2	*2441.00	83.8 AV			3.21 V	15	80.8	3.0
3	4882.00	54.3 PK	74.0	-19.7	3.21 V	45	47.1	7.2
4	4882.00	48.8 AV	54.0	-5.2	3.21 V	45	41.6	7.2
5	7323.00	53.8 PK	74.0	-20.3	3.35 V	48	42.5	11.2
6	7323.00	41.3 AV	54.0	-12.7	3.35 V	48	30.1	11.2

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.3 PK			3.21 H	15	90.1	3.1
2	*2480.00	92.6 AV			3.21 H	15	89.5	3.1
3	2483.50	52.7 PK	74.0	-21.3	3.21 H	15	49.5	3.2
4	2483.50	49.3 AV	54.0	-4.7	3.21 H	15	46.2	3.2
5	4960.00	56.7 PK	74.0	-17.3	2.31 H	1	49.3	7.4
6	4960.00	49.1 AV	54.0	-4.9	2.31 H	1	41.7	7.4
7	7440.00	54.5 PK	74.0	-19.6	3.11 H	18	42.8	11.6
8	7440.00	42.4 AV	54.0	-11.6	3.11 H	18	30.8	11.6

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	89.0 PK			3.21 V	15	85.9	3.1
2	*2480.00	88.4 AV			3.21 V	15	85.2	3.1
3	2483.50	49.8 PK	74.0	-24.2	3.15 V	15	46.6	3.2
4	2483.50	45.2 AV	54.0	-8.8	3.15 V	15	42.0	3.2
5	4960.00	55.3 PK	74.0	-18.7	1.54 V	48	47.9	7.4
6	4960.00	49.4 AV	54.0	-4.6	1.54 V	48	42.0	7.4
7	7440.00	55.0 PK	74.0	-19.0	3.21 V	15	43.4	11.6
8	7440.00	41.9 AV	54.0	-12.1	3.21 V	15	30.3	11.6

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

Right Earbuds: BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.9 PK	74.0	-29.1	1.00 H	109	42.0	2.9
2	2390.00	33.1 AV	54.0	-20.9	1.00 H	109	30.2	2.9
3	*2402.00	87.5 PK			1.49 H	140	84.6	2.9
4	*2402.00	86.4 AV			1.49 H	140	83.5	2.9
5	4804.00	51.0 PK	74.0	-23.1	1.95 H	195	44.0	7.0
6	4804.00	41.0 AV	54.0	-13.1	1.95 H	195	34.0	7.0
7	7206.00	54.6 PK	74.0	-19.4	1.61 H	181	43.8	10.8
8	7206.00	41.8 AV	54.0	-12.2	1.61 H	181	31.0	10.8
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.3 PK	74.0	-29.7	1.26 V	186	41.4	2.9
2	2390.00	32.9 AV	54.0	-21.1	1.26 V	186	30.0	2.9
3	*2402.00	83.1 PK			1.13 V	152	80.2	2.9
4	*2402.00	82.5 AV			1.13 V	152	79.6	2.9
5	4804.00	51.0 PK	74.0	-23.0	1.99 V	55	44.0	7.0
6	4804.00	38.9 AV	54.0	-15.1	1.99 V	55	31.9	7.0
7	7206.00	54.0 PK	74.0	-20.1	1.95 V	203	43.1	10.8
8	7206.00	40.0 AV	54.0	-14.0	1.95 V	203	29.2	10.8

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	87.2 PK			1.23 H	120	84.2	3.0
2	*2441.00	86.2 AV			1.23 H	120	83.2	3.0
3	4882.00	51.1 PK	74.0	-22.9	1.12 H	163	43.9	7.2
4	4882.00	40.6 AV	54.0	-13.4	1.12 H	163	33.4	7.2
5	7323.00	54.0 PK	74.0	-20.0	1.01 H	14	42.8	11.2
6	7323.00	43.1 AV	54.0	-10.9	1.01 H	14	31.9	11.2

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	84.9 PK			1.91 V	109	81.9	3.0
2	*2441.00	84.1 AV			1.91 V	109	81.1	3.0
3	4882.00	50.9 PK	74.0	-23.1	1.88 V	169	43.7	7.2
4	4882.00	38.7 AV	54.0	-15.3	1.88 V	169	31.5	7.2
5	7323.00	53.8 PK	74.0	-20.2	1.84 V	162	42.6	11.2
6	7323.00	40.6 AV	54.0	-13.4	1.84 V	162	29.4	11.2

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	87.8 PK			1.82 H	164	84.7	3.1
2	*2480.00	86.6 AV			1.82 H	164	83.5	3.1
3	2483.50	50.9 PK	74.0	-23.1	1.90 H	135	47.7	3.2
4	2483.50	43.4 AV	54.0	-10.7	1.90 H	135	40.2	3.2
5	4960.00	51.2 PK	74.0	-22.8	1.21 H	137	43.8	7.4
6	4960.00	40.4 AV	54.0	-13.6	1.21 H	137	33.0	7.4
7	7440.00	55.4 PK	74.0	-18.6	1.43 H	114	43.8	11.6
8	7440.00	44.1 AV	54.0	-9.9	1.43 H	114	32.5	11.6
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	85.9 PK			1.85 V	109	82.7	3.1
2	*2480.00	85.1 AV			1.85 V	109	82.0	3.1
3	2483.50	47.8 PK	74.0	-26.2	1.78 V	360	44.6	3.2
4	2483.50	41.9 AV	54.0	-12.1	1.78 V	360	38.8	3.2
5	4960.00	50.9 PK	74.0	-23.2	1.85 V	163	43.4	7.4
6	4960.00	37.6 AV	54.0	-16.4	1.85 V	163	30.2	7.4
7	7440.00	54.7 PK	74.0	-19.3	1.70 V	125	43.1	11.6
8	7440.00	41.3 AV	54.0	-12.8	1.70 V	125	29.6	11.6

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



Left Earbuds: BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.2 PK	74.0	-25.8	3.21 H	145	45.3	2.9
2	2390.00	34.2 AV	54.0	-19.8	3.21 H	145	31.3	2.9
3	*2402.00	91.8 PK			3.21 H	15	88.9	2.9
4	*2402.00	89.9 AV			3.21 H	15	87.0	2.9
5	4804.00	54.5 PK	74.0	-19.5	4.00 H	48	47.5	7.0
6	4804.00	44.8 AV	54.0	-9.2	4.00 H	48	37.8	7.0
7	7206.00	52.1 PK	74.0	-21.9	3.14 H	47	41.3	10.8
8	7206.00	40.2 AV	54.0	-13.8	3.14 H	47	29.4	10.8

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.2 PK	74.0	-18.8	3.21 V	15	52.3	2.9
2	2390.00	34.8 AV	54.0	-19.2	3.21 V	15	31.9	2.9
3	*2402.00	88.3 PK			3.21 V	15	85.4	2.9
4	*2402.00	84.8 AV			3.21 V	15	81.9	2.9
5	4804.00	53.7 PK	74.0	-20.3	2.31 V	15	46.8	7.0
6	4804.00	45.0 AV	54.0	-9.0	2.31 V	15	38.0	7.0
7	7206.00	52.9 PK	74.0	-21.1	1.23 V	321	42.1	10.8
8	7206.00	40.6 AV	54.0	-13.4	1.23 V	321	29.8	10.8

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.0 PK			3.21 H	15	87.0	3.0
2	*2441.00	85.9 AV			3.21 H	15	82.9	3.0
3	4882.00	53.0 PK	74.0	-21.0	3.21 H	15	45.8	7.2
4	4882.00	45.9 AV	54.0	-8.1	3.21 H	15	38.8	7.2
5	7323.00	54.3 PK	74.0	-19.7	4.00 H	4	43.1	11.2
6	7323.00	41.2 AV	54.0	-12.8	4.00 H	4	30.0	11.2

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	84.6 PK			3.21 V	15	81.6	3.0
2	*2441.00	83.5 AV			3.21 V	15	80.5	3.0
3	4882.00	53.2 PK	74.0	-20.8	1.87 V	48	46.0	7.2
4	4882.00	45.2 AV	54.0	-8.8	1.87 V	48	38.0	7.2
5	7323.00	53.9 PK	74.0	-20.2	1.00 V	78	42.6	11.2
6	7323.00	40.5 AV	54.0	-13.5	1.00 V	78	29.3	11.2

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.6 PK			1.00 H	45	90.5	3.1
2	*2480.00	89.4 AV			1.00 H	45	86.3	3.1
3	2483.50	53.4 PK	74.0	-20.6	3.14 H	48	50.2	3.2
4	2483.50	48.0 AV	54.0	-6.0	3.14 H	48	44.9	3.2
5	4960.00	57.1 PK	74.0	-16.9	3.84 H	48	49.7	7.4
6	4960.00	48.4 AV	54.0	-5.6	3.84 H	48	41.0	7.4
7	7440.00	53.5 PK	74.0	-20.5	4.00 H	321	41.9	11.6
8	7440.00	41.8 AV	54.0	-12.2	4.00 H	321	30.2	11.6
ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	89.4 PK			3.21 V	15	86.3	3.1
2	*2480.00	85.4 AV			3.21 V	15	82.3	3.1
3	2483.50	50.7 PK	74.0	-23.4	3.21 V	45	47.5	3.2
4	2483.50	44.3 AV	54.0	-9.7	3.21 V	45	41.1	3.2
5	4960.00	55.0 PK	74.0	-19.0	4.00 V	78	47.6	7.4
6	4960.00	45.5 AV	54.0	-8.5	4.00 V	78	38.1	7.4
7	7440.00	54.5 PK	74.0	-19.5	3.21 V	5	42.9	11.6
8	7440.00	41.8 AV	54.0	-12.2	3.21 V	5	30.2	11.6

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



Right Earbuds: BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.2 PK	74.0	-29.8	1.21 H	101	41.3	2.9
2	2390.00	33.0 AV	54.0	-21.0	1.21 H	101	30.1	2.9
3	*2402.00	87.6 PK			1.56 H	147	84.7	2.9
4	*2402.00	83.5 AV			1.56 H	147	80.6	2.9
5	4804.00	50.9 PK	74.0	-23.1	1.88 H	182	43.9	7.0
6	4804.00	40.8 AV	54.0	-13.2	1.88 H	182	33.9	7.0
7	7206.00	53.9 PK	74.0	-20.1	1.91 H	126	43.1	10.8
8	7206.00	41.3 AV	54.0	-12.7	1.91 H	126	30.4	10.8

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.0 PK	74.0	-30.0	1.04 V	192	41.2	2.9
2	2390.00	32.9 AV	54.0	-21.1	1.04 V	192	30.0	2.9
3	*2402.00	84.4 PK			1.41 V	128	81.5	2.9
4	*2402.00	80.3 AV			1.41 V	128	77.4	2.9
5	4804.00	50.6 PK	74.0	-23.4	1.62 V	166	43.7	7.0
6	4804.00	38.7 AV	54.0	-15.3	1.62 V	166	31.7	7.0
7	7206.00	53.8 PK	74.0	-20.2	1.77 V	104	42.9	10.8
8	7206.00	40.0 AV	54.0	-14.0	1.77 V	104	29.2	10.8

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	87.41			1.49 H	141	84.38	3.03
2	*2441	83.21			1.49 H	141	80.18	3.03
3	4882	51.23	74.00	-22.77	1.68 H	123	44.04	7.19
4	4882	40.69	54.00	-13.31	1.68 H	123	33.50	7.19
5	7323	54.84	74.00	-19.16	1.54 H	184	43.62	11.22
6	7323	41.21	54.00	-12.79	1.54 H	184	29.99	11.22

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441	85.92			1.49 H	192	82.89	3.03
2	*2441	81.60			1.49 H	192	78.57	3.03
3	4882	51.17	74.00	-22.83	1.68 H	117	43.98	7.19
4	4882	38.11	54.00	-15.89	1.68 H	117	30.92	7.19
5	7323	54.11	74.00	-19.89	1.54 H	111	42.89	11.22
6	7323	40.41	54.00	-13.59	1.54 H	111	29.19	11.22

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2505WDG0050

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE : HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480	87.87			1.49 H	187	84.73	3.14
2	*2480	83.51			1.49 H	187	80.37	3.14
3	2483.5	49.32	74.00	-24.68	1.68 H	132	46.16	3.16
4	2483.5	42.45	54.00	-11.55	1.68 H	132	39.29	3.16
5	4960	52.27	74.00	-21.73	1.54 H	127	44.86	7.41
6	4960	38.32	54.00	-15.68	1.54 H	127	30.91	7.41
7	7440	54.15	74.00	-19.85	1.71 H	115	42.54	11.61
8	7440	41.06	54.00	-12.94	1.71 H	115	29.45	11.61

ANTENNA POLARITY & TEST DISTANCE : VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480	86.25			1.49 H	125	83.11	3.14
2	*2480	81.83			1.49 H	125	78.69	3.14
3	2483.5	47.75	74.00	-26.25	1.68 H	175	44.59	3.16
4	2483.5	40.94	54.00	-13.06	1.68 H	175	37.78	3.16
5	4960	50.84	74.00	-23.16	1.54 H	184	43.43	7.41
6	4960	38.56	54.00	-15.44	1.54 H	184	31.15	7.41
7	7440	54.92	74.00	-19.08	1.71 H	192	43.31	11.61
8	7440	40.74	54.00	-13.26	1.71 H	192	29.13	11.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.


Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Sensor	Keysight	U2021XA	MY57320002	Apr. 07, 26
Digital Multimeter	FLUKE	15B	A1220010DG	N/A
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Oct. 10, 25
Oscilloscope	Agilent	DSO9254A	MY51260160	Jul. 07, 25
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Oct. 09, 25
Signal Generator	Agilent	N5183A	MY50140980	Jul. 11, 25
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jul. 11, 25
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A
Test software	ADT	ADT_RF Test Software V6.6.5.3	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. Equipment are calibrated by calibration laboratory accredited to ISO/IEC 17025 by a mutually recognized Accreditation.
3. Test Lab Address: No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.



4.2.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

4.2.5 DEVIATION FROM TEST STANDARD

No deviation.



4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



Test Report No.: RF2505WDG0050

Left Earbuds:
GFSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch



No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.: RF2505WDG0050

Right Earbuds:
GFSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch



No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.: RF2505WDG0050

Left Earbuds:
8DPSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com





**BUREAU
VERITAS**

Test Report No.: RF2505WDG0050

Right Earbuds:

8DPSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942. People's Republic of China.


Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

Left Earbuds: GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.45	145.04	400	PASS
DH3	79	31.6	5	25	158	1.72	271.76	400	PASS
DH5	79	31.6	5	16	101.12	3.024	305.79	400	PASS

Right Earbuds: GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	51	322.32	0.414	133.44	400	PASS
DH3	79	31.6	5	26	164.32	1.75	287.56	400	PASS
DH5	79	31.6	5	16	101.12	3.008	304.17	400	PASS



Left Earbuds: 8DPSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	50	316	0.432	136.51	400	PASS
3DH3	79	31.6	5	25	158	1.73	273.34	400	PASS
3DH5	79	31.6	5	16	101.12	3.04	307.4	400	PASS

Right Earbuds: 8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	51	322.32	0.426	137.31	400	PASS
3DH3	79	31.6	5	27	170.64	1.71	291.79	400	PASS
3DH5	79	31.6	5	17	107.44	3.024	324.9	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

Left Earbuds: GFSK





BUREAU VERITAS

Test Report No.: RF2505WDG0050

Right Earbuds: GFSK




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

Left Earbuds: 8DPSK






BUREAU VERITAS

Test Report No.: RF2505WDG0050

Right Earbuds: 8DPSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.


Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS


Left Earbuds: GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.95
39	2441	0.95
78	2480	0.95


CH 0




CH 39




CH 78



CH 39




CH 78




Left Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.28
39	2441	1.28
78	2480	1.29


CH 0



CH 39




CH 78




Right Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.28
39	2441	1.29
78	2480	1.28


CH 0



CH 39



CH 78




4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.


4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.


4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

CH 39



CH 78





BUREAU VERITAS


Test Report No.: RF2505WDG0050

Left Earbuds: 8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.28	0.85	PASS
39	2441	1.00	1.28	0.85	PASS
78	2480	1.00	1.29	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




Right Earbuds: 8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.28	0.85	PASS
39	2441	1.00	1.29	0.86	PASS
78	2480	1.00	1.28	0.85	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 0.125W.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

Left Earbuds: GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	1.52	1.419	0.125	PASS
39	2441	1.56	1.432	0.125	PASS
78	2480	1.25	1.334	0.125	PASS

Right Earbuds: GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	1.66	1.466	0.125	PASS
39	2441	1.72	1.486	0.125	PASS
78	2480	1.50	1.413	0.125	PASS

Left Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	2.55	1.799	0.125	PASS
39	2441	2.58	1.811	0.125	PASS
78	2480	2.15	1.641	0.125	PASS



Test Report No.: RF2505WDG0050

Right Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	2.67	1.849	0.125	PASS
39	2441	2.72	1.871	0.125	PASS
78	2480	2.45	1.758	0.125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

Left Earbuds: GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.36	1.086
39	2441	0.38	1.091
78	2480	0.01	1.002

Right Earbuds: GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.52	1.127
39	2441	0.58	1.143
78	2480	0.25	1.059

Left Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.11	1.026
39	2441	0.19	1.045
78	2480	0.03	1.007

Right Earbuds: 8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.32	1.076
39	2441	0.39	1.094
78	2480	0.01	1.002



Test Report No.: RF2505WDG0050

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.



BUREAU VERITAS

Test Report No.: RF2505WDG0050

Left Earbuds: GFSK




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch


No. 96, Guantai Road (Houjie Section), Houjie
Town, Dongguan City, Guangdong Province.
523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com

Right Earbuds: GFSK



Left Earbuds:8DPSK






BUREAU VERITAS

Test Report No.: RF2505WDG0050

Right Earbuds:8DPSK




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Left Earbuds: GFSK







BUREAU VERITAS



Test Report No.: RF2505WDG0050

Right Earbuds: GFSK

Hopping on Low Channel



Hopping on High Channel




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province.
523942, People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Left Earbuds:8DPSK







BUREAU VERITAS



Test Report No.: RF2505WDG0050

Right Earbuds:8DPSK

Hopping on Low Channel



Hopping on High Channel



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@bureauveritas.com



Test Report No.: RF2505WDG0050

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF2505WDG0050

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---