

FCC TEST REPORT

REPORT NO.: RF960119L12

MODEL NO.: F5D8231-4 v3000

RECEIVED: Jan. 19, 2007

TESTED: Feb. 04 ~ Feb. 11, 2007

ISSUED: Feb. 13, 2007

APPLICANT: Belkin International, Inc.

ADDRESS: 501 West Walnut Street, Compton, CA
90220-5221

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: 47 14th Lin, Chiapau Tsun, Linko, Taipei, Taiwan,
R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Kueishan, Taoyuan,
Taiwan, R.O.C.

This test report consists of 108 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



No. 2177-01



TABLE OF CONTENTS

1.	CERTIFICATION	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	11
3.4	DESCRIPTION OF SUPPORT UNITS	11
4.	TEST TYPES AND RESULTS	12
4.1	CONDUCTED EMISSION MEASUREMENT	12
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	12
4.1.2	TEST INSTRUMENTS	12
4.1.3	TEST PROCEDURES	13
4.1.4	DEVIATION FROM TEST STANDARD	13
4.1.5	TEST SETUP	14
4.1.6	EUT OPERATING CONDITIONS	14
4.1.7	TEST RESULTS	15
4.2	RADIATED EMISSION MEASUREMENT	33
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	33
4.2.2	TEST INSTRUMENTS	34
4.2.3	TEST PROCEDURES	35
4.2.4	DEVIATION FROM TEST STANDARD	35
4.2.5	TEST SETUP	36
4.2.6	EUT OPERATING CONDITIONS	36
4.2.7	TEST RESULTS	37
4.3	6dB BANDWIDTH MEASUREMENT	55
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	55
4.3.2	TEST INSTRUMENTS	55
4.3.3	TEST PROCEDURE	55
4.3.4	DEVIATION FROM TEST STANDARD	55
4.3.5	TEST SETUP	56
4.3.6	EUT OPERATING CONDITIONS	56
4.3.7	TEST RESULTS	57
4.4	MAXIMUM PEAK OUTPUT POWER	69
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	69
4.4.2	INSTRUMENTS	69
4.4.3	TEST PROCEDURES	69
4.4.4	DEVIATION FROM TEST STANDARD	69
4.4.5	TEST SETUP	70
4.4.6	EUT OPERATING CONDITIONS	70
4.4.7	TEST RESULTS	71
4.5	POWER SPECTRAL DENSITY MEASUREMENT	73
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	73
4.5.2	TEST INSTRUMENTS	73
4.5.3	TEST PROCEDURE	73
4.5.4	DEVIATION FROM TEST STANDARD	73
4.5.5	TEST SETUP	74

4.5.6	EUT OPERATING CONDITION.....	74
4.5.7	TEST RESULTS	75
4.6	BAND EDGES MEASUREMENT.....	87
4.6.1	LIMITS OF BAND EDGES MEASUREMENT.....	87
4.6.2	TEST INSTRUMENTS.....	87
4.6.3	TEST PROCEDURE.....	88
4.6.4	DEVIATION FROM TEST STANDARD	88
4.6.5	EUT OPERATING CONDITION.....	89
4.6.6	TEST RESULTS	89
4.7	ANTENNA REQUIREMENT	105
4.7.1	STANDARD APPLICABLE	105
4.7.2	ANTENNA CONNECTED CONSTRUCTION	105
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	106
6.	INFORMATION ON THE TESTING LABORATORIES.....	107
APPENDIX-A.....		A-1

1. CERTIFICATION

PRODUCT : N1 Wireless Router

MODEL NO.: F5D8231-4 v3000

BRAND: Belkin

APPLICANT : Belkin International, Inc.

TESTED: Feb. 04 ~ Feb. 11, 2007

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS : FCC Part 15, Subpart C (Section 15.247)

ANSI C63.4-2003

The above equipment (model: F5D8231-4 v3000) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Peggy Chen , **DATE:** Feb. 13, 2007
Peggy Chen

TECHNICAL
ACCEPTANCE : Long Chen , **DATE:** Feb. 13, 2007
Responsible for RF Long Chen

APPROVED BY : Gary Chang , **DATE:** Feb. 13, 2007
Gary Chang / Supervisor

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -1.72dB at 0.270MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.06dB at 2483.50MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44dB
Radiated emissions	30MHz ~ 200MHz	3.62 dB
	200MHz ~1000MHz	3.64 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	N1 Wireless Router
MODEL NO.	F5D8231-4 v3000
FCC ID	K7SF5D8231-4C
POWER SUPPLY	12Vdc from AC adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps Draft 802.11n (20MHz): 144.44/ 130.00/ 115.56/ 86.67/ 57.78/ 43.33/ 28.89/ 14.44/ 72.2/ 65.0/ 57.8/ 43.3/ 28.9/ 21.7/ 14.4/ 7.2Mbps Draft 802.11n (40MHz): 300.0/ 270.0/ 240.0/ 180.0/ 120.0/ 90.0/ 60.0/ 30.0/ 150.0/ 135.0/ 120.0/ 90.0/ 60.0/ 45.0/ 30.0/ 15.0Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, Draft 802.11n (20MHz) 7 for Draft 802.11n (40MHz)
MAXIMUM OUTPUT POWER	128.394mW
ANTENNA TYPE	Dipole antenna with 2dBi gain
DATA CABLE	NA
I/O PORTS	RJ45
ASSOCIATED DEVICES	Adapter

NOTE:

1. The EUT was powered by the following adapter:

BRAND:	DVE
MODEL:	DSA-12R-12 AUS 120120
INPUT:	100-120Vac, 50/60Hz, 0.3A
OUTPUT:	12Vdc, 1A
POWER LINE:	1.8m non-shielded cable without core

2. The EUT incorporates a MIMO function with 802.11b, 802.11g, draft 802.11n. Physically, the card provides two completed transmitters and three receivers.
3. The EUT is 2 * 3 spatial MIMO (2Tx & 3Rx) without beam forming function that only operate dual chain configuration (chain 0 and chain 1 transceivers are operational).
4. When the EUT operating in 802.11b is for single Tx.
5. When the EUT operating in 802.11g, the software operation, which is defined by manufacturer, only set single Tx.

6. When the EUT operating in draft 802.11n, the software operation, which is defined by manufacturer, only set 0 ~ 15 of "MCS" (MCS: Modulation and Coding Schemes) for dual Tx.
7. The EUT complies with draft 802.11n standards and backwards compatible with 802.11b, 802.11g products.
8. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 300Mbps.
9. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES


Eleven channels are provided for 802.11b, 802.11g, draft 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for draft 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2422MHz	5	2442MHz
2	2427MHz	6	2447MHz
3	2432MHz	7	2452MHz
4	2437MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	
-	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX CONDITION
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	Single
Draft 802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2	Dual
Draft 802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	15.0	Dual

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX CONDITION
802.11g	1 to 11	1	OFDM	BPSK	6.0	Single
Draft 802.11n (20MHz)	1 to 11	1	OFDM	BPSK	7.2	Dual
Draft 802.11n (40MHz)	1 to 7	1	OFDM	BPSK	15.0	Dual

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX CONDITION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	Single
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	Single
Draft 802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2	Dual
Draft 802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	15.0	Dual

BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX CONDITION
802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0	Single
802.11g	1 to 11	1, 11	OFDM	BPSK	6.0	Single
Draft 802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	7.2	Dual
Draft 802.11n (40MHz)	1 to 7	1, 7	OFDM	BPSK	15.0	Dual

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	TX CONDITION
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0	Single
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0	Single
Draft 802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	7.2	Dual
Draft 802.11n (40MHz)	1 to 7	1, 4, 7	OFDM	BPSK	15.0	Dual

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	33898721680	E2K24CLNS
2	MODEM	ACEEX	1414V/3	0401008260	IFAXDM1414
3	PRINTER	EPSON	LQ-300+	DCGY054146	FCC DoC Approved
4	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m shielded cable
3	1.2 m shielded cable
4	1.2 m shielded cable

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
2. Item 4 acted as communication partners to transfer data.

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 25, 2007
RF signal cable Woken	5D-FB	Cable-HYCO3-01	Jan. 06, 2008
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 08, 2008
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 16, 2008
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 2.
 3. The VCCI Site Registration No. is C-2047.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. The EUT connected with notebook system via a RJ45 cable.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the system in full functions.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: 802.11g OFDM MODULATION – SINGLE TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.266	0.10	52.42	47.61	52.52	47.71	61.23	51.23	-8.71	-3.52
2	0.344	0.10	42.98	-	43.08	-	59.10	49.10	-16.02	-
3	0.885	0.11	40.61	-	40.72	-	56.00	46.00	-15.28	-
4	1.379	0.15	38.17	-	38.32	-	56.00	46.00	-17.68	-
5	12.199	0.40	30.64	-	31.04	-	60.00	50.00	-28.96	-
6	23.129	0.73	41.76	-	42.49	-	60.00	50.00	-17.51	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.269	0.10	48.69	-	48.79	-	61.14	51.14	-12.35	-
2	0.345	0.10	39.89	-	39.99	-	59.07	49.07	-19.08	-
3	0.541	0.13	34.86	-	34.99	-	56.00	46.00	-21.01	-
4	1.426	0.21	37.63	-	37.84	-	56.00	46.00	-18.16	-
5	5.926	0.33	27.47	-	27.80	-	60.00	50.00	-32.20	-
6	21.664	0.62	37.59	-	38.21	-	60.00	50.00	-21.79	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.270	0.10	53.48	49.23	53.58	49.33	61.13	51.13	-7.55	-1.80
2	0.388	0.10	44.99	-	45.09	-	58.11	48.11	-13.02	-
3	0.853	0.11	40.37	-	40.48	-	56.00	46.00	-15.52	-
4	2.523	0.24	36.97	-	37.21	-	56.00	46.00	-18.79	-
5	5.215	0.29	35.75	-	36.04	-	60.00	50.00	-23.96	-
6	21.664	0.65	41.09	-	41.74	-	60.00	50.00	-18.26	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	48.16	-	48.26	-	61.21	51.21	-12.95	-
2	0.384	0.10	40.11	-	40.21	-	58.18	48.18	-17.97	-
3	0.840	0.18	36.50	-	36.68	-	56.00	46.00	-19.32	-
4	2.176	0.23	37.02	-	37.25	-	56.00	46.00	-18.75	-
5	9.938	0.43	26.13	-	26.56	-	60.00	50.00	-33.44	-
6	20.809	0.59	37.15	-	37.74	-	60.00	50.00	-22.26	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.10	53.49	46.39	53.59	46.49	61.08	51.08	-7.49	-4.59
2	0.347	0.10	43.85	-	43.95	-	59.04	49.04	-15.09	-
3	0.884	0.11	40.29	-	40.40	-	56.00	46.00	-15.60	-
4	1.973	0.22	42.30	-	42.52	-	56.00	46.00	-13.48	-
5	14.336	0.46	31.96	-	32.42	-	60.00	50.00	-27.58	-
6	24.961	0.82	37.86	-	38.68	-	60.00	50.00	-21.32	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	6.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.10	48.35	-	48.45	-	61.08	51.08	-12.63	-
2	0.384	0.10	40.19	-	40.29	-	58.18	48.18	-17.89	-
3	1.328	0.21	35.38	-	35.59	-	56.00	46.00	-20.41	-
4	2.023	0.22	32.87	-	33.09	-	56.00	46.00	-22.91	-
5	14.152	0.47	28.06	-	28.53	-	60.00	50.00	-31.47	-
6	21.906	0.63	35.95	-	36.58	-	60.00	50.00	-23.42	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.269	0.10	53.32	48.57	53.42	48.67	61.16	51.16	-7.74	-2.49
2	0.388	0.10	44.81	-	44.91	-	58.10	48.10	-13.19	-
3	0.881	0.11	39.30	-	39.41	-	56.00	46.00	-16.59	-
4	2.473	0.23	41.49	-	41.72	-	56.00	46.00	-14.28	-
5	6.422	0.30	32.57	-	32.87	-	60.00	50.00	-27.13	-
6	20.809	0.61	38.27	-	38.88	-	60.00	50.00	-21.12	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.269	0.10	48.75	-	48.85	-	61.14	51.14	-12.29	-
2	0.353	0.10	38.67	-	38.77	-	58.89	48.89	-20.12	-
3	0.830	0.18	35.52	-	35.70	-	56.00	46.00	-20.30	-
4	2.441	0.23	36.00	-	36.23	-	56.00	46.00	-19.77	-
5	18.246	0.54	31.14	-	31.68	-	60.00	50.00	-28.32	-
6	23.129	0.66	38.55	-	39.21	-	60.00	50.00	-20.79	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.266	0.10	53.12	48.00	53.22	48.10	61.25	51.25	-8.03	-3.15
2	0.383	0.10	44.36	-	44.46	-	58.21	48.21	-13.75	-
3	0.868	0.11	40.05	-	40.16	-	56.00	46.00	-15.84	-
4	2.281	0.23	41.92	-	42.15	-	56.00	46.00	-13.85	-
5	7.043	0.31	30.31	-	30.62	-	60.00	50.00	-29.38	-
6	19.707	0.56	39.53	-	40.09	-	60.00	50.00	-19.91	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
	[MHz]	Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.271	0.10	48.49	-	48.59	-	61.09	51.09	-12.50	-
2	0.348	0.10	39.61	-	39.71	-	59.01	49.01	-19.30	-
3	0.541	0.13	34.82	-	34.95	-	56.00	46.00	-21.05	-
4	1.378	0.21	35.55	-	35.76	-	56.00	46.00	-20.24	-
5	15.434	0.49	30.08	-	30.57	-	60.00	50.00	-29.43	-
6	23.129	0.66	43.11	-	43.77	-	60.00	50.00	-16.23	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.270	0.10	53.69	47.84	53.79	47.94	61.12	51.12	-7.33	-3.18
2	0.346	0.10	43.73	-	43.83	-	59.05	49.05	-15.22	-
3	0.849	0.11	41.02	-	41.13	-	56.00	46.00	-14.87	-
4	2.141	0.22	37.72	-	37.94	-	56.00	46.00	-18.06	-
5	5.371	0.29	34.05	-	34.34	-	60.00	50.00	-25.66	-
6	23.129	0.73	43.61	-	44.34	-	60.00	50.00	-15.66	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	7.2Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.268	0.10	48.36	-	48.46	-	61.19	51.19	-12.73	-
2	0.384	0.10	40.33	-	40.43	-	58.18	48.18	-17.75	-
3	0.533	0.12	35.97	-	36.09	-	56.00	46.00	-19.91	-
4	1.867	0.22	35.81	-	36.03	-	56.00	46.00	-19.97	-
5	7.770	0.37	25.71	-	26.08	-	60.00	50.00	-33.92	-
6	23.129	0.66	40.13	-	40.79	-	60.00	50.00	-19.21	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.270	0.10	53.62	49.30	53.72	49.40	61.12	51.12	-7.40	-1.72
2	0.384	0.10	45.15	-	45.25	-	58.18	48.18	-12.93	-
3	0.834	0.11	41.75	-	41.86	-	56.00	46.00	-14.14	-
4	2.355	0.23	39.11	-	39.34	-	56.00	46.00	-16.66	-
5	5.563	0.29	34.31	-	34.60	-	60.00	50.00	-25.40	-
6	23.129	0.73	45.82	-	46.55	-	60.00	50.00	-13.45	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	48.46	-	48.56	-	61.20	51.20	-12.64	-
2	0.345	0.10	40.05	-	40.15	-	59.08	49.08	-18.93	-
3	1.180	0.21	37.37	-	37.58	-	56.00	46.00	-18.42	-
4	2.438	0.23	34.49	-	34.72	-	56.00	46.00	-21.28	-
5	16.227	0.50	31.23	-	31.73	-	60.00	50.00	-28.27	-
6	23.129	0.66	40.78	-	41.44	-	60.00	50.00	-18.56	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.270	0.10	53.69	48.00	53.79	48.10	61.13	51.13	-7.34	-3.03
2	0.346	0.10	43.77	-	43.87	-	59.06	49.06	-15.19	-
3	0.869	0.11	40.35	-	40.46	-	56.00	46.00	-15.54	-
4	2.242	0.23	41.39	-	41.62	-	56.00	46.00	-14.38	-
5	7.039	0.31	30.71	-	31.02	-	60.00	50.00	-28.98	-
6	21.664	0.65	42.55	-	43.20	-	60.00	50.00	-16.80	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	48.50	-	48.60	-	61.20	51.20	-12.60	-
2	0.384	0.10	40.45	-	40.55	-	58.18	48.18	-17.63	-
3	0.540	0.13	34.29	-	34.42	-	56.00	46.00	-21.58	-
4	1.703	0.22	33.73	-	33.95	-	56.00	46.00	-22.05	-
5	7.023	0.36	26.07	-	26.43	-	60.00	50.00	-33.57	-
6	22.883	0.66	35.90	-	36.56	-	60.00	50.00	-23.44	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	PHASE	Line 1
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	52.68	48.50	52.78	48.60	61.20	51.20	-8.42	-2.60
2	0.388	0.10	44.79	-	44.89	-	58.11	48.11	-13.22	-
3	0.844	0.11	39.08	-	39.19	-	56.00	46.00	-16.81	-
4	1.382	0.15	39.85	-	40.00	-	56.00	46.00	-16.00	-
5	5.672	0.29	33.76	-	34.05	-	60.00	50.00	-25.95	-
6	23.129	0.73	42.95	-	43.68	-	60.00	50.00	-16.32	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	PHASE	Line 2
MODULATION TYPE	BPSK	6dB BANDWIDTH	9 kHz
TRANSFER RATE	15.0Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 60% RH, 991hPa	TESTED BY	Match Tsui

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	48.44	-	48.54	-	61.21	51.21	-12.67	-
2	0.347	0.10	39.87	-	39.97	-	59.04	49.04	-19.07	-
3	0.541	0.13	34.74	-	34.87	-	56.00	46.00	-21.13	-
4	1.367	0.21	38.34	-	38.55	-	56.00	46.00	-17.45	-
5	16.168	0.50	30.87	-	31.37	-	60.00	50.00	-28.63	-
6	21.113	0.60	37.26	-	37.86	-	60.00	50.00	-22.14	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400 / F(kHz)	300
0.490 ~ 1.705	24000 / F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Dec. 29, 2007
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Dec. 01, 2007
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 04, 2008
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-405	Dec. 18, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 16, 2008
Preamplifier Agilent	8449B	3008A1960	Oct. 30, 2007
Preamplifier Agilent	8447D	2944A10631	Oct. 30, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	230128/4	Nov. 14, 2007
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	233233/4	Nov. 14, 2007
Software ADT.	ADT_Radiated_V7.6	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 4.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The IC Site Registration No. is IC4924-4.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

802.11g OFDM MODULATION – SINGLE TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK for 802.11g	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	6.0Mbps	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	171.83	41.25 QP	43.50	-2.25	1.00 H	130	27.55	13.69
2	199.05	40.73 QP	43.50	-2.77	1.50 H	121	29.33	11.40
3	249.60	41.54 QP	46.00	-4.46	1.50 H	97	27.85	13.69
4	296.27	41.40 QP	46.00	-4.60	1.00 H	121	26.74	14.66
5	348.76	40.48 QP	46.00	-5.52	1.00 H	94	24.46	16.02
6	372.09	40.35 QP	46.00	-5.65	1.00 H	106	23.73	16.62
7	409.04	40.46 QP	46.00	-5.54	1.00 H	211	22.84	17.61
8	445.98	43.58 QP	46.00	-2.42	1.50 H	226	24.80	18.78
9	471.25	43.49 QP	46.00	-2.51	1.50 H	235	23.90	19.59
10	496.53	41.66 QP	46.00	-4.34	1.50 H	154	21.24	20.42
11	545.14	44.44 QP	46.00	-1.56	1.50 H	118	22.75	21.69
12	570.41	41.09 QP	46.00	-4.91	1.50 H	109	18.74	22.36
13	619.02	42.94 QP	46.00	-3.06	1.50 H	142	19.37	23.57
14	644.30	40.04 QP	46.00	-5.96	1.00 H	130	15.90	24.14

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK for 802.11g	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	6.0Mbps	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	49.34	35.01 QP	40.00	-4.99	1.00 V	220	20.88	14.13
2	62.95	34.10 QP	40.00	-5.90	1.00 V	10	20.73	13.37
3	148.50	40.74 QP	43.50	-2.76	1.00 V	97	26.09	14.66
4	171.83	41.99 QP	43.50	-1.51	1.00 V	205	28.30	13.69
5	199.05	39.89 QP	43.50	-3.61	1.00 V	91	28.49	11.40
6	420.70	40.48 QP	46.00	-5.52	1.00 V	163	22.50	17.98
7	445.98	44.70 QP	46.00	-1.30	1.00 V	199	25.92	18.78
8	471.25	44.09 QP	46.00	-1.91	1.00 V	244	24.50	19.59
9	494.58	42.27 QP	46.00	-3.73	1.00 V	187	21.92	20.35
10	545.14	42.11 QP	46.00	-3.89	1.00 V	85	20.43	21.69
11	570.41	41.61 QP	46.00	-4.39	1.00 V	61	19.26	22.36
12	595.69	40.68 QP	46.00	-5.32	1.00 V	310	17.66	23.03

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK for draft 802.11n (20MHz)	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	7.2Mbps	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	127.11	38.79 QP	43.50	-4.71	1.50 H	325	26.14	12.65
2	148.50	40.83 QP	43.50	-2.67	1.50 H	145	26.18	14.66
3	348.76	41.34 QP	46.00	-4.66	1.00 H	28	25.32	16.02
4	372.09	42.99 QP	46.00	-3.01	1.50 H	10	26.37	16.62
5	395.43	40.62 QP	46.00	-5.38	1.00 H	172	23.40	17.21
6	445.98	43.11 QP	46.00	-2.89	1.50 H	112	24.34	18.78
7	471.25	40.08 QP	46.00	-5.92	1.50 H	121	20.48	19.59
8	550.97	40.01 QP	46.00	-5.99	1.50 H	202	18.18	21.84
9	595.69	42.47 QP	46.00	-3.53	1.00 H	175	19.44	23.03
10	743.45	44.11 QP	46.00	-1.89	1.00 H	148	18.35	25.75
11	819.28	40.48 QP	46.00	-5.52	1.50 H	10	13.77	26.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	59.06	38.12 QP	40.00	-1.88	1.00 V	43	24.20	13.92
2	171.83	36.00 QP	43.50	-7.50	1.00 V	10	22.30	13.69
3	445.98	38.64 QP	46.00	-7.36	1.00 V	223	19.86	18.78
4	496.53	37.96 QP	46.00	-8.04	1.00 V	145	17.55	20.42
5	743.45	38.34 QP	46.00	-7.66	1.50 V	85	12.58	25.75
6	893.16	42.12 QP	46.00	-3.88	1.00 V	85	14.28	27.85

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK for draft 802.11n (40MHz)	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	15.0Mbps	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.95	37.64 QP	43.50	-5.86	1.50 H	184	24.64	13.00
2	249.60	36.55 QP	46.00	-9.45	1.00 H	268	22.86	13.69
3	296.27	37.48 QP	46.00	-8.52	1.00 H	82	22.82	14.66
4	694.85	37.55 QP	46.00	-8.45	1.00 H	148	12.40	25.15
5	743.45	41.06 QP	46.00	-4.94	1.25 H	181	15.31	25.75
6	893.16	43.36 QP	46.00	-2.64	1.00 H	19	15.51	27.85

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	59.06	36.48 QP	40.00	-3.52	1.25 V	109	22.56	13.92
2	148.50	36.54 QP	43.50	-6.96	1.00 V	118	21.88	14.66
3	445.98	38.24 QP	46.00	-7.76	1.00 V	226	19.46	18.78
4	545.14	36.71 QP	46.00	-9.29	1.50 V	238	15.02	21.69
5	694.85	37.07 QP	46.00	-8.93	1.00 V	10	11.92	25.15
6	893.16	42.18 QP	46.00	-3.82	1.00 V	70	14.34	27.85

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

802.11b DSSS MODULATION – SINGLE TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	1.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	56.56 PK	74.00	-17.44	1.17 H	314	26.08	30.48
2	1608.00	46.50 AV	54.00	-7.50	1.17 H	314	16.02	30.48
3	2390.00	54.65 PK	74.00	-19.35	1.00 H	28	22.21	32.44
4	2390.00	44.58 AV	54.00	-9.42	1.00 H	28	12.14	32.44
5	*2412.00	100.58 PK			1.00 H	32	68.05	32.53
6	*2412.00	96.01 AV			1.00 H	32	63.48	32.53
7	3216.00	47.18 PK	80.58	-33.40	1.05 H	315	12.40	34.78
8	3216.00	39.25 AV	76.01	-36.76	1.05 H	315	4.47	34.78
9	4824.00	50.67 PK	74.00	-23.33	1.01 H	346	11.39	39.28
10	4824.00	39.05 AV	54.00	-14.95	1.01 H	346	-0.23	39.28
11	7236.00	54.25 PK	80.58	-26.33	1.65 H	319	8.35	45.90
12	7236.00	42.38 AV	76.01	-33.63	1.65 H	319	-3.52	45.90

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	1.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	57.53 PK	74.00	-16.47	1.09 V	149	27.05	30.48
2	1608.00	48.53 AV	54.00	-5.47	1.09 V	149	18.05	30.48
3	2390.00	63.58 PK	74.00	-10.42	1.06 V	85	31.14	32.44
4	2390.00	52.06 AV	54.00	-1.94	1.06 V	85	19.62	32.44
5	*2412.00	112.50 PK			1.10 V	173	79.97	32.53
6	*2412.00	107.98 AV			1.10 V	173	75.45	32.53
7	3216.00	49.26 PK	92.50	-43.24	1.03 V	219	14.48	34.78
8	3216.00	41.12 AV	87.98	-46.86	1.03 V	219	6.34	34.78
9	4824.00	51.99 PK	74.00	-22.01	1.30 V	217	12.71	39.28
10	4824.00	44.63 AV	54.00	-9.37	1.30 V	217	5.35	39.28
11	7236.00	56.81 PK	92.50	-35.69	1.74 V	0	10.91	45.90
12	7236.00	44.33 AV	87.98	-43.65	1.74 V	0	-1.57	45.90

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	1.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	45.81 PK	74.00	-28.19	1.31 H	90	15.71	30.10
2	1624.00	39.91 AV	54.00	-14.09	1.31 H	90	9.81	30.10
3	*2437.00	100.02 PK			1.30 H	146	67.61	32.41
4	*2437.00	95.43 AV			1.30 H	146	63.02	32.41
5	3248.00	47.29 PK	80.02	-32.73	1.27 H	93	12.77	34.52
6	3248.00	37.82 AV	75.43	-37.61	1.27 H	93	3.30	34.52
7	4874.00	49.70 PK	74.00	-24.30	1.27 H	165	10.99	38.71
8	4874.00	38.65 AV	54.00	-15.35	1.27 H	165	-0.06	38.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	48.28 PK	74.00	-25.72	1.04 V	56	18.18	30.10
2	1624.00	44.60 AV	54.00	-9.40	1.04 V	56	14.50	30.10
3	*2437.00	111.82 PK			1.11 V	190	79.41	32.41
4	*2437.00	107.39 AV			1.11 V	190	74.98	32.41
5	3248.00	48.11 PK	91.82	-43.71	1.24 V	194	13.59	34.52
6	3248.00	38.80 AV	87.39	-48.59	1.24 V	194	4.28	34.52
7	4874.00	50.56 PK	74.00	-23.44	1.30 V	71	11.85	38.71
8	4874.00	40.28 AV	54.00	-13.72	1.30 V	71	1.57	38.71

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	1.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	56.75 PK	79.08	-22.33	1.22 H	330	26.26	30.49
2	1641.00	46.81 AV	74.52	-27.71	1.22 H	330	16.32	30.49
3	*2462.00	99.08 PK			1.00 H	22	66.32	32.76
4	*2462.00	94.52 AV			1.00 H	22	61.76	32.76
5	2483.50	54.39 PK	74.00	-19.61	1.00 H	55	21.53	32.86
6	2483.50	44.42 AV	54.00	-9.58	1.00 H	55	11.56	32.86
7	3282.00	46.88 PK	79.08	-32.20	1.08 H	122	11.86	35.02
8	3282.00	39.15 AV	74.52	-35.37	1.08 H	122	4.13	35.02
9	4924.00	50.46 PK	74.00	-23.54	1.08 H	316	11.04	39.42
10	4924.00	38.86 AV	54.00	-15.14	1.08 H	316	-0.56	39.42
11	7386.00	54.15 PK	74.00	-19.85	1.52 H	303	8.02	46.13
12	7386.00	42.25 AV	54.00	-11.75	1.52 H	303	-3.88	46.13

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	DBPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	1.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	49.85 PK	91.36	-41.51	1.00 V	25	19.36	30.49
2	1641.00	41.56 AV	86.75	-45.19	1.00 V	25	11.07	30.49
3	*2462.00	111.36 PK			1.14 V	203	78.60	32.76
4	*2462.00	106.75 AV			1.14 V	203	73.99	32.76
5	2483.50	64.54 PK	74.00	-9.46	1.14 V	12	31.68	32.86
6	2483.50	52.94 AV	54.00	-1.06	1.14 V	12	20.08	32.86
7	3282.00	49.85 PK	91.36	-41.51	1.05 V	236	14.83	35.02
8	3282.00	41.56 AV	86.75	-45.19	1.05 V	236	6.54	35.02
9	4924.00	52.34 PK	74.00	-21.66	1.13 V	22	12.92	39.42
10	4924.00	43.78 AV	54.00	-10.22	1.13 V	22	4.36	39.42
11	7386.00	57.22 PK	74.00	-16.78	1.08 V	223	11.09	46.13
12	7386.00	44.69 AV	54.00	-9.31	1.08 V	223	-1.44	46.13

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

802.11g OFDM MODULATION – SINGLE TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	6.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	56.15 PK	74.00	-17.85	1.09 H	303	25.67	30.48
2	1608.00	46.22 AV	54.00	-7.78	1.09 H	303	15.74	30.48
3	2390.00	61.22 PK	74.00	-12.78	1.05 H	315	28.78	32.44
4	2390.00	41.35 AV	54.00	-12.65	1.05 H	315	8.91	32.44
5	*2412.00	96.98 PK			1.03 H	292	64.45	32.53
6	*2412.00	87.02 AV			1.03 H	292	54.49	32.53
7	3216.00	47.02 PK	76.98	-29.96	1.00 H	22	12.24	34.78
8	3216.00	39.05 AV	67.02	-27.97	1.00 H	22	4.27	34.78
9	4824.00	48.52 PK	74.00	-25.48	1.03 H	23	9.24	39.28
10	4824.00	36.02 AV	54.00	-17.98	1.03 H	23	-3.26	39.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	57.12 PK	74.00	-16.88	1.05 V	135	26.64	30.48
2	1608.00	48.21 AV	54.00	-5.79	1.05 V	135	17.73	30.48
3	2390.00	72.85 PK	74.00	-1.15	1.44 V	332	40.41	32.44
4	2390.00	52.79 AV	54.00	-1.21	1.44 V	332	20.35	32.44
5	*2412.00	110.76 PK			1.13 V	337	78.23	32.53
6	*2412.00	100.14 AV			1.13 V	337	67.61	32.53
7	3216.00	49.08 PK	90.76	-41.68	1.05 V	223	14.30	34.78
8	3216.00	40.96 AV	80.14	-39.18	1.05 V	223	6.18	34.78
9	4824.00	49.60 PK	74.00	-24.40	1.08 V	15	10.32	39.28
10	4824.00	37.16 AV	54.00	-16.84	1.08 V	15	-2.12	39.28

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	6.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	40.87 PK	74.00	-33.13	1.23 H	205	10.77	30.10
2	1624.00	28.38 AV	54.00	-25.62	1.23 H	205	-1.72	30.10
3	*2437.00	98.88 PK			1.28 H	55	66.47	32.41
4	*2437.00	89.22 AV			1.28 H	55	56.81	32.41
5	3248.00	48.18 PK	78.88	-30.70	1.00 H	352	13.66	34.52
6	3248.00	39.72 AV	79.22	-39.50	1.00 H	352	5.20	34.52
7	4874.00	49.74 PK	74.00	-24.26	1.00 H	186	11.03	38.71
8	4874.00	35.24 AV	54.00	-18.76	1.00 H	186	-3.47	38.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	42.97 PK	74.00	-31.03	1.00 V	122	12.87	30.10
2	1624.00	34.82 AV	54.00	-19.18	1.00 V	122	4.72	30.10
3	*2437.00	112.11 PK			1.38 V	190	79.70	32.41
4	*2437.00	102.41 AV			1.38 V	190	70.00	32.41
5	3248.00	48.89 PK	92.11	-43.22	1.00 V	70	14.37	34.52
6	3248.00	41.04 AV	82.41	-41.37	1.00 V	70	6.52	34.52
7	4874.00	48.78 PK	74.00	-25.22	1.05 V	127	10.07	38.71
8	4874.00	35.27 AV	54.00	-18.73	1.05 V	127	-3.44	38.71

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	6.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 67% RH, 991hPa	TESTED BY	Morgan Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	59.85 PK	76.85	-17.00	1.05 H	313	29.36	30.49
2	1641.00	45.97 AV	67.01	-21.04	1.05 H	313	15.48	30.49
3	*2462.00	96.85 PK			1.08 H	265	64.09	32.76
4	*2462.00	87.01 AV			1.08 H	265	54.25	32.76
5	2483.50	60.15 PK	74.00	-13.85	1.08 H	303	27.29	32.86
6	2483.50	40.40 AV	54.00	-13.60	1.08 H	303	7.54	32.86
7	3282.00	46.98 PK	76.85	-29.87	1.05 H	233	11.96	35.02
8	3282.00	38.91 AV	67.01	-28.10	1.05 H	233	3.89	35.02
9	4924.00	48.65 PK	74.00	-25.35	1.08 H	5	9.23	39.42
10	4924.00	36.18 AV	54.00	-17.82	1.08 H	5	-3.24	39.42

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	56.89 PK	90.91	-34.02	1.08 V	143	26.40	30.49
2	1641.00	48.12 AV	80.21	-32.09	1.08 V	143	17.63	30.49
3	*2462.00	110.91 PK			1.16 V	349	78.15	32.76
4	*2462.00	100.21 AV			1.16 V	349	67.45	32.76
5	2483.50	71.54 PK	74.00	-2.46	1.00 V	19	38.68	32.86
6	2483.50	52.69 AV	54.00	-1.31	1.00 V	19	19.83	32.86
7	3282.00	49.45 PK	90.91	-41.46	1.08 V	233	14.43	35.02
8	3282.00	40.55 AV	80.21	-39.66	1.08 V	233	5.53	35.02
9	4924.00	49.25 PK	74.00	-24.75	1.05 V	13	9.83	39.42
10	4924.00	37.02 AV	54.00	-16.98	1.05 V	13	-2.40	39.42

- REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	7.2Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	58.11 PK	74.00	-15.89	1.01 H	27	28.03	30.08
2	1608.00	44.36 AV	54.00	-9.64	1.01 H	27	14.28	30.08
3	2390.00	60.13 PK	74.00	-13.87	1.16 H	320	27.90	32.23
4	2390.00	43.85 AV	54.00	-10.15	1.16 H	320	11.62	32.23
5	*2412.00	102.85 PK			1.16 H	320	70.54	32.31
6	*2412.00	93.11 AV			1.16 H	320	60.80	32.31
7	4824.00	50.31 PK	74.00	-23.69	1.29 H	304	11.74	38.57
8	4824.00	38.04 AV	54.00	-15.96	1.29 H	304	-0.53	38.57

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1608.00	55.61 PK	74.00	-18.39	1.09 V	218	25.53	30.08
2	1608.00	47.02 AV	54.00	-6.98	1.09 V	218	16.94	30.08
3	2390.00	68.75 PK	74.00	-5.25	1.00 V	176	36.52	32.23
4	2390.00	52.19 AV	54.00	-1.81	1.00 V	176	19.96	32.23
5	*2412.00	111.56 PK			1.00 V	176	79.25	32.31
6	*2412.00	101.74 AV			1.00 V	176	69.43	32.31
7	4824.00	50.60 PK	74.00	-23.40	1.12 V	93	12.03	38.57
8	4824.00	38.95 AV	54.00	-15.05	1.12 V	93	0.38	38.57

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	7.2Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	58.11 PK	74.00	-15.89	1.18 H	66	28.01	30.10
2	1624.00	44.32 AV	54.00	-9.68	1.18 H	66	14.22	30.10
3	*2437.00	104.45 PK			1.16 H	320	72.04	32.41
4	*2437.00	94.68 AV			1.16 H	320	62.27	32.41
5	4874.00	50.13 PK	74.00	-23.87	1.12 H	57	11.42	38.71
6	4874.00	37.85 AV	54.00	-16.15	1.12 H	57	-0.86	38.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	55.96 PK	74.00	-18.04	1.11 V	229	25.86	30.10
2	1624.00	47.35 AV	54.00	-6.65	1.11 V	229	17.25	30.10
3	*2437.00	113.40 PK			1.01 V	176	80.99	32.41
4	*2437.00	103.65 AV			1.01 V	176	71.24	32.41
5	2488.00	64.13 PK	74.00	-9.87	1.23 V	157	31.53	32.60
6	2488.00	52.57 AV	54.00	-1.43	1.23 V	157	19.97	32.60
7	4874.00	50.96 PK	74.00	-23.04	1.18 V	26	12.25	38.71
8	4874.00	39.31 AV	54.00	-14.69	1.18 V	26	0.60	38.71

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	7.2Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	58.23 PK	83.12	-24.89	1.09 H	256	28.10	30.13
2	1641.00	44.48 AV	73.42	-28.94	1.09 H	256	14.35	30.13
3	*2462.00	103.12 PK			1.15 H	316	70.62	32.50
4	*2462.00	93.42 AV			1.15 H	316	60.92	32.50
5	2483.50	59.95 PK	74.00	-14.05	1.15 H	316	27.37	32.58
6	2483.50	43.60 AV	54.00	-10.40	1.15 H	316	11.02	32.58
7	4924.00	50.42 PK	74.00	-23.58	1.12 H	54	11.58	38.84
8	4924.00	38.15 AV	54.00	-15.85	1.12 H	54	-0.69	38.84

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1641.00	55.82 PK	92.09	-36.27	1.06 V	214	25.69	30.13
2	1641.00	47.23 AV	82.39	-35.16	1.06 V	214	17.10	30.13
3	*2462.00	112.09 PK			1.00 V	177	79.59	32.50
4	*2462.00	102.39 AV			1.00 V	177	69.89	32.50
5	2483.50	68.89 PK	74.00	-5.11	1.00 V	165	36.31	32.58
6	2483.50	52.41 AV	54.00	-1.59	1.00 V	165	19.83	32.58
7	4924.00	50.72 PK	74.00	-23.28	1.18 V	64	11.88	38.84
8	4924.00	39.07 AV	54.00	-14.93	1.18 V	64	0.23	38.84

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * “: Fundamental frequency.

DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	15.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1614.00	56.24 PK	74.00	-17.76	1.11 H	39	26.15	30.09
2	1614.00	42.45 AV	54.00	-11.55	1.11 H	39	12.36	30.09
3	2390.00	52.89 PK	74.00	-21.11	1.01 H	238	20.66	32.23
4	2390.00	42.05 AV	54.00	-11.95	1.01 H	238	9.82	32.23
5	*2422.00	98.75 PK			1.01 H	238	66.40	32.35
6	*2422.00	86.51 AV			1.01 H	238	54.16	32.35
7	4844.00	48.36 PK	74.00	-25.64	1.12 H	54	9.73	38.63
8	4844.00	36.82 AV	54.00	-17.18	1.12 H	54	-1.81	38.63

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1614.00	53.62 PK	74.00	-20.38	1.08 V	69	23.53	30.09
2	1614.00	45.01 AV	54.00	-8.99	1.08 V	69	14.92	30.09
3	2390.00	62.69 PK	74.00	-11.31	1.01 V	209	30.46	32.23
4	2390.00	52.12 AV	54.00	-1.88	1.01 V	209	19.89	32.23
5	*2422.00	109.02 PK			1.01 V	209	76.67	32.35
6	*2422.00	97.13 AV			1.01 V	209	64.78	32.35
7	4844.00	48.95 PK	74.00	-25.05	1.04 V	68	10.32	38.63
8	4844.00	37.41 AV	54.00	-16.59	1.04 V	68	-1.22	38.63

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247.
6. “ * “: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	15.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	56.87 PK	74.00	-17.13	1.19 H	52	26.77	30.10
2	1624.00	42.95 AV	54.00	-11.05	1.19 H	52	12.85	30.10
3	*2437.00	100.96 PK			1.03 H	241	68.55	32.41
4	*2437.00	88.72 AV			1.03 H	241	56.31	32.41
5	4874.00	48.95 PK	74.00	-25.05	1.19 H	65	10.24	38.71
6	4874.00	37.42 AV	54.00	-16.58	1.19 H	65	-1.29	38.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1624.00	53.86 PK	74.00	-20.14	1.22 V	59	23.76	30.10
2	1624.00	45.14 AV	54.00	-8.86	1.22 V	59	15.04	30.10
3	2390.00	62.54 PK	74.00	-11.46	1.02 V	210	30.31	32.23
4	2390.00	51.96 AV	54.00	-2.04	1.02 V	210	19.73	32.23
5	*2437.00	111.13 PK			1.02 V	210	78.72	32.41
6	*2437.00	99.24 AV			1.02 V	210	66.83	32.41
7	4874.00	49.19 PK	74.00	-24.81	1.15 V	68	10.48	38.71
8	4874.00	37.96 AV	54.00	-16.04	1.15 V	68	-0.75	38.71

REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * ”: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 7	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TRANSFER RATE	15.0Mbps	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 63% RH, 991hPa	TESTED BY	Brad Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1634.00	56.02 PK	78.88	-22.86	1.18 H	59	25.90	30.12
2	1634.00	42.11 AV	66.65	-24.54	1.18 H	59	11.99	30.12
3	*2452.00	98.88 PK			1.00 H	236	66.42	32.46
4	*2452.00	86.65 AV			1.00 H	236	54.19	32.46
5	2483.50	52.76 PK	74.00	-21.24	1.00 H	236	20.18	32.58
6	2483.50	41.95 AV	54.00	-12.05	1.00 H	236	9.37	32.58
7	4904.00	48.21 PK	74.00	-25.79	1.19 H	62	9.42	38.79
8	4904.00	36.59 AV	54.00	-17.41	1.19 H	62	-2.20	38.79

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1634.00	53.81 PK	89.13	-35.32	1.12 V	34	23.69	30.12
2	1634.00	45.16 AV	77.26	-32.10	1.12 V	34	15.04	30.12
3	*2452.00	109.13 PK			1.00 V	205	76.67	32.46
4	*2452.00	97.26 AV			1.00 V	205	64.80	32.46
5	2483.50	62.48 PK	74.00	-11.52	1.00 V	189	29.90	32.58
6	2483.50	51.80 AV	54.00	-2.20	1.00 V	189	19.22	32.58
7	4904.00	48.67 PK	74.00	-25.33	1.12 V	59	9.88	38.79
8	4904.00	37.02 AV	54.00	-16.98	1.12 V	59	-1.77	38.79

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247.
 6. “ * ”: Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 TEST RESULTS

802.11b DSSS MODULATION – SINGLE TX:


MODULATION TYPE	DBPSK	TRANSFER RATE	1.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.40	0.5	PASS
6	2437	12.44	0.5	PASS
11	2462	12.40	0.5	PASS


CH 1



CH 6



CH 11




802.11g OFDM MODULATION – SINGLE TX:


MODULATION TYPE	BPSK	TRANSFER RATE	6.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.60	0.5	PASS
6	2437	16.64	0.5	PASS
11	2462	16.56	0.5	PASS


CH 1



CH 6



CH 11




DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:


MODULATION TYPE	BPSK	TRANSFER RATE	7.2Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2412	17.68	17.72	0.5	PASS
6	2437	17.64	17.68	0.5	PASS
11	2462	17.68	17.64	0.5	PASS


FOR CHAIN 0: CH 1




CH 6




CH 11




FOR CHAIN 1: CH 1



CH 6



CH 11




DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:


MODULATION TYPE	BPSK	TRANSFER RATE	15.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN 0	CHAIN 1		
1	2422	27.84	27.68	0.5	PASS
4	2437	28.88	28.00	0.5	PASS
7	2452	28.24	28.64	0.5	PASS


FOR CHAIN 0: CH 1




CH 4




CH 7



FOR CHAIN 1: CH 1



CH 4



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP 40	100040	Jun. 07, 2007
ANRITSU SYNTHESIZED SIGNAL GENERATOR	68247B	984703	May 08, 2007
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Nov. 28, 2007
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION – SINGLE TX:

MODULATION TYPE	DBPSK	TRANSFER RATE	1.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	81.096	19.09	30	PASS
6	2437	100.925	20.04	30	PASS
11	2462	101.158	20.05	30	PASS

802.11g OFDM MODULATION – SINGLE TX:

MODULATION TYPE	BPSK	TRANSFER RATE	6.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	64.269	18.08	30	PASS
6	2437	90.573	19.57	30	PASS
11	2462	63.973	18.06	30	PASS

DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

MODULATION TYPE	BPSK	TRANSFER RATE	7.2Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)		PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	41.400	39.902	16.17	16.01	81.302	19.10	30	PASS
6	2437	64.714	63.680	18.11	18.04	128.394	21.09	30	PASS
11	2462	41.305	40.179	16.16	16.04	81.484	19.11	30	PASS

DRAFT 802.11n (40MHz) OFDM MODULATION – DUAL TX:

MODULATION TYPE	BPSK	TRANSFER RATE	15.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHAN.	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)		PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2422	25.527	25.177	14.07	14.01	50.704	17.05	30	PASS
4	2437	40.926	39.994	16.12	16.02	80.921	19.08	30	PASS
7	2452	25.586	25.177	14.08	14.01	50.763	17.06	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSP 40	100040	Jun. 07, 2007

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6


4.5.7 TEST RESULTS

802.11b DSSS MODULATION – SINGLE TX:


MODULATION TYPE	DBPSK	TRANSFER RATE	1.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-11.39	8	PASS
6	2437	-11.23	8	PASS
11	2462	-12.19	8	PASS


CH 1



CH 6



CH 11




802.11g OFDM MODULATION – SINGLE TX:

MODULATION TYPE	BPSK	TRANSFER RATE	6.0Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-14.09	8	PASS
6	2437	-12.75	8	PASS
11	2462	-14.07	8	PASS

CH 1



DRAFT 802.11n (20MHz) OFDM MODULATION – DUAL TX:

MODULATION TYPE	BPSK	TRANSFER RATE	7.2Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg.C, 63% RH, 991hPa
TESTED BY	Long Chen		

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (mW)		RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (mW)	TOTAL POWER DENSITY (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1				
1	2412	0.022	0.020	-16.67	-16.95	0.042	-13.80	8	PASS
6	2437	0.036	0.033	-14.44	-14.88	0.068	-11.64	8	PASS
11	2462	0.021	0.022	-16.84	-16.63	0.042	-13.72	8	PASS

FOR CHAIN 0: CH 1

