


Vertical



	Freq	Level	Over	Limit	ReadAntenna	Preamp	Cable		Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	deg	cm
1	47.460	37.95	-2.05	40.00	56.07	8.98	27.80	0.70	QP	328
2	132.820	37.80	-5.70	43.50	52.53	11.37	27.43	1.33	Peak	0
3	265.710	36.71	-9.29	46.00	49.27	12.45	26.97	1.96	Peak	0
4	400.540	32.98	-13.02	46.00	42.34	15.95	27.61	2.31	Peak	0
5	479.110	32.79	-13.21	46.00	41.05	17.07	27.99	2.66	Peak	0
6	699.300	41.22	-4.78	46.00	46.62	19.30	28.00	3.30	Peak	0

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 20MHz Ch 1 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1	3216.000	33.28	-20.72	54.00	34.77	30.00	3.63	35.12	AVERAGE	100	HORIZONTAL
2	3216.340	43.97	-30.03	74.00	45.46	30.00	3.63	35.12	PEAK	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3215.960	43.90	-30.10	74.00	45.39	30.00	3.63	35.12	PEAK	100	VERTICAL
2 @	3216.000	35.05	-18.95	54.00	36.54	30.00	3.63	35.12	AVERAGE	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 20MHz Ch 6 Ant. A + Ant. B

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm
1	3249.280	33.23	-20.77	54.00	34.71	30.00	3.64	35.12	AVERAGE	100 HORIZONTAL
2	3249.380	44.09	-29.91	74.00	45.57	30.00	3.64	35.12	PEAK	100 HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1 @	3249.260	35.54	-18.46	54.00	37.01	30.00	3.64	35.12	AVERAGE	100	VERTICAL
2	3249.840	44.34	-29.66	74.00	45.82	30.00	3.64	35.12	PEAK	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 20MHz Ch11 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1 @	3282.660	34.98	-19.02	54.00	36.45	30.00	3.66	35.12	AVERAGE	100	HORIZONTAL
2	3282.660	44.61	-29.39	74.00	46.07	30.00	3.66	35.12	PEAK	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3282.540	45.95	-28.05	74.00	47.42	30.00	3.66	35.12	PEAK	100	VERTICAL
2 @	3282.640	38.29	-15.71	54.00	39.76	30.00	3.66	35.12	AVERAGE	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 40MHz Ch 3 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1	4838.000	33.15	-20.85	54.00	29.28	33.09	5.94	35.16	AVERAGE	100	HORIZONTAL
2	4838.000	44.60	-29.40	74.00	40.74	33.09	5.94	35.16	PEAK	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3229.280	44.43	-29.57	74.00	45.92	30.00	3.63	35.12	PEAK	100	VERTICAL
2 @	3229.300	36.35	-17.65	54.00	37.84	30.00	3.63	35.12	AVERAGE	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 40MHz Ch 6 Ant. A + Ant. B

Horizontal



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp		Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos Pol/Phase
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm
1	3249.280	33.71	-20.29	54.00	35.19	30.00	3.64	35.12	AVERAGE	100 HORIZONTAL
2	3249.860	44.10	-29.90	74.00	45.58	30.00	3.64	35.12	PEAK	100 HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBUV	dB/m	dB	dB		cm	
1 @	3249.260	36.19	-17.81	54.00	37.67	30.00	3.64	35.12	AVERAGE	100	VERTICAL
2	3249.680	44.07	-29.93	74.00	45.55	30.00	3.64	35.12	PEAK	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	Draft n MCS8 40MHz Ch 9 Ant. A + Ant. B

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3269.180	44.98	-29.02	74.00	46.44	30.00	3.66	35.12	PEAK	100	HORIZONTAL
2 @	3269.340	34.74	-19.26	54.00	36.21	30.00	3.66	35.12	AVERAGE	100	HORIZONTAL

Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1 @	3269.340	39.09	-14.91	54.00	40.55	30.00	3.66	35.12	AVERAGE	100	VERTICAL
2	3269.460	45.74	-28.26	74.00	47.20	30.00	3.66	35.12	PEAK	100	VERTICAL

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	802.11b CH 1 Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1	3215.960	32.85	-21.15	54.00	34.34	30.00	3.63	35.12	AVERAGE	100	HORIZONTAL
2	3216.400	44.44	-29.56	74.00	45.94	30.00	3.63	35.12	PEAK	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3215.860	44.97	-29.03	74.00	46.46	30.00	3.63	35.12	PEAK	100	VERTICAL
2 @	3220.840	42.49	-11.51	54.00	43.98	30.00	3.63	35.12	AVERAGE	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	802.11b CH 6 Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1	3249.280	33.40	-20.60	54.00	34.88	30.00	3.64	35.12	AVERAGE	100	HORIZONTAL
2	3249.380	43.46	-30.54	74.00	44.93	30.00	3.64	35.12	PEAK	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1 @	3249.280	34.82	-19.18	54.00	36.30	30.00	3.64	35.12	AVERAGE	100	VERTICAL
2	3249.520	44.22	-29.78	74.00	45.70	30.00	3.64	35.12	PEAK	100	VERTICAL


Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	802.11b CH 11 Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	
1	3282.600	44.57	-29.43	74.00	46.03	30.00	3.66	35.12	PEAK	100	HORIZONTAL
2	3282.640	34.66	-19.34	54.00	36.13	30.00	3.66	35.12	AVERAGE	100	HORIZONTAL


Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1 @	3282.640	39.38	-14.62	54.00	40.84	30.00	3.66	35.12	AVERAGE	100	VERTICAL
2	3282.880	45.37	-28.63	74.00	46.84	30.00	3.66	35.12	PEAK	100	VERTICAL

Temperature	24°C	Humidity	61%
Test Engineer	Aric Lee	Configurations	802.11g CH 1 Ant. A

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier Factor	Remark	Ant Pos	Pol/Phase
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB		cm	
1	3215.860	43.31	-30.69	74.00	44.80	30.00	3.63	35.12	PEAK	100	HORIZONTAL
2	3216.000	32.62	-21.38	54.00	34.11	30.00	3.63	35.12	AVERAGE	100	HORIZONTAL