

MAXIMUM PERMISSIBLE EXPOSURE FOR SUBPART C 2.4 GHz BAND**Calculations**

EUT Power density at the specific separation:

$$S_1 = PG_1 / (4 \pi R^2)$$
$$S_1 = (562.341 * 2.75) / (4 * \pi * 20^2)$$
$$S_1 = 0.307654 \text{ mW/cm}^2 \text{ (at 20 cm)}$$
$$\text{Limit} = 1 \text{ mW/cm}^2$$

Internal Approved Modals Power density at the specific separation:

$$S_2 = PG_2 / (4 \pi R^2)$$
$$S_2 = (95.499 * 1.12) / (4 * \pi * 20^2)$$
$$S_2 = 0.021279 \text{ mW/cm}^2 \text{ (at 20 cm)}$$
$$\text{Limit} = 1 \text{ mW/cm}^2$$

Combine Power density at the specific separation:

$$S_T = S_1 / \text{LPD} + S_2 / \text{LPD}$$
$$S_T = (0.307654 / 1) + (0.021279 / 1)$$
$$S_T = 0.328933 \text{ mW/cm}^2 \text{ (at 20 cm)}$$
$$\text{Limit} = 1 \text{ mW/cm}^2$$

Where

S_1 = DAC-0 Maximum power density (mW/cm²)
 S_2 = Zigbee Maximum power density (mW/cm²)
 S_T = Total Maximum power density (mW/cm²)
 P = Power input to the antenna (mW)
 G_1 = DAC-0 Numeric power gain of the antenna
 G_2 = Zigbee Numeric power gain of the antenna
 R = distance to the center of the radiation of the antenna (20 cm = limit for MPE)
 LPD = Limit of power density

The maximum permissible exposure (MPE) for the general population is 1 mW/cm².

The power density at 20 cm does not exceed the 1 mW/cm². Therefore, the exposure condition is compliant with FCC rules.

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

$$G_1 = \text{Log-1 (dB antenna gain/10)}$$
$$G_1 = \text{Log-1 (4.4 dBi/10)}$$
$$G_1 = 2.75$$

$$G_2 = \text{Log-1 (dB antenna gain/10)}$$
$$G_2 = \text{Log-1 (.5 dBi/10)}$$
$$G_2 = 1.12$$