

FCC PART 15 SUBPART C  
EMI MEASUREMENT AND TEST REPORT


For

**BELKIN CORPORATION**

501W WALNUT STREET  
COMPTON, CA90220

**FCC ID: K7SF8E825-USB**

2003-11-07

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Mini Wireless Optical Mouse, ITE
<b>Test Engineer:</b> Ling Zhang / 	
<b>Report No.:</b> R0309301(T)	
<b>Test Date:</b> 2003-10-03	
<b>Reviewed By:</b> Ming Jing / 	
<b>Prepared By:</b> Bay Area Compliance Laboratory Corporation 230 Commercial Street Sunnyvale, CA 94085 Tel: (408) 732-9162 Fax: (408) 732-9164	

**Note:** This test report is specially limited to the above client company and product model only. It may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

**TABLE OF CONTENTS**

**1 - GENERAL INFORMATION.....3**

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

1.2 OBJECTIVE .....3

1.3 RELATED SUBMITTAL(S)/GRANT(S).....3

1.4 TEST METHODOLOGY .....3

1.5 TEST FACILITY .....3

**2 - SYSTEM TEST CONFIGURATION.....5**

2.1 JUSTIFICATION .....5

2.2 SCHEMATICS AND BLOCK DIAGRAM .....5

2.3 EQUIPMENT MODIFICATIONS .....5

2.4 TEST SETUP CONFIGURATION .....5

**3 - SUMMARY OF TEST RESULTS.....6**

**4 - RADIATED EMISSIONS TEST .....7**

4.1 MEASUREMENT UNCERTAINTY .....7

4.2 EUT SETUP .....7

4.3 SPECTRUM ANALYZER SETUP .....7

4.4 TEST EQUIPMENT LIST AND DETAILS .....7

4.5 TEST PROCEDURE .....8

4.6 CORRECTED AMPLITUDE & MARGIN CALCULATION .....8

4.7 SUMMARY OF TEST RESULTS .....8

4.8 RADIATED EMISSIONS TEST RESULT DATA .....9

4.9 BAND EDGE .....10

4.10 OCCUPIED BANDWIDTH .....11

**5 - CONDUCTED EMISSIONS.....12**

---

## 1 - GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

The *BELKIN CORPORATION*'s product, model *F8E825-USB* or the "EUT" as referred to in this report is a Mini Wireless Optical Mouse. The EUT is measured approximately 3.5" L x 1.7" W x 1.1" H.

*\* The test data gathered are from production sample, serial number: 20339, provided by the manufacturer.*

### 1.2 Objective

This Type approval report is prepared on behalf of *BELKIN CORPORATION* in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine compliance with FCC rules, sec 15.209 and sec 15.227.

### 1.3 Related Submittal(s)/Grant(s)

No Related Submittals.

### 1.4 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2001, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### 1.5 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Sunnyvale, California, USA.

Test site at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2001.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-1298 and R-1234. The test site has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices, CISPR 22: 1997, and AS/NZS 3548: Electromagnetic Interference - Limits and Methods of Measurement of Information Technology Equipment test methods under NVLAP Lab Code 200167-0.

## **2 - SYSTEM TEST CONFIGURATION**

---

### **2.1 Justification**

The EUT was configured for testing according to ANSI C63.4-2001.

### **2.2 Schematics and Block Diagram**

Please refer to Appendix D.

### **2.3 Equipment Modifications**

No modifications were made to the EUT.

### **2.4 Test Setup Configuration**

#### **Test Setup for Transmitter**



EUT

---

**3 - SUMMARY OF TEST RESULTS**

---

FCC RULES	DESCRIPTION OF TEST	RESULT
§ 15.203	Antenna requirement	Compliant
§ 15.227 (b)	Occupied Bandwidth	Compliant
§ 15.205 § 15.209 § 15.227 (a)	Restricted Band Radiated Emission Field Strength	Compliant

## 4 - RADIATED EMISSIONS TEST

### 4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is  $\pm 4.0$  dB.

### 4.2 EUT Setup

The radiated emission tests were performed in the open area 10-meter test site, using the setup accordance with the ANSI C63.4-2001. The specification used was the FCC Part 15 Subpart C limits.

The spacing between the peripherals was 10 cm.

External I/O cables are draped over edge of test table or bundled as required.

The notebook PC was connected to a 120Vac/60Hz power source.

### 4.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR 15.33, the EUT was tested to 1000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency ..... 27 MHz  
 Stop Frequency ..... 1000 MHz  
 Sweep Speed ..... Auto  
 IF Bandwidth ..... 100 kHz  
 Video Bandwidth ..... 100kHz  
 Quasi-Peak Adapter Bandwidth..... 120 kHz  
 Quasi-Peak Adapter Mode ..... Normal  
 Resolution Bandwidth..... 100kHz

### 4.4 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2601A02165	2004-01-07
HP	Amplifier	8447E	2944A10187	2004-09-23
HP	Quasi-Peak Adapter	85650A	3019A05393	2004-06-13
EMCO	Biconical Antenna	3110B	9309-1165	2004-10-11
EMCO	Log Periodic Antenna	3146	2101	2004-10-11

\* **Statement of Traceability:** BACL Corp. certifies that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

#### 4.5 Test Procedure

For the radiated emissions test, the power cord of the host system and all support equipment were connected to the AC floor outlet.

Maximizing procedure was performed on the six (6) highest emissions in the described configurations.

All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB $\mu$ V of specification limits), and are distinguished with a "Qp" in the data table.

#### 4.6 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

#### 4.7 Summary of Test Results

According to the final data in section 4.8, the EUT complied with the FCC 15.227 and FCC 15.209 standards, and had the worst margin of:

**-8.1 dB at 54.29 MHz** in the **Vertical** polarization, 27-1000MHz, 3 meters, transmitter

**4.8 Radiated Emissions Test Result Data**

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	FCC SUBPART C	
Frequency MHz	Ampl. dB $\mu$ V/m	Angle Degree	Height Meter	Polar H/V	Antenna dB $\mu$ V/m	Cable dB	Amp. dB	Corr. Ampl. dB $\mu$ V/m	Limit dB $\mu$ V/ m	Margin dB
Transmitter										
54.29	45.7	15	1.4	V	10.2	1.0	25.0	31.9	40	-8.1 PEAK
54.29	44.9	0	1.2	H	10.2	1.0	25.0	31.1	40	-8.9 PEAK
81.44	42.3	330	1.3	H	9.5	1.2	25.0	28.0	40	-12.0 PEAK
81.44	41.2	0	1.2	H	9.5	1.2	25.0	26.9	40	-13.1 PEAK
27.15	57.7	0	1.2	V	15.3	0.8	25.0	48.8	80	-31.2 FUND/AVE
27.15	49.8	0	1.2	H	15.3	0.8	25.0	40.9	80	-39.1 FUND/AVE
27.15	65.0	0	1.2	V	15.3	0.8	25.0	56.1	100	-43.9 FUND/PEAK
27.15	57.2	0	1.2	H	15.3	0.8	25.0	48.3	100	-51.7 FUND/PEAK

The mouse transmitter was placed in continuous transmit mode for all tests.





## **5 - CONDUCTED EMISSIONS**

---

Not Applicable Due to Battery Operation.