



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	Belkin International, Inc.
Applicant Address	12045 East Waterfront Drive, Playa Vista, CA 90094
FCC ID	K7SF9K1001V5

Product Name	N150 Wireless N Router
Brand Name	Belkin
Model Name	F9K1001V5
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Sep. 11, 2012
Final Test Date	Nov. 23, 2012
Submission Type	Original Equipment



### Statement

**Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v02 and KDB 662911 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes.....	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units .....	7
3.8. Table for Parameters of Test Software Setting .....	8
3.9. Test Configurations .....	9
<b>4. TEST RESULT .....</b>	<b>12</b>
4.1. AC Power Line Conducted Emissions Measurement.....	12
4.2. Maximum Conducted Output Power Measurement.....	18
4.3. Power Spectral Density Measurement .....	21
4.4. 6dB Spectrum Bandwidth Measurement .....	28
4.5. Radiated Emissions Measurement .....	33
4.6. Band Edge Emissions Measurement .....	50
4.7. Antenna Requirements .....	60
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>61</b>
<b>6. TEST LOCATION.....</b>	<b>63</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>64</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT .....</b>	<b>A1 ~ A12</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B5</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>C1 ~ C3</b>





## 1. CERTIFICATE OF COMPLIANCE

Product Name : N150 Wireless N Router  
Brand Name : Belkin  
Model Name : F9K1001V5  
Applicant : Belkin International, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Sep. 11, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao' is written over a horizontal line.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	8.62 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	9.1 dB
4.3	15.247(e)	Power Spectral Density	Complies	13.37 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.19 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.09 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 16.96 MHz
Maximum Conducted Output Power	MCS0 (20MHz): 20.90 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 1RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 10.16 MHz ; 11g: 16.72 MHz
Maximum Conducted Output Power	11b: 18.09 dBm ; 11g: 20.33 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Single (TX)	Two (TX)
Band width Mode	20 MHz	20 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	X	V

**IEEE 802.11n spec**

MCS Index	Nss	Modulation	R	NBPS	NCBPS	NDBPS	Datarate(Mbps)	
							800nsGI	400nsGI
							20MHz	20MHz
0	1	BPSK	1/2	1	52	26	6.5	7.200
1	1	QPSK	1/2	2	104	52	13.0	14.400
2	1	QPSK	3/4	2	104	78	19.5	21.700
3	1	16-QAM	1/2	4	208	104	26.0	28.900
4	1	16-QAM	3/4	4	208	156	39.0	43.300
5	1	64-QAM	2/3	6	312	208	52.0	57.800
6	1	64-QAM	3/4	6	312	234	58.5	65.000
7	1	64-QAM	5/6	6	312	260	65.0	72.200
8	2	BPSK	1/2	1	104	52	13.0	14.444
9	2	QPSK	1/2	2	208	104	26.0	28.889
10	2	QPSK	3/4	2	208	156	39.0	43.333
11	2	16-QAM	1/2	4	416	208	52.0	57.778
12	2	16-QAM	3/4	4	416	312	78.0	86.667
13	2	64-QAM	2/3	6	624	416	104.0	115.556
14	2	64-QAM	3/4	6	624	468	117.0	130.000
15	2	64-QAM	5/6	6	624	520	130.0	144.444

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPS	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	Belkin	MT12-Y090100-A1	INPUT: 120V~60Hz, 0.3A OUTPUT: 9V, 1.0A
Adapter 2	Belkin	DSA-9PFB-09 FUS 090100	INPUT: 100-120V~50/60Hz, 0.3A OUTPUT: +9, 1A

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Arcadyan	-	PIFA Antenna	N/A	1.4	TX/RX
2	Arcadyan	-	Printed Antenna	N/A	1.6	TX/RX

Note: The EUT has two antennas (2TX, 2RX).

**For IEEE 802.11b mode (1TX/1RX):**

Ant. 1 was fixed to use as transmitting antenna.


**For IEEE 802.11g mode (1TX/1RX):**

Ant. 1 and Ant. 2 could transmit/receive diversity function.

Ant. 1 generated the worst test result, so it was worse case.

**For IEEE 802.11n mode (2TX/2RX):**

Ant. 1 and Ant. 2 will transmit/receive the signal simultaneously.



### 3.4. Table for Carrier Frequencies

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Power Spectral Density	MCS0/20MHz	7.2 Mbps	1/6/11	1/2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	11b/BPSK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	1/11	1+2
	11b/BPSK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1

The following test modes were performed for all tests:

**For Conducted Emission test:**

Mode 1.: Adapter 1 (Leader MT12-Y090100-A1)

Mode 2.: Adapter 2 (DVE DSA-9PFB-09 FUS 090100)

**For Radiated Emission test:**

Mode 1.: Adapter 1 (Leader MT12-Y090100-A1)

Mode 2.: Adapter 2 (DVE DSA-9PFB-09 FUS 090100)

**<For MPE and Co-location Test>:**

The EUT could be applied with 2.4GHz WLAN function ; therefore Maximum Permissible Exposure (Please refer to Appendix C).

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	M1330	E2KWM3945ABG

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n

Test Software Version	Hyper Terminal		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	50	71	52

#### Power Parameters of IEEE 802.11b/g


Test Software Version	Hyper Terminal		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	70	68	68
IEEE 802.11g	48	77	52

During the test, "Hyper Terminal" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

### 3.9. Test Configurations


#### 3.9.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz




Item	Connection	Shield	Length
1	Power cable	No	1.45m
2	RJ-45 cable*3	No	1.50m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m

Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.45m
2	RJ-45 cable	No	10m

### 3.9.2. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power Cable	No	1.45m
2	RJ-45 Cable	No	10m
3	RJ-45 Cable	No	10m
4	RJ-45 Cable	No	0.6m
5	RJ-45 Cable	No	0.6m
6	RJ-45 Cable	No	0.6m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.




Temperature	21°C	Humidity	63%
Test Engineer	Ryo Fan	Phase	Line
Configuration	Normal Link / Mode 1 / Adapter 1 (Leader MT12-Y090100-A1)		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.18443	53.52	-10.76	64.28	53.17	0.15	0.20	LINE	QP
2	0.18443	39.50	-14.78	54.28	39.15	0.15	0.20	LINE	AVERAGE
3	0.23162	37.02	-15.37	52.39	36.67	0.15	0.20	LINE	AVERAGE
4	0.23162	50.29	-12.10	62.39	49.94	0.15	0.20	LINE	QP
5	0.25888	50.19	-11.28	61.47	49.84	0.15	0.20	LINE	QP
6	0.25888	39.43	-12.04	51.47	39.08	0.15	0.20	LINE	AVERAGE
7	0.29555	32.44	-17.93	50.37	32.09	0.15	0.20	LINE	AVERAGE
8	0.29555	46.42	-13.95	60.37	46.07	0.15	0.20	LINE	QP
9	0.38724	46.73	-11.39	58.12	46.38	0.15	0.20	LINE	QP
10	0.38724	34.79	-13.33	48.12	34.44	0.15	0.20	LINE	AVERAGE
11	0.41705	34.30	-13.21	47.51	33.95	0.15	0.20	LINE	AVERAGE
12	0.41705	43.04	-14.47	57.51	42.69	0.15	0.20	LINE	QP
13	0.51278	46.95	-9.05	56.00	46.60	0.15	0.20	LINE	QP
14	0.51278	35.44	-10.56	46.00	35.09	0.15	0.20	LINE	AVERAGE
15	0.63048	43.75	-12.25	56.00	43.39	0.16	0.20	LINE	QP
16	0.63048	34.74	-11.26	46.00	34.38	0.16	0.20	LINE	AVERAGE
17	0.70842	39.36	-16.64	56.00	39.00	0.16	0.20	LINE	QP
18	0.70842	30.45	-15.55	46.00	30.09	0.16	0.20	LINE	AVERAGE
19	0.82608	30.84	-15.16	46.00	30.48	0.16	0.20	LINE	AVERAGE
20	0.82608	39.69	-16.31	56.00	39.33	0.16	0.20	LINE	QP
21	0.94809	37.81	-18.19	56.00	37.44	0.17	0.20	LINE	QP
22	0.94809	28.24	-17.76	46.00	27.87	0.17	0.20	LINE	AVERAGE
23	1.426	29.87	-16.13	46.00	29.58	0.18	0.11	LINE	AVERAGE
24	1.426	39.23	-16.77	56.00	38.94	0.18	0.11	LINE	QP
25	7.769	33.23	-26.77	60.00	32.53	0.30	0.40	LINE	QP
26	7.769	24.04	-25.96	50.00	23.34	0.30	0.40	LINE	AVERAGE

Temperature	21°C	Humidity	63%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	Normal Link / Mode 1 / Adapter 1 (Leader MT12-Y090100-A1)		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.17584	34.30	-20.38	54.68	34.02	0.08	0.20	NEUTRAL	AVERAGE
2	0.17584	52.11	-12.57	64.68	51.83	0.08	0.20	NEUTRAL	QP
3	0.19039	54.74	-9.28	64.02	54.46	0.08	0.20	NEUTRAL	QP
4	0.19039	41.19	-12.83	54.02	40.91	0.08	0.20	NEUTRAL	AVERAGE
5	0.22918	53.86	-8.62	62.48	53.58	0.08	0.20	NEUTRAL	QP
6	0.22918	37.99	-14.49	52.48	37.71	0.08	0.20	NEUTRAL	AVERAGE
7	0.25615	35.13	-16.43	51.56	34.85	0.08	0.20	NEUTRAL	AVERAGE
8	0.25615	51.45	-10.11	61.56	51.17	0.08	0.20	NEUTRAL	QP
9	0.29555	47.00	-13.37	60.37	46.72	0.08	0.20	NEUTRAL	QP
10	0.29555	32.10	-18.27	50.37	31.82	0.08	0.20	NEUTRAL	AVERAGE
11	0.38519	33.09	-15.08	48.17	32.81	0.08	0.20	NEUTRAL	AVERAGE
12	0.38519	46.99	-11.18	58.17	46.71	0.08	0.20	NEUTRAL	QP
13	0.41927	44.54	-12.92	57.46	44.26	0.08	0.20	NEUTRAL	QP
14	0.41927	33.28	-14.18	47.46	33.00	0.08	0.20	NEUTRAL	AVERAGE
15	0.51550	46.99	-9.01	56.00	46.71	0.08	0.20	NEUTRAL	QP
16	0.51550	33.04	-12.96	46.00	32.76	0.08	0.20	NEUTRAL	AVERAGE
17	0.57010	42.24	-13.76	56.00	41.96	0.08	0.20	NEUTRAL	QP
18	0.57010	31.35	-14.65	46.00	31.07	0.08	0.20	NEUTRAL	AVERAGE
19	0.63048	45.12	-10.88	56.00	44.84	0.08	0.20	NEUTRAL	QP
20	0.63048	33.76	-12.24	46.00	33.48	0.08	0.20	NEUTRAL	AVERAGE
21	0.70468	28.76	-17.25	46.00	28.47	0.09	0.20	NEUTRAL	AVERAGE
22	0.70468	40.12	-15.89	56.00	39.83	0.09	0.20	NEUTRAL	QP
23	0.82608	26.50	-19.50	46.00	26.21	0.09	0.20	NEUTRAL	AVERAGE
24	0.82608	38.42	-17.58	56.00	38.13	0.09	0.20	NEUTRAL	QP
25	0.94809	26.04	-19.96	46.00	25.75	0.09	0.20	NEUTRAL	AVERAGE
26	0.94809	39.36	-16.64	56.00	39.07	0.09	0.20	NEUTRAL	QP
27	1.166	26.98	-19.02	46.00	26.72	0.09	0.16	NEUTRAL	AVERAGE
28	1.166	39.00	-17.00	56.00	38.74	0.09	0.16	NEUTRAL	QP

Temperature	21°C	Humidity	63%
Test Engineer	Ryo Fan	Phase	Line
Configuration	Normal Link / Mode 2 / Adapter 2 (DVE DSA-9PFB-09 FUS 090100)		



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Pol/Phase	Remark
			dB	dBuV	dBuV	dB	dB		
1	0.15403	47.10	-18.68	65.78	46.74	0.16	0.20	LINE	QP
2	0.15403	31.31	-24.47	55.78	30.95	0.16	0.20	LINE	AVERAGE
3	0.17678	23.94	-30.70	54.64	23.59	0.15	0.20	LINE	AVERAGE
4	0.17678	39.73	-24.91	64.64	39.38	0.15	0.20	LINE	QP
5	0.36725	37.18	-21.38	58.56	36.83	0.15	0.20	LINE	QP
6	0.36725	26.59	-21.97	48.56	26.24	0.15	0.20	LINE	AVERAGE
7	0.68263	21.76	-24.24	46.00	21.40	0.16	0.20	LINE	AVERAGE
8	0.68263	26.23	-29.77	56.00	25.87	0.16	0.20	LINE	QP
9	7.728	26.67	-33.33	60.00	25.98	0.29	0.40	LINE	QP
10	7.728	15.37	-34.63	50.00	14.68	0.29	0.40	LINE	AVERAGE
11	22.655	21.00	-29.00	50.00	19.96	0.54	0.50	LINE	AVERAGE
12	22.655	29.51	-30.49	60.00	28.47	0.54	0.50	LINE	QP

Temperature	21°C	Humidity	63%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	Normal Link / Mode 2 / Adapter 2 (DVE DSA-9PFB-09 FUS 090100)		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15985	24.11	-31.36	55.47	23.83	0.08	0.20	NEUTRAL	AVERAGE
2	0.15985	42.30	-23.17	65.47	42.02	0.08	0.20	NEUTRAL	QP
3	0.36338	39.68	-8.97	48.65	39.40	0.08	0.20	NEUTRAL	AVERAGE
4	0.36338	41.23	-17.42	58.65	40.95	0.08	0.20	NEUTRAL	QP
5	0.67902	29.48	-26.52	56.00	29.20	0.08	0.20	NEUTRAL	QP
6	0.67902	25.98	-20.02	46.00	25.70	0.08	0.20	NEUTRAL	AVERAGE
7	0.92821	26.68	-29.32	56.00	26.39	0.09	0.20	NEUTRAL	QP
8	0.92821	24.43	-21.57	46.00	24.14	0.09	0.20	NEUTRAL	AVERAGE
9	5.898	17.17	-32.83	50.00	16.71	0.16	0.30	NEUTRAL	AVERAGE
10	5.898	20.80	-39.20	60.00	20.34	0.16	0.30	NEUTRAL	QP
11	19.708	29.74	-30.26	60.00	28.85	0.39	0.50	NEUTRAL	QP
12	19.708	21.85	-28.15	50.00	20.96	0.39	0.50	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

### 4.2.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 8.2.3 option 3.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n
Test Date	Nov. 13, 2012		

#### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	Conducted Power (dBm)		Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2			
1	2412 MHz	12.89	13.33	16.13	30.00	Complies
6	2437 MHz	17.57	18.18	20.90	30.00	Complies
11	2462 MHz	13.61	14.06	16.85	30.00	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11b/g
<b>Test Date</b>	Nov. 13, 2012		

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.09	30.00	<b>Complies</b>
6	2437 MHz	17.60	30.00	<b>Complies</b>
11	2462 MHz	17.77	30.00	<b>Complies</b>

**Configuration IEEE 802.11g / Ant. 1**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	12.91	30.00	<b>Complies</b>
6	2437 MHz	20.33	30.00	<b>Complies</b>
11	2462 MHz	14.14	30.00	<b>Complies</b>

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	100 kHz
VB	300 kHz
Detector	RMS
Trace	Single Sweep
Sweep Time	$\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{transmission symbol period})$ .

### 4.3.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 9.1 option 1
2. Spectrum analyzer must be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW in order to ensure bin-to-bin spacing of  $\leq RBW/2$  so that narrowband signals are not lost between frequency bins.
3. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
4. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
5. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
6. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where:  $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$ .
7. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .
8. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Robert Chang	Configurations	IEEE 802.11n
Test Date	Nov. 13, 2012		

#### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/100kHz)		BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)		Single Port. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2		Ant. 1	Ant. 2		
1	2412 MHz	2.80	2.56	-15.23	-12.43	-12.67	4.99	Complies
6	2437 MHz	8.35	7.62	-15.23	-6.88	-7.61	4.99	Complies
11	2462 MHz	3.27	3.13	-15.23	-11.96	-12.10	4.99	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11b/g
<b>Test Date</b>	Nov. 13, 2012		

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	9.96	-15.23	-5.27	8.00	Complies
6	2437 MHz	9.49	-15.23	-5.74	8.00	Complies
11	2462 MHz	9.44	-15.23	-5.79	8.00	Complies


**Configuration IEEE 802.11g / Ant. 1**

Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	2.00	-15.23	-13.23	8.00	Complies
6	2437 MHz	9.86	-15.23	-5.37	8.00	Complies
11	2462 MHz	3.44	-15.23	-11.79	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

### Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 2437 MHz




Date: 13.NOV.2012 11:09:28

### Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / 2437 MHz




Date: 13.NOV.2012 11:08:52

### Power Density Plot on Configuration IEEE 802.11b / Ant. 1 / 2412 MHz



Date: 13.NOV.2012 11:00:14

### Power Density Plot on Configuration IEEE 802.11g / Ant. 1 / 2437 MHz



Date: 13.NOV.2012 11:04:36

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	1-5 % or DTS BW, not exceed 100KHz
VB	$\geq 3 \times RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 5.1.1 EBW Measurement Procedure
3. Multiple antenna system was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11n
<b>Test Date</b>	Nov. 13, 2012		

#### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	13.84	16.72	500	<b>Complies</b>
6	2437 MHz	13.92	16.96	500	<b>Complies</b>
11	2462 MHz	15.68	16.80	500	<b>Complies</b>

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Robert Chang	<b>Configurations</b>	IEEE 802.11b/g
<b>Test Date</b>	Nov. 13, 2012		

**Configuration IEEE 802.11b / Ant. 1**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.08	10.08	500	Complies
6	2437 MHz	8.08	10.16	500	Complies
11	2462 MHz	8.08	10.16	500	Complies


**Configuration IEEE 802.11g / Ant. 1**

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.12	16.24	500	Complies
6	2437 MHz	15.04	16.72	500	Complies
11	2462 MHz	15.04	16.24	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 / 2437 MHz




Date: 13.NOV.2012 11:35:25

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1 / 2437 MHz



Date: 13.NOV.2012 11:25:53

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1 / 2412 MHz



Date: 13.NOV.2012 11:29:33

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For Radiated Emissions below 1GHz



For Radiated Emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	21°C	Humidity	56.4%
Test Engineer	Wen Chao	Configurations	Normal Link
Test Date	Nov. 13, 2012		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	21°C	Humidity	56.4%
Test Engineer	Wen Chao	Configurations	Normal Link / Mode 1 / Adapter 1 (Leader MT12-Y090100-A1)

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		deg	cm	
1 p	32.91	33.58	40.00	-6.42	42.59	0.88	27.99	18.10	Peak	0	100	HORIZONTAL
2	147.37	28.42	43.50	-15.08	42.71	1.78	27.52	11.45	Peak	0	100	HORIZONTAL
3	250.19	35.83	46.00	-10.17	47.50	2.38	26.95	12.90	Peak	0	100	HORIZONTAL
4	299.66	30.88	46.00	-15.12	41.40	2.51	26.83	13.80	Peak	0	100	HORIZONTAL
5	450.01	31.03	46.00	-14.97	38.58	3.24	27.79	17.00	Peak	0	100	HORIZONTAL
6	600.36	33.69	46.00	-12.31	38.26	3.73	27.60	19.30	Peak	0	100	HORIZONTAL


**Vertical**



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	q	52.30	35.20	40.00	-4.80	53.68	1.09	27.91	8.34	QP	163	100 VERTICAL
2	p	108.57	33.66	43.50	-9.84	47.36	1.56	27.74	12.48	Peak	0	400 VERTICAL
3		129.91	33.64	43.50	-9.86	46.80	1.67	27.63	12.80	Peak	0	400 VERTICAL
4		250.19	32.93	46.00	-13.07	44.60	2.38	26.95	12.90	Peak	0	400 VERTICAL
5		299.66	33.09	46.00	-12.91	43.61	2.51	26.83	13.80	Peak	0	400 VERTICAL
6		600.36	34.91	46.00	-11.09	39.48	3.73	27.60	19.30	Peak	0	400 VERTICAL


<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	Normal Link / Mode 2 / Adapter 2 (DVE DSA-9PFB-09 FUS 090100)

**Horizontal**



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1 p	31.94	33.21	40.00	-6.79	41.62	0.87	27.98	18.70	Peak	0	100	HORIZONTAL
2	143.49	28.84	43.50	-14.66	42.87	1.74	27.54	11.77	Peak	0	100	HORIZONTAL
3	250.19	34.37	46.00	-11.63	46.04	2.38	26.95	12.90	Peak	0	100	HORIZONTAL
4	299.66	33.87	46.00	-12.13	44.39	2.51	26.83	13.80	Peak	0	100	HORIZONTAL
5	450.01	31.37	46.00	-14.63	38.92	3.24	27.79	17.00	Peak	0	100	HORIZONTAL
6	600.36	33.22	46.00	-12.78	37.79	3.73	27.60	19.30	Peak	0	100	HORIZONTAL

**Vertical**



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	q	53.22	35.60	40.00	-4.40	54.25	1.10	27.91	8.16	QP	163	100 VERTICAL
2		108.57	33.09	43.50	-10.41	46.79	1.56	27.74	12.48	Peak	0	100 VERTICAL
3	p	143.49	33.37	43.50	-10.13	47.40	1.74	27.54	11.77	Peak	0	100 VERTICAL
4		250.19	30.85	46.00	-15.15	42.52	2.38	26.95	12.90	Peak	0	100 VERTICAL
5		299.66	30.07	46.00	-15.93	40.59	2.51	26.83	13.80	Peak	0	100 VERTICAL
6		450.01	28.39	46.00	-17.61	35.94	3.24	27.79	17.00	Peak	0	100 VERTICAL

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1 + Ant. 2
<b>Test Date</b>	Nov. 09, 2012		

##### *Horizontal*

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4819.31	32.09	54.00	-21.91	27.66	6.27	33.36	35.20	Average	100	152 HORIZONTAL
2	4826.15	43.94	74.00	-30.06	39.48	6.27	33.39	35.20	Peak	100	152 HORIZONTAL

##### *Vertical*

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4819.26	46.25	74.00	-27.75	41.82	6.27	33.36	35.20	Peak	100	150 VERTICAL
2	4823.87	34.45	54.00	-19.55	29.99	6.27	33.39	35.20	Average	100	150 VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1 + Ant. 2
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4875.73	51.05	74.00	-22.95	46.46	6.31	33.48	35.20	Peak	100	207	HORIZONTAL
2	4875.80	36.80	54.00	-17.20	32.21	6.31	33.48	35.20	Average	100	207	HORIZONTAL
3	7306.16	61.05	74.00	-12.95	52.48	7.51	36.48	35.42	Peak	170	106	HORIZONTAL
4	7308.40	45.85	54.00	-8.15	37.26	7.51	36.51	35.43	Average	170	106	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4870.47	58.85	74.00	-15.15	54.29	6.31	33.45	35.20	Peak	100	141	VERTICAL
2	4872.97	43.16	54.00	-10.84	38.57	6.31	33.48	35.20	Average	100	141	VERTICAL
3	7307.86	67.33	74.00	-6.67	58.74	7.51	36.51	35.43	Peak	146	84	VERTICAL
4	7308.40	50.61	54.00	-3.39	42.02	7.51	36.51	35.43	Average	146	84	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4919.39	45.30	74.00	-28.70	40.61	6.35	33.54	35.20	Peak	100	358 HORIZONTAL
2	4920.28	32.64	54.00	-21.36	27.95	6.35	33.54	35.20	Average	100	358 HORIZONTAL
3	7385.97	37.24	54.00	-16.76	28.48	7.61	36.61	35.46	Average	100	148 HORIZONTAL
4	7387.64	49.91	74.00	-24.09	41.12	7.64	36.61	35.46	Peak	100	148 HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4925.46	50.59	74.00	-23.41	45.86	6.35	33.58	35.20	Peak	102	207 VERTICAL
2	4925.70	35.38	54.00	-18.62	30.65	6.35	33.58	35.20	Average	102	207 VERTICAL
3	7383.20	38.89	54.00	-15.11	30.12	7.61	36.61	35.45	Average	100	143 VERTICAL
4	7388.07	52.12	74.00	-21.88	43.33	7.64	36.61	35.46	Peak	100	143 VERTICAL

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11b CH 1 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.95	48.85	74.00	-25.15	44.39	6.27	33.39	35.20	Peak	100	207	HORIZONTAL
2	4823.97	41.61	54.00	-12.39	37.15	6.27	33.39	35.20	Average	100	207	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.96	50.49	54.00	-3.51	46.03	6.27	33.39	35.20	Average	100	321	VERTICAL
2	4824.00	53.80	74.00	-20.20	49.34	6.27	33.39	35.20	Peak	100	321	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11b CH 6 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.96	42.47	54.00	-11.53	37.88	6.31	33.48	35.20	Average	111	207	HORIZONTAL
2	4874.00	49.24	74.00	-24.76	44.65	6.31	33.48	35.20	Peak	111	207	HORIZONTAL
3	7309.83	56.88	74.00	-17.12	48.29	7.51	36.51	35.43	Peak	170	52	HORIZONTAL
4	7310.23	50.52	54.00	-3.48	41.93	7.51	36.51	35.43	Average	170	52	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.96	50.34	54.00	-3.66	45.75	6.31	33.48	35.20	Average	100	141	VERTICAL
2	4873.97	53.87	74.00	-20.13	49.28	6.31	33.48	35.20	Peak	100	141	VERTICAL
3	7310.04	56.76	74.00	-17.24	48.17	7.51	36.51	35.43	Peak	170	130	VERTICAL
4	7310.23	50.81	54.00	-3.19	42.22	7.51	36.51	35.43	Average	170	130	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11b CH 11 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.97	41.58	54.00	-12.42	36.85	6.35	33.58	35.20	Average	100	68	HORIZONTAL
2	4924.12	48.45	74.00	-25.55	43.72	6.35	33.58	35.20	Peak	100	68	HORIZONTAL
3	7385.18	43.21	54.00	-10.79	34.45	7.61	36.61	35.46	Average	180	211	HORIZONTAL
4	7386.16	52.63	74.00	-21.37	43.87	7.61	36.61	35.46	Peak	180	211	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4923.92	53.51	74.00	-20.49	48.78	6.35	33.58	35.20	Peak	101	147	VERTICAL
2	4923.96	50.79	54.00	-3.21	46.06	6.35	33.58	35.20	Average	360	147	VERTICAL
3	7385.22	50.57	54.00	-3.43	41.81	7.61	36.61	35.46	Average	171	111	VERTICAL
4	7386.16	57.50	74.00	-16.50	48.74	7.61	36.61	35.46	Peak	171	111	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11g CH 1 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4819.90	32.26	54.00	-21.74	27.80	6.27	33.39	35.20	Average	100	229	HORIZONTAL
2	4825.51	44.43	74.00	-29.57	39.97	6.27	33.39	35.20	Peak	100	229	HORIZONTAL

### Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4823.79	45.57	74.00	-28.43	41.11	6.27	33.39	35.20	Peak	100	35	VERTICAL
2	4823.95	32.91	54.00	-21.09	28.45	6.27	33.39	35.20	Average	100	35	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11g CH 6 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4873.84	51.22	74.00	-22.78	46.63	6.31	33.48	35.20	Peak	112	206	HORIZONTAL
2	4875.25	37.34	54.00	-16.66	32.75	6.31	33.48	35.20	Average	112	206	HORIZONTAL
3	7307.80	47.65	54.00	-6.35	39.06	7.51	36.51	35.43	Average	168	52	HORIZONTAL
4	7313.34	65.04	74.00	-8.96	56.42	7.54	36.51	35.43	Peak	168	52	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4872.75	45.28	54.00	-8.72	40.69	6.31	33.48	35.20	Average	101	141	VERTICAL
2	4875.19	60.11	74.00	-13.89	55.52	6.31	33.48	35.20	Peak	101	141	VERTICAL
3	7309.08	67.91	74.00	-6.09	59.32	7.51	36.51	35.43	Peak	170	139	VERTICAL
4	7310.52	49.57	54.00	-4.43	40.98	7.51	36.51	35.43	Average	170	139	VERTICAL

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11g CH 11 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4920.01	32.59	54.00	-21.41	27.90	6.35	33.54	35.20	Average	100	356	HORIZONTAL
2	4927.00	46.06	74.00	-27.94	41.33	6.35	33.58	35.20	Peak	100	356	HORIZONTAL
3	7382.94	37.03	54.00	-16.97	28.26	7.61	36.61	35.45	Average	100	213	HORIZONTAL
4	7390.15	49.35	74.00	-24.65	40.56	7.64	36.61	35.46	Peak	100	213	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4923.81	35.36	54.00	-18.64	30.63	6.35	33.58	35.20	Average	100	207	VERTICAL
2	4927.56	48.60	74.00	-25.40	43.87	6.35	33.58	35.20	Peak	100	207	VERTICAL
3	7382.76	36.98	54.00	-17.02	28.21	7.61	36.61	35.45	Average	100	331	VERTICAL
4	7385.06	50.60	74.00	-23.40	41.84	7.61	36.61	35.46	Peak	100	331	VERTICAL

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz / 300 KHz for Peak

### 4.6.3. Test Procedures

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1 + Ant. 2
<b>Test Date</b>	Nov. 09, 2012		

##### Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.68	70.02	74.00	-3.98	37.63	4.34	28.05	0.00	Peak	100	334	HORIZONTAL
2	2390.00	52.91	54.00	-1.09	20.52	4.34	28.05	0.00	Average	100	334	HORIZONTAL
3	2411.20	101.13	54.00			4.34	28.09	0.00	Average	100	334	HORIZONTAL
4	2411.68	113.56	74.00			4.34	28.09	0.00	Peak	100	334	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.36	66.98	74.00	-7.02	34.59	4.34	28.05	0.00	Peak	101	346	HORIZONTAL
2	2390.00	50.52	54.00	-3.48	18.13	4.34	28.05	0.00	Average	101	346	HORIZONTAL
3	2434.44	118.33	74.00			4.36	28.18	0.00	Peak	101	346	HORIZONTAL
4	2436.52	105.92	54.00			4.36	28.18	0.00	Average	101	346	HORIZONTAL
5	2483.50	45.32	54.00	-8.68	12.66	4.40	28.26	0.00	Average	101	346	HORIZONTAL
6	2483.98	60.79	74.00	-13.21	28.13	4.40	28.26	0.00	Peak	101	346	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

##### Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.20	109.65	74.00			4.38	28.22	0.00	Peak	100	80	VERTICAL
2	2461.36	98.75	54.00			4.38	28.22	0.00	Average	100	80	VERTICAL
3	2483.66	52.28	54.00	-1.72	19.62	4.40	28.26	0.00	Average	100	80	VERTICAL
4	2483.66	67.74	74.00	-6.26	35.08	4.40	28.26	0.00	Peak	100	80	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11b CH 1, 6, 11 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.04	62.12	74.00	-11.88	29.73	4.34	28.05	0.00	Peak	104	105	HORIZONTAL
2	2390.00	50.02	54.00	-3.98	17.63	4.34	28.05	0.00	Average	104	105	HORIZONTAL
3	2411.04	112.94	74.00			4.34	28.09	0.00	Peak	104	105	HORIZONTAL
4	2411.20	109.00	54.00			4.34	28.09	0.00	Average	104	105	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2387.76	61.16	74.00	-12.84	28.77	4.34	28.05	0.00	Peak	104	106	HORIZONTAL
2	2390.00	48.07	54.00	-5.93	15.68	4.34	28.05	0.00	Average	104	106	HORIZONTAL
3	2436.04	112.99	74.00			4.36	28.18	0.00	Peak	104	106	HORIZONTAL
4	2436.36	108.91	54.00			4.36	28.18	0.00	Average	104	106	HORIZONTAL
5	2483.50	42.49	54.00	-11.51	9.83	4.40	28.26	0.00	Average	104	106	HORIZONTAL
6	2483.50	53.23	74.00	-20.77	20.57	4.40	28.26	0.00	Peak	104	106	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.04	112.32	74.00			4.38	28.22	0.00	Peak	101	105	HORIZONTAL
2	2461.20	108.45	54.00			4.38	28.22	0.00	Average	101	105	HORIZONTAL
3	2483.50	46.26	54.00	-7.74	13.60	4.40	28.26	0.00	Average	101	105	HORIZONTAL
4	2483.50	57.49	74.00	-16.51	24.83	4.40	28.26	0.00	Peak	101	105	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

<b>Temperature</b>	21°C	<b>Humidity</b>	56.4%
<b>Test Engineer</b>	Wen Chao	<b>Configurations</b>	IEEE 802.11g CH 1, 6, 11 / Ant. 1
<b>Test Date</b>	Nov. 09, 2012		

**Channel 1**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	51.87	54.00	-2.13	19.48	4.34	28.05	0.00	Average	107	88	HORIZONTAL
2	2390.00	65.07	74.00	-8.93	32.68	4.34	28.05	0.00	Peak	107	88	HORIZONTAL
3	2411.52	99.59	54.00			4.34	28.09	0.00	Average	107	88	HORIZONTAL
4	2413.60	110.58	74.00			4.36	28.09	0.00	Peak	107	88	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

**Channel 6**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	52.75	54.00	-1.25	20.36	4.34	28.05	0.00	Average	106	88	HORIZONTAL
2	2390.00	68.79	74.00	-5.21	36.40	4.34	28.05	0.00	Peak	106	88	HORIZONTAL
3	2436.36	106.30	54.00			4.36	28.18	0.00	Average	106	88	HORIZONTAL
4	2437.00	117.73	74.00			4.36	28.18	0.00	Peak	106	88	HORIZONTAL
5	2483.50	44.66	54.00	-9.34	12.00	4.40	28.26	0.00	Average	106	88	HORIZONTAL
6	2483.66	62.30	74.00	-11.70	29.64	4.40	28.26	0.00	Peak	106	88	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

**Channel 11**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.36	100.27	54.00			4.38	28.22	0.00	Average	103	104	HORIZONTAL
2	2462.00	111.38	74.00			4.38	28.22	0.00	Peak	103	104	HORIZONTAL
3	2483.50	52.73	54.00	-1.27	20.07	4.40	28.26	0.00	Average	103	104	HORIZONTAL
4	2483.50	68.47	74.00	-5.53	35.81	4.40	28.26	0.00	Peak	103	104	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Date: 13.NOV.2012 11:09:28

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 (down 30dBc)




Date: 13.NOV.2012 15:04:59

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 6 (down 30dBc)




Date: 13.NOV.2012 15:03:49

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 (down 30dBc)




Date: 13.NOV.2012 15:02:16

Plot on Configuration IEEE 802.11b / Reference Level




Date: 13.NOV.2012 11:00:14

Plot on Configuration IEEE 802.11b / CH 1 (down 30dBc)




Date: 13.NOV.2012 14:52:57

Plot on Configuration IEEE 802.11b / CH 6 (down 30dBc)




Date: 13.NOV.2012 14:54:11

Plot on Configuration IEEE 802.11b / CH 11 (down 30dBc)




Date: 13.NOV.2012 14:55:26

Plot on Configuration IEEE 802.11g / Reference Level




Date: 13.NOV.2012 11:04:36

Plot on Configuration IEEE 802.11g / CH 1 (down 30dBc)




Date: 13.NOV.2012 14:57:45

Plot on Configuration IEEE 802.11g / CH 6 (down 30dBc)



Date: 13.NOV.2012 14:58:48

Plot on Configuration IEEE 802.11g / CH 11 (down 30dBc)



Date: 13.NOV.2012 15:00:03

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2011	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Oct. 31, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Oct. 31, 2012	Conducted (TH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 25, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10784	9kHz ~ 1.3GHz	Feb. 03, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 29, 2011	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100304	9kHz ~ 40GHz	Dec. 14, 2011	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Oct. 29, 2012*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

\*Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110702

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**

**EMC & Wireless Communications Laboratory**

No.52, Hwa Ya 1st Road, Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

**Accreditation Criteria** : ISO/IEC 17025:2005  
**Accreditation Number** : 1190  
**Originally Accredited** : December 15, 2003  
**Effective Period** : January 10, 2010 to January 09, 2013  
**Accredited Scope** : Testing Field, see described in the Appendix  
**Specific Accreditation Program** : Accreditation Program for Designated Testing Laboratory for Commodities Inspection  
Accreditation Program for Telecommunication Equipment Testing Laboratory  
Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : July 02, 2011

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix