



**FCC 47 CFR PART 15 SUBPART C &
INDUSTRY CANADA RSS-210**

TEST REPORT

For

N300 Wireless N Router

Model: F9K1002v1

Trade Name: BELKIN

Issued to

**Belkin International Inc.
12045 E. Waterfront Drive Playa Vista, CA 90094, USA**

Issued by

**Compliance Certification Services Inc.
No. 11, Wu-Gong 6th Rd., Wugu Industrial Park,
Taipei Hsien 248, Taiwan (R.O.C.)
<http://www.ccsrf.com>
service@ccsrf.com**



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	3
2. EUT DESCRIPTION	4
3. TEST METHODOLOGY	5
3.1 EUT CONFIGURATION	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.5 DESCRIPTION OF TEST MODES	7
4. INSTRUMENT CALIBRATION.....	8
4.1 MEASURING INSTRUMENT CALIBRATION	8
4.2 MEASUREMENT EQUIPMENT USED	8
4.3 MEASUREMENT UNCERTAINTY	9
5. FACILITIES AND ACCREDITATIONS	10
5.1 FACILITIES	10
5.2 EQUIPMENT.....	10
5.3 LABORATORY ACCREDITATIONS AND LISTING.....	10
5.4 TABLE OF ACCREDITATIONS AND LISTINGS.....	11
6. SETUP OF EQUIPMENT UNDER TEST	12
6.1 SETUP CONFIGURATION OF EUT.....	12
6.2 SUPPORT EQUIPMENT	12
7. APPLICABLE RULES FOR INDUSTRY CANADA RSS-210	13
8. FCC PART 15.247 REQUIREMENTS & RSS-210 REQUIREMENTS.....	22
8.1 99% BANDWIDTH	22
8.2 6DB BANDWIDTH.....	33
8.3 PEAK POWER.....	44
8.4 AVERAGE POWER	46
8.5 BAND EDGES MEASUREMENT	48
8.6 PEAK POWER SPECTRAL DENSITY.....	57
8.7 SPURIOUS EMISSIONS.....	72
8.8 RADIATED EMISSIONS	85
8.9 POWERLINE CONDUCTED EMISSIONS.....	103
APPENDIX I RADIO FREQUENCY EXPOSURE.....	106
APPENDIX II PHOTOGRAPHS OF TEST SETUP.....	109
APPENDIX 1 - PHOTOGRAPHS OF EUT	



1. TEST RESULT CERTIFICATION

Applicant: Belkin International Inc.
12045 E. Waterfront Drive Playa Viste, CA 90094, USA

Manufacturer: Belkin International Inc.
12045 E. Waterfront Drive Playa Viste, CA 90094, USA

Equipment Under Test: N300 Wireless N Router

Trade Name: BELKIN

Model: F9K1002v1

Date of Test: February 22 ~ March 7, 2011

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C & Industry Canada RSS-210 Issue 8 December, 2010	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247 and Industry Canada RSS-210.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Rex Lai
Section Manager
Compliance Certification Services Inc.

Gina Lo
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	N300 Wireless N Router			
Trade Name	BELKIN			
Model Number	F9K1002v1			
Model Discrepancy	N/A			
Power Adapter	DVE / DSA-12PFE-12 BUS I/P: 100-240V, 50-60Hz, 0.3A O/P: 12V, 1A			
Frequency Range	2412 ~ 2462 MHz			
Transmit Power	Mode	Frequency Range	Output Power (dBm)	Output Power (w)
	802.11b	2412 - 2462	23.28	0.2128
	802.11g	2412 - 2462	22.81	0.1910
	802.11n Standard-20 MHz	2412 - 2462	21.93	0.1558
	802.11n Standard-40 MHz	2422 - 2452	21.83	0.1524
Modulation Technique	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) IEEE 802.11n HT 20 MHz mode Channel mode: OFDM (6.5, 7.2, 13, 14.4, 14.44, 19.5, 21.7, 26, 28.89, 28.9, 39, 43.3, 43.33 52, 57.78, 57.8, 58.5, 65.0, 72.2, 78, 86.67, 104, 115.56, 117, 130, 144.44 Mbps) IEEE 802.11n HT 40 MHz mode: OFDM (13.5, 15, 27, 30, 40.5, 45, 54, 60, 81, 90, 108, 120, 121.5, 135, 150, 162, 180, 216, 240, 243, 270, 300 Mbps)			
Number of Channels	IEEE 802.11b/g mode: 11 Channels IEEE 802.11n HT 20 MHz mode Channel mode: 11 Channels IEEE 802.11n HT 40 MHz mode: 7 Channels			
Antenna Specification	1. PCB Antenna / Gain: 4.9 dBi 2. PCB Antenna / Gain: 3.7 dBi Antenna Calculation for MIMO Mode $10 * \text{LOG}(((10^{(4.9/20)} + 10^{(3.7/20)})^2) / 2) = 7.33 \text{dBi}$			

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **K7SF9K1002V1** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

The tests documented in this report were performed in accordance with IC RSS-210, IC RSS-Gen, IC RSS-102, IC RSS-212, and ANSI C63.4.

This submittal(s) (test report) is intended for IC Certification with Industry Canada RSS-210.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

The tests documented in this report were performed in accordance with IC RSS-210, IC RSS-Gen, IC RSS-102, and ANSI C63.4.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: F9K1002v1) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode was programmed.

The EUT is a 2x2 configuration spatial MIMO (2Tx & 2Rx) without beam forming function that operate in double TX chains and double RX chains. The 2x2 configuration is implemented with two outside TX & RX chains (Chain 1 and the middle RX chain (chain 0)).

After verification, all tests carried out are with the worst-case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode and receiving radiated spurious emission above 1GHz, which worst case was in CH Mid mode only.

IEEE 802.11b mode:

Channel Low(2412MHz), Channel Mid(2437MHz) and Channel High(2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low(2412MHz), Channel Mid(2437MHz) and Channel High(2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 MHz mode Channel mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

IEEE 802.11n HT 40 MHz mode:

Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year and Loop Antenna is scheduled for calibration once three years.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	03/03/2011
Power Meter	Anritsu	ML2495A	1012009	03/28/2011
Power Sensor	Anritsu	MA2411B	0917072	03/09/2011

Wugu 966 Chamber A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	11/03/2011
EMI Test Receiver	R&S	ESCI	100064	02/03/2012
Pre-Amplifier	Mini-Circuits	ZFL-1000LN	SF350700823	01/12/2012
Pre-Amplifier	MITEQ	AFS44-00102650-42-10P-44	1415367	11/19/2011
Bilog Antenna	Sunol Sciences	JB3	A030105	10/06/2011
Horn Antenna	EMCO	3117	00055165	01/12/2012
Loop Antenna	EMCO	6502	8905/2356	06/10/2013
Turn Table	CCS	CC-T-1F	N/A	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R
Site NSA	CCS	N/A	N/A	12/26/2011
Test S/W	EZ-EMC (CCS-3A1RE)			

Conducted Emission room # A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TEST RECEIVER	R&S	ESCI	100234	06/13/2011
LISN (EUT)	FCC	FCC-LISN-50-32-2	08009	03/25/2011
LISN	SCHWARZBECK	NSLK 8127	8127382	01/02/2012
BNC CABLE	MIYAZAKI	5D-FB	BNC B3	08/10/2011
Pulse Limiter	R&S	ESH3-Z2	100374	01/09/2012
THERMO-HYGRO METER	TOP	HA-202	9303-3	01/25/2012
Test S/W	EZ-EMC			



4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Powerline Conducted Emission	+/- 1.1089
3M Semi Anechoic Chamber / 30M~200M	+/- 4.0606
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9979
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5790
3M Semi Anechoic Chamber / 8G~18G	+/- 2.5928
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7212
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9520

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

*Remark: The Powerline Conducted test items was tested at Compliance Certification Services Inc. (Hsintien Lab.)
The test equipments were listed in page 8 and the test data, please refer page 104-105.*

No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

No.81-1, Lane 210, Bade 2nd Rd., Luchu Hsiang, Taoyuan Hsien 338, Taiwan

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 0824-01 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with Industry Canada, Certification and Engineering Bureau, IC 2324G-1 for 3M Semi Anechoic Chamber A, 2324G-2 for 3M Semi Anechoic Chamber B.



5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	 FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	 IC 2324G-1 IC 2324G-2

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No	Equipment	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Notebook PC (Remote)	DELL	PP05L	7T390 A03	E2K5HCKT	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*



7. APPLICABLE RULES FOR INDUSTRY CANADA RSS-210

RSS-210 §2 General Certification Requirements and Specifications

RSS-210 §2.1 RSS-Gen Compliance

In addition to RSS-210, the requirements in RSS-Gen, *General Requirements and Information for the Certification of Radio Apparatus*, must be met.

RSS-210 §2.2 Emissions Falling Within Restricted Frequency Bands

Category I licence-exempt equipment is required to comply with the provisions in RSS-Gen with respect to emissions falling within restricted frequency bands. These restricted frequency bands are listed in RSS-Gen.

RSS-210 §2.3 Receivers

Category I equipment receivers for use with transmitters subject to RSS-210 must comply with the applicable requirements set out in RSS-Gen and be certified under RSS-210. Category II equipment receivers for use with transmitters subject to RSS-210 are exempt from certification, but are subject to compliance with RSS-Gen and RSS-310.

RSS-210 §2.5 General Field Strength Limits

RSS-Gen includes the general field strength limits of unwanted emissions, where applicable, for transmitters and receivers operating in accordance with the provisions specified in this standard. Unwanted emissions of transmitters and receivers are permitted to fall within the restricted bands listed in RSS-Gen, and including the TV bands, but fundamental emissions are prohibited in the restricted bands.

RSS-210 §2.5.1 Transmitters with Wanted Emissions that are Within the General Field Strength Limits

Whether or not their operation is addressed by published RSS standards, transmitters whose wanted and unwanted emissions are within the general field strength limits shown in RSS-Gen, they may operate in any of the frequency bands, other than the restricted bands listed in RSS-Gen and including the TV bands, and shall be certified under RSS-210. Under no conditions may the level of any unwanted emissions exceed the level of the fundamental emission.

Note: Devices operating below 490 kHz in which all emissions are at least 40 dB below the limit listed in RSS-Gen (*General Field Strength Limits for Transmitters at Frequencies below 30 MHz*) are Category II devices and are subject to RSS-310.



RSS-210 §2.7 Tables

RSS-210 §Annex 8: Frequency Hopping and Digital Modulation Systems Operating in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands

This section applies to systems that employ frequency hopping (FH) and digital modulation technology in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. Systems in these bands may employ frequency hopping, digital modulation and or a combination (hybrid) of both techniques.

A frequency hopping system that synchronizes with another or several other systems (to avoid frequency collision among them) via off-air sensing or via connecting cables is not hopping randomly and therefore is not in compliance with RSS-210.

RSS-210 §A8.1 Frequency Hopping Systems

Frequency hopping systems are spread spectrum systems in which the carrier is modulated with coded information in a conventional manner causing a conventional spreading of the RF energy about the carrier frequency. The frequency of the carrier is not fixed but changes at fixed intervals under the direction of a coded sequence.

Frequency hopping systems are not required to employ all available hopping frequencies during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream.

Incorporation of intelligence into a frequency hopping system that enables it to recognize other users of the band and to avoid occupied frequencies is permitted, provided that the frequency hopping system does it individually, and independently chooses or adapts its hopset. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

The following applies to frequency hopping systems in each of the three bands.

(a) The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long term distribution appears evenly distributed.



(b) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125 W. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(d) Frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that a minimum of 15 hopping channels are used.

RSS-210 §A8.2 Digital Modulation Systems

These include systems employing digital modulation techniques resulting in spectral characteristics similar to direct sequence systems. The following applies to all three bands.

RSS-210 §A8.4 Transmitter Output Power and e.i.r.p. Requirements

(4) For systems employing digital modulation techniques operating in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands, the maximum peak conducted power shall not exceed 1 W. Except as provided in Section A8.4(5), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power (see RSS-Gen)

(5) Point-to-point systems in the bands 2400-2483.5 MHz and 5725-5850 MHz are permitted to have an e.i.r.p. higher than 4 W, provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omni-directional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding 4 W e.i.r.p. However, remote stations of point-to-multipoint systems shall be allowed to operate at greater than 4 W e.i.r.p. under the same conditions as for point-to-point systems.

Note: "Fixed, point-to-point operation", excludes point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information.



RSS-210 §A8.5 Out-of-band Emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required.

RSS-Gen §2 General Information

RSS-Gen §2.1.2 Category II Equipment

Category II equipment comprises radio devices where a standard has been prescribed but for which a TAC is not required, that is, equipment certification by Industry Canada or a Certification Body (CB) is not required (certification exempt), pursuant to subsection 4(3) of the Radiocommunication Act. The manufacturer or importer shall nevertheless ensure that the standards are complied with. A test report shall be available on request and the device shall be properly labelled.

RSS-Gen §2.2 Receivers

Receivers that are used for radiocommunication other than broadcasting are defined as Category I equipment or Category II equipment, subject to compliance with applicable Industry Canada standards.

Receivers shall be capable of operation only with transmitters for which RSSs are published. Receivers are classified as described in sections 2.2.1 and 2.2.2.

RSS-Gen §2.2.1 Category I Equipment Receivers

A receiver is classified as Category I equipment if it meets one of the following conditions:

- (a) a stand-alone receiver (see Note 1, below), which operates on any frequency in the band 30-960 MHz, and is used for the reception of signals in that frequency band from a transmitter classified as Category I equipment;
- (b) a Citizen's Band (CB) receiver (26.96-27.410 MHz);
- (c) a scanner receiver.

Note 1: A *stand-alone receiver* is defined as any receiver that is not permanently combined together with a transmitter in a single case (transceiver), in which it functions as the receiver component of the transceiver.

Receivers classified as Category I equipment shall comply with the limits for receiver spurious emissions set out in RSS-Gen; however, equipment certification is granted under the applicable RSS standard along with the associated transmitter classified as Category I equipment. Scanner receivers are covered under their own specific RSS.

RSS-Gen §2.2.2 Category II Equipment Receivers

A receiver is classified as Category II equipment if it does not meet any of the conditions of Section 2.2.1.

Category II receivers shall comply with the applicable testing, labelling and user manual requirements in RSS-310.



RSS-Gen §2.2.3 Licence-exempt Receivers

Certain types of radio apparatus are permitted to operate without licensing from Industry Canada. These are typically low output power devices that are intended primarily for consumer or commercial applications; however, some are intended for applications in law enforcement, medical and other specialized applications.

Licence-exempt radio apparatus shares spectrum with licensed radio services and must operate on a no-interference, no-protection basis. Licence-exempt radio apparatus may not cause radio interference to, and cannot claim protection from interference caused by, licensed radio services.

General requirements for licence-exempt radio apparatus are contained in Section 7.

RSS-Gen §5.6 Exposure of Humans to RF Fields

Category I and Category II equipment shall comply with the applicable requirements of RSS-102.

RSS-Gen §6 Receiver Spurious Emission Standard

Receivers shall comply with the limits of spurious emissions set out in this section, measured over the frequency range determined in accordance with Section 4.10.

RSS-Gen §6.1 Radiated Limits

Radiated spurious emission measurements shall be performed with the receiver antenna connected to the receiver antenna terminals.

Spurious emissions from receivers shall not exceed the radiated limits shown in the table below:

RSS-Gen Table 2 - Spurious Emission Limits for Receivers

Frequency (MHz)	Field Strength microvolts/m at 3 metres
30-88	100
88-216	150
216-960	200
Above 960	500

*Measurements for compliance with limits in the above table may be performed at distances other than 3 metres, in accordance with Section 7.2.7.

**RSS- Gen Table 3: Restricted Frequency Bands** ^(Note)

MHz	MHz	MHz	MHz	GHz
0.090-0.110	8.37625-8.38675	--	1718.8-1722.2	9.0-9.2
--	8.41425-8.41475	156.52475-156.52525	2200-2300	9.3-9.5
2.1735-2.1905	12.29-12.293	156.7-156.9	2310-2390	10.6-12.7
3.020-3.026	12.51975-12.52025	--	--	13.25-13.4
4.125-4.128	12.57675-12.57725	--	2655-2900	14.47-14.5
4.17725-4.17775	13.36-13.41	240-285	3260-3267	15.35-16.2
4.20725-4.20775	16.42-16.423	322-335.4	3332-3339	17.7-21.4
5.677-5.683	16.69475-16.69525	399.9-410	3345.8-3358	22.01-23.12
6.215-6.218	16.80425-16.80475	608-614	3500-4400	23.6-24.0
6.26775-6.26825	25.5-25.67	960-1427	4500-5150	31.2-31.8
6.31175-6.31225	37.5-38.25	1435-1626.5	5350-5460	36.43-36.5
8.291-8.294	73-74.6; 74.8-75.2	1645.5-1646.5	7250-7750	Above 38.6
8.362-8.366	108-138	1660-1710	8025-8500	

Note: Certain frequency bands listed in Table 2 and above 38.6 GHz are designated for low-power licence-exempt applications. These frequency bands and the requirements that apply to the devices are set out in this Standard as well as RSS-310.

RSS- Gen Table 5: General Field Strength Limits for Transmitters at Frequencies Above 30 MHz

Frequency (MHz)	Field Strength (microvolt/m at 3 metres)
30-88	100
88-216	150
216-960	200
Above 960	500

Note: Transmitting devices are not permitted in Table 1 bands or, unless stated otherwise, in TV bands (54-72 MHz, 76-88 MHz, 174-216 MHz, 470-608 MHz and 614-806 MHz).

**RSS- Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)**

Frequency (fundamental or spurious)	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/377F (F in Hz)	300
490-1.705 kHz	24,000/F (F in kHz)	24,000/377F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Note: The emission limits for the bands 9-90 kHz and 110-490 kHz are based on measurements employing an average detector.



RSS-Gen §7.1.2 Transmitter Antenna

A transmitter can only be sold or operated with antennas with which it was approved. Transmitter may be approved with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest gain antenna of each combination of transmitter and antenna type for which approval is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type having equal or lesser gain as an antenna that had been successfully tested with the transmitter, will also be considered approved with the transmitter, and may be used and marketed with the transmitter. For Category I transmitters, the manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer.

For transmitters of RF output power of 10 milliwatts or less, only the portion of the antenna gain that is in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power to demonstrate compliance with the radiated power limits specified in the applicable standard. For transmitters of output power greater than 10 milliwatts, the total antenna gain shall be added to the measured RF output power to demonstrate compliance to the specified radiated power limits. User manuals for transmitters shall display the following notice in a conspicuous location:

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication.

The above notice may be affixed to the device instead of displayed in the user manual.

User manuals for transmitters equipped with detachable antennas shall also contain the following notice in a conspicuous location:

This radio transmitter (identify the device by certification number, or model number if Category II) has been approved by Industry Canada to operate with the antenna types listed below with the maximum permissible gain and required antenna impedance for each antenna type indicated. Antenna types not included in this list, having a gain greater than the maximum gain indicated for that type, are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types approved for use with the transmitter, indicating the maximum permissible antenna gain (in dBi) and required impedance for each.



RSS-Gen §7.2.4 Transmitter and Receiver AC Power Lines Conducted Emission Limits

Except when the requirements applicable to a given device state otherwise, for any radio apparatus equipped to operate from the public utility AC power supply, either directly or indirectly (such as with a battery charger), the radio frequency voltage of emissions conducted back onto the AC power lines in the frequency range of 0.15 MHz to 30 MHz shall not exceed the limits shown in the table below. The more stringent limit applies at the frequency range boundaries.

The conducted emissions shall be measured with a 50 ohm/50 microhenry line impedance stabilization network (LISN).

RSS-Gen Table 4 – AC Power Line Conducted Emission Limits

Frequency Range (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50


**Decreases with the logarithm of the frequency.*



8. FCC PART 15.247 REQUIREMENTS & RSS-210 REQUIREMENTS

8.1 99% BANDWIDTH

Test Configuration



TEST PROCEDURE

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold.

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	14.3147
Mid	2437	14.6543
High	2462	14.6595

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.9525
Mid	2437	16.9372
High	2462	16.9352

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode / Chain 0

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	18.0832
Mid	2437	17.9732
High	2462	17.9684

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	17.9602
Mid	2437	17.9395
High	2462	18.0364

Test mode: draft 802.11n Standard-40 MHz Channel mode / Chain 0

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	35.7076
Mid	2437	35.6840
High	2462	35.7382

Test mode: draft 802.11n Standard-40 MHz Channel mode / Chain 1

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	35.7208
Mid	2437	35.6994
High	2462	35.7064




Test Plot

IEEE 802.11b mode

99% Bandwidth (CH Low)

Agilent 16:34:50 Feb 23, 2010

R T



Center 2.412 00 GHz Span 50 MHz
#Res BW 510 kHz #VBW 1.5 MHz Sweep 1 ms (1001 pts)

Occupied Bandwidth
14.3147 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -63.273 kHz
x dB Bandwidth 18.345 MHz*

99% Bandwidth (CH Mid)

Agilent 16:35:08 Feb 23, 2010

R T



Center 2.437 00 GHz Span 50 MHz
#Res BW 510 kHz #VBW 1.5 MHz Sweep 1 ms (1001 pts)

Occupied Bandwidth
14.6543 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -91.998 kHz
x dB Bandwidth 18.509 MHz*



99% Bandwidth (CH High)

Agilent 16:35:26 Feb 23, 2010

R T



Occupied Bandwidth
14.6595 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -102.185 kHz
x dB Bandwidth 18.524 MHz*

IEEE 802.11g mode

99% Bandwidth (CH Low)

Agilent 16:35:59 Feb 23, 2010

R T



Occupied Bandwidth
16.9525 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -125.983 kHz
x dB Bandwidth 22.245 MHz*



99% Bandwidth (CH Mid)

Agilent 16:36:31 Feb 23, 2010

R T



Occupied Bandwidth
16.9372 MHz


Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -124.127 kHz
x dB Bandwidth 21.795 MHz*

99% Bandwidth (CH High)

Agilent 16:36:56 Feb 23, 2010

R T



Occupied Bandwidth
16.9352 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -108.478 kHz
x dB Bandwidth 21.705 MHz*




IEEE 802.11n HT 20 MHz mode Channel mode / Chain 0

99% Bandwidth (CH Low)

Agilent 16:38:16 Feb 23, 2010

R T



Occupied Bandwidth
18.0832 MHz


Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -41.372 kHz
x dB Bandwidth 22.478 MHz*

99% Bandwidth (CH Mid)

Agilent 16:38:58 Feb 23, 2010

R L



Occupied Bandwidth
17.9732 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -55.752 kHz
x dB Bandwidth 22.348 MHz*



99% Bandwidth (CH High)

Agilent 16:39:21 Feb 23, 2010

R L



Occupied Bandwidth
17.9684 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -61.994 kHz
x dB Bandwidth 22.597 MHz*

IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

99% Bandwidth (CH Low)

Agilent 16:40:57 Feb 23, 2010

R L



Occupied Bandwidth
17.9602 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -19.142 kHz
x dB Bandwidth 22.068 MHz*



99% Bandwidth (CH Mid)

Agilent 16:40:37 Feb 23, 2010

R T



Occupied Bandwidth
17.9395 MHz


Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -29.755 kHz
x dB Bandwidth 23.072 MHz*

99% Bandwidth (CH High)

Agilent 16:40:16 Feb 23, 2010

R T



Occupied Bandwidth
18.0364 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -43.328 kHz
x dB Bandwidth 22.823 MHz*




draft 802.11n Standard-40 MHz Channel mode / Chain 0

99% Bandwidth (CH Low)

Agilent 16:41:56 Feb 23, 2010

R T



Occupied Bandwidth
35.7076 MHz


Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -36.870 kHz
x dB Bandwidth 39.584 MHz*

99% Bandwidth (CH Mid)

Agilent 16:42:16 Feb 23, 2010

R L



Occupied Bandwidth
35.6840 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -62.334 kHz
x dB Bandwidth 39.360 MHz*



99% Bandwidth (CH High)

Agilent 16:42:49 Feb 23, 2010

R T



Occupied Bandwidth

35.7382 MHz

Occ BW % Pwr	99.00 %
x dB	-26.00 dB


Transmit Freq Error	-100.258 kHz
x dB Bandwidth	40.450 MHz*

draft 802.11n Standard-40 MHz Channel mode / Chain1

99% Bandwidth (CH Low)

Agilent 16:41:44 Feb 23, 2010

R T



Occupied Bandwidth

35.7208 MHz

Occ BW % Pwr	99.00 %
x dB	-26.00 dB


Transmit Freq Error	-33.815 kHz
x dB Bandwidth	39.547 MHz*



99% Bandwidth (CH Mid)

Agilent 16:42:22 Feb 23, 2010

R T



Occupied Bandwidth
35.6994 MHz


Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -64.327 kHz
x dB Bandwidth 39.469 MHz*

99% Bandwidth (CH High)

Agilent 16:42:43 Feb 23, 2010

R T



Occupied Bandwidth
35.7064 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -79.108 kHz
x dB Bandwidth 40.430 MHz*




8.2 6DB BANDWIDTH

LIMIT

According to §15.247(a)(2) & RSS-210 §A8.2(a), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100 kHz, VBW = RBW, Span = 50 MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS

No non-compliance noted

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2412	10080	>500	PASS
Mid	2437	10080		PASS
High	2462	10080		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2412	16420	>500	PASS
Mid	2437	16420		PASS
High	2462	16420		PASS

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode / Chain 0

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2412	17580	>500	PASS
Mid	2437	17000		PASS
High	2462	17170		PASS

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2412	17330	>500	PASS
Mid	2437	17170		PASS
High	2462	17170		PASS

Test mode: IEEE 802.11n HT 40 MHz mode / Chain 0

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2422	35250	>500	PASS
Mid	2437	35170		PASS
High	2452	35170		PASS

Test mode: IEEE 802.11n HT 40 MHz mode / Chain 1

Channel	Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low	2422	35250	>500	PASS
Mid	2437	35170		PASS
High	2452	35250		PASS



Test Plot


IEEE 802.11b mode

6dB Bandwidth (CH Low)

Agilent 10:40:19 Mar 7, 2011

R T

Δ Mkr2 10.08 MHz
0.08 dB




6dB Bandwidth (CH Mid)

Agilent 10:41:19 Mar 7, 2011

R T

Δ Mkr2 10.08 MHz
0.34 dB






6dB Bandwidth (CH High)

Agilent 10:42:13 Mar 7, 2011

R T

Δ Mkr2 10.08 MHz
-0.54 dB



Center 2.462 00 GHz Span 50 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.462 50 GHz	2.46 dBm
2R	(1)	Freq	2.466 92 GHz	-3.73 dBm
2Δ	(1)	Freq	10.08 MHz	-0.54 dB


IEEE 802.11g mode

6dB Bandwidth (CH Low)

Agilent 10:45:42 Mar 7, 2011

R T

Δ Mkr2 16.42 MHz
1.83 dB



Center 2.412 00 GHz Span 50 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.415 75 GHz	-6.32 dBm
2R	(1)	Freq	2.403 75 GHz	-13.84 dBm
2Δ	(1)	Freq	16.42 MHz	1.83 dB




6dB Bandwidth (CH Mid)

Agilent 10:44:47 Mar 7, 2011

R T

Δ Mkr2 16.42 MHz
2.05 dB




6dB Bandwidth (CH High)

Agilent 10:43:56 Mar 7, 2011

R T

Δ Mkr2 16.42 MHz
1.71 dB






IEEE 802.11n HT 20 MHz mode Channel mode / Chain 0

6dB Bandwidth (CH Low)

Agilent 10:47:03 Mar 7, 2011

R T

Δ Mkr2 17.58 MHz
0.23 dB



Ref 15.43 dBm Atten 20 dB Span 50 MHz

Center 2.412 00 GHz #Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.409 50 GHz	-7.78 dBm
2R	(1)	Freq	2.403 17 GHz	-14.29 dBm
2Δ	(1)	Freq	17.58 MHz	0.23 dB

6dB Bandwidth (CH Mid)

Agilent 10:48:54 Mar 7, 2011

R T

Δ Mkr2 17.00 MHz
0.30 dB



Ref 15.43 dBm Atten 20 dB Span 50 MHz

Center 2.437 00 GHz #Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.438 25 GHz	-8.19 dBm
2R	(1)	Freq	2.428 17 GHz	-15.36 dBm
2Δ	(1)	Freq	17.00 MHz	0.30 dB




6dB Bandwidth (CH High)

Agilent 10:52:31 Mar 7, 2011

R T

Δ Mkr2 17.17 MHz
0.86 dB




IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

6dB Bandwidth (CH Low)

Agilent 10:56:46 Mar 7, 2011

R T

Δ Mkr2 17.33 MHz
-0.13 dB






6dB Bandwidth (CH Mid)

Agilent 10:55:39 Mar 7, 2011

R T

Δ Mkr2 17.17 MHz
0.36 dB




Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.432 00 GHz	-3.08 dBm
2R	(1)	Freq	2.428 25 GHz	-9.64 dBm
2Δ	(1)	Freq	17.17 MHz	0.36 dB

6dB Bandwidth (CH High)

Agilent 10:54:33 Mar 7, 2011

R T

Δ Mkr2 17.17 MHz
0.34 dB



Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.457 00 GHz	-3.99 dBm
2R	(1)	Freq	2.453 33 GHz	-11.08 dBm
2Δ	(1)	Freq	17.17 MHz	0.34 dB




IEEE 802.11n HT 40 MHz mode / Chain 0

6dB Bandwidth (CH Low)

Agilent 11:03:11 Mar 7, 2011

R T

Δ Mkr2 35.25 MHz
-1.39 dB




6dB Bandwidth (CH Mid)

Agilent 11:02:26 Mar 7, 2011

R T

Δ Mkr2 35.17 MHz
-1.00 dB






6dB Bandwidth (CH High)

Agilent 11:01:23 Mar 7, 2011

R T

Δ Mkr2 35.17 MHz
-3.33 dB



Center 2.452 00 GHz Span 50 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.447 00 GHz	-11.85 dBm
2R	(1)	Freq	2.434 42 GHz	-17.98 dBm
2Δ	(1)	Freq	35.17 MHz	-3.33 dB

IEEE 802.11n HT 40 MHz mode / Chain 1

6dB Bandwidth (CH Low)

Agilent 10:58:36 Mar 7, 2011

R T

Δ Mkr2 35.25 MHz
3.18 dB



Center 2.422 00 GHz Span 50 MHz
#Res BW 100 kHz #VBW 100 kHz Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.413 25 GHz	-5.90 dBm
2R	(1)	Freq	2.404 33 GHz	-14.52 dBm
2Δ	(1)	Freq	35.25 MHz	3.18 dB



6dB Bandwidth (CH Mid)


Agilent 10:59:25 Mar 7, 2011

R T

Δ Mkr2 35.17 MHz
1.17 dB

Ref 15.43 dBm

Atten 20 dB



Center 2.437 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.432 00 GHz	-6.35 dBm
2R	(1)	Freq	2.419 33 GHz	-14.18 dBm
2Δ	(1)	Freq	35.17 MHz	1.17 dB

6dB Bandwidth (CH High)


Agilent 11:00:16 Mar 7, 2011

R T

Δ Mkr2 35.25 MHz
1.40 dB

Ref 15.43 dBm

Atten 20 dB



Center 2.452 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

Marker	Trace	Type	X Axis	Amplitude
1	(1)	Freq	2.444 50 GHz	-6.86 dBm
2R	(1)	Freq	2.434 33 GHz	-14.98 dBm
2Δ	(1)	Freq	35.25 MHz	1.40 dB




8.3 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. According to RSS-210 §A8.4(4), for systems employing digital modulation techniques operating in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz, the maximum peak conducted output power shall not exceed 1 W.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

**Peak Power Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	17.64	0.0581	1.00	PASS
Mid	2437	23.28	0.2128		PASS
High	2462	17.72	0.0592		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	18.11	0.0647	1.00	PASS
Mid	2437	22.81	0.1910		PASS
High	2462	17.92	0.0619		PASS

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	14.86	14.93	17.91	0.0617	0.6310	PASS
Mid	2437	18.91	18.92	21.93	0.1558		PASS
High	2462	14.83	14.86	17.86	0.0610		PASS

Test mode: IEEE 802.11n HT 40 MHz mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2422	14.61	14.93	17.78	0.0600	0.6310	PASS
Mid	2437	18.82	18.82	21.83	0.1524		PASS
High	2452	14.72	14.75	17.75	0.0595		PASS

Remark: 1. Total Output Power (w) = Chain 0 (10^{^(Output Power /10)/1000}) + Chain 1 (10^{^(Output Power /10)/1000})
 2. The maximum antenna gain is 7.33dBi; therefore the reduction due to antenna gain is 2dBi, so the limit is 28dBm




8.4 AVERAGE POWER

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

**Average Power Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	15.14	0.0327
Mid	2437	19.73	0.0940
High	2462	15.16	0.0328

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	8.19	0.0066
Mid	2437	12.69	0.0186
High	2462	8.27	0.0067

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)
Low	2412	4.87	5.17	8.03
Mid	2437	9.23	8.91	12.08
High	2462	5.15	5.04	8.11

Test mode: IEEE 802.11n HT 40 MHz mode

Channel	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)
Low	2422	3.59	4.05	6.84
Mid	2437	7.68	7.68	10.69
High	2452	3.68	3.74	6.72

Remark: Total Output Power (w) = Chain 0 ($10^{(Output Power / 10) / 1000}$) + Chain 1 ($10^{(Output Power / 10) / 1000}$)




8.5 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d) & RSS-210 §A8.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.


The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

TEST RESULTS

No non-compliance noted.



Band Edges (IEEE 802.11b mode / CH Low)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2399.5000	-35.20	-13.97	-21.23
2	2411.5000	6.03	-13.97	20.00




Band Edges (IEEE 802.11b mode / CH High)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2461.4700	5.92	-14.08	20.00
2	2519.9300	-52.94	-14.08	-38.86




Band Edges (IEEE 802.11g mode / CH Low)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2400.0000	-38.88	-23.08	-15.80
2	2407.0000	-3.08	-23.08	20.00




Band Edges (IEEE 802.11g mode / CH High)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2457.0300	-2.97	-22.97	20.00
2	2483.5467	-48.56	-22.97	-25.59




Band Edges (IEEE 802.11n HT 20 MHz mode/ CH Low)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2399.8750	-41.05	-26.43	-14.62
2	2407.0000	-6.43	-26.43	20.00




Band Edges (IEEE 802.11n HT 20 MHz mode/ CH High)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2457.0300	-6.33	-26.33	20.00
2	2486.6300	-51.65	-26.33	-25.32




Band Edges (IEEE 802.11n HT 40 MHz mode / CH Low)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2398.2500	-42.32	-29.90	-12.42
2	2417.0000	-9.90	-29.90	20.00



Band Edges (IEEE 802.11n HT 40 MHz mode / CH High)



No.	Frequency(MHz)	Level(dBm)	Limit(dBm)	Margin(dBm)
1	2455.6733	-10.28	-30.28	20.00
2	2520.0533	-53.22	-30.28	-22.94




8.6 PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e) & RSS-210 §A8.2, for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f) & RSS-210 §A8.3, the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 300 kHz, Sweep time = 100 s
3. Record the max reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-7.11	8.00	PASS
Mid	2437	0.35		PASS
High	2462	-10.72		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-17.73	8.00	PASS
Mid	2437	-13.71		PASS
High	2462	-17.54		PASS

Test mode: IEEE 802.11n HT 20 MHz mode Channel mode

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-22.69	-22.00	-19.32	6.00	PASS
Mid	2437	-18.32	-18.57	-15.43		PASS
High	2462	-22.38	-21.52	-18.92		PASS

Test mode: IEEE 802.11n HT 40 MHz mode

Channel	Frequency (MHz)	Chain 0 PPSD (dBm)	Chain 1 PPSD (dBm)	PPSD (dBm)	Limit (dBm)	Result
Low	2422	-25.68	-25.44	-22.55	6.00	PASS
Mid	2437	-21.47	-21.80	-18.62		PASS
High	2452	-25.59	-23.78	-21.58		PASS

Remark: 1. Total PPSD (dBm) = $10 * \text{LOG}(10^{\wedge}(\text{Chain 0 PPSD} / 10) + 10^{\wedge}(\text{Chain 1 PPSD} / 10))$

2. The maximum antenna gain is 7.33dBi; therefore the reduction due to antenna gain is 2dBi, so the limit is 6dBm



Test mode: IEEE 802.11n HT 20 MHz mode with combiner

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-22.33	6.00	PASS
Mid	2437	-18.27		PASS
High	2462	-22.20		PASS

Test mode: IEEE 802.11n HT 40 MHz mode with combiner

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2422	-25.52	6.00	PASS
Mid	2437	-21.42		PASS
High	2452	-23.92		PASS

Remark:

1. The maximum antenna gain is 7.33dBi; therefore the reduction due to antenna gain is 2dBi, so the limit is 6dBm



Test Plot


IEEE 802.11b mode

PPSD (CH Low)

Agilent 14:59:09 Feb 23, 2010

R T

Mkr1 2.415 545 5 GHz
-7.11 dBm




PPSD (CH Mid)

Agilent 15:10:59 Feb 23, 2010

R T

Mkr1 2.437 420 6 GHz
0.35 dBm






PPSD (CH High)

Agilent 15:15:37 Feb 23, 2010

R T

Mkr1 2.462 172 6 GHz
-10.72 dBm




IEEE 802.11g mode

PPSD (CH Low)

Agilent 15:20:42 Feb 23, 2010

R T

Mkr1 2.412 608 0 GHz
-17.73 dBm






PPSD (CH Mid)

Agilent 15:24:33 Feb 23, 2010

R T

Mkr1 2.431 942 5 GHz
-13.71 dBm




PPSD (CH High)

Agilent 15:28:27 Feb 23, 2010

R T

Mkr1 2.462 607 5 GHz
-17.54 dBm






IEEE 802.11n HT 20 MHz mode Channel mode / Chain 0

PPSD (CH Low)

Agilent 15:33:15 Feb 23, 2010

R T

Mkr1 2.414 468 1 GHz
-22.69 dBm




PPSD (CH Mid)

Agilent 15:37:12 Feb 23, 2010

R T

Mkr1 2.434 487 9 GHz
-18.32 dBm






PPSD (CH High)

Agilent 15:40:30 Feb 23, 2010

R T

Mkr1 2.457 965 1 GHz
-22.38 dBm




IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

PPSD (CH Low)

Agilent 15:49:35 Feb 23, 2010

R T

Mkr1 2.410 417 1 GHz
-22.00 dBm






PPSD (CH Mid)

Agilent 15:53:54 Feb 23, 2010

R T

Mkr1 2.439 467 1 GHz
-18.57 dBm




PPSD (CH High)

Agilent 15:57:31 Feb 23, 2010

R T

Mkr1 2.464 467 1 GHz
-21.52 dBm





IEEE 802.11n HT 40 MHz mode / Chain 0


PPSD (CH Low)

Agilent 16:02:38 Feb 23, 2010

R T

Mkr1 2.417 613 1 GHz

-25.68 dBm




PPSD (CH Mid)

Agilent 16:06:12 Feb 23, 2010

R T

Mkr1 2.432 613 0 GHz

-21.47 dBm






PPSD (CH High)

Agilent 16:09:35 Feb 23, 2010

R L

Mkr1 2.450 434 9 GHz
-25.59 dBm




IEEE 802.11n HT 40 MHz mode / Chain 1

PPSD (CH Low)

Agilent 16:16:44 Feb 23, 2010

R L

Mkr1 2.420 434 4 GHz
-25.44 dBm






PPSD (CH Mid)

Agilent 16:22:45 Feb 23, 2010

R T

Mkr1 2.432 612 0 GHz
-21.80 dBm




PPSD (CH High)

Agilent 16:28:30 Feb 23, 2010

R T

Mkr1 2.449 433 4 GHz
-23.78 dBm





IEEE 802.11n HT 20 MHz mode with combiner


PPSD (CH Low)

Agilent 17:13:00 Feb 23, 2010

R T

Mkr1 2.415 715 1 GHz

-22.33 dBm




PPSD (CH Mid)

Agilent 17:17:49 Feb 23, 2010

R T

Mkr1 2.439 468 1 GHz

-18.27 dBm






PPSD (CH High)

Agilent 17:22:24 Feb 23, 2010

R T

Mkr1 2.459 167 6 GHz
-22.20 dBm




IEEE 802.11n HT 40 MHz mode with combiner

PPSD (CH Low)

Agilent 16:59:28 Feb 23, 2010

R L

Mkr1 2.417 613 6 GHz
-25.52 dBm






PPSD (CH Mid)

Agilent 17:06:29 Feb 23, 2010

R T

Mkr1 2.432 613 0 GHz
-21.42 dBm




PPSD (CH High)

Agilent 17:09:25 Feb 23, 2010

R T

Mkr1 2.449 433 4 GHz
-23.92 dBm






8.7 SPURIOUS EMISSIONS

8.7.1 Conducted Measurement

LIMIT

According to §15.247(d) & RSS-210 §A8.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




CH High

Agilent 15:16:21 Feb 23, 2010

R T

Mkr1 2.47 GHz
3.59 dBm




IEEE 802.11g mode

CH Low

Agilent 15:21:16 Feb 23, 2010

R T

Mkr1 2.42 GHz
-6.93 dBm






CH Mid

Agilent 15:25:04 Feb 23, 2010

R L

Mkr1 2.45 GHz
-2.27 dBm




Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)

CH High

Agilent 15:29:09 Feb 23, 2010

R T

Mkr1 2.47 GHz
-6.47 dBm



Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)




CH High

Agilent 15:41:05 Feb 23, 2010

R T

Mkr1 2.45 GHz
-10.73 dBm




IEEE 802.11n HT 20 MHz mode Channel mode / Chain 1

CH Low

Agilent 15:50:10 Feb 23, 2010

R T

Mkr1 2.42 GHz
-10.21 dBm






CH Mid

Agilent 15:54:25 Feb 23, 2010

R T

Mkr1 2.45 GHz
-6.94 dBm




CH High

Agilent 15:58:06 Feb 23, 2010

R L

Mkr1 2.47 GHz
-8.75 dBm






CH High

Agilent 16:10:07 Feb 23, 2010

R L

Mkr1 2.45 GHz
-13.54 dBm




IEEE 802.11n HT 40 MHz mode / Chain 1

CH Low

Agilent 16:17:21 Feb 23, 2010

R T

Mkr1 2.42 GHz
-13.46 dBm






CH Mid

Agilent 16:23:30 Feb 23, 2010

R L

Mkr1 2.45 GHz
-8.56 dBm




CH High

Agilent 16:29:13 Feb 23, 2010

R T

Mkr1 2.45 GHz
-12.26 dBm






CH High

Agilent 17:22:55 Feb 23, 2010

R T

Mkr1 2.45 GHz
-9.82 dBm



Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)


IEEE 802.11n HT 40 MHz mode with combiner

CH Low

Agilent 17:00:04 Feb 23, 2010

R T

Mkr1 2.42 GHz
-14.34 dBm



Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)




CH Mid

Agilent 17:07:01 Feb 23, 2010

R T

Mkr1 2.42 GHz
-9.90 dBm




Center 13.02 GHz
#Res BW 100 kHz
#VBW 100 kHz
Span 25.97 GHz
Sweep 3.131 s (1001 pts)

CH High

Agilent 17:10:07 Feb 23, 2010

R L

Mkr1 2.45 GHz
-10.54 dBm



Center 13.02 GHz
#Res BW 100 kHz
#VBW 100 kHz
Span 25.97 GHz
Sweep 3.131 s (1001 pts)



8.8 RADIATED EMISSIONS

LIMIT

1. According to §15.205, 209(a) & RSS-210 Clause 2.6 (Transmitter) and IC RSS-GEN Clause 6 (Receiver), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




Test Configuration

9kHz ~ 30MHz




30MHz ~ 1GHz





Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

**Below 1GHz****Operation Mode:** Normal Link**Test Date:** March 2, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
152.87	48.79	-10.32	38.48	43.50	-5.02	Peak	V
249.87	48.81	-10.90	37.91	46.00	-8.09	Peak	V
408.30	44.05	-6.89	37.16	46.00	-8.84	Peak	V
500.45	43.50	-5.14	38.36	46.00	-7.64	Peak	V
534.40	41.92	-4.68	37.24	46.00	-8.76	Peak	V
660.50	41.78	-2.82	38.96	46.00	-7.04	Peak	V
962.82	36.57	0.49	37.06	54.00	-16.94	Peak	V
156.10	31.86	-10.42	21.44	43.50	-22.06	QP	H
249.87	50.94	-10.90	40.03	46.00	-5.97	Peak	H
321.00	46.18	-8.74	37.44	46.00	-8.56	Peak	H
500.45	40.11	-5.14	34.96	46.00	-11.04	Peak	H
586.13	43.70	-4.17	39.53	46.00	-6.47	Peak	H
660.50	44.20	-2.82	41.39	46.00	-4.61	Peak	H

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

**Above 1 GHz****Operation Mode:** TX / IEEE 802.11b / CH Low**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1430.00	58.79	---	-10.62	48.17	---	74.00	54.00	-5.83	Peak	V
4825.00	52.46	49.83	2.61	55.07	52.44	74.00	54.00	-1.56	AVG	V
2310-2390	-	-	-	-	-	-	-	-	-	V
N/A										
1313.33	59.22	---	-10.74	48.47	---	74.00	54.00	-5.53	Peak	H
4825.00	51.45	48.43	2.61	54.06	51.04	74.00	54.00	-2.96	AVG	H
2310-2390	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.

**Operation Mode:** TX / IEEE 802.11b / CH Mid**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1186.67	58.87	---	-10.88	47.99	---	74.00	54.00	-6.01	Peak	V
4875.00	51.19	45.63	2.71	53.90	48.34	74.00	54.00	-5.66	AVG	V
5200.00	47.18	---	2.95	50.13	---	74.00	54.00	-3.87	Peak	V
7308.33	44.08	---	7.23	51.31	---	74.00	54.00	-2.69	Peak	V
N/A										
1103.33	58.66	---	-10.96	47.70	---	74.00	54.00	-6.30	Peak	H
4875.00	52.00	49.49	2.71	54.71	52.20	74.00	54.00	-1.80	AVG	H
5200.00	48.64	---	2.95	51.59	---	74.00	54.00	-2.41	Peak	H
7308.33	49.94	45.24	7.23	57.17	52.47	74.00	54.00	-1.53	AVG	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11b / CH High**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1176.67	58.33	---	-10.89	47.45	---	74.00	54.00	-6.55	Peak	V
4925.00	50.91	46.87	2.81	53.72	49.68	74.00	54.00	-4.32	AVG	V
2483.5-2500	-	-	-	-	-	-	-	-	-	V
N/A										
1326.67	58.41	---	-10.73	47.68	---	74.00	54.00	-6.32	Peak	H
5200.00	50.56	44.03	2.95	53.51	46.98	74.00	54.00	-7.02	AVG	H
2483.5-2500	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.

**Operation Mode:** TX / IEEE 802.11g / CH Low**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1360.00	58.91	---	-10.70	48.22	---	74.00	54.00	-5.78	Peak	V
3366.67	51.18	---	-1.20	49.98	---	74.00	54.00	-4.02	AVG	V
5200.00	50.77	43.90	2.95	53.72	46.85	74.00	54.00	-7.15	AVG	V
2310-2390	-	-	-	-	-	-	-	-	-	V
N/A										
1360.00	58.36	---	-10.70	47.66	---	74.00	54.00	-6.34	Peak	H
3375.00	50.22	---	-1.18	49.04	---	74.00	54.00	-4.96	AVG	H
4116.67	50.46	---	0.83	51.29	---	74.00	54.00	-2.71	AVG	H
5200.00	50.05	44.30	2.95	53.00	47.25	74.00	54.00	-6.75	AVG	H
2310-2390	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.

**Operation Mode:** TX / IEEE 802.11g / CH Mid**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1573.33	59.02	---	-9.80	49.21	---	74.00	54.00	-4.79	Peak	V
3908.33	48.94	---	0.24	49.18	---	74.00	54.00	-4.82	AVG	V
N/A										
1433.33	58.34	---	-10.62	47.72	---	74.00	54.00	-6.28	Peak	H
3366.67	51.55	---	-1.20	50.35	---	74.00	54.00	-3.65	Peak	H
5200.00	51.25	44.71	2.95	54.20	47.66	74.00	54.00	-6.34	AVG	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11g / CH High**Test Date:** March 1, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1123.33	58.59	---	-10.94	47.65	---	74.00	54.00	-6.35	Peak	V
3333.33	51.44	---	-1.29	50.15	---	74.00	54.00	-3.85	Peak	V
3383.33	52.77	---	-1.16	51.61	---	74.00	54.00	-2.39	Peak	V
2483.5-2500	-	-	-	-	-	-	-	-	-	V
N/A										
1430.00	58.09	---	-10.62	47.46	---	74.00	54.00	-6.54	Peak	H
3383.33	53.26	---	-1.16	52.11	---	74.00	54.00	-1.89	Peak	H
2483.5-2500	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.



Operation Mode: TX / IEEE 802.11n HT 20 MHz mode Channel mode / CH Low

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1210.00	58.53	---	-10.85	47.68	---	74.00	54.00	-6.32	Peak	V
3350.00	53.47	---	-1.25	52.22	---	74.00	54.00	-1.78	AVG	V
2310-2390	-	-	-	-	-	-	-	-	-	V
N/A										
1330.00	59.04	---	-10.73	48.32	---	74.00	54.00	-5.68	Peak	H
5200.00	50.60	44.50	2.95	53.55	47.45	74.00	54.00	-6.55	AVG	H
2310-2390	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.



Operation Mode: TX / IEEE 802.11n HT 20 MHz mode Channel mode / CH Mid

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1330.00	59.04	---	-10.73	48.31	---	74.00	54.00	-5.69	Peak	V
3383.33	51.42	---	-1.16	50.26	---	74.00	54.00	-3.74	AVG	V
N/A										
1260.00	58.57	---	-10.80	47.77	---	74.00	54.00	-6.23	Peak	H
5200.00	50.84	44.19	2.95	53.79	47.14	74.00	54.00	-6.86	AVG	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11n HT 20 MHz mode Channel mode / CH High

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1176.67	58.46	---	-10.89	47.57	---	74.00	54.00	-6.43	Peak	V
3375.00	52.32	---	-1.18	51.14	---	74.00	54.00	-2.86	AVG	V
4891.67	50.71	35.78	2.74	53.45	38.52	74.00	54.00	-15.48	AVG	V
2483.5-2500	-	-	-	-	-	-	-	-	-	V
N/A										
1036.67	59.56	---	-11.03	48.53	---	74.00	54.00	-5.47	Peak	H
5200.00	51.02	45.85	2.95	53.97	48.80	74.00	54.00	-5.20	AVG	H
2483.5-2500	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.



Operation Mode: TX / IEEE 802.11n HT 40 MHz mode
/ CH Low

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1176.67	59.50	---	-10.89	48.62	---	74.00	54.00	-5.38	Peak	V
3350.00	52.02	---	-1.25	50.77	---	74.00	54.00	-3.23	AVG	V
2310-2390	-	-	-	-	-	-	-	-	-	V
N/A										
1396.67	58.45	---	-10.66	47.79	---	74.00	54.00	-6.21	Peak	H
3375.00	51.26	---	-1.18	50.08	---	74.00	54.00	-3.92	AVG	H
5200.00	51.81	47.67	2.95	54.76	50.62	74.00	54.00	-3.38	AVG	H
2310-2390	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.



Operation Mode: TX / IEEE 802.11n HT 40 MHz mode
/ CH Mid

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1580.00	58.84	---	-9.74	49.11	---	74.00	54.00	-4.89	Peak	V
3391.67	51.46	---	-1.14	50.32	---	74.00	54.00	-3.68	AVG	V
N/A										
1350.00	58.37	---	-10.71	47.66	---	74.00	54.00	-6.34	Peak	H
3383.33	50.09	---	-1.16	48.93	---	74.00	54.00	-5.07	AVG	H
5200.00	50.85	45.85	2.95	53.80	48.80	74.00	54.00	-5.20	AVG	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: TX / IEEE 802.11n HT 40 MHz mode
/ CH High

Test Date: March 1, 2011

Temperature: 24°C

Tested by: Tom Jen

Humidity: 48 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1716.67	58.70	---	-8.35	50.35	---	74.00	54.00	-3.65	Peak	V
3366.67	53.41	---	-1.20	52.21	---	74.00	54.00	-1.79	AVG	V
5200.00	50.34	46.22	2.95	53.30	49.17	74.00	54.00	-4.83	AVG	V
2483.5-2500	-	-	-	-	-	-	-	-	-	V
N/A										
1223.33	58.13	---	-10.84	47.30	---	74.00	54.00	-6.70	Peak	H
3358.33	51.35	---	-1.22	50.12	---	74.00	54.00	-3.88	AVG	H
5200.00	51.90	47.55	2.95	54.85	50.50	74.00	54.00	-3.50	AVG	H
2483.5-2500	-	-	-	-	-	-	-	-	-	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).
7. Data of measurement within this frequency range shown " - " in the table above means the radiated emissions at the band-edges have been investigated and there is no significant emissions.

**Operation Mode:** RX / IEEE 802.11g / CH Mid**Test Date:** March 2, 2011**Temperature:** 24°C**Tested by:** Tom Jen**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1186.67	55.71	---	-10.88	44.84	---	74.00	54.00	-9.16	Peak	V
1576.67	57.36	---	-9.77	47.59	---	74.00	54.00	-6.41	Peak	V
N/A										
1226.67	53.41	---	-10.83	42.57	---	74.00	54.00	-11.43	Peak	H
3416.67	50.04	-	-1.07	48.97	-	74.00	54.00	-5.03	Peak	H
5200.00	51.43	43.45	2.95	54.39	46.40	74.00	54.00	-7.60	AVG	H
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



8.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a) & RSS-Gen §7.2.2, except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link **Test Date:** 2011/2/22
Temperature: 24°C **Tested by:** Howard Pang
Humidity: 60% RH

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Note
0.1730	22.26	10.85	33.11	54.81	-21.70	AVG	L1
0.1740	42.63	10.84	53.47	64.76	-11.29	QP	L1
0.1900	40.97	10.81	51.78	64.03	-12.25	QP	L1
0.1903	20.22	10.81	31.03	54.02	-22.99	AVG	L1
0.2340	37.45	10.75	48.20	62.30	-14.10	QP	L1
0.2340	15.20	10.75	25.95	52.30	-26.35	AVG	L1
0.3140	34.30	10.68	44.98	59.86	-14.88	QP	L1
0.3140	25.77	10.68	36.45	49.86	-13.41	AVG	L1
0.3540	34.28	10.65	44.93	58.87	-13.94	QP	L1
0.3540	16.45	10.65	27.10	48.87	-21.77	AVG	L1
2.5740	30.28	10.62	40.90	56.00	-15.10	QP	L1
2.5820	13.95	10.62	24.57	46.00	-21.43	AVG	L1
0.2481	19.76	10.59	30.35	51.82	-21.47	AVG	L2
0.2500	45.44	10.59	56.03	61.75	-5.72	QP	L2
0.2980	44.12	10.56	54.68	60.30	-5.62	QP	L2
0.2980	24.16	10.56	34.72	50.30	-15.58	AVG	L2
0.3379	39.59	10.53	50.12	59.25	-9.13	QP	L2
0.3379	23.00	10.53	33.53	49.25	-15.72	AVG	L2
0.3940	43.25	10.51	53.76	57.98	-4.22	QP	L2
0.3940	18.20	10.51	28.71	47.98	-19.27	AVG	L2
0.4300	39.76	10.53	50.29	57.25	-6.96	QP	L2
0.4300	12.40	10.53	22.93	47.25	-24.32	AVG	L2
0.6660	35.08	10.54	45.62	56.00	-10.38	QP	L2
0.6660	12.49	10.54	23.03	46.00	-22.97	AVG	L2

Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)



Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)

