

FCC RADIO TEST REPORT

Applicant's company	Belkin International, Inc.
Applicant Address	12045 East Waterfront Drive, Playa Vista, CA 90094, USA
FCC ID	K7SF9K1002V2

Product Name	N300
Brand Name	Belkin
Model Name	F9K1002v2
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Dec. 31, 2010
Final Test Date	May 05, 2011
Submission Type	Original Equipment



Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

.1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting	7
3.9. Test Configurations	9
4. TEST RESULT	11
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Peak Output Power Measurement	19
4.3. Power Spectral Density Measurement	23
4.4. 6dB Spectrum Bandwidth Measurement	28
4.5. Radiated Emissions Measurement	33
4.6. Band Edge Emissions Measurement	53
4.7. Antenna Requirements	62
5. LIST OF MEASURING EQUIPMENTS	63
6. TEST LOCATION.....	65
7. TAF CERTIFICATE OF ACCREDITATION	66
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A13
APPENDIX B. TEST PHOTOS.....	B1 ~ B6
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C3

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR111229	Rev. 01	Initial issue of report	Feb. 24, 2011
FR111229	Rev. 02	For client's request, test results for all test modes should be recorded in the report. Add test data of Mode 2 in the report.	May 13, 2011



1. CERTIFICATE OF COMPLIANCE

Product Name : N300
Brand Name : Belkin
Model Name : F9K1002v2
Applicant : Belkin International, Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 31, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Jordan Hsiao 2011.5.17

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	2.89 dB
4.2	15.247(b)(3)	Peak Conducted Output Power	Complies	0.35 dB
4.3	15.247(e)	Power Spectral Density	Complies	3.63 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.30 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.15 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adpater
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 17.48 MHz ; MCS0 (40MHz): 35.92 MHz
Conducted Output Power	MCS0 (20MHz): 29.65 dBm ; MCS0 (40MHz): 29.53 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11b/g

Items	Description
Product Type	WLAN (1TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adpater
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11b/g: 11
Channel Band Width (99%)	11b: 14.68 MHz ; 11g: 16.40 MHz
Conducted Output Power	11b: 27.07 dBm ; 11g: 28.14 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	V

IEEE 802.11n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	DVE	DSA-9PFB-09 FUS 090100	Input: 100-240VAC, 50/60Hz, 0.3A Output: 9VDC, 1.0A
Adapter 2	LEI	MT12-Y090100-A1	Input: 120VAC, 60Hz, 0.3A Output: 9VDC, 1.0A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Antenna Gain
1	Arcadyan	N/A	PCB antenna	I-PEX	4.5
2	Arcadyan	N/A	PCB antenna	I-PEX	4.5

Note: The EUT has two antennas. The EUT supports the antenna with TX diversity function.


For IEEE 802.11bg Mode (1TX/2RX):

Ant. 1 could transmit/receive simultaneously.

Ant. 1 & Ant. 2 could receive simultaneously.

For IEEE 802.11n Mode (2TX/2RX):

Ant. 1 & Ant. 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Peak Output Power	MCS0/20MHz	7.2 Mbps	1/6/11	1 / 2 / 1+2
	MCS0/40MHz	15 Mbps	3/6/9	1 / 2 / 1+2
	11b/BPSK	1 Mbps	1/6/11	1 / 2 / 1+2
	11g/BPSK	6 Mbps	1/6/11	1 / 2 / 1+2
Power Spectral Density 6dB Spectrum Bandwidth	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	MCS0/40MHz	15 Mbps	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Radiated Emissions 9kHz~1GHz	CTX	6 Mbps	-	-
Radiated Emissions 1GHz~10 th Harmonic	MCS0/20MHz	7.2 Mbps	1/6/11	1+2
	MCS0/40MHz	15 Mbps	3/6/9	1+2
	11b/BPSK	1 Mbps	1/6/11	1+2
	11g/BPSK	6 Mbps	1/6/11	1+2
Band Edge Emissions	MCS0/20MHz	7.2 Mbps	1/11	1+2
	MCS0/40MHz	15 Mbps	3/9	1+2
	11b/BPSK	1 Mbps	1/11	1+2
	11g/BPSK	6 Mbps	1/11	1+2

Note:

All the test modes are list as below:

Test Mode 1: EUT with adapter 1

Test Mode 2: EUT with adapter 2

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	187376	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	187376	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	QA 1.0.2.4		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n 20MHz, Ant. 1 / Ant. 2	14/14	17/16	17/17

Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	QA 1.0.2.4		
Frequency	2422 MHz	2437 MHz	2452 MHz
IEEE 802.11n 40MHz, Ant. 1 / Ant. 2	0D/0F	0E/10	0E/10

Power Parameters of IEEE 802.11b

Test Software Version	QA 1.0.2.4		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b, Ant. 1	17	11	14

Power Parameters of IEEE 802.11g


Test Software Version	QA 1.0.2.4		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g, Ant. 1	15	15	17


At the same time, "QA 1.0.2.4" was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration

Test Configuration: 9KHz~1GHz





AC MAIN

1

EUT

2

Notebook

RJ-11 RJ-45 LPT PS/2 USB DC USB 2.0

1. POWER CABLE, 146 CM, NON-SHIELDED
2. RJ-45 CABLE, 1000 CM, NON-SHIELDED

[illegible]

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50


4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.



- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Line
Configuration	CTX / Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15650	34.98	-20.67	55.65	34.71	0.07	0.20	AVERAGE
2	0.15650	50.10	-15.55	65.65	49.83	0.07	0.20	QP
3	0.19242	45.38	-18.55	63.93	45.13	0.05	0.20	QP
4	0.19242	29.73	-24.20	53.93	29.48	0.05	0.20	AVERAGE
5	0.22319	20.26	-32.44	52.70	20.01	0.05	0.20	AVERAGE
6	0.22319	39.80	-22.90	62.70	39.55	0.05	0.20	QP
7	0.26724	38.72	-22.48	61.20	38.48	0.04	0.20	QP
8	0.26724	24.27	-26.93	51.20	24.03	0.04	0.20	AVERAGE
9	0.37545	43.01	-15.37	58.38	42.78	0.03	0.20	QP
10	0.37545	28.00	-20.38	48.38	27.77	0.03	0.20	AVERAGE
11	8.729	29.83	-30.17	60.00	29.22	0.31	0.30	QP
12	8.729	20.22	-29.78	50.00	19.61	0.31	0.30	AVERAGE

Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	CTX / Mode 1		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15485	38.99	-16.74	55.74	38.69	0.10	0.20	AVERAGE
2	0.15485	49.70	-16.03	65.74	49.40	0.10	0.20	QP
3	0.32512	38.57	-11.00	49.57	38.30	0.07	0.20	AVERAGE
4	0.32512	42.34	-17.23	59.57	42.07	0.07	0.20	QP
5	0.38113	45.36	-2.89	48.25	45.09	0.07	0.20	AVERAGE
6	0.38113	50.44	-7.81	58.25	50.17	0.07	0.20	QP
7	0.48890	29.96	-16.22	46.19	29.78	0.07	0.11	AVERAGE
8	0.48890	37.56	-18.62	56.19	37.38	0.07	0.11	QP
9	0.54644	37.30	-18.70	56.00	37.03	0.07	0.20	QP
10	0.54644	30.54	-15.46	46.00	30.27	0.07	0.20	AVERAGE
11	0.72744	37.74	-18.26	56.00	37.47	0.07	0.20	QP
12	0.72744	32.49	-13.51	46.00	32.22	0.07	0.20	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.


Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Line
Configuration	CTX / Mode 2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 @	0.17866	57.13	-7.42	64.55	56.87	0.06	0.20	QP
2	0.17866	39.70	-14.85	54.55	39.44	0.06	0.20	AVERAGE
3	0.23910	53.42	-8.70	62.13	53.18	0.04	0.20	QP
4	0.23910	40.62	-11.50	52.13	40.38	0.04	0.20	AVERAGE
5	0.27009	32.52	-18.59	51.12	32.28	0.04	0.20	AVERAGE
6	0.27009	46.85	-14.26	61.12	46.61	0.04	0.20	QP
7	0.29712	36.43	-13.89	50.32	36.19	0.04	0.20	AVERAGE
8 @	0.29712	53.70	-6.62	60.32	53.46	0.04	0.20	QP
9	0.35201	46.48	-12.43	58.91	46.25	0.03	0.20	QP
10	0.35201	30.98	-17.93	48.91	30.75	0.03	0.20	AVERAGE
11	0.41705	48.61	-8.90	57.51	48.38	0.03	0.20	QP
12	0.41705	35.13	-12.38	47.51	34.90	0.03	0.20	AVERAGE
13	0.47110	44.21	-12.28	56.49	43.98	0.03	0.20	QP
14	0.47110	31.43	-15.06	46.49	31.20	0.03	0.20	AVERAGE
15	0.53782	47.51	-8.49	56.00	47.28	0.03	0.20	QP
16	0.53782	34.48	-11.52	46.00	34.25	0.03	0.20	AVERAGE
17	0.65430	47.06	-8.94	56.00	46.83	0.03	0.20	QP
18	0.65430	32.84	-13.16	46.00	32.61	0.03	0.20	AVERAGE
19	0.77519	46.15	-9.85	56.00	45.92	0.03	0.20	QP
20	0.77519	31.59	-14.41	46.00	31.36	0.03	0.20	AVERAGE
21	0.88969	44.77	-11.23	56.00	44.54	0.03	0.20	QP
22	0.88969	29.75	-16.25	46.00	29.52	0.03	0.20	AVERAGE
23	1.021	43.60	-12.40	56.00	43.37	0.03	0.20	QP

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
24	1.021	27.13	-18.87	46.00	26.90	0.03	0.20	AVERAGE
25	7.526	42.52	-17.48	60.00	41.85	0.27	0.40	QP
26	7.526	30.35	-19.65	50.00	29.68	0.27	0.40	AVERAGE

Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	CTX / Mode 2		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17772	42.36	-12.23	54.59	42.07	0.09	0.20	AVERAGE
2	0.17772	58.41	-6.18	64.59	58.12	0.09	0.20	QP
3	0.18938	55.76	-8.30	64.06	55.48	0.08	0.20	QP
4	0.18938	43.19	-10.87	54.06	42.91	0.08	0.20	AVERAGE
5	0.20075	45.86	-7.72	53.58	45.58	0.08	0.20	AVERAGE
6	0.20075	57.58	-6.00	63.58	57.30	0.08	0.20	QP
7	0.23784	42.83	-9.34	52.17	42.55	0.08	0.20	AVERAGE
8	0.23784	57.93	-4.24	62.17	57.65	0.08	0.20	QP
9	0.26866	41.25	-9.91	51.16	40.97	0.08	0.20	AVERAGE
10	0.26866	52.50	-8.66	61.16	52.22	0.08	0.20	QP
11	0.29869	40.40	-9.87	50.28	40.13	0.07	0.20	AVERAGE
12	0.29869	52.79	-7.48	60.28	52.52	0.07	0.20	QP
13	0.35388	52.93	-5.94	58.87	52.66	0.07	0.20	QP
14	0.35388	37.35	-11.52	48.87	37.08	0.07	0.20	AVERAGE
15	0.39344	36.47	-11.52	47.99	36.20	0.07	0.20	AVERAGE
16	0.39344	47.87	-10.12	57.99	47.60	0.07	0.20	QP
17	0.41485	51.83	-5.72	57.55	51.56	0.07	0.20	QP
18	0.41485	37.98	-9.57	47.55	37.71	0.07	0.20	AVERAGE
19	0.43742	46.75	-10.36	57.11	46.48	0.07	0.20	QP
20	0.43742	35.08	-12.03	47.11	34.81	0.07	0.20	AVERAGE
21	0.48119	44.50	-11.82	56.32	44.33	0.07	0.10	QP
22	0.48119	33.78	-12.54	46.32	33.61	0.07	0.10	AVERAGE
23	0.51007	31.44	-14.56	46.00	31.17	0.07	0.20	AVERAGE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
24	0.51007	43.97	-12.03	56.00	43.70	0.07	0.20	QP
25	0.53498	51.16	-4.84	56.00	50.89	0.07	0.20	QP
26	0.53498	38.28	-7.72	46.00	38.01	0.07	0.20	AVERAGE
27	0.59164	46.61	-9.39	56.00	46.34	0.07	0.20	QP
28	0.59164	36.04	-9.96	46.00	35.77	0.07	0.20	AVERAGE
29	0.65084	51.16	-4.84	56.00	50.89	0.07	0.20	QP
30	0.65084	35.18	-10.82	46.00	34.91	0.07	0.20	AVERAGE
31	0.76610	48.01	-7.99	56.00	47.74	0.07	0.20	QP
32	0.76610	32.73	-13.27	46.00	32.46	0.07	0.20	AVERAGE
33	0.88499	47.28	-8.72	56.00	47.01	0.07	0.20	QP
34	0.88499	32.68	-13.32	46.00	32.41	0.07	0.20	AVERAGE
35	1.005	47.52	-8.48	56.00	47.25	0.07	0.20	QP
36	1.005	33.65	-12.35	46.00	33.38	0.07	0.20	AVERAGE
37	1.071	33.51	-12.49	46.00	33.25	0.07	0.18	AVERAGE
38	1.071	41.70	-14.30	56.00	41.44	0.07	0.18	QP
39	1.124	31.98	-14.02	46.00	31.73	0.07	0.17	AVERAGE
40	1.124	46.67	-9.33	56.00	46.42	0.07	0.17	QP
41	1.184	44.42	-11.58	56.00	44.19	0.07	0.16	QP
42	1.184	32.28	-13.72	46.00	32.05	0.07	0.16	AVERAGE
43	1.241	44.63	-11.37	56.00	44.41	0.08	0.15	QP
44	1.241	29.62	-16.38	46.00	29.40	0.08	0.15	AVERAGE
45	1.312	41.46	-14.54	56.00	41.25	0.08	0.13	QP
46	1.312	30.78	-15.22	46.00	30.57	0.08	0.13	AVERAGE
47	1.382	40.35	-15.65	56.00	40.15	0.08	0.12	QP
48	1.382	30.27	-15.73	46.00	30.07	0.08	0.12	AVERAGE
49	1.418	42.96	-13.04	56.00	42.77	0.08	0.11	QP
50	1.418	29.96	-16.04	46.00	29.77	0.08	0.11	AVERAGE
51	1.480	42.32	-13.68	56.00	42.13	0.08	0.10	QP
52	1.480	28.55	-17.45	46.00	28.36	0.08	0.10	AVERAGE
53	1.535	29.47	-16.53	46.00	29.28	0.08	0.11	AVERAGE
54	1.535	42.27	-13.73	56.00	42.08	0.08	0.11	QP
55	1.652	40.08	-15.92	56.00	39.86	0.08	0.13	QP
56	1.652	28.43	-17.57	46.00	28.21	0.08	0.13	AVERAGE
57	3.901	27.20	-18.80	46.00	26.76	0.14	0.30	AVERAGE
58	3.901	36.51	-19.49	56.00	36.07	0.14	0.30	QP
59	4.926	29.90	-16.10	46.00	29.40	0.20	0.30	AVERAGE
60	4.926	39.01	-16.99	56.00	38.51	0.20	0.30	QP
61	5.564	42.47	-17.53	60.00	41.94	0.23	0.30	QP
62	5.564	32.04	-17.96	50.00	31.51	0.23	0.30	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

4.2.3. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	☒ ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	☐ ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n
Test Date	Jan. 19, 2011		

Configuration IEEE 802.11n MCS0 20MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	25.07	30.00	Complies
6	2437 MHz	26.76	30.00	Complies
11	2462 MHz	26.83	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.87	30.00	Complies
6	2437 MHz	25.63	30.00	Complies
11	2462 MHz	26.44	30.00	Complies

Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	27.98	30.00	Complies
6	2437 MHz	29.24	30.00	Complies
11	2462 MHz	29.65	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	26.33	30.00	Complies
6	2437 MHz	26.11	30.00	Complies
9	2452 MHz	26.00	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	26.05	30.00	Complies
6	2437 MHz	26.89	30.00	Complies
9	2452 MHz	26.50	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	29.20	30.00	Complies
6	2437 MHz	29.53	30.00	Complies
9	2452 MHz	29.27	30.00	Complies

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b/g
Test Date	Jan. 19, 2011		

Configuration IEEE 802.11b Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	27.07	30.00	Complies
6	2437 MHz	24.12	30.00	Complies
11	2462 MHz	24.64	30.00	Complies

Configuration IEEE 802.11g Ant. 1

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	28.14	30.00	Complies
6	2437 MHz	27.83	30.00	Complies
11	2462 MHz	28.04	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30 kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.
5. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/3kHz) Ant. 1	Power Density (dBm/3kHz) Ant. 2	Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-0.24	-3.64	1.39	8.00	Complies
6	2437 MHz	-0.06	-3.44	1.58	8.00	Complies
11	2462 MHz	-0.97	-2.81	1.22	8.00	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2

Channel	Frequency	Power Density (dBm/3kHz) Ant. 1	Power Density (dBm/3kHz) Ant. 2	Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
3	2422 MHz	-4.17	-6.91	-2.32	8.00	Complies
6	2437 MHz	-4.25	-6.20	-2.11	8.00	Complies
9	2452 MHz	-4.85	-6.02	-2.39	8.00	Complies

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	4.37	8.00	Complies
6	2437 MHz	2.44	8.00	Complies
11	2462 MHz	2.16	8.00	Complies


Configuration IEEE 802.11g Ant. 1

Channel	Frequency	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	2.68	8.00	Complies
6	2437 MHz	1.42	8.00	Complies
11	2462 MHz	2.85	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration IEEE 802.11b Ant. 1 / 2412 MHz




Date: 19.JAN.2011 12:05:01

Power Density Plot on Configuration IEEE 802.11g Ant. 1 / 2462 MHz




Date: 19.JAN.2011 12:19:59

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 / 2437 MHz



Date: 5.MAY.2011 13:40:41

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 / 2422 MHz



Date: 5.MAY.2011 13:53:12

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.96	17.48	500	Complies
6	2437 MHz	16.28	17.48	500	Complies
11	2462 MHz	16.60	17.48	500	Complies

Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	35.20	35.84	500	Complies
6	2437 MHz	35.04	35.92	500	Complies
9	2452 MHz	35.76	35.92	500	Complies

Temperature	23°C	Humidity	61%
Test Engineer	Johnson Chang	Configurations	IEEE 802.11b/g

Configuration IEEE 802.11b Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	11.04	14.44	500	Complies
6	2437 MHz	10.16	14.68	500	Complies
11	2462 MHz	11.04	14.56	500	Complies


Configuration IEEE 802.11g Ant. 1

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.40	500	Complies
6	2437 MHz	16.40	16.40	500	Complies
11	2462 MHz	16.32	16.40	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. 1 / 2462 MHz




Date: 19.JAN.2011 12:09:47

6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. 1 / 2412 MHz




Date: 19.JAN.2011 12:12:14

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 / 2412 MHz



Date: 19.JAN.2011 12:22:09

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 / 2462 MHz



Date: 19.JAN.2011 11:44:05

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	CTX

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	CTX / Mode 1

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	41.64	31.57	40.00	-8.43	47.36	0.70	27.80	11.31	0	100	Peak	HORIZONTAL
2	400.54	32.34	46.00	-13.66	41.42	2.31	27.61	16.22	0	100	Peak	HORIZONTAL
3	533.43	32.63	46.00	-13.37	39.97	2.77	28.10	17.99	0	100	Peak	HORIZONTAL
4	640.13	33.80	46.00	-12.20	39.79	3.14	28.06	18.93	0	100	Peak	HORIZONTAL
5	768.17	32.11	46.00	-13.89	36.52	3.43	27.73	19.89	0	100	Peak	HORIZONTAL
6 p	896.21	39.23	46.00	-6.77	41.92	3.58	27.41	21.14	0	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	53.28	30.84	40.00	-9.16	50.75	0.76	27.79	7.12	0	400	Peak	VERTICAL
2	132.82	33.61	43.50	-9.89	47.89	1.33	27.43	11.82	0	400	Peak	VERTICAL
3	384.05	33.57	46.00	-12.43	43.01	2.27	27.49	15.78	0	400	Peak	VERTICAL
4	640.13	38.76	46.00	-7.24	44.75	3.14	28.06	18.93	0	400	Peak	VERTICAL
5	664.38	39.43	46.00	-6.57	45.04	3.44	28.04	18.99	0	400	Peak	VERTICAL
6 p	801.15	40.98	46.00	-5.02	45.00	3.30	27.60	20.28	0	400	Peak	VERTICAL

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	CTX / Mode 2

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	127.97	31.85	43.50	-11.65	45.90	1.28	27.46	12.13	0	100	Peak	HORIZONTAL
2	250.19	35.84	46.00	-10.16	48.27	1.90	27.00	12.67	0	100	Peak	HORIZONTAL
3	384.05	34.53	46.00	-11.47	43.97	2.27	27.49	15.78	0	100	Peak	HORIZONTAL
4	640.13	34.30	46.00	-11.70	40.29	3.14	28.06	18.93	0	100	Peak	HORIZONTAL
5	768.17	30.04	46.00	-15.96	34.45	3.43	27.73	19.89	0	100	Peak	HORIZONTAL
6 p	896.21	36.17	46.00	-9.83	38.86	3.58	27.41	21.14	0	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	97.90	29.52	43.50	-13.98	45.54	1.16	27.61	10.43	0	400	Peak	VERTICAL
2	250.19	31.02	46.00	-14.98	43.45	1.90	27.00	12.67	0	400	Peak	VERTICAL
3	384.05	34.30	46.00	-11.70	43.74	2.27	27.49	15.78	0	400	Peak	VERTICAL
4	640.13	35.66	46.00	-10.34	41.65	3.14	28.06	18.93	0	400	Peak	VERTICAL
5	768.17	30.29	46.00	-15.71	34.70	3.43	27.73	19.89	0	400	Peak	VERTICAL
6	896.21	35.01	46.00	-10.99	37.70	3.58	27.41	21.14	0	400	Peak	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4823.40	43.16	74.00	-30.84	40.71	4.26	35.20	33.39	228	100	Peak	HORIZONTAL
2 a	4823.91	30.66	54.00	-23.34	28.21	4.26	35.20	33.39	228	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4820.16	31.83	54.00	-22.17	29.38	4.26	35.20	33.39	319	100	Average	VERTICAL
2 p	4825.48	43.84	74.00	-30.16	41.39	4.26	35.20	33.39	319	100	Peak	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4874.25	43.63	74.00	-30.37	41.12	4.29	35.20	33.42	165	100	Peak	HORIZONTAL
2 a	4874.26	30.80	54.00	-23.20	28.29	4.29	35.20	33.42	165	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4874.33	30.72	54.00	-23.28	28.21	4.29	35.20	33.42	204	100	Average	VERTICAL
2 p	4874.56	42.71	74.00	-31.29	40.20	4.29	35.20	33.42	204	100	Peak	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch11 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4922.70	44.16	74.00	-29.84	41.39	4.39	35.20	33.58	281	133	Peak	HORIZONTAL
2	4924.00	33.87	54.00	-20.13	31.10	4.39	35.20	33.58	281	133	Average	HORIZONTAL
3 a	7380.10	48.04	54.00	-5.96	41.49	5.39	35.45	36.61	137	133	Average	HORIZONTAL
4 p	7384.00	62.38	74.00	-11.62	55.84	5.39	35.46	36.61	137	133	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4923.90	33.08	54.00	-20.92	30.31	4.39	35.20	33.58	268	101	Average	VERTICAL
2	4924.36	45.54	74.00	-28.46	42.77	4.39	35.20	33.58	268	101	Peak	VERTICAL
3 p	7386.16	50.97	74.00	-23.03	44.43	5.39	35.46	36.61	100	101	Peak	VERTICAL
4 a	7386.34	38.57	54.00	-15.43	32.03	5.39	35.46	36.61	100	101	Average	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4843.81	42.52	74.00	-31.48	40.01	4.29	35.20	33.42	46	100	Peak	HORIZONTAL
2 a	4844.04	30.06	54.00	-23.94	27.55	4.29	35.20	33.42	46	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4843.70	41.78	74.00	-32.22	39.27	4.29	35.20	33.42	351	100	Peak	VERTICAL
2 a	4843.92	31.13	54.00	-22.87	28.62	4.29	35.20	33.42	351	100	Average	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4874.00	42.37	74.00	-31.63	39.44	4.46	35.20	33.67	54	100	Peak	HORIZONTAL
2 a	4874.00	30.99	54.00	-23.01	27.94	4.48	35.20	33.77	54	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4874.26	30.51	54.00	-23.49	27.90	4.33	35.20	33.48	350	100	Average	VERTICAL
2 p	4874.34	42.13	74.00	-31.87	39.52	4.33	35.20	33.48	350	100	Peak	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2010		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4903.95	30.39	54.00	-23.61	27.72	4.36	35.20	33.51	49	100	Average	HORIZONTAL
2 p	4904.22	43.02	74.00	-30.98	40.35	4.36	35.20	33.51	49	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4904.15	31.30	54.00	-22.70	28.63	4.36	35.20	33.51	351	100	Average	VERTICAL
2 p	4904.47	42.89	74.00	-31.11	40.22	4.36	35.20	33.51	351	100	Peak	VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.94	50.02	54.00	-3.98	48.68	3.31	33.06	35.03	276	129	Average	HORIZONTAL
2	4823.95	52.68	74.00	-21.32	51.34	3.31	33.06	35.03	276	129	Peak	HORIZONTAL
3	7250.68	52.28	54.00	-1.72	47.80	4.06	35.82	35.40	113	128	Average	HORIZONTAL
4	7250.80	57.57	74.00	-16.43	53.09	4.06	35.82	35.40	113	128	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4823.91	53.18	74.00	-20.82	51.84	3.31	33.06	35.03	248	106	Peak	VERTICAL
2	4823.96	50.76	54.00	-3.24	49.42	3.31	33.06	35.03	248	106	Average	VERTICAL
3	7250.70	43.73	54.00	-10.27	39.25	4.06	35.82	35.40	281	106	Average	VERTICAL
4	7250.90	50.71	74.00	-23.29	46.23	4.06	35.82	35.40	281	106	Peak	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 6 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.94	41.72	54.00	-12.28	40.26	3.33	33.16	35.03	265	126	Average	HORIZONTAL
2	4874.09	47.28	74.00	-26.72	45.82	3.33	33.16	35.03	265	126	Peak	HORIZONTAL
3	7310.62	59.23	74.00	-14.77	54.61	4.06	35.96	35.40	103	129	Peak	HORIZONTAL
4	7311.67	53.70	54.00	-0.30	49.08	4.06	35.96	35.40	103	129	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4873.76	46.70	74.00	-27.30	45.24	3.33	33.16	35.03	258	115	Peak	VERTICAL
2	4873.94	40.86	54.00	-13.14	39.40	3.33	33.16	35.03	258	115	Average	VERTICAL
3	7310.80	48.24	74.00	-25.76	43.62	4.06	35.96	35.40	81	100	Peak	VERTICAL
4	7311.69	38.74	54.00	-15.26	34.12	4.06	35.96	35.40	81	100	Average	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 11 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4923.93	45.16	54.00	-8.84	43.56	3.35	33.26	35.01	276	124 Average	HORIZONTAL
2	4923.96	49.65	74.00	-24.35	48.05	3.35	33.26	35.01	276	124 Peak	HORIZONTAL
3	7385.20	53.19	54.00	-0.81	48.44	4.06	36.09	35.40	23	129 Average	HORIZONTAL
4	7385.66	59.31	74.00	-14.69	54.56	4.06	36.09	35.40	23	129 Peak	HORIZONTAL

Vertical

			Limit	Over	Read	CableAntenna	Preamp	T/Pos	A/Pos		ase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	4923.96	44.80	54.00	-9.20	43.20	3.35	33.26	35.01	253	104 Average	VERTICAL
2	4923.96	49.33	74.00	-24.67	47.73	3.35	33.26	35.01	253	104 Peak	VERTICAL
3	7385.20	43.78	54.00	-10.22	39.03	4.06	36.09	35.40	279	103 Average	VERTICAL
4	7386.04	51.73	74.00	-22.27	46.98	4.06	36.09	35.40	279	103 Peak	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4821.78	45.78	74.00	-28.22	44.44	3.31	33.06	35.03	266	113	Peak	HORIZONTAL
2	4824.09	31.34	54.00	-22.66	30.00	3.31	33.06	35.03	266	113	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4822.04	44.38	74.00	-29.62	43.04	3.31	33.06	35.03	76	100	Peak	VERTICAL
2	4826.47	30.38	54.00	-23.62	29.04	3.31	33.06	35.03	76	100	Average	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 6 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4872.14	44.40	74.00	-29.60	42.94	3.33	33.16	35.03	275	100	Peak	HORIZONTAL
2	4874.90	30.31	54.00	-23.69	28.85	3.33	33.16	35.03	275	100	Average	HORIZONTAL
3	7307.50	71.98	74.00	-2.02	67.36	4.06	35.96	35.40	125	136	Peak	HORIZONTAL
4	7308.80	51.52	54.00	-2.48	46.90	4.06	35.96	35.40	125	136	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4874.86	43.85	74.00	-30.15	42.39	3.33	33.16	35.03	116	100	Peak	VERTICAL
2	4875.69	30.26	54.00	-23.74	28.80	3.33	33.16	35.03	116	100	Average	VERTICAL
3	7310.88	61.37	74.00	-12.63	56.75	4.06	35.96	35.40	277	106	Peak	VERTICAL
4	7313.12	41.43	54.00	-12.57	36.81	4.06	35.96	35.40	277	106	Average	VERTICAL

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 11 / Ant. 1
Test Date	May 05, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4920.56	44.93	74.00	-29.07	43.36	3.35	33.23	35.01	272	100	Peak	HORIZONTAL
2	4921.48	31.22	54.00	-22.78	29.65	3.35	33.23	35.01	272	100	Average	HORIZONTAL
3	7381.48	66.02	74.00	-7.98	61.27	4.06	36.09	35.40	30	134	Peak	HORIZONTAL
4	7388.00	46.38	54.00	-7.62	41.63	4.06	36.09	35.40	30	134	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	deg	cm		
1	4925.60	31.61	54.00	-22.39	30.01	3.35	33.26	35.01	265	100	Average	VERTICAL
2	4925.72	44.08	74.00	-29.92	42.48	3.35	33.26	35.01	265	100	Peak	VERTICAL
3	7384.12	39.11	54.00	-14.89	34.36	4.06	36.09	35.40	279	103	Average	VERTICAL
4	7384.48	58.64	74.00	-15.36	53.89	4.06	36.09	35.40	279	103	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1 + Ant. 2
Test Date	Dec. 31, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	2360.00	68.53	74.00	-5.47	37.71	2.85	0.00	27.97	109	169	Peak	HORIZONTAL
2 !	2360.00	52.72	54.00	-1.28	21.90	2.85	0.00	27.97	109	169	Average	HORIZONTAL
3 p	2409.60	112.67	74.00			2.88	0.00	28.09	109	169	Peak	HORIZONTAL
4 a	2410.40	103.48	54.00			2.88	0.00	28.09	109	169	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	2384.80	53.74	54.00	-0.26	22.83	2.86	0.00	28.05	254	187	Average	HORIZONTAL
2	2385.20	64.77	74.00	-9.23	33.86	2.86	0.00	28.05	254	187	Peak	HORIZONTAL
3 a	2442.20	105.07	54.00			2.91	0.00	28.18	254	187	Average	HORIZONTAL
4 p	2443.40	114.32	74.00			2.91	0.00	28.18	254	187	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	2359.98	53.85	54.00	-0.15	23.03	2.85	0.00	27.97	328	101	Average	HORIZONTAL
2	2360.00	59.70	74.00	-14.30	28.88	2.85	0.00	27.97	328	101	Peak	HORIZONTAL
3 p	2469.20	108.33	74.00			2.93	0.00	28.26	328	101	Peak	HORIZONTAL
4 a	2469.20	98.30	54.00			2.93	0.00	28.26	328	101	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2462 MHz.

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1 + Ant. 2
Test Date	Jan. 18, 2011		

Channel 3

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	2387.00	71.04	74.00	-2.96	40.13	2.86	0.00	28.05	96	185	Peak	HORIZONTAL
2 !	2390.00	52.83	54.00	-1.17	21.90	2.88	0.00	28.05	96	185	Average	HORIZONTAL
3 a	2433.00	96.70	54.00			2.89	0.00	28.13	96	185	Average	HORIZONTAL
4 p	2438.00	107.56	74.00			2.89	0.00	28.18	96	185	Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2390.00	65.55	74.00	-8.45	34.62	2.88	0.00	28.05	96	185	Peak	HORIZONTAL
2	2390.00	47.32	54.00	-6.68	16.39	2.88	0.00	28.05	96	185	Average	HORIZONTAL
3 p	2426.00	107.45	74.00			2.89	0.00	28.13	96	185	Peak	HORIZONTAL
4 a	2433.00	97.54	54.00			2.89	0.00	28.13	96	185	Average	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2320.00	60.75	74.00	-13.25	30.03	2.83	0.00	27.89	15	100	Peak	VERTICAL
2 !	2320.00	53.77	54.00	-0.23	23.05	2.83	0.00	27.89	15	100	Average	VERTICAL
3 a	2441.00	91.91	54.00			2.91	0.00	28.18	15	100	Average	VERTICAL
4 p	2458.00	103.20	74.00			2.91	0.00	28.22	15	100	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1
Test Date	May 05, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2385.24	53.67	54.00	-0.33	23.29	2.21	28.17	0.00	99	155 Average	HORIZONTAL
2	2385.60	64.04	74.00	-9.96	33.66	2.21	28.17	0.00	99	155 Peak	HORIZONTAL
3	2411.20	114.13	54.00			2.22	28.21	0.00	99	155 Average	HORIZONTAL
4	2411.20	117.87	74.00			2.22	28.21	0.00	99	155 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2388.00	61.26	74.00	-12.74	30.88	2.21	28.17	0.00	99	158 Peak	HORIZONTAL
2	2390.00	48.78	54.00	-5.22	18.39	2.22	28.17	0.00	99	158 Average	HORIZONTAL
3	2436.00	113.95	74.00			2.23	28.29	0.00	99	158 Peak	HORIZONTAL
4	2438.60	110.07	54.00			2.23	28.29	0.00	99	158 Average	HORIZONTAL
5	2483.50	46.09	54.00	-7.91	15.45	2.26	28.38	0.00	99	158 Average	HORIZONTAL
6	2484.50	56.58	74.00	-17.42	25.94	2.26	28.38	0.00	99	158 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2459.40	114.50	74.00			2.24	28.33	0.00	98	152 Peak	HORIZONTAL
2	2460.20	110.99	54.00			2.24	28.33	0.00	98	152 Average	HORIZONTAL
3	2483.50	48.83	54.00	-5.17	18.19	2.26	28.38	0.00	98	152 Average	HORIZONTAL
4	2483.50	59.79	74.00	-14.21	29.15	2.26	28.38	0.00	98	152 Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	22°C	Humidity	58.1%
Test Engineer	Magic Lai	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1
Test Date	May 05, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2359.20	63.54	74.00	-10.46	33.25	2.19	28.10	0.00	122	128 Peak	HORIZONTAL
2	2359.84	53.48	54.00	-0.52	23.19	2.19	28.10	0.00	122	128 Average	HORIZONTAL
3	2389.60	72.06	74.00	-1.94	41.68	2.21	28.17	0.00	122	128 Peak	HORIZONTAL
4	2412.80	103.27	54.00			2.22	28.21	0.00	122	128 Average	HORIZONTAL
5	2413.20	112.90	74.00			2.22	28.21	0.00	122	128 Peak	HORIZONTAL

Item 4, 5 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2384.00	64.57	74.00	-9.43	34.19	2.21	28.17	0.00	262	125 Peak	HORIZONTAL
2	2384.72	53.72	54.00	-0.28	23.34	2.21	28.17	0.00	262	125 Average	HORIZONTAL
3	2432.20	112.92	74.00			2.23	28.25	0.00	262	125 Peak	HORIZONTAL
4	2437.80	102.10	54.00			2.23	28.29	0.00	262	125 Average	HORIZONTAL
5	2489.50	48.69	54.00	-5.31	18.01	2.26	28.42	0.00	262	125 Average	HORIZONTAL
6	2489.90	59.08	74.00	-14.92	28.40	2.26	28.42	0.00	262	125 Peak	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	deg	cm		
1	2463.60	114.36	74.00			2.24	28.33	0.00	105	175 Peak	HORIZONTAL
2	2465.40	104.53	54.00			2.24	28.33	0.00	105	175 Average	HORIZONTAL
3	2483.50	51.69	54.00	-2.31	21.05	2.26	28.38	0.00	105	175 Average	HORIZONTAL
4	2483.70	72.59	74.00	-1.41	41.95	2.26	28.38	0.00	105	175 Peak	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 / 2412 MHz



Date: 19.JAN.2011 12:23:45


High Band Edge Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. 1 + Ant. 2 / 2462 MHz



Date: 19.JAN.2011 12:28:26


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 / 2422 MHz




Date: 19.JAN.2011 11:49:54

High Band Edge Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. 1 + Ant. 2 / 2452 MHz



Date: 19.JAN.2011 11:45:41



Ref 20 dBm Att 30 dB RBW 100 kHz VBW 100 kHz SWT 1 s Delta 1 [T1] 47.28 dB 16.600000000 MHz

20 Offset 1 dB Marker 1 [T1] 1

D1 -15.188 dBm 2 3978.000 MHz

D2 -4.802 dBm

1 PR View

A

SVL

300

Start 2.32 GHz 10 MHz/ Stop 2.42 GHz

Ref 20 dBm Att 30 dB BW 100 kHz VSW 100 kHz SW 1 a Delta 1 [T1]

20 Offset 1 dB

Marker 1 [T1] -44.39 dBm

2.483800000 GHz


1.98 VSW

2.454 GHz

Start 2.454 GHz 10 MHz/ Stop 2.554 GHz


Issued Date : May 13, 2011

Low Band Edge Plot on Configuration IEEE 802.11g Ant. 1 / 2412 MHz



Date: 19.JAN.2011 12:13:50

High Band Edge Plot on Configuration IEEE 802.11g Ant. 1 / 2462 MHz



Date: 19.JAN.2011 12:20:07

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 01, 2010	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Oct. 28, 2010	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 16, 2010	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Jan. 04, 2011	Conduction (CO01-CB)
COND Cable	-	Cable	-	0.15MHz~30MHz	Dec. 04, 2010	Conduction (CO01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Oct. 12, 2010	Radiation (05CH01-CB)
Pre-Amplifier	SCHAFFNER	CPA9231A	18561	9KHz ~ 2GHz	Aug. 24, 2010	Radiation (05CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02121	1GHz~26.5GHz	Jul. 23, 2010	Radiation (05CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Bilog Antenna	SCHAFFNER	CBL61112B	2894	30MHz - 1GHz	Oct. 17, 2010	Radiation (05CH01-CB)
Horn Antenna	COM-POWER	AH-118	071028	1GHz ~ 18GHz	Dec. 09, 2010	Radiation (05CH01CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 08, 2010	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (05CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (05CH01-CB)
RF Cable-low	Woken	Low Cable-2	-	30 MHz - 1 GHz	Nov. 17, 2010	Radiation (05CH01-CB)
RF Cable-high	Woken	High Cable-5	-	1 GHz ~ 26.5 GHz	Nov. 17, 2010	Radiation (05CH01-CB)
RF Cable-high	Woken	High Cable-6	-	1 GHz ~ 26.5 GHz	Nov. 17, 2010	Radiation (05CH01-CB)
RF Cable-high	Woken	High Cable-3	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	-	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Oct. 17, 2010	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 22, 2010	Radiation (03CH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 08, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2010	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Nov. 17, 2010	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP	100304	9kHz ~ 40GHz	Nov. 22, 2010	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 06, 2011	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2010	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: For “*” Calibration Interval of instruments listed above is two years.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihsu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : December 30, 2009

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix