



RF EXPOSURE REPORT

REPORT NO.: SA111207C05

MODEL NO.: F9K1104v1

FCC ID: K7SF9K1104V1

RECEIVED: Nov. 03, 2011

TESTED: Nov. 03 ~ Dec. 08, 2011

ISSUED: Dec. 14, 2011

APPLICANT: Belkin International, Inc.

ADDRESS: 12045 East Waterfront Drive, Playa Vista,
CA 90094 USA

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product, certification, approval, or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE.....	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
2.2 MPE CALCULATION FORMULA	5
2.3 CLASSIFICATION	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



RELEASE CONTROL RECORD


ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	NA	Dec. 14, 2011



1. CERTIFICATION

PRODUCT: Dual Band 3T3R Router
MODEL: F9K1104v1
BRAND: Belkin
APPLICANT: Belkin International, Inc.
TESTED: Nov. 03 ~ Dec. 08, 2011
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment (Model: F9K1104v1) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , DATE : Dec. 14, 2011
Pettie Chen / Specialist

APPROVED BY :  , DATE : Dec. 14, 2011
Gary Chang / Technical Manager

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 23cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MODULATION MODE	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	802.11b	23.0	7.8	23	0.181	1
	802.11g	28.0	7.8	23	0.572	1
	802.11n (20MHz)	28.0	7.8	23	0.572	1
	802.11n (40MHz)	28.0	7.8	23	0.572	1
5180-5240	802.11a	15.0	6.8	23	0.023	1
	802.11n (20MHz)	15.0	6.8	23	0.023	1
	802.11n (40MHz)	15.0	6.8	23	0.023	1
5745-5825	802.11a	27.5	6.8	23	0.405	1
	802.11n (20MHz)	27.1	6.8	23	0.369	1
	802.11n (40MHz)	27.3	6.8	23	0.387	1

NOTE:

For 2.4GHz Band: Directional gain = $3.1\text{dBi} + 10\log(3) = 7.8\text{dBi}$

For 5.0GHz Band: Directional gain = $2.0\text{dBi} + 10\log(3) = 6.8\text{dBi}$

CONCLUSION:

Both of the WLAN 2.4G & 5.0G can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. $WLAN\ 2.4G + WLAN\ 5.0G = 0.572 + 0.405 = 0.977$

Therefore, the maximum calculation of this situation is 0.977, which is less than the "1" limit.