



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	Belkin International, Inc.
Applicant Address	12045 East Waterfront Drive, Playa Vista, CA 90094
FCC ID	K7SF9K1116V1

Product Name	AC750 DB Wi-Fi Dual-Band AC+ Router
Equipment Marketing Name	1. AC750 DB Wi-Fi Dual-Band AC+ Router 2. AC1200 DB Wi-Fi Dual-Band AC+ Router
Brand Name	belkin
Model No.	1. F9K1116V2 2. F9K1123V2
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Feb. 29, 2016
Final Test Date	Mar. 31, 2016
Submission Type	Class II Change

### Statement

**Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r05 and KDB 662911 D01 v02r01.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





## Table of Contents

<b>1. VERIFICATION OF COMPLIANCE</b> .....	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT</b> .....	<b>2</b>
<b>3. GENERAL INFORMATION</b> .....	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes.....	6
3.6. Table for Testing Locations.....	7
3.7. Table for Multiple Listing and Class II Change.....	7
3.8. Table for Supporting Units .....	8
3.9. Test Configurations .....	9
<b>4. TEST RESULT</b> .....	<b>11</b>
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Radiated Emissions Measurement .....	15
4.3. Antenna Requirements .....	21
<b>5. LIST OF MEASURING EQUIPMENTS</b> .....	<b>22</b>
<b>6. MEASUREMENT UNCERTAINTY</b> .....	<b>23</b>
<b>APPENDIX A. TEST PHOTOS</b> .....	<b>A1 ~ A3</b>






## 1. VERIFICATION OF COMPLIANCE

**Product Name** : AC750 DB WI-FI Dual-Band AC+ Router  
**Equipment Marketing Name** : 1. AC750 DB WI-FI Dual-Band AC+ Router  
2. AC1200 DB WI-FI Dual-Band AC+ Router  
**Brand Name** : belkin  
**Model No.** : 1. F9K1116V2  
2. F9K1123V2  
**Applicant** : Belkin International, Inc.  
**Test Rule Part(s)** : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 29, 2016 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.49 dB
4.2	15.247(d)	Radiated Emissions	Complies	6.16 dB
4.3	15.203	Antenna Requirements	Complies	-

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Product Type	IEEE 802.11b/g: WLAN (1TX, 1RX) IEEE 802.11n: WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: see the below table
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	IEEE 802.11b: DSSS (1/ 2/ 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n: see the below table
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description	
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming

**Antenna and Band width**

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
Band width Mode				
IEEE 802.11b	V	X	X	X
IEEE 802.11g	V	X	X	X
IEEE 802.11n	X	X	V	V

**IEEE 11n Spec.**

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	1,2	MCS 0-7, MCS 8-15
802.11n (HT40)	1,2	MCS 0-7, MCS 8-15

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).  
Then EUT supports HT20 and HT40.

Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n

**3.2. Accessories**

Power	Brand	Model	Rating
Adapter	LEI	MU12AR120100-A1	Input: 100-240V ~ 50/60Hz 0.3A Output: 12V, 1A
Others			
RJ-45 Cable*1, Non-shielded, 1.2m			

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)		Remark
					2.4GHz	5GHz	
1	SerComm	AC900	Printed Antenna	I-PEX	3.15	4.34	TX/RX
2	SerComm	AC900	Printed Antenna	I-PEX	4.97	4.56	TX/RX

Note: The EUT has two antennas.

<For 2.4GHz Band>:

**For IEEE 802.11b/g mode (1TX/1RX):**

Only Ant. 1 can be used as transmitting/receiving antenna.

**For IEEE 802.11n mode (2TX/2RX):**

Both Ant. 1 and Ant. 2 could transmit/receive simultaneously.


<For 5GHz Band>:

**For IEEE 802.11a mode (1TX/1RX):**

Only Ant. 1 can be used as transmitting/receiving antenna.

**For IEEE 802.11n/ac mode (2TX/2RX):**

Both Ant. 1 and Ant. 2 could transmit/receive simultaneously.



### 3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Ant.
AC Power Line Conducted Emissions	Normal Link	-	-	-
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-

The following test modes were performed for all tests:

#### For Conducted Emission and Radiated Emission test:

Mode 1. Normal Link - EUT with AC Adapter

Note: The EUT can only be used in Y axis.

#### For Co-location MPE test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to FA4N1172-28) test is added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

### 3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D
CO01-CB	Conduction	Hsin Chu	TW0006	IC 4086D

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

### 3.7. Table for Multiple Listing and Class II Change

The model names in the following table are all refer to the identical product.

Equipment Marketing Name	Model No.	Name of F/W version
AC750 DB Wi-Fi Dual-Band AC+ Router	F9K1116V2	F9K1116V2
AC1200 DB Wi-Fi Dual-Band AC+ Router	F9K1123V2	F9K1123V2

Note: The difference between these models is only the name of F/W version. Model No.: F9K1116V2 was selected as representative model for the test and its data was recorded in this report.

This product is an extension of original one reported under Sporton project number: FR2N1310AA

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Adding a new power adapter (Model Name: MU12AR120100-A1).	1. AC Power Line Conducted Emissions 2. Radiated Emissions (below 1GHz)
2. Updating model name to "F9K1116V2" from "F9K1116V1".	It is not necessary to perform for all tests.
3. Adding a new model number. (Model No. F9K1123V2).	
4. Adding two equipment marketing name (AC750 DB Wi-Fi Dual-Band AC+ Router and AC1200 DB Wi-Fi Dual-Band AC+ Router)	
5. Changing the second source DDR2.	
6. Removing two adapters (Model No.: DSA-18PFG-12 FUS 120150 and Model No.: DSA-12PFE-12 BUS 120100).	
7. Updating address to "12045 East Waterfront Drive, Playa Vista, CA 90094" from "12045 E. Waterfront Drive Playa Vista, CA 90094, USA".	
8. Updating brand name to "belkin" from "Belkin".	

### 3.8. Table for Supporting Units

For Test Site No: 03CH01-CB


Support Unit	Brand	Model	FCC ID
NB*2	DELL	E4300	DoC
NB*2	Apple	Mac Book	DoC
Flash disk	Silicon	I-Series	DoC

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
NB*4	DELL	E6430	DoC
Flash disk	Silicon	I-Series	DoC


### 3.9. Test Configurations

#### 3.9.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	1.2m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m
5	RJ-45 cable*3	No	1.5m

### 3.9.2. Radiation Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m
3	RJ-45 cable	No	10m
4	RJ-45 cable*3	No	1.5m
5	RJ-45 cable	No	1.2m

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.




4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	58%
Test Engineer	Deven Huang	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1500	39.56	-16.44	56.00	29.52	10.02	0.02	LINE	Average
2	0.1500	53.51	-12.49	66.00	43.47	10.02	0.02	LINE	QP
3	0.1749	36.95	-17.77	54.72	27.01	9.92	0.02	LINE	Average
4	0.1749	48.24	-16.48	64.72	38.30	9.92	0.02	LINE	QP
5	0.3771	32.83	-15.51	48.34	22.87	9.92	0.04	LINE	Average
6	0.3771	39.35	-18.99	58.34	29.39	9.92	0.04	LINE	QP
7	0.6863	26.07	-19.93	46.00	16.10	9.93	0.04	LINE	Average
8	0.6863	32.96	-23.04	56.00	22.99	9.93	0.04	LINE	QP
9	3.0253	20.75	-25.25	46.00	10.72	9.98	0.05	LINE	Average
10	3.0253	27.76	-28.24	56.00	17.73	9.98	0.05	LINE	QP
11	10.0186	22.23	-27.77	50.00	11.83	10.15	0.25	LINE	Average
12	10.0186	28.90	-31.10	60.00	18.50	10.15	0.25	LINE	QP

Temperature	23°C	Humidity	58%
Test Engineer	Deven Huang	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1500	39.74	-16.26	56.00	29.70	10.02	0.02	NEUTRAL	Average
2	0.1500	53.05	-12.95	66.00	43.01	10.02	0.02	NEUTRAL	QP
3	0.1641	37.49	-17.76	55.25	27.45	10.02	0.02	NEUTRAL	Average
4	0.1641	51.82	-13.43	65.25	41.78	10.02	0.02	NEUTRAL	QP
5	0.1924	34.89	-19.04	53.93	24.95	9.92	0.02	NEUTRAL	Average
6	0.1924	45.34	-18.59	63.93	35.40	9.92	0.02	NEUTRAL	QP
7	0.6578	26.47	-19.53	46.00	16.50	9.93	0.04	NEUTRAL	Average
8	0.6578	33.27	-22.73	56.00	23.30	9.93	0.04	NEUTRAL	QP
9	2.9935	20.80	-25.20	46.00	10.77	9.98	0.05	NEUTRAL	Average
10	2.9935	27.79	-28.21	56.00	17.76	9.98	0.05	NEUTRAL	QP
11	12.6489	21.92	-28.08	50.00	11.48	10.19	0.25	NEUTRAL	Average
12	12.6489	28.38	-31.62	60.00	17.94	10.19	0.25	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Radiated Emissions Measurement

### 4.2.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

### 4.2.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.2.4. Test Setup Layout

For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



#### 4.2.5. Test Deviation

There is no deviation with the original standard.

#### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	22.2°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Lucke Hsieh	<b>Configurations</b>	Normal Link
<b>Test Date</b>	Mar. 30, 2016		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	22.2°C	Humidity	57%
Test Engineer	Lucke Hsieh	Configurations	Normal Link

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	125.06	29.68	43.50	-13.82	42.14	0.97	18.94	32.37	150	234 Peak	HORIZONTAL
2	250.19	33.32	46.00	-12.68	45.18	1.34	19.10	32.30	150	257 Peak	HORIZONTAL
3	312.27	34.56	46.00	-11.44	44.99	1.51	20.35	32.29	100	127 Peak	HORIZONTAL
4	375.32	35.27	46.00	-10.73	43.84	1.67	22.08	32.32	100	119 Peak	HORIZONTAL
5	500.45	37.97	46.00	-8.03	44.35	1.94	24.03	32.35	200	66 Peak	HORIZONTAL
6	819.58	39.24	46.00	-6.76	41.87	2.48	27.03	32.14	125	253 Peak	HORIZONTAL

**Vertical**



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	44.55	33.84	40.00	-6.16	48.29	0.59	17.37	32.41	100	284 QP	VERTICAL
2	68.80	32.78	40.00	-7.22	51.47	0.72	12.99	32.40	125	149 QP	VERTICAL
3	74.62	32.99	40.00	-7.01	51.41	0.75	13.23	32.40	150	25 QP	VERTICAL
4	125.06	36.72	43.50	-6.78	49.18	0.97	18.94	32.37	100	360 Peak	VERTICAL
5	250.19	34.13	46.00	-11.87	45.99	1.34	19.10	32.30	200	162 Peak	VERTICAL
6	500.45	35.85	46.00	-10.15	42.23	1.94	24.03	32.35	125	359 Peak	VERTICAL

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### **4.3. Antenna Requirements**

#### **4.3.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### **4.3.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 27, 2016	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Dec. 08, 2015	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Dec. 23, 2015	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150kHz ~ 30MHz	May 25, 2015	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	37880	20MHz ~ 2GHz	Sep. 03, 2015	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2016*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Oct. 22, 2015	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 18, 2016	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 27, 2016	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-17	N/A	1 GHz ~ 18 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
Test Software	Audix	E3	6.2009-10-7	N/A	N/A	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“\*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

## 6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%