



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	RELM WIRELESS CORP. – BK RADIO
	7100 TECHNOLOGY DRIVE WEST MELBOURNE, FLORIDA 32904 USA
FCC ID	K95KNGM150LP
MODEL NUMBER	KNG-M150LP
PRODUCT DESCRIPTION	MIBILE VHF LAND MOBILE TRANSCEIVER
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

Date: 6/21/2016

Applicant: RELM WIRELESS CORP. - BK RADIO

FCC ID: K95KNGM150LP

Report: W:\R\RELM_K95\1079XUT15\1079XUT15 RF EXP MPE RPT REV2.DOCX

RF Exposure Requirements

General information

Device type: MOBILE VHF LAND MOBILE TRANSCEIVER

Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Fixed mounted	Any	omni	0

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

Applicant: RELM WIRELESS CORP. - BK RADIO

FCC ID: K95KNGM150LP

Report: W:\R\RELM_K95\1079XUT15\1079XUT15 RF EXP MPE RPT REV2.DOCX

**Minimum Separation Distance for Mobile or Fixed Devices
General Population/Uncontrolled Exposure**

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	58.5	W	<i>equals</i>	Max Power	58500	mW
Duty Cycle	50	%	<i>equals</i>	Duty Factor	0.5	numeric
Antenna Gain	0	dBi	<i>equals</i>	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Loss	1	numeric
Power Density	0.2	mW/cm ²				
Enter power Density from the chart to the right						
Frequency	174	MHz				

Rule Part 1.1310, Table 1 (B)

Frequency range	Power density	Enter this value
MHz	mW/cm ²	mW/cm ²
0.3-1.34	100	100
1.34-30	180/f ²	0.0
30-300	0.2	0.2
300-1,500	f/1500	0.1
1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	108 cm	1.08 m
------------------------------------	---------------	---------------

Minimum Separation in Inches 42.44019 Inches

Applicant: RELM WIRELESS CORP. - BK RADIO

FCC ID: K95KNGM150LP

Report: W:\R\RELM_K95\1079XUT15\1079XUT15 RF EXP MPE RPT REV2.DOCX