

APPLICANT: D-Link

FCC ID: KA22002080002-1

MPE CALCULATION FOR 4 dBi ANTENNA

Highest gain in 11a band

Formula used in the MPE Calculations:

$$E^2/3770 = S, \text{ mW/cm}^2$$

$$P_{\text{watts}} * G_{\text{gain}} = 10^{(P_{\text{dBm}} - 30 + G_{\text{dBi}})/10}$$

$$E, \text{ V/m} = (P_{\text{watts}} * G_{\text{gain}} * 30)^{.5}/d, \text{ meters}$$

$$d = ((P_{\text{watts}} * G * 30) / 3770 * S)^{0.5} \text{ ----- (A)}$$

Since

$$S (\text{mW/cm}^2) = 1.00 \quad \text{from 1.1310 Table 1}$$

$$P (\text{dBm}) = 17.30 \quad \text{EUT output power}$$

$$G (\text{dBi}) = 4.00 \quad \text{EUT antenna gain}$$

Substitute these parameters into the A above, we have

$$\text{MPE safe distance } d (\text{cm}) = 3.28$$

MPE CALCULATION FOR 3 dBi ANTENNA

Highest gain in 11b external

Formula used in the MPE Calculations:

$$E^2/3770 = S, \text{ mW/cm}^2$$

$$P_{\text{watts}} * G_{\text{gain}} = 10^{(P_{\text{dBm}} - 30 + G_{\text{dBi}})/10}$$

$$E, \text{ V/m} = (P_{\text{watts}} * G_{\text{gain}} * 30)^{.5}/d, \text{ meters}$$

$$d = ((P_{\text{watts}} * G * 30) / 3770 * S)^{0.5} \text{ ----- (A)}$$

Since

$$S (\text{mW/cm}^2) = 1.00 \quad \text{from 1.1310 Table 1}$$

$$P (\text{dBm}) = 20.90 \quad \text{EUT output power}$$

$$G (\text{dBi}) = 3.00 \quad \text{EUT antenna gain}$$

Substitute these parameters into the A above, we have

$$\text{MPE safe distance } d (\text{cm}) = 4.42$$

NOTE: For mobile or fixed location transmitters, minimum separation distance is 20 cm, even if calculations indicate MPE distance is less