

1		2		3		4		5		6																																																																																																					
								Remark		Description																																																																																																					
								Editor		Date																																																																																																					
以下内容由供应商印刷																																																																																																															
Input: 100-240Vac, 50/60 Hz, 0.3A Max P/N: CAP1610LCA...A1 S/N: T50J1YMXXXXXX (见 S/N 编码规则) MAC ID: XXXXXXXXXXXXXXX H/W Ver.: A1 F/W Ver.: XXXX, 具体内容 PM 提供, 如: 1.00 Wi-Fi Name(SSID):dlink-xxxx (软件自动生成的) Wi-Fi Password:XXXXXXXX (软件自动生成的)																																																																																																															
工厂打印字体: Arial, 4pt																																																																																																															
以下内容由工厂在供应商印刷的基础上打印																																																																																																															
S/N内容(不含"S/N:") MAC内容(不含"MAC ID:")																																																																																																															
条码类型: code39																																																																																																															
S/N编号规则: T50J1YMXXXXXX T50J1:"0"为数字 固定 Y: 年份 2009-9 2010-A 2011-B 2012-C... 依此类推 M: 月份 1-9 10-A 11-B 12-C XXXXXX: 000001 - 999999,按生产流水号																																																																																																															
NOTES(技术要求):																																																																																																															
1. 黑色印刷, 无边框, R1.5 (Black printing,no frame,R1.5)																																																																																																															
2.材料: 50#PET/100#PET/100#哑银龙,背胶 (Material:50#PET/100#PET/100#PET-silver,adhesive)																																																																																																															
3.原材料及后处理工艺均能满足ROSH和WEEE的要求。 (Raw materials and the corresponding post processing should meet requirements defined in the ROSH and WEEE.)																																																																																																															
<table><tr><td colspan="2">DIM</td><td colspan="2">TOL±</td><td colspan="2">△</td><td colspan="2"></td><td colspan="2">MTN 深圳市迈腾电子有限公司 www.mtncn.com SHENZHEN MTN ELECTRONICS CO.,LTD</td></tr><tr><td colspan="2">RANGE</td><td>C1</td><td>C2</td><td>C3</td><td>C4</td><td colspan="2"></td><td colspan="2">TITLE:</td></tr><tr><td colspan="2">0-6</td><td>0.1</td><td>0.1</td><td>0.15</td><td>0.2</td><td colspan="2"></td><td colspan="2">SN贴纸</td></tr><tr><td colspan="2">6-30</td><td>0.2</td><td>0.3</td><td>0.4</td><td>0.5</td><td colspan="2"></td><td colspan="2">UNIT'S</td></tr><tr><td colspan="2">30-80</td><td>0.25</td><td>0.5</td><td>0.9</td><td>1.2</td><td colspan="2"></td><td colspan="2">mm</td></tr><tr><td colspan="2">80-180</td><td>0.3</td><td>0.8</td><td>1.2</td><td>1.5</td><td colspan="2"></td><td colspan="2">SCALE</td></tr><tr><td colspan="2">180-315</td><td>0.5</td><td>1.3</td><td>1.8</td><td>3</td><td colspan="2"></td><td colspan="2">1:1</td></tr><tr><td colspan="2">315-500</td><td>0.7</td><td>1.5</td><td>2.5</td><td>4</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">500-800</td><td>0.9</td><td>1.8</td><td>3</td><td>5</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">ANG.TOL±</td><td colspan="2">0°~30°/0.1°</td><td colspan="2">30°~60°/0.3°</td><td colspan="2">60°~90°/0.5°</td><td colspan="2"></td></tr></table>												DIM		TOL±		△				MTN 深圳市迈腾电子有限公司 www.mtncn.com SHENZHEN MTN ELECTRONICS CO.,LTD		RANGE		C1	C2	C3	C4			TITLE:		0-6		0.1	0.1	0.15	0.2			SN贴纸		6-30		0.2	0.3	0.4	0.5			UNIT'S		30-80		0.25	0.5	0.9	1.2			mm		80-180		0.3	0.8	1.2	1.5			SCALE		180-315		0.5	1.3	1.8	3			1:1		315-500		0.7	1.5	2.5	4					500-800		0.9	1.8	3	5					ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°			
DIM		TOL±		△				MTN 深圳市迈腾电子有限公司 www.mtncn.com SHENZHEN MTN ELECTRONICS CO.,LTD																																																																																																							
RANGE		C1	C2	C3	C4			TITLE:																																																																																																							
0-6		0.1	0.1	0.15	0.2			SN贴纸																																																																																																							
6-30		0.2	0.3	0.4	0.5			UNIT'S																																																																																																							
30-80		0.25	0.5	0.9	1.2			mm																																																																																																							
80-180		0.3	0.8	1.2	1.5			SCALE																																																																																																							
180-315		0.5	1.3	1.8	3			1:1																																																																																																							
315-500		0.7	1.5	2.5	4																																																																																																										
500-800		0.9	1.8	3	5																																																																																																										
ANG.TOL±		0°~30°/0.1°		30°~60°/0.3°		60°~90°/0.5°																																																																																																									
对应空白贴纸料号: 17.P5.561A04805																																																																																																															
1		2		3		4		5		6																																																																																																					

