

## FCC Test Report

**Report No.:** RF160914E10

**FCC ID:** KA2AP1655A1

**Test Model:** DAP-1655, COVR-1300E

**Received Date:** Sep. 14, 2016

**Test Date:** Nov. 10 to 22, 2016

**Issued Date:** Apr. 13, 2017

**Applicant:** D-Link Corporation

**Address:** No 289, Xinhua 3rd Rd, Neihu District, Taipei City 11494, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (1):** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>4</b>
<b>1 Certificate of Conformity</b> .....	<b>5</b>
<b>2 Summary of Test Results</b> .....	<b>6</b>
2.1 Measurement Uncertainty .....	6
2.2 Modification Record .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Description of Test Modes .....	10
3.2.1 Test Mode Applicability and Tested Channel Detail .....	11
3.3 Duty Cycle of Test Signal .....	13
3.4 Description of Support Units .....	14
3.4.1 Configuration of System under Test .....	15
3.5 General Description of Applied Standards .....	16
<b>4 Test Types and Results</b> .....	<b>17</b>
4.1 Radiated Emission and Bandedge Measurement .....	17
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	17
4.1.2 Test Instruments .....	18
4.1.3 Test Procedures .....	19
4.1.4 Deviation from Test Standard .....	19
4.1.5 Test Setup .....	20
4.1.6 EUT Operating Conditions .....	21
4.1.7 Test Results .....	22
4.2 Conducted Emission Measurement .....	35
4.2.1 Limits of Conducted Emission Measurement .....	35
4.2.2 Test Instruments .....	35
4.2.3 Test Procedures .....	36
4.2.4 Deviation from Test Standard .....	36
4.2.5 Test Setup .....	36
4.2.6 EUT Operating Conditions .....	36
4.2.7 Test Results .....	37
4.3 6dB Bandwidth Measurement .....	39
4.3.1 Limits of 6dB Bandwidth Measurement .....	39
4.3.2 Test Setup .....	39
4.3.3 Test Instruments .....	39
4.3.4 Test Procedure .....	39
4.3.5 Deviation from Test Standard .....	39
4.3.6 EUT Operating Conditions .....	39
4.3.7 Test Result .....	40
4.4 Conducted Output Power Measurement .....	42
4.4.1 Limits of Conducted Output Power Measurement .....	42
4.4.2 Test Setup .....	42
4.4.3 Test Instruments .....	42
4.4.4 Test Procedures .....	42
4.4.5 Deviation from Test Standard .....	42
4.4.6 EUT Operating Conditions .....	42
4.4.7 Test Results .....	43
4.5 Power Spectral Density Measurement .....	45
4.5.1 Limits of Power Spectral Density Measurement .....	45
4.5.2 Test Setup .....	45
4.5.3 Test Instruments .....	45
4.5.4 Test Procedure .....	45
4.5.5 Deviation from Test Standard .....	45
4.5.6 EUT Operating Condition .....	45

4.5.7 Test Results .....	46
4.6 Conducted Out of Band Emission Measurement .....	49
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	49
4.6.2 Test Setup.....	49
4.6.3 Test Instruments .....	49
4.6.4 Test Procedure .....	49
4.6.5 Deviation from Test Standard .....	49
4.6.6 EUT Operating Condition .....	49
4.6.7 Test Results .....	49
<b>5 Pictures of Test Arrangements.....</b>	<b>58</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>59</b>

### Release Control Record

Issue No.	Description	Date Issued
RF160914E10	Original release.	Apr. 13, 2017

## 1 Certificate of Conformity

**Product:** Covr AC1300 Wi-Fi Range Extender

**Brand:** D-Link

**Test Model:** DAP-1655, COVR-1300E

**Sample Status:** MASS-PRODUCTION

**Applicant:** D-Link Corporation

**Test Date:** Nov. 10 to 22, 2016

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Cindy Hsin , **Date:** Apr. 13, 2017  
Cindy Hsin / Specialist

**Approved by :** May Chen , **Date:** Apr. 13, 2017  
May Chen / Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -17.67dB at 0.34141MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2483.50MHz, 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.43 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.41 dB
	6GHz ~ 18GHz	3.49 dB
	18GHz ~ 40GHz	3.30 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

Product	Covr AC1300 Wi-Fi Range Extender
Brand	D-Link
Test Model	DAP-1655, COVR-1300E
Sample Status	MASS-PRODUCTION
Power Supply Rating	12Vdf from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT20/40 in 2.4GHz band
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.7Mbps
Operating Frequency	<b>2.4GHz:</b> 2.412 ~ 2.462GHz <b>5GHz:</b> 5.18 ~ 5.24GHz and 5.745 ~ 5.825GHz
Number of Channel	<b>2.4GHz:</b> 802.11b, 802.11g, 802.11n (HT20), VHT20: 11 802.11n (HT40), VHT40: 7 <b>5GHz:</b> 802.11a, 802.11n (HT20), 802.11ac (VHT20): 9 802.11n (HT40), 802.11ac (VHT40): 4 802.11ac (VHT80): 2
Output Power	<b>2.4GHz:</b> <b>CDD Mode:</b> 324.61mW <b>Beamforming Mode:</b> 234.797mW <b>5GHz:</b> <b>5.18GHz ~ 5.24GHz:</b> <b>CDD Mode:</b> 250.367mW <b>Beamforming Mode:</b> 249.488mW <b>5.745GHz ~ 5.825GHz:</b> <b>CDD Mode:</b> 279.463mW <b>Beamforming Mode:</b> 276.264mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x1
Data Cable Supplied	NA

Note:

1. The EUT must be supplied with a power adapter as following table:

Brand	Model No.	Spec.
D-Link	WA-12M12R	AC Input: 100-240V, 0.5A, 50/60Hz DC Output: 12V, 1A DC Output cable: Unshielded, 1.2m

2. The EUT has two model names, which are identical to each other in all aspects except for the followings:

Brand Name	Model Name	Different
D-Link	DAP-1655	-
	COVR-1300E	for Maketing request

From the above models, models: **DAP-1655** was selected as representative model for the test and its data was recorded in this report.

3. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	WLAN (5GHz)

**Note:** The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The antenna provided to the EUT, please refer to the following table:

Antenna No.	Chain No.	Model	Antenna Gain(dBi)	Frequency range (GHz)	Antenna Type	Connector Type
1	Chain 0	NA	1.43	2.4~2.4835	PIFA	I-pex (MHF)
			2.99	5.15~5.85		
2	Chain 1	NA	1.99	2.4~2.4835	PIFA	I-pex (MHF)
			2.99	5.15~5.85		

5. The EUT incorporates a MIMO function.

2.4GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11b	1 ~ 11Mbps	2TX	2RX
802.11g	6 ~ 54Mbps	2TX	2RX
802.11n (HT20)	MCS 0~7	2TX	2RX
	MCS 8~15	2TX	2RX
802.11n (HT40)	MCS 0~7	2TX	2RX
	MCS 8~15	2TX	2RX
VHT20	MCS0~8 Nss=1	2TX	2RX
	MCS0~8 Nss=2	2TX	2RX
VHT40	MCS0~9 Nss=1	2TX	2RX
	MCS0~9 Nss=2	2TX	2RX
5GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11a	6 ~ 54Mbps	2TX	2RX
802.11n (HT20)	MCS 0~7	2TX	2RX
	MCS 8~15	2TX	2RX
802.11n (HT40)	MCS 0~7	2TX	2RX
	MCS 8~15	2TX	2RX
802.11ac (VHT20)	MCS0~8 Nss=1	2TX	2RX
	MCS0~8 Nss=2	2TX	2RX
802.11ac (VHT40)	MCS0~9 Nss=1	2TX	2RX
	MCS0~9 Nss=2	2TX	2RX
802.11ac (VHT80)	MCS0~9 Nss=1	2TX	2RX
	MCS0~9 Nss=2	2TX	2RX

Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
2. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and 802.11ac mode for 20MHz (40MHz), therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)
3. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report (except Output power test item).

6. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), VHT20:

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), VHT40:

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

**NOTE:**

1. The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **X-plane**. **NOTE: 1.**  
 The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **Y-plane**.

#### **Radiated Emission Test (Above 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

#### **Radiated Emission Test (Below 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	6	DSSS	DBPSK	1

### Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	6	DSSS	DBPSK	1

### Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

CDD Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5
Beamforming Mode (Output power only)					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5
802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	13.5

### Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	25deg. C, 62%RH	120Vac, 60Hz	Jyunchun Lin
RE<1G	25deg. C, 71%RH	120Vac, 60Hz	Andy Ho
PLC	23deg. C, 73%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Gary Cheng

### 3.3 Duty Cycle of Test Signal

If duty cycle of test signal is  $\geq 98\%$ , duty factor is not required.


Duty cycle of test signal is  $< 98\%$ , duty factor shall be considered

**802.11b:** Duty cycle =  $12.487/12.575 = 0.993$

**802.11g:** Duty cycle =  $2.063/2.103 = 0.981$

**802.11n (HT20):** Duty cycle =  $4.985/5.085 = 0.98$

**802.11n (HT40):** Duty cycle =  $2.426/2.513 = 0.965$ , Duty factor =  $10 * \log(1/0.965) = 0.15$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab


Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	10	No	0	Provided by Lab
2.	DC Cable	1	1.2	No	0	Supplied by client

Note: The core(s) is(are) originally attached to the cable(s).

### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**  
**KDB 558074 D01 DTS Meas Guidance v03r05**  
**KDB 662911 D01 Multiple Transmitter Output v02r01**  
**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

## 4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 20, 2016	July 19, 2017
Pre-Amplifier <sup>(*)</sup> EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna <sup>(*)</sup> Electro-Metrics	EM-6879	264	Dec. 16, 2014	Dec. 15, 2016
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-01	Nov. 10, 2016	Nov. 09, 2017
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-406	Jan. 04, 2016	Jan. 03, 2017
RF Cable	8D	966-4-1 966-4-2 966-4-3	Apr. 02, 2016	Apr. 01, 2017
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-4-01	Oct. 05, 2016	Oct. 04, 2017
Horn_Antenna SCHWARZBECK	BBHA 9120D	9120D-783	Jan. 19, 2016	Jan. 18, 2017
Pre-Amplifier Agilent	8449B	3008A01922	Sep. 18, 2016	Sep. 17, 2017
RF Cable	EMC104-SM-SM-2000 EMC104-SM-SM-5000 EMC104-SM-SM-5000	150318 150323 150324	Mar. 30, 2016	Mar. 29, 2017
Pre-Amplifier EMCI	EMC184045	980143	Jan. 15, 2016	Jan. 14, 2017
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Jan. 08, 2016	Jan. 07, 2017
RF Cable	SUCOFLEX 102	36432/2 36441/2	Jan. 16, 2016	Jan. 15, 2017
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208410	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP02	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 28, 2016	June 27, 2017
Power meter Anritsu	ML2495A	0824006	May 26, 2016	May 25, 2017
Power sensor Anritsu	MA2411B	0738172	May 26, 2016	May 25, 2017

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. \*The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 4.
4. The FCC Site Registration No. is 292998
5. The CANADA Site Registration No. is 20331-2
- 6 Loop antenna was used for all emissions below 30 MHz.
7. Tested Date: Nov. 15 to 18, 2016

#### 4.1.3 Test Procedures

##### **For Radiated emission below 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### **For Radiated emission above 30MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle < 98%) or 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



### For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop which is placed on remote site.
- Controlling software (QCARCT.exe V3.0.187.0) has been activated to set the EUT on specific status.

#### 4.1.7 Test Results

#### Above 1GHz Data:

#### 802.11b

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.1 PK	74.0	-25.9	2.19 H	281	53.8	-5.7
2	2390.00	38.0 AV	54.0	-16.0	2.19 H	281	43.7	-5.7
3	*2412.00	106.3 PK			2.19 H	281	111.9	-5.6
4	*2412.00	104.1 AV			2.19 H	281	109.7	-5.6
5	4824.00	46.0 PK	74.0	-28.0	2.64 H	223	45.2	0.8
6	4824.00	43.2 AV	54.0	-10.8	2.64 H	223	42.4	0.8

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.1 PK	74.0	-18.9	2.19 V	280	60.8	-5.7
2	2390.00	43.3 AV	54.0	-10.7	2.19 V	280	49.0	-5.7
3	*2412.00	111.3 PK			2.19 V	280	116.9	-5.6
4	*2412.00	108.9 AV			2.19 V	280	114.5	-5.6
5	4824.00	48.9 PK	74.0	-25.1	2.66 V	230	48.1	0.8
6	4824.00	45.9 AV	54.0	-8.1	2.66 V	230	45.1	0.8

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.7 PK	74.0	-27.3	2.23 H	283	52.4	-5.7
2	2390.00	39.2 AV	54.0	-14.8	2.23 H	283	44.9	-5.7
3	*2437.00	106.5 PK			2.23 H	283	112.0	-5.5
4	*2437.00	104.3 AV			2.23 H	283	109.8	-5.5
5	2483.50	54.8 PK	74.0	-19.2	2.23 H	283	60.2	-5.4
6	2483.50	39.5 AV	54.0	-14.5	2.23 H	283	44.9	-5.4
7	4874.00	50.2 PK	74.0	-23.8	2.00 H	265	49.3	0.9
8	4874.00	48.3 AV	54.0	-5.7	2.00 H	265	47.4	0.9
9	7331.00	49.9 PK	74.0	-24.1	2.19 H	293	42.4	7.5
10	7331.00	45.9 AV	54.0	-8.1	2.19 H	293	38.4	7.5

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.9 PK	74.0	-20.1	3.36 V	360	59.6	-5.7
2	2390.00	44.9 AV	54.0	-9.1	3.36 V	360	50.6	-5.7
3	*2437.00	112.2 PK			3.36 V	360	117.7	-5.5
4	*2437.00	109.9 AV			3.36 V	360	115.4	-5.5
5	2483.50	56.1 PK	74.0	-17.9	3.36 V	360	61.6	-5.5
6	2483.50	44.8 AV	54.0	-9.2	3.36 V	360	50.3	-5.5
7	4874.00	53.1 PK	74.0	-20.9	1.50 V	360	52.2	0.9
8	4874.00	51.5 AV	54.0	-2.5	1.50 V	360	50.6	0.9
9	7331.00	52.9 PK	74.0	-21.1	1.07 V	57	45.4	7.5
10	7331.00	48.6 AV	54.0	-5.4	1.07 V	57	41.1	7.5

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.8 PK			1.50 H	243	112.2	-5.4
2	*2462.00	104.3 AV			1.50 H	243	109.7	-5.4
3	2483.50	54.0 PK	74.0	-20.0	1.50 H	243	59.5	-5.5
4	2483.50	42.4 AV	54.0	-11.6	1.50 H	243	47.9	-5.5
5	4924.00	50.0 PK	74.0	-24.0	1.94 H	267	48.9	1.1
6	4924.00	48.3 AV	54.0	-5.7	1.94 H	267	47.2	1.1
7	7386.00	49.8 PK	74.0	-24.2	2.20 H	281	42.2	7.6
8	7386.00	46.1 AV	54.0	-7.9	2.20 H	281	38.5	7.6

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.9 PK			2.12 V	360	117.3	-5.4
2	*2462.00	109.5 AV			2.12 V	360	114.9	-5.4
3	2483.50	59.8 PK	74.0	-14.2	2.12 V	360	65.3	-5.5
4	2483.50	47.8 AV	54.0	-6.2	2.12 V	360	53.3	-5.5
5	4924.00	46.2 PK	74.0	-27.8	1.38 V	123	45.1	1.1
6	4924.00	42.1 AV	54.0	-11.9	1.38 V	123	41.0	1.1
7	7386.00	50.3 PK	74.0	-23.7	2.84 V	204	42.7	7.6
8	7386.00	40.1 AV	54.0	-13.9	2.84 V	204	32.5	7.6

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

**802.11g**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.8 PK	74.0	-14.2	1.25 H	239	65.5	-5.7
2	2390.00	48.2 AV	54.0	-5.8	1.25 H	239	53.9	-5.7
3	*2412.00	107.6 PK			1.25 H	239	113.2	-5.6
4	*2412.00	97.3 AV			1.25 H	239	102.9	-5.6
5	4824.00	49.0 PK	74.0	-25.0	2.13 H	163	48.2	0.8
6	4824.00	30.4 AV	54.0	-23.6	2.13 H	163	29.6	0.8

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.1 PK	74.0	-6.9	2.07 V	360	72.8	-5.7
2	2390.00	53.6 AV	54.0	-0.4	2.07 V	360	59.3	-5.7
3	*2412.00	112.9 PK			2.07 V	360	118.5	-5.6
4	*2412.00	102.3 AV			2.07 V	360	107.9	-5.6
5	4824.00	48.6 PK	74.0	-25.4	2.09 V	139	47.8	0.8
6	4824.00	30.2 AV	54.0	-23.8	2.09 V	139	29.4	0.8

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	1.22 H	240	73.4	-5.7
2	2390.00	51.1 AV	54.0	-2.9	1.22 H	240	56.8	-5.7
3	*2437.00	110.9 PK			1.22 H	240	116.4	-5.5
4	*2437.00	100.4 AV			1.22 H	240	105.9	-5.5
5	2483.50	66.8 PK	74.0	-7.2	1.22 H	240	72.3	-5.5
6	2483.50	49.9 AV	54.0	-4.1	1.22 H	240	55.4	-5.5
7	4874.00	49.2 PK	74.0	-24.8	2.08 H	150	48.3	0.9
8	4874.00	30.4 AV	54.0	-23.6	2.08 H	150	29.5	0.9
9	7311.00	47.9 PK	74.0	-26.1	1.95 H	148	40.5	7.4
10	7311.00	34.6 AV	54.0	-19.4	1.95 H	148	27.2	7.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	70.7 PK	74.0	-3.3	1.79 V	32	76.4	-5.7
2	2390.00	53.7 AV	54.0	-0.3	1.79 V	32	59.4	-5.7
3	*2437.00	116.4 PK			1.79 V	32	121.9	-5.5
4	*2437.00	106.0 AV			1.79 V	32	111.5	-5.5
5	2483.50	70.2 PK	74.0	-3.8	1.79 V	32	75.7	-5.5
6	2483.50	51.9 AV	54.0	-2.1	1.79 V	32	57.4	-5.5
7	4874.00	48.7 PK	74.0	-25.3	2.05 V	138	47.8	0.9
8	4874.00	30.1 AV	54.0	-23.9	2.05 V	138	29.2	0.9
9	7311.00	50.8 PK	74.0	-23.2	1.99 V	146	43.4	7.4
10	7311.00	38.2 AV	54.0	-15.8	1.99 V	146	30.8	7.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.7 PK			1.27 H	231	115.1	-5.4
2	*2462.00	98.7 AV			1.27 H	231	104.1	-5.4
3	2483.50	61.0 PK	74.0	-13.0	1.27 H	231	66.5	-5.5
4	2483.50	47.8 AV	54.0	-6.2	1.27 H	231	53.3	-5.5
5	4924.00	49.5 PK	74.0	-24.5	2.05 H	137	48.4	1.1
6	4924.00	30.6 AV	54.0	-23.4	2.05 H	137	29.5	1.1
7	7386.00	48.5 PK	74.0	-25.5	1.92 H	149	40.9	7.6
8	7386.00	35.0 AV	54.0	-19.0	1.92 H	149	27.4	7.6

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.7 PK			2.10 V	24	120.1	-5.4
2	*2462.00	104.4 AV			2.10 V	24	109.8	-5.4
3	2483.50	68.3 PK	74.0	-5.7	2.10 V	24	73.8	-5.5
4	2483.50	53.2 AV	54.0	-0.8	2.10 V	24	58.7	-5.5
5	4924.00	49.0 PK	74.0	-25.0	2.03 V	134	47.9	1.1
6	4924.00	30.5 AV	54.0	-23.5	2.03 V	134	29.4	1.1
7	7386.00	51.3 PK	74.0	-22.7	2.02 V	137	43.7	7.6
8	7386.00	38.6 AV	54.0	-15.4	2.02 V	137	31.0	7.6

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

**802.11n (HT20)**

<b>CHANNEL</b>	TX Channel 1	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	60.5 PK	74.0	-13.5	2.11 H	16	66.2	-5.7
2	2390.00	48.1 AV	54.0	-5.9	2.11 H	16	53.8	-5.7
3	*2412.00	108.3 PK			2.11 H	16	113.9	-5.6
4	*2412.00	96.2 AV			2.11 H	16	101.8	-5.6
5	4824.00	50.5 PK	74.0	-23.5	2.03 H	128	49.7	0.8
6	4824.00	31.3 AV	54.0	-22.7	2.03 H	128	30.5	0.8

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.6 PK	74.0	-6.4	2.14 V	0	73.3	-5.7
2	2390.00	53.5 AV	54.0	-0.5	2.14 V	0	59.2	-5.7
3	*2412.00	113.3 PK			2.14 V	0	118.9	-5.6
4	*2412.00	101.2 AV			2.14 V	0	106.8	-5.6
5	4824.00	48.9 PK	74.0	-25.1	1.97 V	127	48.1	0.8
6	4824.00	30.3 AV	54.0	-23.7	1.97 V	127	29.5	0.8

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	2.10 H	23	73.4	-5.7
2	2390.00	50.8 AV	54.0	-3.2	2.10 H	23	56.5	-5.7
3	*2437.00	105.0 PK			2.10 H	23	110.5	-5.5
4	*2437.00	102.3 AV			2.10 H	23	107.8	-5.5
5	2483.50	67.3 PK	74.0	-6.7	2.10 H	23	72.8	-5.5
6	2483.50	50.2 AV	54.0	-3.8	2.10 H	23	55.7	-5.5
7	4874.00	49.9 PK	74.0	-24.1	2.03 H	128	49.0	0.9
8	4874.00	30.8 AV	54.0	-23.2	2.03 H	128	29.9	0.9
9	7311.00	48.8 PK	74.0	-25.2	1.95 H	161	41.4	7.4
10	7311.00	35.2 AV	54.0	-18.8	1.95 H	161	27.8	7.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	71.0 PK	74.0	-3.0	2.73 V	208	76.7	-5.7
2	2390.00	53.2 AV	54.0	-0.8	2.73 V	208	58.9	-5.7
3	*2437.00	109.3 PK			2.73 V	208	114.8	-5.5
4	*2437.00	107.9 AV			2.73 V	208	113.4	-5.5
5	2483.50	70.6 PK	74.0	-3.4	2.73 V	208	76.1	-5.5
6	2483.50	52.1 AV	54.0	-1.9	2.73 V	208	57.6	-5.5
7	4874.00	49.0 PK	74.0	-25.0	2.02 V	130	48.1	0.9
8	4874.00	30.3 AV	54.0	-23.7	2.02 V	130	29.4	0.9
9	7311.00	51.5 PK	74.0	-22.5	2.02 V	150	44.1	7.4
10	7311.00	39.0 AV	54.0	-15.0	2.02 V	150	31.6	7.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 11	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.4 PK			2.14 H	29	114.8	-5.4
2	*2462.00	97.8 AV			2.14 H	29	103.2	-5.4
3	2483.50	60.2 PK	74.0	-13.8	2.14 H	29	65.7	-5.5
4	2483.50	48.5 AV	54.0	-5.5	2.14 H	29	54.0	-5.5
5	4924.00	50.2 PK	74.0	-23.8	2.07 H	119	49.1	1.1
6	4924.00	30.8 AV	54.0	-23.2	2.07 H	119	29.7	1.1
7	7386.00	48.6 PK	74.0	-25.4	1.91 H	165	41.0	7.6
8	7386.00	34.8 AV	54.0	-19.2	1.91 H	165	27.2	7.6

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.5 PK			1.23 V	32	119.9	-5.4
2	*2462.00	102.9 AV			1.23 V	32	108.3	-5.4
3	2483.50	67.3 PK	74.0	-6.7	1.58 V	30	72.8	-5.5
<b>4</b>	<b>2483.50</b>	<b>53.9 AV</b>	<b>54.0</b>	<b>-0.1</b>	<b>1.58 V</b>	<b>30</b>	<b>59.4</b>	<b>-5.5</b>
5	4924.00	48.9 PK	74.0	-25.1	1.98 V	122	47.8	1.1
6	4924.00	30.2 AV	54.0	-23.8	1.98 V	122	29.1	1.1
7	7386.00	51.5 PK	74.0	-22.5	2.03 V	162	43.9	7.6
8	7386.00	39.2 AV	54.0	-14.8	2.03 V	162	31.6	7.6

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

802.11n (HT40)

<b>CHANNEL</b>	TX Channel 3	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.6 PK	74.0	-14.4	1.69 H	332	65.3	-5.7
2	2390.00	48.6 AV	54.0	-5.4	1.69 H	332	54.3	-5.7
3	*2422.00	104.3 PK			1.69 H	332	109.8	-5.5
4	*2422.00	93.6 AV			1.69 H	332	99.1	-5.5
5	4844.00	49.7 PK	74.0	-24.3	2.02 H	131	48.9	0.8
6	4844.00	30.2 AV	54.0	-23.8	2.02 H	131	29.4	0.8
7	7266.00	48.9 PK	74.0	-25.1	1.93 H	177	41.4	7.5
8	7266.00	34.9 AV	54.0	-19.1	1.93 H	177	27.4	7.5

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.7 PK	74.0	-7.3	3.69 V	32	72.4	-5.7
2	<b>2390.00</b>	<b>53.9 AV</b>	<b>54.0</b>	<b>-0.1</b>	<b>3.69 V</b>	<b>32</b>	<b>59.6</b>	<b>-5.7</b>
3	*2422.00	108.2 PK			3.69 V	32	113.7	-5.5
4	*2422.00	98.0 AV			3.69 V	32	103.5	-5.5
5	4844.00	49.2 PK	74.0	-24.8	1.96 V	125	48.4	0.8
6	4844.00	30.4 AV	54.0	-23.6	1.96 V	125	29.6	0.8
7	7266.00	52.0 PK	74.0	-22.0	1.97 V	162	44.5	7.5
8	7266.00	39.5 AV	54.0	-14.5	1.97 V	162	32.0	7.5

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.7 PK	74.0	-15.3	1.34 H	205	64.4	-5.7
2	2390.00	47.5 AV	54.0	-6.5	1.34 H	205	53.2	-5.7
3	*2437.00	105.2 PK			1.34 H	205	110.7	-5.5
4	*2437.00	94.8 AV			1.34 H	205	100.3	-5.5
5	2495.90	58.6 PK	74.0	-15.4	1.34 H	205	64.0	-5.4
6	2495.90	42.8 AV	54.0	-11.2	1.34 H	205	48.2	-5.4
7	4874.00	50.1 PK	74.0	-23.9	2.05 H	117	49.2	0.9
8	4874.00	30.4 AV	54.0	-23.6	2.05 H	117	29.5	0.9
9	7311.00	49.6 PK	74.0	-24.4	1.89 H	176	42.2	7.4
10	7311.00	35.3 AV	54.0	-18.7	1.89 H	176	27.9	7.4

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	66.3 PK	74.0	-7.7	3.57 V	36	72.0	-5.7
2	2390.00	53.2 AV	54.0	-0.8	3.57 V	36	58.9	-5.7
3	*2437.00	109.2 PK			3.57 V	36	114.7	-5.5
4	*2437.00	99.2 AV			3.57 V	36	104.7	-5.5
5	2495.90	61.9 PK	74.0	-12.1	3.57 V	36	67.3	-5.4
6	2495.90	45.7 AV	54.0	-8.3	3.57 V	36	51.1	-5.4
7	4874.00	49.4 PK	74.0	-24.6	1.93 V	127	48.5	0.9
8	4874.00	30.8 AV	54.0	-23.2	1.93 V	127	29.9	0.9
9	7311.00	51.9 PK	74.0	-22.1	1.96 V	173	44.5	7.4
10	7311.00	39.1 AV	54.0	-14.9	1.96 V	173	31.7	7.4

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

<b>CHANNEL</b>	TX Channel 9	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	103.4 PK			1.58 H	212	108.9	-5.5
2	*2452.00	92.7 AV			1.58 H	212	98.2	-5.5
3	2483.50	57.9 PK	74.0	-16.1	1.58 H	212	63.4	-5.5
4	2483.50	47.2 AV	54.0	-6.8	1.58 H	212	52.7	-5.5
5	4904.00	49.2 PK	74.0	-24.8	2.11 H	126	48.2	1.0
6	4904.00	30.1 AV	54.0	-23.9	2.11 H	126	29.1	1.0
7	7356.00	48.4 PK	74.0	-25.6	1.94 H	176	40.8	7.6
8	7356.00	34.7 AV	54.0	-19.3	1.94 H	176	27.1	7.6

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	107.4 PK			2.51 V	29	112.9	-5.5
2	*2452.00	97.4 AV			2.51 V	29	102.9	-5.5
3	2483.50	69.6 PK	74.0	-4.4	2.51 V	29	75.1	-5.5
<b>4</b>	<b>2483.50</b>	<b>53.9 AV</b>	<b>54.0</b>	<b>-0.1</b>	<b>2.51 V</b>	<b>29</b>	<b>59.4</b>	<b>-5.5</b>
5	4904.00	49.7 PK	74.0	-24.3	1.96 V	141	48.7	1.0
6	4904.00	30.9 AV	54.0	-23.1	1.96 V	141	29.9	1.0
7	7356.00	52.1 PK	74.0	-21.9	1.91 V	185	44.5	7.6
8	7356.00	39.0 AV	54.0	-15.0	1.91 V	185	31.4	7.6

**REMARKS:**

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

**Below 1GHz Data:**

**802.11b**

<b>CHANNEL</b>	TX Channel 6	<b>DETECTOR FUNCTION</b>	Quasi-Peak (QP)
<b>FREQUENCY RANGE</b>	9kHz ~ 1GHz		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	47.53	30.4 QP	40.0	-9.6	1.50 H	276	39.2	-8.8
2	125.00	40.7 QP	43.5	-2.8	1.50 H	94	51.0	-10.3
3	250.02	25.6 QP	46.0	-20.4	1.50 H	81	35.6	-10.0
4	537.60	34.0 QP	46.0	-12.0	1.50 H	305	36.3	-2.3
5	671.97	39.5 QP	46.0	-6.5	1.00 H	2	39.3	0.2
6	766.16	30.5 QP	46.0	-15.5	1.00 H	317	28.3	2.2

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.36	36.7 QP	40.0	-3.3	1.00 V	52	46.6	-9.9
2	125.00	42.2 QP	43.5	-1.3	1.00 V	360	52.5	-10.3
3	194.08	26.5 QP	43.5	-17.0	1.00 V	294	38.2	-11.7
4	537.60	34.4 QP	46.0	-11.6	1.00 V	221	36.7	-2.3
5	613.53	30.6 QP	46.0	-15.4	1.00 V	246	30.8	-0.2
6	1000.00	32.1 QP	54.0	-21.9	1.00 V	79	27.2	4.9

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2016	Oct. 23, 2017
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 26, 2016	Oct. 25, 2017
RF Cable	5D-FB	COCCAB-001	Sep. 30, 2016	Sep. 29, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 20, 2016	June 19, 2017
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

**Note:**

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
- 3 Tested Date:Nov. 22, 2016

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.


#### 4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.20	31.74	25.14	41.94	35.34	66.00	56.00	-24.06	-20.66
2	0.18906	10.20	33.95	17.66	44.15	27.86	64.08	54.08	-19.93	-26.22
3	<b>0.34141</b>	<b>10.23</b>	<b>31.27</b>	<b>20.77</b>	<b>41.50</b>	<b>31.00</b>	<b>59.17</b>	<b>49.17</b>	<b>-17.67</b>	<b>-18.17</b>
4	0.43125	10.24	22.36	8.79	32.60	19.03	57.23	47.23	-24.63	-28.20
5	5.24609	10.40	18.02	8.60	28.42	19.00	60.00	50.00	-31.58	-31.00
6	24.09766	11.76	17.16	10.84	28.92	22.60	60.00	50.00	-31.08	-27.40

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16562	10.18	29.79	16.54	39.97	26.72	65.18	55.18	-25.21	-28.46
2	0.19297	10.17	34.20	16.67	44.37	26.84	63.91	53.91	-19.54	-27.07
3	0.34141	10.22	27.43	18.40	37.65	28.62	59.17	49.17	-21.52	-20.55
4	0.43516	10.24	22.56	7.71	32.80	17.95	57.15	47.15	-24.35	-29.20
5	0.82578	10.25	11.59	1.28	21.84	11.53	56.00	46.00	-34.16	-34.47
6	5.49219	10.32	12.90	7.11	23.22	17.43	60.00	50.00	-36.78	-32.57

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	8.14	8.13	0.5	Pass
6	2437	8.12	8.14	0.5	Pass
11	2462	8.13	8.14	0.5	Pass

##### 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.34	16.37	0.5	Pass
6	2437	16.34	16.35	0.5	Pass
11	2462	16.33	16.34	0.5	Pass

##### 802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
1	2412	16.95	16.59	0.5	Pass
6	2437	16.88	16.93	0.5	Pass
11	2462	16.87	17.31	0.5	Pass

##### 802.11n (HT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
3	2422	35.19	33.94	0.5	Pass
6	2437	35.21	35.11	0.5	Pass
9	2452	35.29	35.17	0.5	Pass

**Spectrum Plot of Worst Value**


**802.11b / Chain 0 : CH 6**




**802.11g / Chain 0 : CH 11**



**802.11n (HT20) / Chain 1 : CH 1**



**802.11n (HT40) / Chain 1 : CH3**



## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(N_{ANT}/N_{SS})$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results

##### CDD Mode

##### 802.11b

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	21.16	21.03	257.382	24.11	30.00	Pass
6	2437	22.27	21.93	324.61	25.11	30.00	Pass
11	2462	22.23	21.58	310.989	24.93	30.00	Pass

##### 802.11g

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	19.32	19.41	172.804	22.38	30.00	Pass
6	2437	21.62	21.68	292.442	24.66	30.00	Pass
11	2462	20.53	20.12	215.782	23.34	30.00	Pass

##### 802.11n (HT20)

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.57	18.72	146.418	21.66	30.00	Pass
6	2437	20.93	20.45	234.797	23.71	30.00	Pass
11	2462	19.43	18.93	165.863	22.20	30.00	Pass

##### 802.11n (HT40)

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.28	17.14	105.217	20.22	30.00	Pass
6	2437	18.88	18.46	147.414	21.69	30.00	Pass
9	2452	16.97	16.43	93.728	19.72	30.00	Pass

## Beamforming Mode

### 802.11n (HT20)

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
1	2412	18.57	18.72	146.418	21.66	30.00	Pass
6	2437	20.93	20.45	234.797	23.71	30.00	Pass
11	2462	19.43	18.93	165.863	22.20	30.00	Pass

**Note:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2]$  = 4.72dBi < 6dBi , so the power limit shall not be reduced.

### 802.11n (HT40)

Chan.	Freq. (MHz)	Average Power (dBm)		Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
3	2422	17.28	17.14	105.217	20.22	30.00	Pass
6	2437	18.88	18.46	147.414	21.69	30.00	Pass
9	2452	16.97	16.43	93.728	19.72	30.00	Pass


**Note:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2]$  = 4.72dBi < 6dBi , so the power limit shall not be reduced.

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

Same as Item 4.3.6

#### 4.5.7 Test Results

##### 802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-7.11	3.01	-4.10	8.00	Pass
	6	2437	-6.04	3.01	-3.03	8.00	Pass
	11	2462	-6.04	3.01	-3.03	8.00	Pass
1	1	2412	-7.31	3.01	-4.30	8.00	Pass
	6	2437	-6.53	3.01	-3.52	8.00	Pass
	11	2462	-6.92	3.01	-3.91	8.00	Pass

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.72\text{dBi} < 6\text{dBi}$ , so the power density limit shall not be reduced.

##### 802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-13.04	3.01	-10.03	8.00	Pass
	6	2437	-10.06	3.01	-7.05	8.00	Pass
	11	2462	-12.47	3.01	-9.46	8.00	Pass
1	1	2412	-12.48	3.01	-9.47	8.00	Pass
	6	2437	-7.39	3.01	-4.38	8.00	Pass
	11	2462	-11.39	3.01	-8.38	8.00	Pass

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.72\text{dBi} < 6\text{dBi}$ , so the power density limit shall not be reduced.

##### 802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm/3kHz)	10 log (N=2) dB	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-13.08	3.01	-10.07	8.00	Pass
	6	2437	-10.87	3.01	-7.86	8.00	Pass
	11	2462	-11.70	3.01	-8.69	8.00	Pass
1	1	2412	-13.75	3.01	-10.74	8.00	Pass
	6	2437	-11.46	3.01	-8.45	8.00	Pass
	11	2462	-13.30	3.01	-10.29	8.00	Pass

**NOTE:** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.72\text{dBi} < 6\text{dBi}$ , so the power density limit shall not be reduced.

### 802.11n (HT40)


TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=2) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-17.78	3.01	0.15	-14.62	8	Pass
	6	2437	-16.25	3.01	0.15	-13.09	8	Pass
	9	2452	-17.99	3.01	0.15	-14.83	8	Pass
1	3	2422	-18.25	3.01	0.15	-15.09	8	Pass
	6	2437	-16.89	3.01	0.15	-13.73	8	Pass
	9	2452	-18.82	3.01	0.15	-15.66	8	Pass

**NOTE: 1.** Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 4.72\text{dBi} < 6\text{dBi}$  , so the power density limit shall not be reduced.


2.Refer to section 3.2 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b / Chain 0 : CH6




802.11g / Chain 1: CH6



802.11n (HT20) / Chain 0 : CH6



802.11n (HT40) / Chain 0 : CH6




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.


### 4.6.6 EUT Operating Condition

Same as Item 4.3.6

### 4.6.7 Test Results


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dBoffset below D1. It shows compliance with the requirement.

802.11b




Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




### Chain 1


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




802.11g

Maximum REF




Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




### Chain 1


#### CH 1




#### CH 6




#### CH 11




#### CH 1 Band edge



#### CH 11 Band edge




# 802.11n (HT20)




## Chain 0


### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




### Chain 1


#### CH 1




#### CH 6




#### CH 11




#### CH 1 Band edge



#### CH 11 Band edge




# 802.11n (HT40)




## Chain 0


### CH 3




### CH 6




### CH 9



### CH 3 Band edge




### CH 9 Band edge




### Chain 1


#### CH 3




#### CH 6




#### CH 9



#### CH 3 Band edge



#### CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---