

RF Exposure Report

Report No.: SA180123E04C

FCC ID: KA2COVR2200A1

Test Model: COVR-2200

Received Date: Feb. 09, 2018

Test Date: June 15, 2018

Issued Date: July 02, 2018

Applicant: D-LINK Corporation

Address: 17595 Mt. Herrmann, Fountain Valley, California, United States 92708

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
SA180123E04C	Original release.	July 02, 2018

1 Certificate of Conformity

Product: Tri Band Whole Home Wi-Fi Extender

Brand: D-Link

Test Model: COVR-2200

Sample Status: ENGINEERING SAMPLE

Applicant: D-LINK Corporation

Test Date: June 15, 2018


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

July 02, 2018

Approved by :


May Chen / Manager

Date:

July 02, 2018

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 35cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Ant No.	Model	Antenna Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type
Dual-Ant 0	290-60110	5.23	2.4~2.4835	PCB	i-pex(MHF)
		3.76	5.15~5.25		
		3.04	5.25~5.35		
Dual-Ant 1	290-60111	4.76	2.4~2.4835	PCB	i-pex(MHF)
		5.45	5.15~5.25		
		5.31	5.25~5.35		
5g_Ant 1	290-60107	5.24	5.47~5.725	PCB	i-pex(MHF)
		5.23	5.725~5.85		
5g_Ant 1_B	290-60105	5.12	5.47~5.725	Dipole	i-pex(MHF)
		5.09	5.725~5.85		
5g_Ant 0	290-60108	3.84	5.47~5.725	PCB	i-pex(MHF)
		5.15	5.725~5.85		
5g_Ant 0_B	290-60106	3.45	5.47~5.725	Dipole	i-pex(MHF)
		3.48	5.725~5.85		

Condition	Antenna No.	
1	5g_Ant 1	5g_Ant 0
2	5g_Ant 1_B	5g_Ant 0_B
3	5g_Ant 1_B	5g_Ant 0
4	5g_Ant 1	5g_Ant 0_B

Note:

1. For Antenna Port Conducted Measurement, **Condition 1** was selected for final test.

2.5 Calculation Result of Maximum Conducted Power

For 2.4GHz and 5GHz (U-NII-1 band and U-NII-3 band) data was copied from the original test report (Report No.: SA180123E04)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	694.376	8.01	35	0.28526	1
WLAN UNII-1	5240	620.455	7.66	35	0.23516	1
WLAN UNII-2A	5310	249.765	7.26	35	0.08633	1
WLAN UNII-2C	5610	247.429	7.58	35	0.09207	1
WLAN UNII-3	5785	993.819	8.20	35	0.42654	1

Note:

2.4GHz: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 8.01\text{dBi}$

5GHz:

U-NII-1: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 7.66\text{dBi}$

U-NII-2A: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 7.26\text{dBi}$

U-NII-2C: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 7.58\text{dBi}$

U-NII-3: Directional gain = $10 \log[(10^{\text{Chain0/20}} + 10^{\text{Chain1/20}})^2 / 2] = 8.20\text{dBi}$

Conclusion:

The formula of calculated the MPE is:

$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$\text{WLAN 2.4GHz} + \text{WLAN 5GHz (low band)} + \text{WLAN 5GHz (high band)} = 0.28526 / 1 + 0.23516 / 1 + 0.42654 / 1 = 0.94696$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---