

FCC Radio Test Report

FCC ID: KA2COVRP2500A1

This report concerns (check one): ☒ Original Grant ☐ Class I Change ☐ Class II Change

Project No. : 1708C071
Equipment : Whole Home Powerline Wi-Fi Extender, Whole Home Powerline Wi-Fi System
Test Model : COVR-P2500
Series Model : COVR-P2502
Applicant : D-LINK Corporation
Address : 17595 Mt. Herrmann, Fountain Valley, California, United States 92708

Date of Receipt : Aug. 03, 2017
Date of Test : Aug. 03, 2017 ~ Sep. 18, 2017
Issued Date : Sep. 19, 2017
Tested by : BTL Inc.

Testing Engineer : Shawn Xiao
(Shawn Xiao)

Technical Manager : David Mao
(David Mao)

Authorized Signatory : Steven Lu
(Steven Lu)

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

BTL's report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 . GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	13
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	14
3.5 DESCRIPTION OF SUPPORT UNITS	14
4 . EMC EMISSION TEST	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 EUT TEST CONDITIONS	16
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 TEST PROCEDURE	18
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	19
4.2.5 EUT OPERATING CONDITIONS	20
4.2.6 EUT TEST CONDITIONS	20
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	20
4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)	20
4.2.9 TEST RESULTS (ABOVE 1000MHZ)	20
5 . BANDWIDTH TEST	21
5.1 APPLIED PROCEDURES	21
5.1.1 TEST PROCEDURE	21
5.1.2 DEVIATION FROM STANDARD	21
5.1.3 TEST SETUP	21
5.1.4 EUT OPERATION CONDITIONS	21
5.1.5 EUT TEST CONDITIONS	21
5.1.6 TEST RESULTS	21
6 . MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST	22

Table of Contents	Page
6.1 APPLIED PROCEDURES / LIMIT	22
6.1.1 TEST PROCEDURE	22
6.1.2 DEVIATION FROM STANDARD	22
6.1.3 TEST SETUP	22
6.1.4 EUT OPERATION CONDITIONS	22
6.1.5 EUT TEST CONDITIONS	22
6.1.6 TEST RESULTS	22
7 . ANTENNA CONDUCTED SPURIOUS EMISSION	23
7.1 APPLIED PROCEDURES / LIMIT	23
7.1.1 TEST PROCEDURE	23
7.1.2 DEVIATION FROM STANDARD	23
7.1.3 TEST SETUP	23
7.1.4 EUT OPERATION CONDITIONS	23
7.1.5 EUT TEST CONDITIONS	23
7.1.6 TEST RESULTS	23
8 . POWER SPECTRAL DENSITY TEST	24
8.1 APPLIED PROCEDURES / LIMIT	24
8.1.1 TEST PROCEDURE	24
8.1.2 DEVIATION FROM STANDARD	24
8.1.3 TEST SETUP	24
8.1.4 EUT OPERATION CONDITIONS	24
8.1.5 EUT TEST CONDITIONS	24
8.1.6 TEST RESULTS	24
9 . MEASUREMENT INSTRUMENTS LIST	25
10 . EUT TEST PHOTO	27
APPENDIX A - CONDUCTED EMISSION	31
APPENDIX B - RADIATED EMISSION (9KHZ TO 30MHZ)	34
APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)	39
APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)	46
APPENDIX E - BANDWIDTH	95
APPENDIX F - MAXIMUM PEAK CONDUCTED OUTPUT POWER	104
APPENDIX G - ANTENNA CONDUCTED SPURIOUS EMISSION	109
APPENDIX H - POWER SPECTRAL DENSITY	158

REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FCCP-1-1708C071	Original Issue.	Sep. 19, 2017

1. CERTIFICATION

Equipment : Whole Home Powerline Wi-Fi Extender、Whole Home Powerline Wi-Fi System
Brand Name : D-Link
Test Model : COVR-P2500
Series Model : COVR-P2502
Applicant : D-LINK Corporation
Manufacturer : D-LINK Corporation
Address : No.289, Sinhu 3rd Rd., Neihu District Taipei City 114, Taiwan, R.O.C
Date of Test : Aug. 03, 2017 ~ Sep. 18, 2017
Test Sample : Engineering Sample
Standard(s) : FCC Part15, Subpart C:(15.247) / ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1708C071) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP according to the ISO-17025 quality assessment standard and technical standard(s).

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): FCC Part15 (15.247) , Subpart C			
Standard(s) Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(d)	Antenna conducted Spurious Emission	PASS	
15.247(a)(2)	6dB Bandwidth	PASS	
15.247(b)(3)	Peak Output Power	PASS	
15.247(e)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	
15.247(d)/ 15.205/ 15.209	Transmitter Radiated Emissions	PASS	

Note:

(1) "N/A" denotes test is not applicable in this test report.

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, Guangdong, China.

BTL's test firm number for FCC: 854385

BTL's designation number for FCC: CN5020

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2 U_{CISPR} requirement.

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)
DG-C02	CISPR	150 KHz ~ 30MHz	2.32

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz ~ 200MHz	V	3.82
		30MHz ~ 200MHz	H	3.78
		200MHz ~ 1,000MHz	V	4.10
		200MHz ~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	Whole Home Powerline Wi-Fi Extender、Whole Home Powerline Wi-Fi System	
Brand Name	D-Link	
Test Model	COVR-P2500	
Series Model	COVR-P2502	
Model Difference	Only differ in single pack or double pack. COVR - P2500 is single pack while COVR - P2502 is double pack	
Product Description	Operation Frequency	2412~2462 MHz
	Modulation Technology	802.11b:DSSS 802.11g:OFDM 802.11n:OFDM
	Bit Rate of Transmitter	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n up to 300 Mbps
	Output Power (Max.)	802.11b: 28.91dBm 802.11g: 29.35dBm 802.11n(20MHz): 29.29dBm 802.11n(40MHz): 29.38dBm
Power Source	AC Mains.	
Power Rating	AC 100-240V, 50/60Hz, 0.3A	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

CH01 - CH11 for 802.11b, 802.11g, 802.11n(20MHz) CH03 - CH09 for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	CHANGSHU HONGBO	DB_ANT-1 TO IPEX	Dipole	N/A	3.11
2	CHANGSHU HONGBO	DB_ANT-1 TO IPEX	Dipole	N/A	3.11

Note:

This EUT supports MIMO 2X2, any transmit signals are uncorrelated with each other, so Directional gain = G_{ANT} , that is Directional gain=3.11 less than than 6dB.

4.

Operating Mode	
TX Mode	2TX
802.11b	V (ANT 1 + ANT 2)
802.11g	V (ANT 1 + ANT 2)
802.11n(20MHz)	V (ANT 1 + ANT 2)
802.11n(40MHz)	V (ANT 1 + ANT 2)

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09
Mode 5	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 5	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

For Band Edge Test	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

6dB Spectrum Bandwidth	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

Maximum Conducted Output Power	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

Power Spectral Density	
Final Test Mode	Description
Mode 1	TX B MODE CHANNEL 01/06/11
Mode 2	TX G MODE CHANNEL 01/06/11
Mode 3	TX N-20MHZ MODE CHANNEL 01/06/11
Mode 4	TX N-40MHZ MODE CHANNEL 03/06/09

Note:


- (1) The measurements are performed at the high, middle, low available channels.
- (2) 802.11b mode: DBPSK (1Mbps)
 802.11g mode: OFDM (6Mbps)
 802.11n HT20 mode : BPSK (13Mbps)
 802.11n HT40 mode : BPSK (27Mbps)
 For radiated emission tests, the highest output powers were set for final test.
- (3) For radiated below 1G test, the 802.11b is found to be the worst case and recorded.
- (4) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN

Test software version	cmd		
Frequency (MHz)	2412	2437	2462
802.11b	21	24	22
802.11g	17	19	16
802.11n (20MHz)	16	19	15
Frequency (MHz)	2422	2437	2452
802.11n (40MHz)	12	20	12

3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
A	Notebook	Lenovo	INSPIRON 1420-	DOC	JX193A01SDC2

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	10m	RJ45 Cable

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 -0.50	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " * " decreases with the logarithm of the frequency
- (2) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was placed on the test table and programmed in normal function.

4.1.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

4.1.7 TEST RESULTS

Please refer to the Appendix A.

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9KHz-1000MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:
 Measurement Value = Reading Level + Correct Factor
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)
 Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz~110KHz for QP detector
Start ~ Stop Frequency	110KHz~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

4.2.2 TEST PROCEDURE


- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- For the actual test configuration, please refer to the related Item -EUT Test Photos.

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For Radiated Emissions Below 30MHz



4.2.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.2.6 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Appendix B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.2.8 TEST RESULTS (30MHZ TO 1000MHZ)

Please refer to the Appendix C.

4.2.9 TEST RESULTS (ABOVE 1000MHZ)

Please refer to the Appendix D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = 2.5 ms.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

5.1.6 TEST RESULTS

Please refer to the Appendix E.

6. MAXIMUM PEAK CONDUCTED OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Maximum Output Power	1 Watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,
- The maximum peak conducted output power was performed in accordance with method 9.1.2 of FCC KDB 558074 D01 DTS Meas Guidance and FCC KDB 662911 D01 Multiple Transmitter Output.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

6.1.6 TEST RESULTS

Please refer to the Appendix F.

7. ANTENNA CONDUCTED SPURIOUS EMISSION

7.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits.

7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto.
- Offset=antenna gain+cable loss

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

7.1.6 TEST RESULTS

Please refer to the Appendix G.

8. POWER SPECTRAL DENSITY TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW=3KHz, VBW=10KHz, Sweep time = Auto.

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP



8.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.1.5 EUT TEST CONDITIONS

Temperature: 25°C Relative Humidity: 55% Test Voltage: AC 120V/60Hz

8.1.6 TEST RESULTS

Please refer to the Appendix H.

9. MEASUREMENT INSTRUMENTS LIST

Conducted Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100382	Mar. 26, 2018
2	LISN	EMCO	3816/2	52765	Mar. 26, 2018
3	50Ω Terminator	SHX	TF2-3G-A	8122901	Mar. 26, 2018
4	TWO-LINE V-NETWORK	R&S	ENV216	101447	Mar. 26, 2018
5	Cable	N/A	RG223	12m	Oct. 20, 2017
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

Radiated Emission Below 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 26, 2018
2	Amplifier	HP	8447D	2944A09673	Oct. 20, 2017
3	Receiver	Agilent	N9038A	MY52130039	Sep. 03, 2018
4	Cable	emci	LMR-400(30MHz-1 GHz)(8m+5m)	N/A	Jun. 26, 2018
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Sep. 05, 2018

Radiated Emission Above 1GHz					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Double Ridged Guide Antenna	ETS	3115	75789	Mar. 26, 2018
2	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Jun. 08, 2018
3	Amplifier	Agilent	8449B	3008A02274	May. 16, 2018
4	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 26, 2018
5	Receiver	Agilent	N9038A	MY52130039	Sep. 03, 2018
6	Antenna	EM	EM-6876-1	230	Jul. 07, 2018
7	Controller	CT	SC100	N/A	N/A
8	Controller	MF	MF-7802	MF780208416	N/A
9	Cable	emci	EMC104-SM-SM-1 2000(12m)	N/A	Jun. 26, 2018
10	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A

6dB Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 03, 2018

Peak Output Power					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	ANRITSU	ML2495A	1128009	Mar. 26, 2018
2	Pulse Power Sensor	ANRITSU	MA 2411B	1027500	Mar. 26, 2018

Antenna Conducted Spurious Emission					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 03, 2018

Power Spectral Density					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 03, 2018

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.


10. EUT TEST PHOTO

Conducted Measurement Photos



Radiated Measurement Photos

9KHz to 30MHz





Radiated Measurement Photos

30MHz to 1000MHz



Radiated Measurement Photos


Above 1000MHz



APPENDIX A - CONDUCTED EMISSION

Test Mode : TX Mode


Line



No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1545	20.91	9.79	30.70	65.75	-35.05	Peak	
2 *	0.4335	14.02	9.80	23.82	57.19	-33.37	Peak	
3	0.9690	11.23	9.84	21.07	56.00	-34.93	Peak	
4	1.5945	9.26	9.91	19.17	56.00	-36.83	Peak	
5	2.7195	7.69	9.98	17.67	56.00	-38.33	Peak	
6	7.6785	8.71	10.21	18.92	60.00	-41.08	Peak	

Test Mode : TX Mode

Neutral




No.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	0.1545	20.04	9.68	29.72	65.75	-36.03	Peak	
2 *	0.4470	14.44	9.69	24.13	56.93	-32.80	Peak	
3	0.7575	10.52	9.72	20.24	56.00	-35.76	Peak	
4	0.9645	11.44	9.75	21.19	56.00	-34.81	Peak	
5	1.5090	10.95	9.79	20.74	56.00	-35.26	Peak	
6	16.8630	7.39	10.67	18.06	60.00	-41.94	Peak	

APPENDIX B - RADIATED EMISSION (9KHZ TO 30MHZ)

Test Mode: TX B MODE CHANNEL 01


Ant 0°



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	0.0135	34.22	20.47	54.69	127.38	-72.69	AVG	
2	0.0209	31.64	19.59	51.23	125.56	-74.33	AVG	
3	0.0515	25.49	18.69	44.18	118.00	-73.82	AVG	

Test Mode: TX B MODE CHANNEL 01


Ant 0°



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.1731	28.46	16.88	45.34	104.62	-59.28	AVG	
2 *	2.2847	26.49	15.43	41.92	69.54	-27.62	QP	
3	5.5641	20.75	14.30	35.05	69.54	-34.49	QP	

Test Mode:	TX B MODE CHANNEL 01
------------	----------------------


Ant 90°



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	0.0132	35.49	20.50	55.99	127.46	-71.47	AVG	
2	0.0232	32.46	19.53	51.99	124.99	-73.00	AVG	
3	0.0605	23.69	18.51	42.20	115.78	-73.58	AVG	

Test Mode: TX B MODE CHANNEL 01

Ant 90°




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	0.2455	26.48	16.67	43.15	102.15	-59.00	AVG	
2 *	2.2968	20.86	15.43	36.29	69.54	-33.25	QP	
3	5.0312	21.71	14.37	36.08	69.54	-33.46	QP	

APPENDIX C - RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX B MODE CHANNEL 01

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	77.5300	38.18	-17.67	20.51	40.00	-19.49	Peak	
2	250.1900	38.18	-14.90	23.28	46.00	-22.72	Peak	
3	375.3200	40.34	-11.65	28.69	46.00	-17.31	Peak	
4	450.0100	37.42	-9.94	27.48	46.00	-18.52	Peak	
5 *	500.4500	42.95	-8.71	34.24	46.00	-11.76	Peak	
6	624.6100	37.93	-5.95	31.98	46.00	-14.02	Peak	

Test Mode: TX B MODE CHANNEL 01

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	250.1900	45.02	-14.90	30.12	46.00	-15.88	Peak	
2	324.8800	42.78	-12.39	30.39	46.00	-15.61	Peak	
3	375.3200	42.08	-11.65	30.43	46.00	-15.57	Peak	
4	450.0100	35.82	-9.94	25.88	46.00	-20.12	Peak	
5	500.4500	33.41	-8.71	24.70	46.00	-21.30	Peak	
6 *	771.0800	33.06	-1.99	31.07	46.00	-14.93	Peak	

Test Mode: TX B MODE CHANNEL 06

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	77.5300	38.21	-17.67	20.54	40.00	-19.46	Peak	
2	181.3200	33.68	-12.15	21.53	43.50	-21.97	Peak	
3	250.1900	40.38	-14.90	25.48	46.00	-20.52	Peak	
4	375.3200	39.87	-11.65	28.22	46.00	-17.78	Peak	
5 *	500.4500	42.97	-8.71	34.26	46.00	-11.74	Peak	
6	624.6100	38.55	-5.95	32.60	46.00	-13.40	Peak	

Test Mode: TX B MODE CHANNEL 06

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	250.1900	49.25	-14.90	34.35	46.00	-11.65	Peak	
2	303.5400	42.75	-12.77	29.98	46.00	-16.02	Peak	
3	375.3200	46.23	-11.65	34.58	46.00	-11.42	Peak	
4	450.0100	39.86	-9.94	29.92	46.00	-16.08	Peak	
5	500.4500	40.17	-8.71	31.46	46.00	-14.54	Peak	
6 *	874.8700	34.62	0.51	35.13	46.00	-10.87	Peak	

Test Mode: TX B MODE CHANNEL 11

Vertical

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	77.5300	37.18	-17.67	19.51	40.00	-20.49	Peak	
2	250.1900	38.25	-14.90	23.35	46.00	-22.65	Peak	
3	375.3200	40.18	-11.65	28.53	46.00	-17.47	Peak	
4	450.0100	37.28	-9.94	27.34	46.00	-18.66	Peak	
5 *	500.4500	42.21	-8.71	33.50	46.00	-12.50	Peak	
6	624.6100	38.44	-5.95	32.49	46.00	-13.51	Peak	

Test Mode: TX B MODE CHANNEL 11

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	250.1900	49.12	-14.90	34.22	46.00	-11.78	Peak	
2	324.8800	38.61	-12.39	26.22	46.00	-19.78	Peak	
3	375.3200	47.64	-11.65	35.99	46.00	-10.01	Peak	
4	450.0100	40.08	-9.94	30.14	46.00	-15.86	Peak	
5	500.4500	40.67	-8.71	31.96	46.00	-14.04	Peak	
6 *	832.1900	37.85	-0.48	37.37	46.00	-8.63	Peak	

APPENDIX D - RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	25.21	33.06	58.27	74.00	-15.73	Peak	
2	2390.0000	16.29	33.06	49.35	54.00	-4.65	AVG	
3 *	2411.0000	70.60	33.14	103.74	54.00	49.74	AVG	No Limit
4	2411.2000	73.56	33.14	106.70	74.00	32.70	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9647.9700	39.09	15.83	54.92	74.00	-19.08	Peak	
2 *	9647.9900	34.93	15.83	50.76	54.00	-3.24	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	28.02	33.06	61.08	74.00	-12.92	Peak	
2	2390.0000	18.89	33.06	51.95	54.00	-2.05	AVG	
3	2411.2000	79.03	33.14	112.17	74.00	38.17	Peak	No Limit
4 *	2413.1000	76.08	33.14	109.22	54.00	55.22	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2412MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9647.9650	34.67	15.83	50.50	54.00	-3.50	AVG	
2	9648.0550	39.84	15.83	55.67	74.00	-18.33	Peak	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2436.0000	69.11	33.23	102.34	54.00	48.34	AVG	No Limit
2	2436.1000	72.08	33.23	105.31	74.00	31.31	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9747.8800	40.02	15.90	55.92	74.00	-18.08	Peak	
2 *	9747.9650	35.42	15.90	51.32	54.00	-2.68	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2436.0000	74.49	33.23	107.72	54.00	53.72	AVG	No Limit
2	2436.1000	77.44	33.23	110.67	74.00	36.67	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX B MODE 2437MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9747.9700	32.99	15.90	48.89	54.00	-5.11	AVG	
2	9748.0050	38.48	15.90	54.38	74.00	-19.62	Peak	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2461.2000	69.14	33.32	102.46	74.00	28.46	Peak	No Limit
2 *	2463.1000	66.22	33.33	99.55	54.00	45.55	AVG	No Limit
3	2483.5000	24.13	33.41	57.54	74.00	-16.46	Peak	
4	2483.5000	15.05	33.41	48.46	54.00	-5.54	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9847.9349	35.97	15.98	51.95	74.00	-22.05	Peak	
2 *	9847.9600	29.45	15.98	45.43	54.00	-8.57	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2461.0000	67.47	33.32	100.79	54.00	46.79	AVG	No Limit
2	2461.2000	70.43	33.32	103.75	74.00	29.75	Peak	No Limit
3	2483.5000	26.19	33.41	59.60	74.00	-14.40	Peak	
4	2483.5000	17.37	33.41	50.78	54.00	-3.22	AVG	

Orthogonal Axis :	X
Test Mode :	TX B MODE 2462MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9848.0250	35.36	15.98	51.34	54.00	-2.66	AVG	
2	9848.2500	41.87	15.98	57.85	74.00	-16.15	Peak	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	26.89	33.06	59.95	74.00	-14.05	Peak	
2	2390.0000	14.89	33.06	47.95	54.00	-6.05	AVG	
3	2413.2000	71.72	33.14	104.86	74.00	30.86	Peak	No Limit
4 *	2413.5000	62.83	33.14	95.97	54.00	41.97	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9647.7920	32.97	15.83	48.80	74.00	-25.20	Peak	
2 *	9647.8540	22.67	15.83	38.50	54.00	-15.50	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	30.16	33.06	63.22	74.00	-10.78	Peak	
2	2390.0000	17.78	33.06	50.84	54.00	-3.16	AVG	
3	2410.9000	77.46	33.13	110.59	74.00	36.59	Peak	No Limit
4 *	2413.3000	68.00	33.14	101.14	54.00	47.14	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2412MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9648.3120	21.34	15.83	37.17	54.00	-16.83	AVG	
2	9648.3920	33.83	15.83	49.66	74.00	-24.34	Peak	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2435.7000	62.63	33.23	95.86	54.00	41.86	AVG	No Limit
2	2439.6000	71.89	33.24	105.13	74.00	31.13	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz

Vertical


80 dBuV/m



No.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	9747.9120	34.27	15.90	50.17	74.00	-23.83	Peak	
2 *	9748.0920	22.52	15.90	38.42	54.00	-15.58	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2435.3000	76.52	33.23	109.75	74.00	35.75	Peak	No Limit
2 *	2435.7000	67.09	33.23	100.32	54.00	46.32	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX G MODE 2437MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9748.3940	32.18	15.90	48.08	74.00	-25.92	Peak	
2 *	9748.4720	21.87	15.90	37.77	54.00	-16.23	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2460.6000	67.56	33.32	100.88	74.00	26.88	Peak	No Limit
2 *	2463.5000	58.53	33.33	91.86	54.00	37.86	AVG	No Limit
3	2483.5000	29.57	33.41	62.98	74.00	-11.02	Peak	
4	2483.5000	16.36	33.41	49.77	54.00	-4.23	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9847.7960	21.53	15.98	37.51	54.00	-16.49	AVG	
2	9848.0260	32.41	15.98	48.39	74.00	-25.61	Peak	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2460.0000	70.25	33.32	103.57	74.00	29.57	Peak	No Limit
2 *	2460.6000	60.33	33.32	93.65	54.00	39.65	AVG	No Limit
3	2483.5000	29.39	33.41	62.80	74.00	-11.20	Peak	
4	2483.5000	18.26	33.41	51.67	54.00	-2.33	AVG	

Orthogonal Axis :	X
Test Mode :	TX G MODE 2462MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9847.5020	32.21	15.98	48.19	74.00	-25.81	Peak	
2 *	9847.7120	21.82	15.98	37.80	54.00	-16.20	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	29.77	33.06	62.83	74.00	-11.17	Peak	
2	2390.0000	15.24	33.06	48.30	54.00	-5.70	AVG	
3	2413.5000	72.24	33.14	105.38	74.00	31.38	Peak	No Limit
4 *	2413.5000	62.18	33.14	95.32	54.00	41.32	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9647.4050	33.03	15.83	48.86	74.00	-25.14	Peak	
2 *	9647.8800	22.34	15.83	38.17	54.00	-15.83	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	28.85	33.06	61.91	74.00	-12.09	Peak	
2	2390.0000	18.26	33.06	51.32	54.00	-2.68	AVG	
3	2410.0000	76.60	33.13	109.73	74.00	35.73	Peak	No Limit
4 *	2413.5000	66.86	33.14	100.00	54.00	46.00	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2412MHz

Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9647.0380	33.49	15.83	49.32	74.00	-24.68	Peak	
2 *	9648.2480	21.51	15.83	37.34	54.00	-16.66	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437MHz

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2435.6000	62.85	33.23	96.08	54.00	42.08	AVG	No Limit
2	2437.7000	73.54	33.24	106.78	74.00	32.78	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9747.8650	22.18	15.90	38.08	54.00	-15.92	AVG	
2	9748.1300	34.05	15.90	49.95	74.00	-24.05	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2435.5000	77.42	33.23	110.65	74.00	36.65	Peak	No Limit
2 *	2435.9000	66.90	33.23	100.13	54.00	46.13	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2437MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9747.9800	22.21	15.90	38.11	54.00	-15.89	AVG	
2	9747.9940	32.38	15.90	48.28	74.00	-25.72	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2462MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2461.1000	68.58	33.32	101.90	74.00	27.90	Peak	No Limit
2 *	2463.5000	58.41	33.33	91.74	54.00	37.74	AVG	No Limit
3	2483.5000	28.34	33.41	61.75	74.00	-12.25	Peak	
4	2483.5000	15.97	33.41	49.38	54.00	-4.62	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2462MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9847.9600	21.64	15.98	37.62	54.00	-16.38	AVG	
2	9848.6500	34.94	15.98	50.92	74.00	-23.08	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2462MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2460.8000	72.20	33.32	105.52	74.00	31.52	Peak	No Limit
2 *	2463.5000	61.31	33.33	94.64	54.00	40.64	AVG	No Limit
3	2483.5000	30.20	33.41	63.61	74.00	-10.39	Peak	
4	2483.5000	18.49	33.41	51.90	54.00	-2.10	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-20M MODE 2462MHz

Horizontal


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9847.8080	21.49	15.98	37.47	54.00	-16.53	AVG	
2	9847.8560	32.34	15.98	48.32	74.00	-25.68	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2422MHz

Vertical




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	26.35	33.06	59.41	74.00	-14.59	Peak	
2	2390.0000	15.34	33.06	48.40	54.00	-5.60	AVG	
3 *	2425.0000	55.59	33.19	88.78	54.00	34.78	AVG	No Limit
4	2427.4000	65.38	33.20	98.58	74.00	24.58	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2422MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9688.0460	22.07	15.86	37.93	54.00	-16.07	AVG	
2	9688.2740	32.48	15.86	48.34	74.00	-25.66	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2422MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2390.0000	31.15	33.06	64.21	74.00	-9.79	Peak	
2	2390.0000	18.26	33.06	51.32	54.00	-2.68	AVG	
3 *	2419.4000	60.17	33.17	93.34	54.00	39.34	AVG	No Limit
4	2423.8000	70.16	33.18	103.34	74.00	29.34	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2422MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9687.8980	21.10	15.86	36.96	54.00	-17.04	AVG	
2	9688.2520	32.33	15.86	48.19	74.00	-25.81	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2437MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2434.2000	61.63	33.22	94.85	54.00	40.85	AVG	No Limit
2	2434.4000	72.02	33.22	105.24	74.00	31.24	Peak	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2437MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	9747.9080	21.70	15.90	37.60	54.00	-16.40	AVG	
2	9748.8920	32.71	15.90	48.61	74.00	-25.39	Peak	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2437MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2432.0000	76.32	33.21	109.53	74.00	35.53	Peak	No Limit
2 *	2432.8000	65.72	33.22	98.94	54.00	44.94	AVG	No Limit

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2437MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9747.8740	32.13	15.90	48.03	74.00	-25.97	Peak	
2 *	9748.6020	21.68	15.90	37.58	54.00	-16.42	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2452MHz

Vertical

120 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1 *	2449.0000	53.83	33.28	87.11	54.00	33.11	AVG	No Limit
2	2453.2000	64.20	33.29	97.49	74.00	23.49	Peak	No Limit
3	2483.5000	27.08	33.41	60.49	74.00	-13.51	Peak	
4	2483.5000	16.40	33.41	49.81	54.00	-4.19	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2452MHz

Vertical


80 dBuV/m



No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9807.3500	32.92	15.95	48.87	74.00	-25.13	Peak	
2 *	9807.9560	21.15	15.95	37.10	54.00	-16.90	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2452MHz

Horizontal




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	2447.2000	65.42	33.27	98.69	74.00	24.69	Peak	No Limit
2 *	2448.2000	57.30	33.28	90.58	54.00	36.58	AVG	No Limit
3	2483.5000	26.38	33.41	59.79	74.00	-14.21	Peak	
4	2483.5000	18.42	33.41	51.83	54.00	-2.17	AVG	

Orthogonal Axis :	X
Test Mode :	TX N-40M MODE 2452MHz

Horizontal

80 dBuV/m




No.	Freq. MHz	Reading Level dBuV/m	Correct Factor dB	Measure ment dBuV/m	Limit dBuV/m	Margin dB	Detector	Comment
1	9808.6820	31.71	15.95	47.66	74.00	-26.34	Peak	
2 *	9808.8160	20.94	15.95	36.89	54.00	-17.11	AVG	

APPENDIX E - BANDWIDTH

Test Mode : TX B Mode_CH01/06/11


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	7.06	12.80	500	Complies
2437	7.03	13.16	500	Complies
2462	7.09	13.88	500	Complies

TX CH01




Date: 16.AUG.2017 18:34:47

TX CH06



Date: 16.AUG.2017 18:37:23

TX CH11




Date: 16.AUG.2017 18:38:47

Test Mode: TX G Mode_CH01/06/11


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	12.67	16.20	500	Complies
2437	13.86	16.24	500	Complies
2462	13.80	16.24	500	Complies

TX CH01




Date: 16.AUG.2017 19:18:10

TX CH06



Date: 16.AUG.2017 19:19:28

TX CH11




Date: 16.AUG.2017 19:20:46

Test Mode : TX N-20MHz Mode_CH01/06/11


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2412	15.14	17.36	500	Complies
2437	15.04	17.36	500	Complies
2462	13.92	17.36	500	Complies

TX CH01




Date: 16.AUG.2017 19:26:12

TX CH06



Date: 16.AUG.2017 19:27:21

TX CH11




Date: 16.AUG.2017 19:28:25

Test Mode : TX N-40MHz Mode_CH03/06/09


Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied BW (MHz)	Min. Limit (kHz)	Test Result
2422	32.64	35.60	500	Complies
2437	27.59	35.60	500	Complies
2452	31.43	35.68	500	Complies

TX CH03




Date: 16.AUG.2017 19:35:40

TX CH06



Date: 16.AUG.2017 19:37:37

TX CH09



Date: 16.AUG.2017 19:38:51

APPENDIX F - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Test Mode :TX B Mode_CH01/06/11_ANT 1

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	24.49	0.28	30.00	1.00	Complies
2437	25.31	0.34	30.00	1.00	Complies
2462	24.41	0.28	30.00	1.00	Complies

Test Mode :TX B Mode_CH01/06/11_ANT 2

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	24.19	0.26	30.00	1.00	Complies
2437	26.41	0.44	30.00	1.00	Complies
2462	24.82	0.30	30.00	1.00	Complies

Test Mode :TX B Mode_CH01/06/11_Total

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	27.35	0.54	30.00	1.00	Complies
2437	28.91	0.78	30.00	1.00	Complies
2462	27.63	0.58	30.00	1.00	Complies

Test Mode :TX G Mode_CH01/06/11_ANT 1					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	25.84	0.38	30.00	1.00	Complies
2437	26.25	0.42	30.00	1.00	Complies
2462	24.83	0.30	30.00	1.00	Complies

Test Mode :TX G Mode_CH01/06/11_ANT 2					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	25.77	0.38	30.00	1.00	Complies
2437	26.42	0.44	30.00	1.00	Complies
2462	25.43	0.35	30.00	1.00	Complies

Test Mode :TX G Mode_CH01/06/11_Total					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	28.82	0.76	30.00	1.00	Complies
2437	29.35	0.86	30.00	1.00	Complies
2462	28.15	0.65	30.00	1.00	Complies

Test Mode :TX N20 Mode_CH01/06/11_ANT 1					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	24.76	0.30	30.00	1.00	Complies
2437	26.25	0.42	30.00	1.00	Complies
2462	23.94	0.25	30.00	1.00	Complies

Test Mode :TX N20 Mode_CH01/06/11_ANT 2					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	25.13	0.33	30.00	1.00	Complies
2437	26.31	0.43	30.00	1.00	Complies
2462	24.81	0.30	30.00	1.00	Complies

Test Mode :TX N20 Mode_CH01/06/11_Total					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2412	27.96	0.63	30.00	1.00	Complies
2437	29.29	0.85	30.00	1.00	Complies
2462	27.41	0.55	30.00	1.00	Complies

Test Mode :TX N40 Mode_CH03/06/09_ANT 1					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2422	20.37	0.11	30.00	1.00	Complies
2437	26.08	0.41	30.00	1.00	Complies
2452	20.74	0.12	30.00	1.00	Complies


Test Mode :TX N40 Mode_CH03/06/09_ANT 2					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2422	21.53	0.14	30.00	1.00	Complies
2437	26.64	0.46	30.00	1.00	Complies
2452	21.76	0.15	30.00	1.00	Complies

Test Mode :TX N40 Mode_CH03/06/09_Total					
Frequency (MHz)	Conducted Power (dBm)	Conducted Power (W)	Max. Limit (dBm)	Max. Limit (W)	Result
2422	24.00	0.25	30.00	1.00	Complies
2437	29.38	0.87	30.00	1.00	Complies
2452	24.29	0.27	30.00	1.00	Complies

APPENDIX G - ANTENNA CONDUCTED SPURIOUS EMISSION


Test Mode : TX B Mode_ANT 1

TX B mode CH01




Date: 16.AUG.2017 18:35:21

TX B mode CH11




Date: 16.AUG.2017 18:39:21


TX B mode CH01 (10 Harmonic of the frequency)



Date: 16.AUG.2017 18:35:00




Date: 16.AUG.2017 18:35:07




Date: 16.AUG.2017 18:35:14


TX B mode CH06 (10 Harmonic of the frequency)



Date: 16.AUG.2017 18:37:36




Date: 16.AUG.2017 18:37:42




Date: 16.AUG.2017 18:37:49


TX B mode CH11 (10 Harmonic of the frequency)



Date: 16.AUG.2017 18:39:00




Date: 16.AUG.2017 18:39:07



Date: 16.AUG.2017 18:39:14


Test Mode : TX B Mode_ANT 2

TX B mode CH01




Date: 16.AUG.2017 19:13:04

TX B mode CH11




Date: 16.AUG.2017 19:16:49


TX B mode CH01 (10 Harmonic of the frequency)



Date: 16.AUG.2017 19:12:44




Date: 16.AUG.2017 19:12:51




Date: 16.AUG.2017 19:12:58


TX B mode CH06 (10 Harmonic of the frequency)



Date: 16.AUG.2017 19:15:15




Date: 16.AUG.2017 19:15:22




Date: 16.AUG.2017 19:15:29


TX B mode CH11 (10 Harmonic of the frequency)



Date: 16.AUG.2017 19:16:29




Date: 16.AUG.2017 19:16:36



Date: 16.AUG.2017 19:16:43


Test Mode : TX G Mode_ANT 1

TX G mode CH01



Date: 16.AUG.2017 19:18:43

TX G mode CH11



Date: 16.AUG.2017 19:21:21