



RADIO TEST REPORT

Report No.:STS2106200W08

Issued for

D-Link Corporation

14420 Myford Road Suite 100 Irvine California United States
92606

Product Name:	2K QHD Indoor Wi-Fi Camera
Brand Name:	D-Link
Model Name:	DCS-8350LH
Series Model:	N/A
FCC ID:	KA2CS8350LHA1
Test Standard:	FCC Part 15.407

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ,
Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name..... : D-Link Corporation
Address : 14420 Myford Road Suite 100 Irvine California United States 92606
Manufacturer's Name : Shenzhen Aoni Electronic Co.,Ltd
Address : Building 5, Honghui Industrial Park, 2nd Road Liuxian, Baoan District, Shenzhen, P.R. China, 518101

Product Description

Product Name..... : 2K QHD Indoor Wi-Fi Camera
Brand Name : D-Link
Model Name : DCS-8350LH
Series Model..... : N/A

Test Standards..... : FCC Part15.407

Test Procedure.....ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test..... :

Date of receipt of test item : 28 June 2021

Date (s) of performance of tests : 28 June 2021 ~ 16 July 2021

Date of Issue..... : 16 July 2021

Test Result..... : **Pass**

Testing Engineer :

(Chris Chen)

Technical Manager :

(Sean she)

Authorized Signatory :

(Vita Li)





Table of Contents	Page
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.3 TEST SOFTWARE AND POWER LEVEL	12
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	14
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	15
3 . EMC EMISSION TEST	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.2 RADIATED EMISSION AND (BANDEGE) MEASUREMENT	20
4. POWER SPECTRAL DENSITY TEST	63
4.1 LIMIT	63
4.2 TEST PROCEDURE	63
4.3 DEVIATION FROM STANDARD	63
4.4 TEST SETUP	64
4.5 EUT OPERATION CONDITIONS	64
4.6 TEST RESULTS	65
5. BANDWIDTH MEASUREMENT	69
5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT	69
5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT	72
5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT	75
6. MAXIMUM CONDUCTED OUTPUT POWER	77
6.1 LIMIT	77
6.2 TEST PROCEDURE	77
6.3 DEVIATION FROM STANDARD	77
6.4 TEST SETUP	77
6.5 EUT OPERATION CONDITIONS	77
6.6 TEST RESULTS	78
7. AUTOMATICALLY DISCONTINUE TRANSMISSION	86
7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	86
7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION	86



Table of Contents	Page
8. ANTENNA REQUIREMENT	87
8.1 STANDARD REQUIREMENT	87
8.2 EUT ANTENNA	87
APPENDIX - PHOTOS OF TEST SETUP	88



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	16 July 2021	STS2106200W08	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

§ 15.407, KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

FCC Part 15.407		
FCC standard	Test Item	Results
15.207	AC Conducted Emission	PASS
15.407 (a) /15.407 (e)	26dB/6dB &99% Bandwidth	PASS
15.407(a)	Maximum Conducted Output Power	PASS
15.407(b)/15.205/15.209	Radiated Emission And (bandedge Emissions) Measurement	PASS
15.407(a)	Power Spectral Density	PASS
15.407(c)	Automatically Discontinue Transmission	PASS
15.203	Antenna Requirement	PASS

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.68\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 2.68\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 4.39\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 5.10\text{dB}$
6	All emissions, radiated >6G	$\pm 5.48\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.79\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.80\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	2K QHD Indoor Wi-Fi Camera	
Trade Name	D-Link	
Model Name	DCS-8350LH	
Series Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a 2K QHD Indoor Wi-Fi Camera	
		IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.310GHz IEEE 802.11ac(VHT80): 5.210GHz
		IEEE 802.11a/ n(HT20)/ac(VHT20): 5.260GHz-5.320GHz IEEE 802.11n(HT40)/ac(VHT40): 5.270GHz-5.310GHz IEEE 802.11ac(VHT80): 5.290GHz
		Operation Frequency: IEEE 802.11a/ n(HT20)/ac(VHT20): 5.500GHz-5.700GHz IEEE 802.11n(HT40)/ac(VHT40): 5.510GHz-5.670GHz IEEE 802.11ac(VHT80): 5.530GHz-5.610GHz
		IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz
		Modulation Type: 802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11ac(OFDM): BPSK,QPSK,16-QAM,64-QAM,256-QAM
		Antenna Designation: Please refer to the Note 3.
		Max.Output Power(Conducted): 13.25 dBm
	More details of EUT technical specification, please refer to the User Manual.	
Test Channel	Please refer to the Note 2.	
Adapter	Model: KA06E-0501200US Input: 100-240V 50/60Hz Output:5.0V 1.2A 6.0W	
Hardware version number	A1	
Software version number	V1.0	
Connecting I/O Port(s)	Please refer to the Note 1.	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.



2. Operation Frequency of channel

5.180GHz-5.240GHz		5.500GHz-5.720GHz	
Channel	Frequency	Channel	Frequency
36	5180	100	5500
38	5190	102	5510
40	5200	104	5520
42	5210	106	5530
44	5220	108	5540
46	5230	110	5550
48	5240	112	5560
		116	5580
		118	5590
5.260GHz-5.320GHz		120	5600
Channel	Frequency	122	5610
52	5260	124	5620
54	5270	126	5630
56	5280	128	5640
58	5290	132	5660
60	5300	134	5670
62	5310	136	5680
64	5320	140	5700
5.745GHz-5.825GHz			
Channel	Frequency		
149	5745		
151	5755		
153	5765		
155	5775		
157	5785		
159	5795		
161	5805		
165	5825		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

5GHz:

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
36	5180	52	5260
40	5200	60	5300
48	5240	64	5320

For 802.11a/n(HT20) /ac (VHT20)			
Channel	Freq.(MHz)	Channel	Freq.(MHz)
100	5500	149	5745
116	5580	157	5785
140	5700	165	5825



For 802.11n(HT40) /ac (VHT40)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
38	5190	54	5270
46	5230	62	5310

For 802.11n(HT40) /ac (VHT40)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
102	5510	151	5755
110	5550	159	5795
134	5670		

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
42	5210	155	5775

For 802.11ac (VHT80)

Channel	Freq.(MHz)	Channel	Freq.(MHz)
106	5530	155	5775
122	5610		

3.	Ant	Brand	Model Name	Ant Type	Connector	Gain (dBi)	NOTE
	A	D-Link	DCS-8350LH	FPC	N/A	2dBi	WLAN Ant

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11a HT20 CH36&CH40&CH48	6 Mbps
Mode 2	TX IEEE 802.11a HT20 CH52&CH60&CH64	6 Mbps
Mode 3	TX IEEE 802.11a HT20 CH100&CH116&CH140	6 Mbps
Mode 4	TX IEEE 802.11a HT20 CH149&CH157&CH165	6 Mbps
Mode 5	TX IEEE 802.11n HT20 CH36&CH40&CH48	MCS 0
Mode 6	TX IEEE 802.11ac HT20 CH36&CH40&CH48	NSS1 MCS0
Mode 7	TX IEEE 802.11n HT20 CH52&CH60&CH64	MCS 0
Mode 8	TX IEEE 802.11ac HT20 CH52&CH60&CH64	NSS1 MCS0
Mode 9	TX IEEE 802.11n HT20 CH100&CH116&CH140	MCS 0
Mode 10	TX IEEE 802.11ac HT20 CH100&CH116&CH140	NSS1 MCS0
Mode 11	TX IEEE 802.11n HT20 CH149&CH157&CH165	MCS 0
Mode 12	TX IEEE 802.11ac HT20 CH149&CH157&CH165	NSS1 MCS0
Mode 13	TX IEEE 802.11n HT40 CH38&CH46	MCS 0
Mode 14	TX IEEE 802.11ac HT40 CH38&CH46	NSS1 MCS0
Mode 15	TX IEEE 802.11n HT40 CH54 &CH62	MCS 0
Mode 16	TX IEEE 802.11ac HT40 CH54 &CH62	NSS1 MCS0
Mode 17	TX IEEE 802.11n HT40 CH102&CH110&CH134	MCS 0
Mode 18	TX IEEE 802.11ac HT40 CH102&CH110&CH134	NSS1 MCS0
Mode 19	TX IEEE 802.11n HT40 CH151&CH159	MCS 0
Mode 20	TX IEEE 802.11ac HT40 CH151&CH159	NSS1 MCS0
Mode 21	TX IEEE 802.11ac HT80 CH42	NSS1 MCS0
Mode 22	TX IEEE 802.11ac HT80 CH58	NSS1 MCS0
Mode 23	TX IEEE 802.11ac HT80 CH106&122	NSS1 MCS0
Mode 24	TX IEEE 802.11ac HT80 CH155	NSS1 MCS0

- Note: (1) The measurements are performed at the highest, middle, lowest available channels.
(2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
(3) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.
(4) The battery is fully-charged during the radiated and RF conducted test.



AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 25: Keeping TX + WLAN Link

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-1 (5150MHz-5250MHz)	802.11a	2	default	SecureCRT
		802.11n(HT20)		default	
		802.11n(HT40)		default	
		802.11ac(VHT20)		default	
		802.11ac(VHT40)		default	
		802.11ac(VHT80)		default	
RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-2A (5250MHz-5350MHz)	802.11a	2	default	SecureCRT
		802.11n(HT20)		default	
		802.11n(HT40)		default	
		802.11ac(VHT20)		default	
		802.11ac(VHT40)		default	
		802.11ac(VHT80)		default	
RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-2C (5470MHz-5725MHz)	802.11a	2	default	SecureCRT
		802.11n(HT20)		default	
		802.11n(HT40)		default	
		802.11ac(VHT20)		default	
		802.11ac(VHT40)		default	
		802.11ac(VHT80)		40	




RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
WIFI(5G)	U-NII-3 (5725MHz-5850MHz)	802.11a	2	default	SecureCRT
		802.11n(HT20)		default	
		802.11n(HT40)		default	
		802.11ac(VHT20)		default	
		802.11ac(VHT40)		default	
		802.11ac(VHT80)		default	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-1	Adapter	N/A	KA06E-0501200US	N/A	N/A
C-1	USB Cable	N/A	N/A	210cm	NO

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-2	Notebook	LENOVO	ThinkPad E470	N/A	N/A
C-2	USB Cable	N/A	N/A	150cm	NO

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (2) “YES” is means “with core”; “NO” is means “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
Signal Analyzer	R&S	FSV 40-N	101823	2020.10.10	2021.10.09
Active loop Antenna	ZHINAN	ZN30900C	16035	2021.04.11	2022.04.10
Bilog Antenna	TESEQ	CBL6111D	34678	2020.10.12	2022.10.11
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2019.10.15	2021.10.14
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	J211020657	2020.10.12	2022.10.11
Pre-Amplifier(0.1M-3G Hz)	EM	EM330	060665	2020.10.12	2021.10.11
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2020.10.12	2021.10.11
Pre-Amplifier (18G-40GHz)	SKET	LNPA-1840-50	SK2018101801	2020.10.10	2021.10.09
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Turn table	EM	SC100_1	60531	N/A	N/A
Antenna mast	EM	SC100	N/A	N/A	N/A
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 RE)			

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2020.10.12	2021.10.11
LISN	R&S	ENV216	101242	2020.10.12	2021.10.11
LISN	EMCO	3810/2NM	23625	2020.10.12	2021.10.11
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	EZ-EMC(Ver.STSLAB-03A1 CE)			

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
MIMO Power measurement test Set	Keysight	U2021XA	MY55520005	2020.10.10	2021.10.09
			MY55520006	2020.10.10	2021.10.09
			MY56120038	2020.10.10	2021.10.09
			MY56280002	2020.10.10	2021.10.09
Signal Analyzer	Agilent	N9020A	MY51110105	2021.03.04	2022.03.03
Temperature & Humidity	HH660	Mieo	N/A	2020.10.13	2021.10.12
Test SW	FARAD	LZ-RF /LzRf-3A3			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN is at least 80 cm from the nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.6 TEST RESULTS


Temperature:	26.0(C)	Relative Humidity:	52%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode :	Mode 25		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1580	17.10	20.33	37.43	65.57	-28.14	QP
2	0.1580	4.65	20.33	24.98	55.57	-30.59	AVG
3	0.5220	24.96	20.52	45.48	56.00	-10.52	QP
4	0.5220	20.91	20.52	41.43	46.00	-4.57	AVG
5	1.3780	14.89	20.30	35.19	56.00	-20.81	QP
6	1.3780	4.10	20.30	24.40	46.00	-21.60	AVG
7	3.5620	14.41	20.38	34.79	56.00	-21.21	QP
8	3.5620	3.10	20.38	23.48	46.00	-22.52	AVG
9	7.7780	15.71	20.74	36.45	60.00	-23.55	QP
10	7.7780	3.71	20.74	24.45	50.00	-25.55	AVG
11	23.8780	20.10	22.66	42.76	60.00	-17.24	QP
12	23.8780	6.18	22.66	28.84	50.00	-21.16	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) – Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)

100.0 dBuV






Temperature:	26.0(C)	Relative Humidity:	52%RH
Test Voltage	AC 120V/60Hz	Phase:	N
Test Mode	Mode 25		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1580	15.47	20.33	35.80	65.57	-29.77	QP
2	0.1580	0.35	20.33	20.68	55.57	-34.89	AVG
3	0.5260	18.55	20.52	39.07	56.00	-16.93	QP
4	0.5260	10.76	20.52	31.28	46.00	-14.72	AVG
5	1.1460	14.01	20.30	34.31	56.00	-21.69	QP
6	1.1460	0.97	20.30	21.27	46.00	-24.73	AVG
7	2.6220	11.36	20.33	31.69	56.00	-24.31	QP
8	2.6220	-1.43	20.33	18.90	46.00	-27.10	AVG
9	6.8780	13.52	20.57	34.09	60.00	-25.91	QP
10	6.8780	0.01	20.57	20.58	50.00	-29.42	AVG
11	23.8460	20.00	22.67	42.67	60.00	-17.33	QP
12	23.8460	5.03	22.67	27.70	50.00	-22.30	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Margin = Result (Result = Reading + Factor) - Limit
3. Factor = LISN factor + Cable loss + Limiter (10dB)





3.2 RADIATED EMISSION AND (BANDEDGE) MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.407(b)7&15.205/209(a), then the limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	68.2	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15E.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Note: In case the emission radiated emission above 1000MHz fall within the restricted band the restricted frequency bands, the peak limit is 74 dBuV/m.

**LIMITS OF EMISSIONS OUTSIDE OF THE FREQUENCY BANDS**

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Note: dBuV/m(at 3M) = EIRP(dBm) + 95.2.

Peak Limit = -27dBm/MHz + 95.2 = 68.2 dBuV/m.

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz (Peak/AV)
Stop Frequency	10th carrier harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /3 MHz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.2 DEVIATION FROM TEST STANDARD


No deviation

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$

**3.2.6 TEST RESULTS (Between 9KHz – 30 MHz)**

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage :	AC 120V/60Hz	Polarization :	--
Test Mode :	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})(\text{dB})$;

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (Between 30MHz – 1GHz)**

Temperature	23.1(C)	Relative Humidity:	60%RH
Test Voltage	AC 120V/60Hz	Polarization:	Horizontal
Test Mode	Mode 1~24(Mode 9 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	167.7400	54.38	-19.58	34.80	43.50	-8.70	peak
2	334.5800	49.38	-13.56	35.82	46.00	-10.18	peak
3	493.6600	44.60	-8.15	36.45	46.00	-9.55	peak
4	672.1400	33.88	-4.52	29.36	46.00	-16.64	peak
5	816.6700	30.79	-1.97	28.82	46.00	-17.18	peak
6	998.0600	29.31	2.04	31.35	54.00	-22.65	peak

Remark:

1. Margin = Result (Result = Reading + Factor) – Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) – Amplifier gain





Temperature	23.1(C)	Relative Humidity:	60%RH
Test Voltage	AC 120V/60Hz	Polarization:	Vertical
Test Mode	Mode 1~24(Mode 9 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	95.9600	58.07	-20.67	37.40	43.50	-6.10	QP
2	333.6100	46.35	-13.59	32.76	46.00	-13.24	QP
3	442.2500	43.71	-9.99	33.72	46.00	-12.28	QP
4	612.0000	33.95	-5.50	28.45	46.00	-17.55	QP
5	837.0400	30.46	-0.46	30.00	46.00	-16.00	QP
6	995.1500	27.48	2.04	29.52	54.00	-24.48	QP

Remark:

1. Margin = Result (Result = Reading + Factor) - Limit
2. Factor = Antenna factor + Cable attenuation factor (cable loss) - Amplifier gain





3.2.8 TEST RESULTS (Above 1000 MHz)

U-NII-1 5150-5250MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11a20/ 5180 MHz)										
3262.90	44.84	44.70	6.70	28.20	-9.80	35.04	74.00	-38.96	Pk	Vertical
3262.90	41.57	44.70	6.70	28.20	-9.80	31.77	54.00	-22.23	AV	Vertical
3253.08	45.25	44.70	6.70	28.20	-9.80	35.45	68.20	-32.75	Pk	Horizontal
3253.08	41.82	44.70	6.70	28.20	-9.80	32.02	54.00	-21.98	AV	Horizontal
3990.99	38.71	44.20	7.90	29.70	-6.60	32.11	74.00	-41.89	Pk	Vertical
3990.99	35.68	44.20	7.90	29.70	-6.60	29.08	54.00	-24.92	AV	Vertical
3988.71	39.45	44.20	7.90	29.70	-6.60	32.85	74.00	-41.15	Pk	Horizontal
3988.71	36.13	44.20	7.90	29.70	-6.60	29.53	54.00	-24.47	AV	Horizontal
7234.74	37.30	43.50	11.40	35.50	3.40	40.70	68.20	-27.50	Pk	Vertical
7234.74	34.68	43.50	11.40	35.50	3.40	38.08	54.00	-15.92	AV	Vertical
7223.69	36.64	43.50	11.40	35.50	3.40	40.04	68.20	-28.16	Pk	Horizontal
7223.69	34.19	43.50	11.40	35.50	3.40	37.59	54.00	-16.41	AV	Horizontal
10360.01	39.66	44.50	13.80	38.80	8.10	47.76	68.20	-20.44	Pk	Vertical
10360.01	36.24	44.50	13.80	38.80	8.10	44.34	54.00	-9.66	AV	Vertical
10360.19	39.76	44.50	13.80	38.80	8.10	47.86	68.20	-20.34	Pk	Horizontal
10360.19	35.93	44.50	13.80	38.80	8.10	44.03	54.00	-9.97	AV	Horizontal
11028.73	32.79	43.60	14.30	39.50	10.20	42.99	74.00	-31.01	Pk	Vertical
11028.73	29.87	43.60	14.30	39.50	10.20	40.07	54.00	-13.93	AV	Vertical
11022.83	33.53	43.60	14.30	39.50	10.20	43.73	74.00	-30.27	Pk	Horizontal
11022.83	30.98	43.60	14.30	39.50	10.20	41.18	54.00	-12.82	AV	Horizontal
13295.41	31.98	42.60	15.90	38.90	12.20	44.18	74.00	-29.82	Pk	Vertical
13295.41	30.00	42.60	15.90	38.90	12.20	42.20	54.00	-11.80	AV	Vertical
13280.66	32.99	42.60	15.90	38.90	12.20	45.19	74.00	-28.81	Pk	Horizontal
13280.66	29.39	42.60	15.90	38.90	12.20	41.59	54.00	-12.41	AV	Horizontal
Mid Channel (802.11a20/ 5200 MHz)										
3248.20	44.68	44.70	6.70	28.20	-9.80	34.88	68.20	-33.32	Pk	Vertical
3248.20	41.41	44.70	6.70	28.20	-9.80	31.61	54.00	-22.39	AV	Vertical
3254.54	43.76	44.70	6.70	28.20	-9.80	33.96	68.20	-34.24	Pk	Horizontal
3254.54	41.21	44.70	6.70	28.20	-9.80	31.41	54.00	-22.59	AV	Horizontal
3991.72	38.93	44.20	7.90	29.70	-6.60	32.33	74.00	-41.67	Pk	Vertical
3991.72	35.75	44.20	7.90	29.70	-6.60	29.15	54.00	-24.85	AV	Vertical
3982.08	40.11	44.20	7.90	29.70	-6.60	33.51	74.00	-40.49	Pk	Horizontal
3982.08	36.76	44.20	7.90	29.70	-6.60	30.16	54.00	-23.84	AV	Horizontal
7218.22	37.34	43.50	11.40	35.50	3.40	40.74	68.20	-27.46	Pk	Vertical
7218.22	34.34	43.50	11.40	35.50	3.40	37.74	54.00	-16.26	AV	Vertical
7231.45	37.92	43.50	11.40	35.50	3.40	41.32	68.20	-26.88	Pk	Horizontal
7231.45	33.95	43.50	11.40	35.50	3.40	37.35	54.00	-16.65	AV	Horizontal
10400.01	39.26	44.50	13.80	38.80	8.10	47.36	68.20	-20.84	Pk	Vertical
10400.01	36.36	44.50	13.80	38.80	8.10	44.46	54.00	-9.54	AV	Vertical
10400.03	38.79	44.50	13.80	38.80	8.10	46.89	68.20	-21.31	Pk	Horizontal
10400.03	36.49	44.50	13.80	38.80	8.10	44.59	54.00	-9.41	AV	Horizontal
11033.18	32.76	43.60	14.30	39.50	10.20	42.96	74.00	-31.04	Pk	Vertical
11033.18	31.17	43.60	14.30	39.50	10.20	41.37	54.00	-12.63	AV	Vertical
11017.20	33.54	43.60	14.30	39.50	10.20	43.74	74.00	-30.26	Pk	Horizontal
11017.20	30.72	43.60	14.30	39.50	10.20	40.92	54.00	-13.08	AV	Horizontal
13280.37	32.55	42.60	15.90	38.90	12.20	44.75	74.00	-29.25	Pk	Vertical
13280.37	28.65	42.60	15.90	38.90	12.20	40.85	54.00	-13.15	AV	Vertical
13290.42	32.17	42.60	15.90	38.90	12.20	44.37	74.00	-29.63	Pk	Horizontal
13290.42	29.60	42.60	15.90	38.90	12.20	41.80	54.00	-12.20	AV	Horizontal



High Channel (802.11a20/ 5240 MHz)										
3262.25	45.05	44.70	6.70	28.20	-9.80	35.25	74.00	-38.75	Pk	Vertical
3262.25	41.46	44.70	6.70	28.20	-9.80	31.66	54.00	-22.34	AV	Vertical
3256.20	44.96	44.70	6.70	28.20	-9.80	35.16	68.20	-33.04	Pk	Horizontal
3256.20	41.56	44.70	6.70	28.20	-9.80	31.76	54.00	-22.24	AV	Horizontal
3993.24	38.86	44.20	7.90	29.70	-6.60	32.26	74.00	-41.74	Pk	Vertical
3993.24	35.71	44.20	7.90	29.70	-6.60	29.11	54.00	-24.89	AV	Vertical
3981.72	38.81	44.20	7.90	29.70	-6.60	32.21	74.00	-41.79	Pk	Horizontal
3981.72	35.76	44.20	7.90	29.70	-6.60	29.16	54.00	-24.84	AV	Horizontal
7218.95	36.80	43.50	11.40	35.50	3.40	40.20	68.20	-28.00	Pk	Vertical
7218.95	34.40	43.50	11.40	35.50	3.40	37.80	54.00	-16.20	AV	Vertical
7219.05	37.27	43.50	11.40	35.50	3.40	40.67	68.20	-27.53	Pk	Horizontal
7219.05	34.69	43.50	11.40	35.50	3.40	38.09	54.00	-15.91	AV	Horizontal
10479.94	39.67	44.50	13.80	38.80	8.10	47.77	68.20	-20.43	Pk	Vertical
10479.94	36.19	44.50	13.80	38.80	8.10	44.29	54.00	-9.71	AV	Vertical
10479.96	40.05	44.50	13.80	38.80	8.10	48.15	68.20	-20.05	Pk	Horizontal
10479.96	35.71	44.50	13.80	38.80	8.10	43.81	54.00	-10.19	AV	Horizontal
11031.97	33.15	43.60	14.30	39.50	10.20	43.35	74.00	-30.65	Pk	Vertical
11031.97	30.20	43.60	14.30	39.50	10.20	40.40	54.00	-13.60	AV	Vertical
11028.13	33.98	43.60	14.30	39.50	10.20	44.18	74.00	-29.82	Pk	Horizontal
11028.13	30.66	43.60	14.30	39.50	10.20	40.86	54.00	-13.14	AV	Horizontal
13299.82	31.69	42.60	15.90	38.90	12.20	43.89	74.00	-30.11	Pk	Vertical
13299.82	28.95	42.60	15.90	38.90	12.20	41.15	54.00	-12.85	AV	Vertical
13292.46	31.58	42.60	15.90	38.90	12.20	43.78	74.00	-30.22	Pk	Horizontal
13292.46	29.12	42.60	15.90	38.90	12.20	41.32	54.00	-12.68	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a, 802.11n (HT-20), 802.11n (HT-40), 802.11ac (VHT-20), 802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11a.
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



U-NII-2A 5250-5350MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11n20/ 5260 MHz)										
3259.19	45.03	44.70	6.70	28.20	-9.80	35.23	68.20	-32.97	Pk	Vertical
3259.19	42.09	44.70	6.70	28.20	-9.80	32.29	54.00	-21.71	AV	Vertical
3258.67	45.09	44.70	6.70	28.20	-9.80	35.29	68.20	-32.91	Pk	Horizontal
3258.67	41.15	44.70	6.70	28.20	-9.80	31.35	54.00	-22.65	AV	Horizontal
3980.95	39.91	44.20	7.90	29.70	-6.60	33.31	74.00	-40.69	Pk	Vertical
3980.95	35.99	44.20	7.90	29.70	-6.60	29.39	54.00	-24.61	AV	Vertical
3990.72	39.65	44.20	7.90	29.70	-6.60	33.05	74.00	-40.95	Pk	Horizontal
3990.72	36.60	44.20	7.90	29.70	-6.60	30.00	54.00	-24.00	AV	Horizontal
7227.04	36.53	43.50	11.40	35.50	3.40	39.93	68.20	-28.27	Pk	Vertical
7227.04	34.07	43.50	11.40	35.50	3.40	37.47	54.00	-16.53	AV	Vertical
7234.94	37.07	43.50	11.40	35.50	3.40	40.47	68.20	-27.73	Pk	Horizontal
7234.94	34.73	43.50	11.40	35.50	3.40	38.13	54.00	-15.87	AV	Horizontal
10520.32	40.16	44.50	13.90	38.80	8.20	48.36	68.20	-19.84	Pk	Vertical
10520.32	36.99	44.50	13.90	38.80	8.20	45.19	54.00	-8.81	AV	Vertical
10520.03	39.09	44.50	13.90	38.80	8.20	47.29	68.20	-20.91	Pk	Horizontal
10520.03	36.38	44.50	13.90	38.80	8.20	44.58	54.00	-9.42	AV	Horizontal
11023.63	33.16	43.60	14.30	39.50	10.20	43.36	74.00	-30.64	Pk	Vertical
11023.63	29.83	43.60	14.30	39.50	10.20	40.03	54.00	-13.97	AV	Vertical
11030.65	34.07	43.60	14.30	39.50	10.20	44.27	74.00	-29.73	Pk	Horizontal
11030.65	31.06	43.60	14.30	39.50	10.20	41.26	54.00	-12.74	AV	Horizontal
13285.14	32.64	42.60	15.90	38.90	12.20	44.84	74.00	-29.16	Pk	Vertical
13285.14	29.60	42.60	15.90	38.90	12.20	41.80	54.00	-12.20	AV	Vertical
13290.34	32.90	42.60	15.90	38.90	12.20	45.10	74.00	-28.90	Pk	Horizontal
13290.34	29.64	42.60	15.90	38.90	12.20	41.84	54.00	-12.16	AV	Horizontal
Mid Channel (802.11n20/ 5300 MHz)										
3260.90	44.26	44.70	6.70	28.20	-9.80	34.46	74.00	-39.54	Pk	Vertical
3260.90	40.93	44.70	6.70	28.20	-9.80	31.13	54.00	-22.87	AV	Vertical
3254.65	44.88	44.70	6.70	28.20	-9.80	35.08	68.20	-33.12	Pk	Horizontal
3254.65	41.12	44.70	6.70	28.20	-9.80	31.32	54.00	-22.68	AV	Horizontal
3998.24	39.32	44.20	7.90	29.70	-6.60	32.72	74.00	-41.28	Pk	Vertical
3998.24	36.63	44.20	7.90	29.70	-6.60	30.03	54.00	-23.97	AV	Vertical
3993.50	38.76	44.20	7.90	29.70	-6.60	32.16	74.00	-41.84	Pk	Horizontal
3993.50	36.25	44.20	7.90	29.70	-6.60	29.65	54.00	-24.35	AV	Horizontal
7221.65	36.69	43.50	11.40	35.50	3.40	40.09	68.20	-28.11	Pk	Vertical
7221.65	34.46	43.50	11.40	35.50	3.40	37.86	54.00	-16.14	AV	Vertical
7230.00	36.80	43.50	11.40	35.50	3.40	40.20	68.20	-28.00	Pk	Horizontal
7230.00	34.53	43.50	11.40	35.50	3.40	37.93	54.00	-16.07	AV	Horizontal
10600.03	39.93	44.50	13.80	38.80	8.10	48.03	74.00	-25.97	Pk	Vertical
10600.03	36.18	44.50	13.80	38.80	8.10	44.28	54.00	-9.72	AV	Vertical
10600.15	39.32	44.50	13.80	38.80	8.10	47.42	74.00	-26.58	Pk	Horizontal
10600.15	36.77	44.50	13.80	38.80	8.10	44.87	54.00	-9.13	AV	Horizontal
11025.17	33.58	43.60	14.30	39.50	10.20	43.78	74.00	-30.22	Pk	Vertical
11025.17	30.89	43.60	14.30	39.50	10.20	41.09	54.00	-12.91	AV	Vertical
11019.63	33.36	43.60	14.30	39.50	10.20	43.56	74.00	-30.44	Pk	Horizontal
11019.63	30.97	43.60	14.30	39.50	10.20	41.17	54.00	-12.83	AV	Horizontal
13286.50	32.73	42.60	15.90	38.90	12.20	44.93	74.00	-29.07	Pk	Vertical
13286.50	28.65	42.60	15.90	38.90	12.20	40.85	54.00	-13.15	AV	Vertical
13281.61	31.58	42.60	15.90	38.90	12.20	43.78	74.00	-30.22	Pk	Horizontal
13281.61	28.61	42.60	15.90	38.90	12.20	40.81	54.00	-13.19	AV	Horizontal



High Channel (802.11n20/ 5320 MHz)										
3250.14	45.17	44.70	6.70	28.20	-9.80	35.37	68.20	-32.83	Pk	Vertical
3250.14	41.94	44.70	6.70	28.20	-9.80	32.14	54.00	-21.86	AV	Vertical
3250.80	43.99	44.70	6.70	28.20	-9.80	34.19	68.20	-34.01	Pk	Horizontal
3250.80	40.98	44.70	6.70	28.20	-9.80	31.18	54.00	-22.82	AV	Horizontal
3990.63	39.05	44.20	7.90	29.70	-6.60	32.45	74.00	-41.55	Pk	Vertical
3990.63	36.73	44.20	7.90	29.70	-6.60	30.13	54.00	-23.87	AV	Vertical
3994.81	38.81	44.20	7.90	29.70	-6.60	32.21	74.00	-41.79	Pk	Horizontal
3994.81	37.05	44.20	7.90	29.70	-6.60	30.45	54.00	-23.55	AV	Horizontal
7234.61	37.70	43.50	11.40	35.50	3.40	41.10	68.20	-27.10	Pk	Vertical
7234.61	34.81	43.50	11.40	35.50	3.40	38.21	54.00	-15.79	AV	Vertical
7227.64	36.74	43.50	11.40	35.50	3.40	40.14	68.20	-28.06	Pk	Horizontal
7227.64	34.00	43.50	11.40	35.50	3.40	37.40	54.00	-16.60	AV	Horizontal
10640.14	40.13	44.50	13.80	38.80	8.10	48.23	74.00	-25.77	Pk	Vertical
10640.14	36.63	44.50	13.80	38.80	8.10	44.73	54.00	-9.27	AV	Vertical
10640.09	40.17	44.50	13.80	38.80	8.10	48.27	74.00	-25.73	Pk	Horizontal
10640.09	36.76	44.50	13.80	38.80	8.10	44.86	54.00	-9.14	AV	Horizontal
11017.50	33.34	43.60	14.30	39.50	10.20	43.54	74.00	-30.46	Pk	Vertical
11017.50	30.71	43.60	14.30	39.50	10.20	40.91	54.00	-13.09	AV	Vertical
11030.05	33.00	43.60	14.30	39.50	10.20	43.20	74.00	-30.80	Pk	Horizontal
11030.05	31.15	43.60	14.30	39.50	10.20	41.35	54.00	-12.65	AV	Horizontal
13291.62	32.18	42.70	18.00	37.10	12.40	44.58	74.00	-29.42	Pk	Vertical
13291.62	29.22	42.70	18.00	37.10	12.40	41.62	54.00	-12.38	AV	Vertical
13289.58	32.01	42.70	18.00	37.10	12.40	44.41	74.00	-29.59	Pk	Horizontal
13289.58	29.58	42.70	18.00	37.10	12.40	41.98	54.00	-12.02	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11n (HT-20).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



U-NII-2C 5470-5725MHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Orrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Low Channel (802.11n20/ 5500 MHz)										
3263.50	43.93	44.70	6.70	28.20	-9.80	34.13	74.00	-39.87	Pk	Vertical
3263.50	41.77	44.70	6.70	28.20	-9.80	31.97	54.00	-22.03	AV	Vertical
3245.33	44.58	44.70	6.70	28.20	-9.80	34.78	68.20	-33.42	Pk	Horizontal
3245.33	41.19	44.70	6.70	28.20	-9.80	31.39	54.00	-22.61	AV	Horizontal
3982.96	39.82	44.20	7.90	29.70	-6.60	33.22	74.00	-40.78	Pk	Vertical
3982.96	36.08	44.20	7.90	29.70	-6.60	29.48	54.00	-24.52	AV	Vertical
3995.32	39.93	44.20	7.90	29.70	-6.60	33.33	74.00	-40.67	Pk	Horizontal
3995.32	36.52	44.20	7.90	29.70	-6.60	29.92	54.00	-24.08	AV	Horizontal
7223.87	36.76	43.50	11.40	35.50	3.40	40.16	68.20	-28.04	Pk	Vertical
7223.87	33.58	43.50	11.40	35.50	3.40	36.98	54.00	-17.02	AV	Vertical
7223.64	37.65	43.50	11.40	35.50	3.40	41.05	68.20	-27.15	Pk	Horizontal
7223.64	33.65	43.50	11.40	35.50	3.40	37.05	54.00	-16.95	AV	Horizontal
10345.23	38.99	44.50	13.80	38.80	8.10	47.09	68.20	-21.11	Pk	Vertical
10345.23	35.93	44.50	13.80	38.80	8.10	44.03	54.00	-9.97	AV	Vertical
10353.31	39.20	44.50	13.80	38.80	8.10	47.30	68.20	-20.90	Pk	Horizontal
10353.31	36.76	44.50	13.80	38.80	8.10	44.86	54.00	-9.14	AV	Horizontal
11000.18	32.83	43.60	14.30	39.50	10.20	43.03	74.00	-30.97	Pk	Vertical
11000.18	30.69	43.60	14.30	39.50	10.20	40.89	54.00	-13.11	AV	Vertical
10999.99	33.07	43.60	14.30	39.50	10.20	43.27	74.00	-30.73	Pk	Horizontal
10999.99	30.77	43.60	14.30	39.50	10.20	40.97	54.00	-13.03	AV	Horizontal
13281.96	31.81	42.60	15.90	38.90	12.20	44.01	74.00	-29.99	Pk	Vertical
13281.96	28.74	42.60	15.90	38.90	12.20	40.94	54.00	-13.06	AV	Vertical
13291.69	32.07	42.60	15.90	38.90	12.20	44.27	74.00	-29.73	Pk	Horizontal
13291.69	28.60	42.60	15.90	38.90	12.20	40.80	54.00	-13.20	AV	Horizontal
Mid Channel (802.11n20/ 5580 MHz)										
3261.81	44.88	44.70	6.70	28.20	-9.80	35.08	74.00	-38.92	Pk	Vertical
3261.81	41.81	44.70	6.70	28.20	-9.80	32.01	54.00	-21.99	AV	Vertical
3264.77	44.92	44.70	6.70	28.20	-9.80	35.12	74.00	-38.88	Pk	Horizontal
3264.77	41.37	44.70	6.70	28.20	-9.80	31.57	54.00	-22.43	AV	Horizontal
3987.83	38.70	44.20	7.90	29.70	-6.60	32.10	74.00	-41.90	Pk	Vertical
3987.83	37.13	44.20	7.90	29.70	-6.60	30.53	54.00	-23.47	AV	Vertical
3982.47	39.20	44.20	7.90	29.70	-6.60	32.60	74.00	-41.40	Pk	Horizontal
3982.47	36.51	44.20	7.90	29.70	-6.60	29.91	54.00	-24.09	AV	Horizontal
7232.57	37.74	43.50	11.40	35.50	3.40	41.14	68.20	-27.06	Pk	Vertical
7232.57	33.89	43.50	11.40	35.50	3.40	37.29	54.00	-16.71	AV	Vertical
7219.60	36.57	43.50	11.40	35.50	3.40	39.97	68.20	-28.23	Pk	Horizontal
7219.60	34.91	43.50	11.40	35.50	3.40	38.31	54.00	-15.69	AV	Horizontal
10395.05	38.86	44.50	13.80	38.80	8.10	46.96	68.20	-21.24	Pk	Vertical
10395.05	35.83	44.50	13.80	38.80	8.10	43.93	54.00	-10.07	AV	Vertical
10392.89	39.01	44.50	13.80	38.80	8.10	47.11	68.20	-21.09	Pk	Horizontal
10392.89	36.26	44.50	13.80	38.80	8.10	44.36	54.00	-9.64	AV	Horizontal
11160.31	33.54	43.60	14.30	39.50	10.20	43.74	74.00	-30.26	Pk	Vertical
11160.31	29.85	43.60	14.30	39.50	10.20	40.05	54.00	-13.95	AV	Vertical
11160.01	33.64	43.60	14.30	39.50	10.20	43.84	74.00	-30.16	Pk	Horizontal
11160.01	30.27	43.60	14.30	39.50	10.20	40.47	54.00	-13.53	AV	Horizontal
13291.13	32.56	42.60	15.90	38.90	12.20	44.76	74.00	-29.24	Pk	Vertical
13291.13	29.81	42.60	15.90	38.90	12.20	42.01	54.00	-11.99	AV	Vertical
13295.58	31.69	42.60	15.90	38.90	12.20	43.89	74.00	-30.11	Pk	Horizontal
13295.58	29.67	42.60	15.90	38.90	12.20	41.87	54.00	-12.13	AV	Horizontal



High Channel (802.11n20/ 5700 MHz)										
3258.19	44.90	44.70	6.70	28.20	-9.80	35.10	68.20	-33.10	Pk	Vertical
3258.19	40.79	44.70	6.70	28.20	-9.80	30.99	54.00	-23.01	AV	Vertical
3260.52	44.46	44.70	6.70	28.20	-9.80	34.66	74.00	-39.34	Pk	Horizontal
3260.52	41.59	44.70	6.70	28.20	-9.80	31.79	54.00	-22.21	AV	Horizontal
3989.80	39.86	44.20	7.90	29.70	-6.60	33.26	74.00	-40.74	Pk	Vertical
3989.80	36.40	44.20	7.90	29.70	-6.60	29.80	54.00	-24.20	AV	Vertical
3995.35	38.75	44.20	7.90	29.70	-6.60	32.15	74.00	-41.85	Pk	Horizontal
3995.35	36.94	44.20	7.90	29.70	-6.60	30.34	54.00	-23.66	AV	Horizontal
7234.60	37.55	43.50	11.40	35.50	3.40	40.95	68.20	-27.25	Pk	Vertical
7234.60	34.66	43.50	11.40	35.50	3.40	38.06	54.00	-15.94	AV	Vertical
7232.17	37.52	43.50	11.40	35.50	3.40	40.92	68.20	-27.28	Pk	Horizontal
7232.17	34.50	43.50	11.40	35.50	3.40	37.90	54.00	-16.10	AV	Horizontal
10467.71	39.53	44.50	13.80	38.80	8.10	47.63	68.20	-20.57	Pk	Vertical
10467.71	36.29	44.50	13.80	38.80	8.10	44.39	54.00	-9.61	AV	Vertical
10474.35	39.50	44.50	13.80	38.80	8.10	47.60	68.20	-20.60	Pk	Horizontal
10474.35	36.84	44.50	13.80	38.80	8.10	44.94	54.00	-9.06	AV	Horizontal
11400.38	33.84	43.60	14.30	39.50	10.20	44.04	74.00	-29.96	Pk	Vertical
11400.38	29.76	43.60	14.30	39.50	10.20	39.96	54.00	-14.04	AV	Vertical
11400.39	33.46	43.60	14.30	39.50	10.20	43.66	74.00	-30.34	Pk	Horizontal
11400.39	29.99	43.60	14.30	39.50	10.20	40.19	54.00	-13.81	AV	Horizontal
13287.92	32.62	42.60	15.90	38.90	12.20	44.82	74.00	-29.18	Pk	Vertical
13287.92	29.70	42.60	15.90	38.90	12.20	41.90	54.00	-12.10	AV	Vertical
13297.09	31.73	42.60	15.90	38.90	12.20	43.93	74.00	-30.07	Pk	Horizontal
13297.09	29.02	42.60	15.90	38.90	12.20	41.22	54.00	-12.78	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11n (HT-20).
3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



U-NII-3(5.725-5.850) GHz

Frequency (MHz)	Reading (dBuV)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
Channel (802.11ac80/ 5775 MHz)										
3264.22	45.33	44.70	6.70	28.20	-9.80	35.53	74.00	-38.47	Pk	Vertical
3264.22	41.24	44.70	6.70	28.20	-9.80	31.44	54.00	-22.56	AV	Vertical
3263.20	44.04	44.70	6.70	28.20	-9.80	34.24	74.00	-39.76	Pk	Horizontal
3263.20	41.67	44.70	6.70	28.20	-9.80	31.87	54.00	-22.13	AV	Horizontal
4011.58	40.04	44.20	7.90	29.70	-6.60	33.44	74.00	-40.56	Pk	Vertical
4011.58	36.73	44.20	7.90	29.70	-6.60	30.13	54.00	-23.87	AV	Vertical
4011.69	39.68	44.20	7.90	29.70	-6.60	33.08	74.00	-40.92	Pk	Horizontal
4011.69	36.46	44.20	7.90	29.70	-6.60	29.86	54.00	-24.14	AV	Horizontal
7258.51	37.62	43.50	11.40	35.50	3.40	41.02	74.00	-32.98	Pk	Vertical
7258.51	33.69	43.50	11.40	35.50	3.40	37.09	54.00	-16.91	AV	Vertical
7273.76	38.12	43.50	11.40	35.50	3.40	41.52	74.00	-32.48	Pk	Horizontal
7273.76	34.66	43.50	11.40	35.50	3.40	38.06	54.00	-15.94	AV	Horizontal
10560.29	40.08	44.50	13.90	38.80	8.20	48.28	68.20	-19.92	Pk	Vertical
10560.29	36.51	44.50	13.90	38.80	8.20	44.71	54.00	-9.29	AV	Vertical
10564.75	39.55	44.50	13.90	38.80	8.20	47.75	68.20	-20.45	Pk	Horizontal
10564.75	36.77	44.50	13.90	38.80	8.20	44.97	54.00	-9.03	AV	Horizontal
11550.02	33.97	43.60	14.30	39.50	10.20	44.17	74.00	-29.83	Pk	Vertical
11550.02	31.17	43.60	14.30	39.50	10.20	41.37	54.00	-12.63	AV	Vertical
11550.00	33.96	43.60	14.30	39.50	10.20	44.16	74.00	-29.84	Pk	Horizontal
11550.00	30.44	43.60	14.30	39.50	10.20	40.64	54.00	-13.36	AV	Horizontal
13368.07	32.58	42.60	15.90	38.90	12.20	44.78	74.00	-29.22	Pk	Vertical
13368.07	28.94	42.60	15.90	38.90	12.20	41.14	54.00	-12.86	AV	Vertical
13353.67	31.73	42.60	15.90	38.90	12.20	43.93	74.00	-30.07	Pk	Horizontal
13353.67	29.82	42.60	15.90	38.90	12.20	42.02	54.00	-11.98	AV	Horizontal

Remark:


- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Scan with 802.11a,802.11n (HT-20),802.11n (HT-40), 802.11ac (VHT-20),802.11ac (VHT-40), 802.11ac (VHT-80) the worst case is 802.11ac (VHT-80).
- The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.9 RESTRICTED FREQUENCY BANDS AND BAND EDGE


U-NII-1 5150-5250MHz

802.11a20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5042.250	51.54	-6.00	45.54	74.00	-28.46	peak
2	5150.000	53.19	-5.73	47.46	74.00	-26.54	peak

802.11a20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5015.250	51.90	-6.12	45.78	74.00	-28.22	peak
2	5150.000	51.34	-5.73	45.61	74.00	-28.39	peak




802.11a20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.47	-5.23	45.24	74.00	-28.76	peak
2	5394.480	51.98	-5.24	46.74	74.00	-27.26	peak


802.11a20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.45	-5.23	45.22	74.00	-28.78	peak
2	5388.040	51.66	-5.25	46.41	74.00	-27.59	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.800	52.08	-6.99	45.09	74.00	-28.91	peak
2	5150.000	62.45	-5.73	56.72	74.00	-17.28	peak
3	5150.000	52.04	-5.73	46.31	54.00	-7.69	AVG

802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4955.200	52.44	-6.48	45.96	74.00	-28.04	peak
2	5150.000	57.78	-5.73	52.05	74.00	-21.95	peak




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.00	-5.23	44.77	74.00	-29.23	peak
2	5379.080	51.46	-5.24	46.22	74.00	-27.78	peak


802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.19	-5.23	44.96	74.00	-29.04	peak
2	5383.560	52.36	-5.24	47.12	74.00	-26.88	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4957.300	52.07	-6.47	45.60	74.00	-28.40	peak
2	5150.000	62.40	-5.73	56.67	74.00	-17.33	peak
3	5150.000	52.30	-5.73	46.57	54.00	-7.43	AVG

802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5067.200	51.61	-5.89	45.72	74.00	-28.28	peak
2	5150.000	56.73	-5.73	51.00	74.00	-23.00	peak



802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	52.42	-5.23	47.19	74.00	-26.81	peak
2	5366.070	53.57	-5.24	48.33	74.00	-25.67	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	50.39	-5.23	45.16	74.00	-28.84	peak
2	5420.630	51.99	-5.20	46.79	74.00	-27.21	peak

Note: All modes have been tested. Only the worst mode shown in the report.




U-NII-2A 5250-5350MHz

802.11n20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5049.950	51.74	-5.97	45.77	74.00	-28.23	peak
2	5150.000	49.91	-5.73	44.18	74.00	-29.82	peak


802.11n20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4929.250	52.03	-6.65	45.38	74.00	-28.62	peak
2	5150.000	49.44	-5.73	43.71	74.00	-30.29	peak




802.11n20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	61.30	-5.23	56.07	74.00	-17.93	peak
2	5350.000	51.48	-5.23	46.25	54.00	-7.75	AVG
3	5391.600	51.86	-5.25	46.61	74.00	-27.39	peak


802.11n20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	56.71	-5.23	51.48	74.00	-22.52	peak
2	5411.600	51.80	-5.22	46.58	74.00	-27.42	peak




802.11n40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5021.900	51.67	-6.09	45.58	74.00	-28.42	peak
2	5150.000	50.92	-5.73	45.19	74.00	-28.81	peak

802.11n40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5066.100	52.07	-5.90	46.17	74.00	-27.83	peak
2	5150.000	50.21	-5.73	44.48	74.00	-29.52	peak




802.11n40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	67.20	-5.23	61.97	74.00	-12.03	peak
2	5350.000	56.87	-5.23	51.64	54.00	-2.36	AVG
3	5374.400	57.17	-5.24	51.93	74.00	-22.07	peak


802.11n40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	62.52	-5.23	57.29	74.00	-16.71	peak
2	5350.000	52.85	-5.23	47.62	54.00	-6.38	AVG
3	5372.200	54.91	-5.24	49.67	74.00	-24.33	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5032.100	51.03	-6.04	44.99	74.00	-29.01	peak
2	5150.000	50.66	-5.73	44.93	74.00	-29.07	peak

802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5063.550	51.70	-5.90	45.80	74.00	-28.20	peak
2	5150.000	50.04	-5.73	44.31	74.00	-29.69	peak



802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	69.69	-5.23	64.46	74.00	-9.54	peak
2	5350.000	56.57	-5.23	51.34	54.00	-2.66	AVG
3	5427.760	56.14	-5.19	50.95	74.00	-23.05	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5350.000	65.39	-5.23	60.16	74.00	-13.84	peak
2	5350.000	55.90	-5.23	50.67	54.00	-3.33	AVG
3	5412.940	57.97	-5.22	52.75	74.00	-21.25	peak

Note: All modes have been tested. Only the worst mode shown in the report.




U-NII-2C 5470-5725MHz

802.11a20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5368.240	52.30	-5.24	47.06	74.00	-26.94	peak
2	5460.000	55.01	-5.11	49.90	68.20	-18.30	peak
3	5470.000	62.20	-5.09	57.11	68.20	-11.09	peak
4	5470.000	52.21	-5.09	47.12	54.00	-6.88	AVG


802.11a20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5437.780	52.21	-5.16	47.05	74.00	-26.95	peak
2	5460.000	52.09	-5.11	46.98	68.20	-21.22	peak
3	5470.000	57.11	-5.09	52.02	68.20	-16.18	peak




802.11a20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	52.76	-4.57	48.19	68.20	-20.01	peak
2	5850.000	51.39	-4.10	47.29	68.20	-20.91	peak


802.11a20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	51.83	-4.57	47.26	68.20	-20.94	peak
2	5807.200	53.75	-4.29	49.46	68.20	-18.74	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	62.27	-5.11	57.16	68.20	-11.04	peak
2	5460.000	52.76	-5.11	47.65	54.00	-6.35	AVG
3	5470.000	69.76	-5.09	64.67	68.20	-3.53	peak
4	5470.000	58.29	-5.09	53.20	54.00	-0.80	AVG


802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5460.000	58.63	-5.11	53.52	68.20	-14.68	peak
2	5470.000	65.73	-5.09	60.64	68.20	-7.56	peak
3	5470.000	55.33	-5.09	50.24	54.00	-3.76	AVG




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	51.95	-4.57	47.38	68.20	-20.82	peak
2	5807.200	56.98	-4.29	52.69	68.20	-15.51	peak

802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	50.30	-4.57	45.73	68.20	-22.47	peak
2	5778.800	53.23	-4.39	48.84	68.20	-19.36	peak




802.11ac80-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5420.500	54.43	-5.20	49.23	74.00	-24.77	peak
2	5460.000	68.13	-5.11	63.02	68.20	-5.18	peak
3	5460.000	58.35	-5.11	53.24	54.00	-0.76	AVG
4	5470.000	65.49	-5.09	60.40	68.20	-7.80	peak
5	5470.000	55.61	-5.09	50.52	68.20	-17.68	RMS


802.11ac80-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5430.750	57.04	-5.18	51.86	74.00	-22.14	peak
2	5460.000	62.03	-5.11	56.92	68.20	-11.28	peak
3	5460.000	51.13	-5.11	46.02	54.00	-7.98	AVG
4	5470.000	58.51	-5.09	53.42	68.20	-14.78	peak




802.11ac80-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	50.13	-4.57	45.56	68.20	-22.64	peak
2	5779.500	54.01	-4.39	49.62	68.20	-18.58	peak

802.11ac80-H-V




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	50.03	-4.57	45.46	68.20	-22.74	peak
2	5898.500	51.04	-3.88	47.16	68.20	-21.04	peak

Note: All modes have been tested. Only the worst mode shown in the report.



U-NII-3(5.725-5.85 GHz)


802.11a20-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5627.375	51.36	-4.69	46.67	68.20	-21.53	peak
2	5705.375	58.26	-4.64	53.62	106.70	-53.08	peak
3	5725.000	74.57	-4.57	70.00	122.20	-52.20	peak
4	5850.000	51.29	-4.10	47.19	122.20	-75.01	peak
5	5898.125	51.09	-3.89	47.20	88.09	-40.89	peak
6	5945.750	50.58	-3.96	46.62	68.20	-21.58	peak




802.11a20-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5611.625	51.67	-4.69	46.98	68.20	-21.22	peak
2	5704.625	57.12	-4.64	52.48	106.50	-54.02	peak
3	5725.000	73.51	-4.57	68.94	122.20	-53.26	peak
4	5850.000	49.68	-4.10	45.58	122.20	-76.62	peak
5	5914.625	51.70	-3.91	47.79	75.88	-28.09	peak
6	5936.375	51.28	-3.94	47.34	68.20	-20.86	peak




802.11a20-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5637.500	51.77	-4.69	47.08	68.20	-21.12	peak
2	5687.750	51.47	-4.67	46.80	96.14	-49.34	peak
3	5725.000	49.58	-4.57	45.01	122.20	-77.19	peak
4	5850.000	50.18	-4.10	46.08	122.20	-76.12	peak
5	5911.625	51.27	-3.90	47.37	78.10	-30.73	peak
6	5928.500	51.25	-3.92	47.33	68.20	-20.87	peak




802.11a20-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5636.375	51.39	-4.68	46.71	68.20	-21.49	peak
2	5679.875	50.99	-4.67	46.32	90.31	-43.99	peak
3	5725.000	49.74	-4.57	45.17	122.20	-77.03	peak
4	5850.000	53.43	-4.10	49.33	122.20	-72.87	peak
5	5908.625	51.04	-3.90	47.14	80.32	-33.18	peak
6	5940.875	50.85	-3.94	46.91	68.20	-21.29	peak




802.11ac40-L-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5628.875	51.46	-4.68	46.78	68.20	-21.42	peak
2	5702.375	58.03	-4.66	53.37	105.87	-52.50	peak
3	5725.000	69.90	-4.57	65.33	122.20	-56.87	peak
4	5850.000	48.72	-4.10	44.62	122.20	-77.58	peak
5	5908.625	50.53	-3.90	46.63	80.32	-33.69	peak
6	5937.500	51.45	-3.94	47.51	68.20	-20.69	peak




802.11ac40-L-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5643.125	51.68	-4.68	47.00	68.20	-21.20	peak
2	5707.625	60.22	-4.64	55.58	107.33	-51.75	peak
3	5725.000	67.85	-4.57	63.28	122.20	-58.92	peak
4	5850.000	49.33	-4.10	45.23	122.20	-76.97	peak
5	5924.375	50.71	-3.92	46.79	68.66	-21.87	peak
6	5943.125	50.67	-3.95	46.72	68.20	-21.48	peak




802.11ac40-H-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5633.750	52.10	-4.69	47.41	68.20	-20.79	peak
2	5674.250	51.21	-4.67	46.54	86.14	-39.60	peak
3	5725.000	51.32	-4.57	46.75	122.20	-75.45	peak
4	5850.000	50.79	-4.10	46.69	122.20	-75.51	peak
5	5913.875	52.22	-3.91	48.31	76.43	-28.12	peak
6	5935.625	51.04	-3.94	47.10	68.20	-21.10	peak




802.11ac40-H-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5635.250	51.11	-4.68	46.43	68.20	-21.77	peak
2	5684.750	51.24	-4.66	46.58	93.92	-47.34	peak
3	5725.000	51.30	-4.57	46.73	122.20	-75.47	peak
4	5850.000	51.53	-4.10	47.43	122.20	-74.77	peak
5	5911.250	50.95	-3.90	47.05	78.38	-31.33	peak
6	5928.125	50.68	-3.93	46.75	68.20	-21.45	peak




802.11ac80-H



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5638.625	57.61	-4.69	52.92	68.20	-15.28	peak
2	5700.125	68.60	-4.66	63.94	105.23	-41.29	peak
3	5725.000	71.29	-4.57	66.72	122.20	-55.48	peak
4	5850.000	58.34	-4.10	54.24	122.20	-67.96	peak
5	5873.000	61.05	-4.00	57.05	105.76	-48.71	peak
6	5926.250	53.79	-3.93	49.86	68.20	-18.34	peak



802.11ac80-V



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5646.125	56.64	-4.69	51.95	68.20	-16.25	peak
2	5685.500	67.22	-4.66	62.56	94.47	-31.91	peak
3	5725.000	73.91	-4.57	69.34	122.20	-52.86	peak
4	5850.000	65.61	-4.10	61.51	122.20	-60.69	peak
5	5891.000	56.44	-3.92	52.52	93.36	-40.84	peak
6	5935.250	51.08	-3.94	47.14	68.20	-21.06	peak

Note: All modes have been tested. Only the worst mode shown in the report.



4. POWER SPECTRAL DENSITY TEST

4.1 LIMIT

1. For mobile and portable client devices in the 5.15-5.25 GHz band, , the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
2. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
3. For the band 5.725-5.850 GHz, the peak power spectral density shall not exceed 30 dBm in any 500KHz band. If transmitting antenna directional gain is greater than 6 dBi, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2 TEST PROCEDURE

1. The setting follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
2. Set span to encompass the EBW
3. Set RBW = 1MHz.
4. Set the VBW $\geq$ 3MHz.
5. Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. Detector = power averaging (rms), if available. Otherwise, use sample detector mode
8. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed to ensure that the average accurately represents the true average over the on and off periods of the transmitter.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



**4.6 TEST RESULTS**

5150-5250MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5180	1.746	0.099	1.845	11	PASS
5200	0.989	0.099	1.088	11	PASS
5240	0.042	0.099	0.141	11	PASS
802.11n20					
5180	0.578	0.211	0.789	11	PASS
5200	0.224	0.211	0.435	11	PASS
5240	-0.530	0.211	-0.319	11	PASS
802.11n40					
5190	-3.806	0.252	-3.554	11	PASS
5230	-3.712	0.252	-3.460	11	PASS
802.11ac20					
5180	0.409	0.159	0.568	11	PASS
5200	0.174	0.159	0.333	11	PASS
5240	-0.269	0.159	-0.110	11	PASS
802.11ac40					
5190	-3.619	0.172	-3.447	11	PASS
5230	-3.954	0.172	-3.782	11	PASS
802.11ac80					
5210	-4.715	0.297	-4.418	11	PASS



5250-5350MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5260	-0.588	0.062	-0.526	11	PASS
5300	1.936	0.062	1.998	11	PASS
5320	-1.722	0.062	-1.660	11	PASS
802.11n20					
5260	-1.395	0.209	-1.186	11	PASS
5300	-1.801	0.209	-1.592	11	PASS
5320	-2.057	0.209	-1.848	11	PASS
802.11n40					
5270	-4.169	0.376	-3.793	11	PASS
5310	-4.757	0.376	-4.381	11	PASS
802.11ac20					
5260	-1.208	0.145	-1.063	11	PASS
5300	-1.801	0.145	-1.656	11	PASS
5320	-2.028	0.145	-1.883	11	PASS
802.11ac40					
5270	-3.983	0.298	-3.685	11	PASS
5310	-4.749	0.298	-4.451	11	PASS
802.11ac80					
5290	-7.020	0.259	-6.761	11	PASS



5470-5725MHz					
Frequency	Direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a					
5500	1.109	0.159	1.268	11	PASS
5580	1.763	0.159	1.922	11	PASS
5700	1.760	0.159	1.919	11	PASS
802.11n20					
5500	0.841	0.274	1.115	11	PASS
5580	1.348	0.274	1.622	11	PASS
5700	1.394	0.274	1.668	11	PASS
802.11n40					
5510	-0.542	0.439	-0.103	11	PASS
5550	0.159	0.439	0.598	11	PASS
5670	0.130	0.439	0.569	11	PASS
802.11ac20					
5500	1.049	0.106	1.155	11	PASS
5580	1.748	0.106	1.854	11	PASS
5700	2.333	0.106	2.439	11	PASS
802.11ac40					
5510	-0.639	0.302	-0.337	11	PASS
5550	-0.048	0.302	0.254	11	PASS
5670	0.205	0.302	0.507	11	PASS
802.11ac80					
5530	-2.010	0.273	-1.737	11	PASS
5610	-1.130	0.273	-0.857	11	PASS



5725-5850MHz						
Frequency	Use RBW 510KHz direct measurement Direct measurement Power Density (dBm)	Convert to RBW 500KHz direct measurement Power Density (dBm)	Duty cycle factor (dB)	Final Power Density (dBm)	Limit (dBm)	Result
802.11a						
5745	0.571	0.485	0.218	0.703	30	PASS
5785	-0.308	-0.394	0.218	-0.176	30	PASS
5825	-1.974	-2.060	0.218	-1.842	30	PASS
802.11n20						
5745	-1.201	-1.287	0.233	-1.054	30	PASS
5785	-1.460	-1.546	0.233	-1.313	30	PASS
5825	-2.005	-2.091	0.233	-1.858	30	PASS
802.11n40						
5755	-4.106	-4.192	0.316	-3.876	30	PASS
5795	-4.474	-4.560	0.316	-4.244	30	PASS
802.11ac20						
5745	-0.970	-1.056	0.323	-0.733	30	PASS
5785	-1.373	-1.459	0.323	-1.136	30	PASS
5825	-1.801	-1.887	0.323	-1.564	30	PASS
802.11ac40						
5755	-8.726	-8.812	0.366	-8.446	30	PASS
5795	-4.044	-4.130	0.366	-3.764	30	PASS
802.11ac80						
5775	-6.317	-6.403	0.274	-6.129	30	PASS

Note: 1. RB conversion formula: $10 \cdot \log(500\text{KHz}/\text{RBW})$

2. Test plots see Attachment A.

5. BANDWIDTH MEASUREMENT

5.1 EMISSION BANDWIDTH (EBW) 26 BANDWID PROCEDURES / LIMIT

The following procedure shall be used for measuring 26 bandwidth.

5.1.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW $\geq$ RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.1.5 TEST RESULTS**

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5180	20.49	Pass
5200	20.60	Pass
5240	20.83	Pass
802.11n(HT20)		
5180	21.46	Pass
5200	21.23	Pass
5240	21.19	Pass
802.11n(HT40)		
5190	41.32	Pass
5230	41.33	Pass
802.11ac(VHT20)		
5180	20.92	Pass
5200	21.26	Pass
5240	21.18	Pass
802.11ac(VHT40)		
5190	41.43	Pass
5230	41.66	Pass
802.11ac(VHT80)		
5210	80.98	Pass

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5260	20.53	Pass
5300	21.15	Pass
5320	20.39	Pass
802.11n(HT20)		
5260	20.74	Pass
5300	20.92	Pass
5320	20.94	Pass
802.11n(HT40)		
5270	41.34	Pass
5310	41.19	Pass
802.11ac(VHT20)		
5260	20.60	Pass
5300	21.09	Pass
5320	20.90	Pass
802.11ac(VHT40)		
5270	41.67	Pass
5310	41.21	Pass
802.11ac(VHT80)		
5290	84.45	Pass



Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5500	25.92	Pass
5580	25.45	Pass
5700	20.60	Pass
802.11n(HT20)		
5500	25.89	Pass
5580	25.85	Pass
5700	20.93	Pass
802.11n(HT40)		
5510	56.00	Pass
5550	55.99	Pass
5670	54.30	Pass
802.11ac(VHT20)		
5500	25.96	Pass
5580	25.89	Pass
5700	22.32	Pass
802.11ac(VHT40)		
5510	56.00	Pass
5550	56.00	Pass
5670	54.75	Pass
802.11ac(VHT80)		
5530	115.00	Pass
5610	115.00	Pass

Frequency (MHz)	26dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	20.84	Pass
5785	20.68	Pass
5825	20.56	Pass
802.11n(HT20)		
5745	20.93	Pass
5785	20.73	Pass
5825	20.87	Pass
802.11n(HT40)		
5755	41.60	Pass
5795	41.48	Pass
802.11ac(VHT20)		
5745	20.82	Pass
5785	20.84	Pass
5825	20.74	Pass
802.11ac(VHT40)		
5755	40.30	Pass
5795	41.74	Pass
802.11ac(VHT80)		
5775	81.71	Pass

Test plot see Attachment B.

5.2 OCCUPIED BANDWIDTH (99%) TEST APPLIED PROCEDURES / LIMIT

The following procedure shall be used for measuring (99 %) power bandwidth.

5.2.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

5.2.2 DEVIATION FROM STANDARD

No deviation.

5.2.3 TEST SETUP



5.2.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.2.5 TEST RESULTS**

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5180	16.58	Pass
5200	16.61	Pass
5240	16.58	Pass
802.11n(HT20)		
5180	17.66	Pass
5200	17.72	Pass
5240	17.71	Pass
802.11n(HT40)		
5190	36.15	Pass
5230	36.14	Pass
802.11ac(VHT20)		
5180	17.66	Pass
5200	17.67	Pass
5240	17.69	Pass
802.11ac(VHT40)		
5190	36.18	Pass
5230	36.18	Pass
802.11ac(VHT80)		
5210	75.63	Pass

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5260	16.51	Pass
5300	16.60	Pass
5320	16.58	Pass
802.11n(HT20)		
5260	17.61	Pass
5300	17.66	Pass
5320	17.62	Pass
802.11n(HT40)		
5270	36.16	Pass
5310	36.11	Pass
802.11ac(VHT20)		
5260	17.61	Pass
5300	17.65	Pass
5320	17.61	Pass
802.11ac(VHT40)		
5270	36.14	Pass
5310	36.13	Pass
802.11ac(VHT80)		
5290	75.67	Pass



Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5500	16.76	Pass
5580	16.72	Pass
5700	16.56	Pass
802.11n(HT20)		
5500	17.77	Pass
5580	17.73	Pass
5700	17.64	Pass
802.11n(HT40)		
5510	36.90	Pass
5550	36.91	Pass
5670	36.37	Pass
802.11ac(VHT20)		
5500	17.84	Pass
5580	17.78	Pass
5700	17.65	Pass
802.11ac(VHT40)		
5510	36.92	Pass
5550	36.75	Pass
5670	36.33	Pass
802.11ac(VHT80)		
5530	77.18	Pass
5610	76.27	Pass

Frequency (MHz)	99% Bandwidth (MHz)	Pass/Fail
802.11a		
5745	16.59	Pass
5785	16.55	Pass
5825	16.57	Pass
802.11n(HT20)		
5745	17.68	Pass
5785	17.63	Pass
5825	17.63	Pass
802.11n(HT40)		
5755	36.15	Pass
5795	36.23	Pass
802.11ac(VHT20)		
5745	17.60	Pass
5785	17.63	Pass
5825	17.61	Pass
802.11ac(VHT40)		
5755	35.97	Pass
5795	36.25	Pass
802.11ac(VHT80)		
5775	75.69	Pass

Test plot See Attachment B.

5.3 MINIMUM EMISSION BANDWIDTH(6 DB) PROCEDURES / LIMIT

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.725-5.85 GHz. The following procedure shall be used for measuring this bandwidth.

5.3.1 TEST PROCEDURE

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures v02r01.
 - a) Set RBW = 100 kHz.
 - b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.2 DEVIATION FROM STANDARD

No deviation.

5.3.3 TEST SETUP



5.3.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.3.5 TEST RESULTS**

Frequency (MHz)	6dB Bandwidth (MHz)	Pass/Fail
802.11a		
5745	16.33	Pass
5785	16.33	Pass
5825	16.33	Pass
802.11n(HT20)		
5745	17.53	Pass
5785	17.05	Pass
5825	17.24	Pass
802.11n(HT40)		
5755	35.34	Pass
5795	35.72	Pass
802.11ac(VHT20)		
5745	17.56	Pass
5785	17.31	Pass
5825	17.50	Pass
802.11ac(VHT40)		
5755	35.11	Pass
5795	35.74	Pass
802.11ac(VHT80)		
5775	75.42	Pass

Test plots see Attachment C.

6. MAXIMUM CONDUCTED OUTPUT POWER

6.1 LIMIT

For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz, If transmitting antennas of directional gain greater than 6 dBi are used.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. If transmitting antennas of directional gain greater than 6 dBi are used.

FCC Part15 (15.407) , Subpart E				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.407(a) (1) (iv)	Peak Output Power	0.25 watt	5150-5250	PASS
		The lesser of 250 mW or 11 dBm + 10 log (26 dB emission bandwidth)	5250-5350 5470-5725	
15.407(a) (3)		1 watt	5725-5825	


6.2 TEST PROCEDURE

The EUT was directly connected to the Power Sensor&PC

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 5 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULTS

U-NII-1 (5.15-5.25GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
36	5180	12.39	0.099	12.49	23.98
40	5200	12.27	0.099	12.37	23.98
48	5240	11.21	0.099	11.31	23.98
802.11n(HT20)					
36	5180	12.04	0.211	12.25	23.98
40	5200	11.80	0.211	12.01	23.98
48	5240	10.97	0.211	11.18	23.98
802.11n(HT40)					
38	5190	11.66	0.252	11.91	23.98
46	5230	10.91	0.252	11.16	23.98
802.11ac(VHT20)					
36	5180	11.75	0.159	11.91	23.98
40	5200	11.60	0.159	11.76	23.98
48	5240	10.77	0.159	10.93	23.98
802.11ac(VHT40)					
38	5190	11.98	0.172	12.15	23.98
46	5230	11.18	0.172	11.35	23.98
802.11ac(VHT80)					
42	5210	9.56	0.297	9.86	23.98

U-NII-2A(5.25-5.35GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
52	5260	10.83	0.062	10.89	23.98
60	5300	9.48	0.062	9.54	23.98
64	5320	9.33	0.062	9.39	23.98
802.11n(HT20)					
52	5260	10.94	0.209	11.15	23.98
60	5300	9.65	0.209	9.86	23.98
64	5320	9.40	0.209	9.61	23.98
802.11n(HT40)					
54	5270	10.63	0.376	11.01	23.98
62	5310	9.26	0.376	9.64	23.98
802.11ac(VHT20)					
52	5260	10.89	0.145	11.03	23.98
60	5300	9.55	0.145	9.69	23.98
64	5320	9.37	0.145	9.51	23.98
802.11ac(VHT40)					
54	5270	10.55	0.298	10.85	23.98
62	5310	9.23	0.298	9.53	23.98
802.11ac(VHT80)					
58	5290	8.34	0.259	8.60	23.98




U-NII-2C(5.47-5.725GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
100	5500	10.93	0.159	11.09	23.98
116	5580	13.01	0.159	13.17	23.98
140	5700	12.59	0.159	12.75	23.98
802.11n(HT20)					
100	5500	10.75	0.274	11.02	23.98
116	5580	12.98	0.274	13.25	23.98
140	5700	12.44	0.274	12.71	23.98
802.11n(HT40)					
102	5510	10.91	0.439	11.35	23.98
110	5550	12.41	0.439	12.85	23.98
134	5670	12.52	0.439	12.96	23.98
802.11ac(VHT20)					
100	5500	10.80	0.106	10.91	23.98
116	5580	12.94	0.106	13.05	23.98
140	5700	12.49	0.106	12.60	23.98
802.11ac(VHT40)					
102	5510	10.92	0.302	11.22	23.98
110	5550	12.44	0.302	12.74	23.98
134	5670	12.56	0.302	12.86	23.98
802.11ac(VHT80)					
106	5530	9.17	0.273	9.44	23.98
122	5610	10.11	0.273	10.38	23.98

U-NII-3 (5.725-5.85GHz)					
Test Channel	Frequency (MHz)	Direct measurement AV Power (dBm)	Duty cycle factor (dB)	Final AV Power (dBm)	LIMIT (dBm)
802.11a					
149	5745	11.40	0.218	11.62	30.00
157	5785	11.69	0.218	11.91	30.00
165	5825	11.20	0.218	11.42	30.00
802.11n(HT20)					
149	5745	11.36	0.233	11.59	30.00
157	5785	11.62	0.233	11.85	30.00
165	5825	11.04	0.233	11.27	30.00
802.11n(HT40)					
151	5755	11.23	0.316	11.55	30.00
159	5795	11.51	0.316	11.83	30.00
802.11ac(VHT20)					
149	5745	11.33	0.323	11.65	30.00
157	5785	11.64	0.323	11.96	30.00
165	5825	11.09	0.323	11.41	30.00
802.11ac(VHT40)					
151	5755	11.25	0.366	11.62	30.00
159	5795	11.56	0.366	11.93	30.00
802.11ac(VHT80)					
155	5775	12.62	0.274	12.89	30.00



5210MHz



5290MHz



5530MHz



5610MHz




5775MHz



Duty Cycle


U-NII-1				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	2.088	2.136	97.75%	0.099
n20	1.932	2.028	95.27%	0.211
n40	0.954	1.011	94.36%	0.252
ac20	1.932	2.004	96.41%	0.159
ac40	0.963	1.002	96.11%	0.172
ac80	1.950	2.088	93.39%	0.297
U-NII-2A				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	2.088	2.118	98.58%	0.062
n20	1.944	2.040	95.29%	0.209
n40	0.972	1.060	91.70%	0.376
ac20	1.950	2.016	96.73%	0.145
ac40	0.956	1.024	93.36%	0.298
ac80	1.956	2.076	94.22%	0.259
U-NII-2C				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	2.094	2.172	96.41%	0.159
n20	1.932	2.058	93.88%	0.274
n40	0.960	1.062	90.40%	0.439
ac20	1.944	1.992	97.59%	0.106
ac40	0.957	1.026	93.27%	0.302
ac80	1.944	2.070	93.91%	0.273
U-NII-3				
Mode	Ton(ms)	Tp(ms)	Duty cycle(%)	Duty factor(dB)
a	2.094	2.202	95.10%	0.218
n20	1.956	2.064	94.77%	0.233
n40	0.954	1.026	92.98%	0.316
ac20	1.944	2.094	92.84%	0.323
ac40	0.954	1.038	91.91%	0.366
ac80	1.932	2.058	93.88%	0.274




U-NII-1-a20



U-NII-1-n20



U-NII-1-n40



U-NII-1-ac20



U-NII-1-ac40



U-NII-1-ac80



U-NII-2A-a20



U-NII-2A-n20



U-NII-2A-n40



U-NII-2A-ac20



U-NII-2A-ac40



U-NII-2A-ac80



U-NII-2C-a20



U-NII-2C-n20




U-NII-2C-n40



U-NII-2C-ac20



U-NII-2C-ac40



U-NII-2C-ac80



U-NII-3-a20



U-NII-3-n20



U-NII-3-n40



U-NII-3-ac20



U-NII-3-ac40



U-NII-3-ac80



7. AUTOMATICALLY DISCONTINUE TRANSMISSION

7.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

7.2 TEST RESULT OF AUTOMATICALLY DISCONTINUE TRANSMISSION

During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission





8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is FPC Antenna. It comply with the standard requirement.



**APPENDIX - PHOTOS OF TEST SETUP**

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

※※※※※END OF THE REPORT※※※※※

