



# FCC TEST REPORT

**REPORT NO.:** RF950516H01

**MODEL NO.:** DWL-2700AP

**RECEIVED:** May 16, 2006

**TESTED:** July 1 to 19, 2006

**ISSUED:** July 22, 2006

**APPLICANT:** D-Link Corporation

**ADDRESS:** No.289, Shinhu 3rd Rd., Neihu District, Taipei City  
114, Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.

This test report consists of 72 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.





## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	8
3.3	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL: .....	9
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	11
3.5	DESCRIPTION OF SUPPORT UNITS.....	12
3.6	CONFIGURATION OF SYSTEM UNDER TEST .....	13
4	TEST TYPES AND RESULTS .....	15
4.1	CONDUCTED EMISSION MEASUREMENT .....	15
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	15
4.1.2	TEST INSTRUMENTS.....	15
4.1.3	TEST PROCEDURES .....	16
4.1.4	TEST SETUP .....	16
4.1.5	EUT OPERATING CONDITIONS.....	17
4.1.6	TEST RESULTS .....	18
4.2	RADIATED EMISSION MEASUREMENT .....	22
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	22
4.2.2	TEST INSTRUMENTS.....	23
4.2.3	TEST PROCEDURES .....	24
4.2.4	TEST SETUP .....	25
4.2.5	EUT OPERATING CONDITIONS.....	25
4.2.6	TEST RESULTS .....	26
4.2.7	TEST RESULTS –DSSS.....	28
4.2.8	TEST RESULTS – OFDM.....	35
4.3	6dB BANDWIDTH MEASUREMENT .....	42
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	42
4.3.2	TEST INSTRUMENTS.....	42
4.3.3	TEST PROCEDURE.....	43
4.3.4	TEST SETUP .....	43



4.3.5	EUT OPERATING CONDITIONS.....	43
4.3.6	TEST RESULTS –DSSS.....	44
4.3.7	TEST RESULTS-OFDM.....	47
4.4	MAXIMUM PEAK OUTPUT POWER.....	50
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	50
4.4.2	TEST INSTRUMENTS.....	50
4.4.3	TEST PROCEDURES .....	51
4.4.4	TEST SETUP .....	51
4.4.5	EUT OPERATING CONDITIONS.....	51
4.4.6	TEST RESULTS – DSSS.....	52
4.4.7	TEST RESULTS –OFDM.....	53
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	54
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	54
4.5.2	TEST INSTRUMENTS.....	54
4.5.3	TEST PROCEDURE.....	55
4.5.4	TEST SETUP .....	55
4.5.5	EUT OPERATING CONDITIONS.....	55
4.5.6	TEST RESULTS –DSSS.....	56
4.5.7	TEST RESULTS –OFDM.....	59
4.6	BAND EDGES MEASUREMENT.....	62
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	62
4.6.2	TEST INSTRUMENTS.....	62
4.6.3	TEST PROCEDURE.....	62
4.6.4	EUT OPERATING CONDITION.....	62
4.6.5	TEST RESULTS .....	63
4.7	ANTENNA REQUIREMENT.....	68
4.7.1	STANDARD APPLICABLE.....	68
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	68
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	69
6	INFORMATION ON THE TESTING LABORATORIES .....	71
	APPENDIX-A.....	A-1



## 1 CERTIFICATION

**PRODUCT :** IEEE802.11g Outdoor Access Point  
**BRAND NAME :** D-Link  
**MODEL NO. :** DWL-2700AP  
**TESTED:** July 1 to 19, 2006  
**APPLICANT :** D-Link Corporation  
**TEST ITEM:** ENGINEERING SAMPLE  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2003

The above equipment (Model: DWL-2700AP) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Carol Liao , **DATE:** July 22, 2006  
( Carol Liao )

**TECHNICAL ACCEPTANCE :** Hank Chung , **DATE:** July 22, 2006  
Responsible for RF ( Hank Chung )

**APPROVED BY :** May Chen , **DATE:** July 22, 2006  
( May Chen, Deputy Manager )

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -14.27 dB at 3.413 MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.0 dB at 2387.00 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	IEEE802.11g Outdoor Access Point
<b>MODEL NO.</b>	DWL-2700AP
<b>FCC ID</b>	KA2DWL2700APB1
<b>POWER SUPPLY</b>	DC 48V from POE (Power Over Ethernet)
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>CHANNEL SPACING</b>	5MHz
<b>OUTPUT POWER</b>	802.11b: 223.872mW 802.11g: 354.813mW
<b>ANTENNA TYPE</b>	Please see note 3 (on next page)
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	RJ45 Port x 1
<b>ASSOCIATED DEVICES</b>	RJ45 cable x 1 (30 m, Shielded)

#### NOTE:

- The EUT was powered by following POE (Power Over Ethernet):

POE:	
<b>Brand:</b>	D-Link
<b>Model No.:</b>	EBU-101-T2 LF
<b>Input power :</b>	100-240V~0.6A, 50~60Hz
<b>Output power :</b>	48V===0.4A

2. The POE can be powered with following power adapters:

<b>Adapter 1:</b>	
<b>Brand:</b>	LEAD YEAR ENT.
<b>Model No.:</b>	TG-6001-48V
<b>Input power :</b>	100~240Vac/1.6A 50~60Hz
<b>Output power :</b>	48.0V/1.1A

<b>Adapter 2:</b>	
<b>Brand:</b>	LEAD YEAR ENT.
<b>Model No.:</b>	TG-4201-48V-IV
<b>Input power :</b>	100~240V/1.6A 50~60Hz
<b>Output power :</b>	48.0V/0.875A

3. There are two antennas provided to this EUT, please refer to the following table:

No.	Antenna Type	Gain (dBi)	Cable lose(dB)	Arrester lose(dB)	Net Gain (dBi)	Antenna Connector
1	Monopole	5	0.8	0.8	3.4	RP-N Type Male
2	Dipole	4.5	0.8	0.8	2.9	RP-N plug

From above antennas, antenna 1 was selected as representative antenna for the test.

4. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.

5. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g normal mode: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

### 3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	NA

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

#### **Power Line Conducted Emission Test:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

- The EUT was tested under the following test modes, and its data were recorded in this report:

Test Mode	Description
Mode 1	With adapter 1 + POE
Mode 2	With adapter 2 + POE

#### **Radiated Emission Test (Below 1 GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1	DSSS	CCK	11

- The EUT was tested under the following test modes, and its data were recorded in this report:

Test Mode	Description
Mode 1	With adapter 1 + POE
Mode 2	With adapter 2 + POE

**Radiated Emission Test (Above 1 GHz):**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

The EUT was pre-tested in chamber as the following test modes:

Test Mode	Power
Mode 1	With adapter 1 + POE
Mode 2	With adapter 2 + POE

**Mode 1**, the worse case one, was chosen for final test.

**Bandedge Measurement:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	CCK	11
802.11g	1 to 11	1, 11	OFDM	BPSK	6

**Antenna Port Conducted Measurement:**

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6



### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is an IEEE802.11g Outdoor Access Point. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**47 CFR Part 15, Subpart C. (15.247)**  
**ANSI C63.4 : 2003**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of 47 CFR Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


No.	Product	Brand	Model No.	Serial No.	FCC ID
1	NOTEBOOK COMPUTER	Compaq	N800C	470048-515	DoC

No.	Signal cable description
1	NA

Note: 1. All power cords of the above support units are unshielded (1.8m).


### 3.6 CONFIGURATION OF SYSTEM UNDER TEST

For Conducted Emission test:



- NOTE:**
1. Support unit 1 was kept in the control room during the test.
  2. Please refer to the photos of test configuration in Item 5 also.

**For Radiated Emissions test:**



- NOTE:**
1. Support unit 1 was kept in the control room during the test.
  2. Please refer to the photos of test configuration in Item 5 also.

## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS


DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver	ESCS 30	847124/029	Dec. 15, 2006
Line-Impedance Stabilization Network(for EUT)	ENV-216	100071	Nov. 10, 2006
Line-Impedance Stabilization Network(for Peripheral)	KNW-407	8/1395/12	Jul. 19, 2006
RF Cable (JETBAO)	RG233/U	Cable_CB_01	Dec. 09, 2006
Terminator	50	2	Oct. 08, 2006
Software	ADT_Cond_V7.3. 2	NA	NA

- NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in ADT Shielded Room No. B.  
 3. The VCCI Con B Registration No. is C-2193.

#### 4.1.3 TEST PROCEDURES

- The EUT/HOST was placed 0.4 meters from the conducting wall of the shielded room with EUT/HOST being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT/HOST were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMIN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.5 EUT OPERATING CONDITIONS


- a. Placed the EUT on the testing table.
- b. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- c. The communication partner run “Art52 Build 58” test program to enable EUT under transmission/receiving condition continuously at specific channel frequency via STP cable.

#### 4.1.6 TEST RESULTS

<b>MODULATION TYPE</b>	BPSK	<b>CHANNEL</b>	Channel 11
<b>TEST MODE</b>	Mode 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	6Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 960hPa	<b>PHASE</b>	Line (L)
<b>TESTED BY</b>	Eric Lee		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	9.60	31.47	-	41.07	-	64.43	54.43	-23.36	-
2	0.423	9.60	26.42	-	36.02	-	57.38	47.38	-21.36	-
3	0.484	9.60	17.74	-	27.34	-	56.27	46.27	-28.93	-
<b>4</b>	<b>3.413</b>	<b>9.70</b>	<b>32.03</b>	-	<b>41.73</b>	-	<b>56.00</b>	<b>46.00</b>	<b>-14.27</b>	-
5	16.227	10.10	27.65	-	37.75	-	60.00	50.00	-22.25	-
6	30.000	10.10	11.99	-	22.09	-	60.00	50.00	-37.91	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>MODULATION TYPE</b>	BPSK	<b>CHANNEL</b>	Channel 11
<b>TEST MODE</b>	Mode 1	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	6Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 960hPa	<b>PHASE</b>	Neutral (N)
<b>TESTED BY</b>	Eric Lee		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.184	9.60	30.09	-	39.69	-	64.31	54.31	-24.62	-
2	0.248	9.60	21.01	-	30.61	-	61.84	51.84	-31.23	-
3	0.427	9.60	27.00	-	36.60	-	57.30	47.30	-20.70	-
4	1.650	9.66	22.05	-	31.71	-	56.00	46.00	-24.29	-
5	3.117	9.70	23.77	-	33.47	-	56.00	46.00	-22.53	-
6	16.227	10.02	27.43	-	37.45	-	60.00	50.00	-22.55	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>MODULATION TYPE</b>	BPSK	<b>CHANNEL</b>	Channel 11
<b>TEST MODE</b>	Mode 2	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	6Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 960hPa	<b>PHASE</b>	Line (L)
<b>TESTED BY</b>	Eric Lee		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.169	9.60	38.75	-	48.35	-	64.99	54.99	-16.64	-
2	0.285	9.60	25.33	-	34.93	-	60.68	50.68	-25.75	-
3	0.508	9.60	20.09	-	29.69	-	56.00	46.00	-26.31	-
4	1.655	9.67	21.79	-	31.46	-	56.00	46.00	-24.54	-
5	16.227	10.10	28.55	-	38.65	-	60.00	50.00	-21.35	-
6	21.055	10.10	24.76	-	34.86	-	60.00	50.00	-25.14	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



<b>MODULATION TYPE</b>	BPSK	<b>CHANNEL</b>	Channel 11
<b>TEST MODE</b>	Mode 2	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	6Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	25deg. C, 65%RH, 960hPa	<b>PHASE</b>	Neutral (N)
<b>TESTED BY</b>	Eric Lee		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	9.60	38.28	-	47.88	-	64.97	54.97	-17.09	-
2	0.232	9.60	29.92	-	39.52	-	62.38	52.38	-22.86	-
3	0.512	9.60	25.59	-	35.19	-	56.00	46.00	-20.81	-
4	1.877	9.69	23.54	-	33.23	-	56.00	46.00	-22.77	-
5	16.230	10.02	28.55	-	38.57	-	60.00	50.00	-21.43	-
6	21.113	10.10	25.37	-	35.47	-	60.00	50.00	-24.53	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.



## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 03, 2007
HP Pre_Amplifier	8449B	3008A01922	Oct. 02, 2006
ROHDE & SCHWARZ Test Receiver	ESCS30	100375	Sep. 19, 2006
CHASE Broadband Antenna	VULB9168	138	Dec. 11, 2006
Schwarzbeck Horn_Antenna	BBHA9120	D124	Dec. 27, 2006
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 05, 2007
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 08, 2009
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 08, 2009
R&S Loop Antenna	HFH2-Z2	881058/15	Nov. 29, 2007
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek)	SF102	22054-2	Nov. 16. 2006
RF Cable(RICHTEC)	9913-30M N-N Cable	STCCAB-30M- 1GHz	Jul. 15, 2007
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

- Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Biconical and Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: R3271A) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824A-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~40GHz)	1.88 dB


#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5

#### 4.2.6 TEST RESULTS

##### Below 1GHz Worst-Case Data

<b>MODULATION TYPE</b>	CCK	<b>CHANNEL</b>	Channel 1
<b>TEST MODE</b>	Mode 1	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	11Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	27deg. C, 53%RH, 960hPa	<b>DETECTOR FUNCTION</b>	Quasi-Peak, 120kHz
<b>TESTED BY</b>	Tony Chen		

##### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	133.32	24.30 QP	43.50	-19.20	1.42 H	104	11.40	12.90
2	492.80	28.10 QP	46.00	-17.90	1.43 H	279	6.60	21.60
3	533.29	38.90 QP	46.00	-7.10	1.01 H	273	16.10	22.70
4	666.62	39.30 QP	46.00	-6.70	1.29 H	236	14.00	25.30
5	799.92	37.40 QP	46.00	-8.60	1.00 H	245	9.80	27.60
6	933.22	35.50 QP	46.00	-10.50	1.23 H	236	5.90	29.50

##### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.11	36.80 QP	43.50	-6.70	1.07 V	3	23.10	13.70
2	399.97	34.10 QP	46.00	-11.90	1.14 V	27	15.10	19.00
3	490.90	34.20 QP	46.00	-11.80	1.36 V	1	12.60	21.50
4	533.30	40.80 QP	46.00	-5.20	1.00 V	301	18.10	22.70
5	666.61	38.50 QP	46.00	-7.50	1.00 V	268	13.20	25.30
6	933.24	34.90 QP	46.00	-11.10	1.03 V	210	5.30	29.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

**Below 1GHz Worst-Case Data**

<b>MODULATION TYPE</b>	CCK	<b>CHANNEL</b>	Channel 1
<b>TEST MODE</b>	Mode 2	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>TRANSFER RATE</b>	11Mbps
<b>ENVIRONMENTAL CONDITIONS</b>	27deg. C, 53%RH, 960hPa	<b>DETECTOR FUNCTION</b>	Quasi-Peak, 120kHz
<b>TESTED BY</b>	Tony Chen		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	133.32	22.90 QP	43.50	-20.60	1.16 H	122	10.00	12.90
2	488.54	30.70 QP	46.00	-15.30	1.32 H	258	9.20	21.50
3	533.28	37.30 QP	46.00	-8.70	1.00 H	238	14.60	22.70
4	666.60	37.60 QP	46.00	-8.40	1.10 H	253	12.30	25.30
5	799.92	36.40 QP	46.00	-9.60	1.00 H	246	8.80	27.60
6	933.24	32.70 QP	46.00	-13.30	1.00 H	320	3.10	29.50

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	148.07	34.40 QP	43.50	-9.10	1.17 V	22	20.70	13.70
2	399.96	34.50 QP	46.00	-11.50	1.21 V	15	15.50	19.00
3	478.89	32.00 QP	46.00	-14.00	1.18 V	340	10.80	21.20
4	533.28	38.70 QP	46.00	-7.30	1.05 V	162	16.00	22.70
5	666.60	37.40 QP	46.00	-8.60	1.00 V	332	12.10	25.30
6	933.24	34.00 QP	46.00	-12.00	1.17 V	350	4.40	29.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

#### 4.2.7 TEST RESULTS –DSSS 802.11b DSSS modulation

<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.30 PK	74.00	-21.70	1.04 H	319	22.50	29.80
1	2390.00	42.60 AV	54.00	-11.40	1.04 H	319	12.80	29.80
2	*2412.00	98.00 PK			1.04 H	200	68.10	29.90
2	*2412.00	93.60 AV			1.04 H	200	63.70	29.90
3	4824.00	43.80 PK	74.00	-30.20	1.19 H	211	8.80	35.00
3	4824.00	35.40 AV	54.00	-18.60	1.19 H	211	0.40	35.00
4	7236.00	50.40 PK	74.00	-23.60	1.18 H	27	9.20	41.10
4	7236.00	37.70 AV	54.00	-16.30	1.18 H	27	-3.50	41.10

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2387.00	60.70 PK	74.00	-13.30	1.18 V	316	31.00	29.70
1	<b>2387.00</b>	<b>53.00 AV</b>	<b>54.00</b>	<b>-1.00</b>	<b>1.18 V</b>	<b>316</b>	<b>23.30</b>	<b>29.70</b>
2	2390.00	59.00 PK	74.00	-15.00	1.18 V	316	29.20	29.80
2	2390.00	47.90 AV	54.00	-6.10	1.18 V	316	18.10	29.80
3	*2412.00	111.40 PK			1.13 V	309	81.50	29.90
3	*2412.00	107.20 AV			1.13 V	309	77.30	29.90
4	4824.00	46.10 PK	74.00	-27.90	1.07 V	143	11.10	35.00
4	4824.00	38.80 AV	54.00	-15.20	1.07 V	143	3.80	35.00
5	7236.00	51.80 PK	74.00	-22.20	1.42 V	317	10.60	41.10
5	7236.00	38.50 AV	54.00	-15.50	1.42 V	317	-2.70	41.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	43.70 PK	74.00	-30.30	1.36 H	2	14.10	29.60
1	2360.00	32.70 AV	54.00	-21.30	1.36 H	2	3.10	29.60
2	*2437.00	100.10 PK			1.09 H	182	70.10	30.00
2	*2437.00	96.30 AV			1.09 H	182	66.30	30.00
3	4874.00	45.30 PK	74.00	-28.70	1.18 H	206	10.10	35.20
3	4874.00	36.80 AV	54.00	-17.20	1.18 H	206	1.60	35.20
4	7311.00	51.00 PK	74.00	-23.00	1.17 H	22	9.60	41.40
4	7311.00	38.30 AV	54.00	-15.70	1.17 H	22	-3.10	41.40

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	55.00 PK	74.00	-19.00	1.41 V	319	25.40	29.60
1	2360.00	46.90 AV	54.00	-7.10	1.41 V	319	17.30	29.60
2	*2437.00	114.40 PK			1.13 V	16	84.40	30.00
2	*2437.00	110.70 AV			1.13 V	16	80.70	30.00
3	4874.00	47.80 PK	74.00	-26.20	1.09 V	149	12.60	35.20
3	4874.00	40.70 AV	54.00	-13.30	1.09 V	149	5.50	35.20
4	7311.00	53.00 PK	74.00	-21.00	1.06 V	163	11.60	41.40
4	7311.00	42.50 AV	54.00	-11.50	1.06 V	163	1.10	41.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency



<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	95.90 PK			1.03 H	240	65.80	30.10
1	*2462.00	92.30 AV			1.03 H	240	62.20	30.10
2	2483.50	53.40 PK	74.00	-20.60	1.00 H	182	23.20	30.20
2	2483.50	43.30 AV	54.00	-10.70	1.00 H	182	13.10	30.20
3	2488.00	54.20 PK	74.00	-19.80	1.00 H	182	24.00	30.20
3	2488.00	44.00 AV	54.00	-10.00	1.00 H	182	13.80	30.20
4	4924.00	44.60 PK	74.00	-29.40	1.17 H	210	9.20	35.40
4	4924.00	36.20 AV	54.00	-17.80	1.17 H	210	0.80	35.40
5	7386.00	50.80 PK	74.00	-23.20	1.11 H	37	9.20	41.60
5	7386.00	38.10 AV	54.00	-15.90	1.11 H	37	-3.50	41.60



#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.60 PK			1.11 V	11	80.50	30.10
1	*2462.00	107.20 AV			1.11 V	11	77.10	30.10
2	2483.50	58.90 PK	74.00	-15.10	1.34 V	15	28.70	30.20
2	2483.50	49.10 AV	54.00	-4.90	1.34 V	15	18.90	30.20
3	2487.00	60.90 PK	74.00	-13.10	1.34 V	15	30.70	30.20
3	2487.00	52.60 AV	54.00	-1.40	1.34 V	15	22.40	30.20
4	4924.00	47.00 PK	74.00	-27.00	1.09 V	157	11.60	35.40
4	4924.00	39.50 AV	54.00	-14.50	1.09 V	157	4.10	35.40
5	7386.00	52.50 PK	74.00	-21.50	1.44 V	319	10.90	41.60
5	7386.00	39.20 AV	54.00	-14.80	1.44 V	319	-2.40	41.60



- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency





RESTRICTED BANDEDGE (802.11b MODE, CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11b MODE,CH11, HORIZONTAL )



RESTRICTED BANDEDGE (802.11b MODE, CH11, VERTICAL )



#### 4.2.8 TEST RESULTS – OFDM 802.11g Normal OFDM modulation

<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.20 PK	74.00	-19.80	1.00 H	218	24.40	29.80
1	2390.00	43.30 AV	54.00	-10.70	1.00 H	218	13.50	29.80
2	*2412.00	99.90 PK			1.04 H	195	70.00	29.90
2	*2412.00	88.90 AV			1.04 H	195	59.00	29.90
3	4824.00	43.20 PK	74.00	-30.80	1.35 H	355	8.20	35.00
3	4824.00	30.00 AV	54.00	-24.00	1.35 H	355	-5.00	35.00
4	7236.00	50.80 PK	74.00	-23.20	1.09 H	27	9.60	41.10
4	7236.00	37.40 AV	54.00	-16.60	1.09 H	27	-3.80	41.10

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	66.70 PK	74.00	-7.30	1.18 V	314	36.90	29.80
1	2390.00	52.70 AV	54.00	-1.30	1.18 V	314	22.90	29.80
2	*2412.00	113.20 PK			1.00 V	312	83.30	29.90
2	*2412.00	102.50 AV			1.00 V	312	72.60	29.90
3	4824.00	43.20 PK	74.00	-30.80	1.38 V	167	8.20	35.00
3	4824.00	30.10 AV	54.00	-23.90	1.38 V	167	-4.90	35.00
4	7236.00	52.00 PK	74.00	-22.00	1.39 V	160	10.80	41.10
4	7236.00	38.70 AV	54.00	-15.30	1.39 V	160	-2.50	41.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. " \* " : Fundamental frequency

<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	43.80 PK	74.00	-30.20	1.35 H	0	14.20	29.60
1	2360.00	32.80 AV	54.00	-21.20	1.35 H	0	3.20	29.60
2	*2437.00	103.50 PK			1.02 H	242	73.50	30.00
2	*2437.00	94.30 AV			1.02 H	242	64.30	30.00
3	4874.00	43.50 PK	74.00	-30.50	1.38 H	352	8.30	35.20
3	4874.00	30.30 AV	54.00	-23.70	1.38 H	352	-4.90	35.20
4	7311.00	51.10 PK	74.00	-22.90	1.07 H	25	9.70	41.40
4	7311.00	37.70 AV	54.00	-16.30	1.07 H	25	-3.70	41.40

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2360.00	56.70 PK	74.00	-17.30	1.54 V	4	27.10	29.60
1	2360.00	47.10 AV	54.00	-6.90	1.54 V	4	17.50	29.60
2	*2437.00	115.80 PK			1.00 V	171	85.80	30.00
2	*2437.00	106.10 AV			1.00 V	171	76.10	30.00
3	4874.00	44.20 PK	74.00	-29.80	1.33 V	151	9.00	35.20
3	4874.00	31.20 AV	54.00	-22.80	1.33 V	151	-4.00	35.20
4	7311.00	53.90 PK	74.00	-20.10	1.33 V	159	12.50	41.40
4	7311.00	40.70 AV	54.00	-13.30	1.33 V	159	-0.70	41.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency

<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	1000~25000MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION &amp; BANDWIDTH</b>	Peak (PK) Average (AV) 1 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 65%RH, 960hPa	<b>TESTED BY</b>	Wen Yu

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M



No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	97.50 PK			1.03 H	240	67.40	30.10
1	*2462.00	87.10 AV			1.03 H	240	57.00	30.10
2	2483.50	56.40 PK	74.00	-17.60	1.00 H	196	26.20	30.20
2	2483.50	44.20 AV	54.00	-9.80	1.00 H	196	14.00	30.20
3	4924.00	43.50 PK	74.00	-30.50	1.33 H	0	8.10	35.40
3	4924.00	30.20 AV	54.00	-23.80	1.33 H	0	-5.20	35.40
4	7386.00	51.20 PK	74.00	-22.80	1.06 H	38	9.60	41.60
4	7386.00	37.80 AV	54.00	-16.20	1.06 H	38	-3.80	41.60

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.30 PK			1.12 V	9	82.20	30.10
1	*2462.00	101.60 AV			1.12 V	9	71.50	30.10
2	2483.50	67.70 PK	74.00	-6.30	1.33 V	14	37.50	30.20
2	2483.50	52.90 AV	54.00	-1.10	1.33 V	14	22.70	30.20
3	4924.00	43.40 PK	74.00	-30.60	1.36 V	156	8.00	35.40
3	4924.00	31.30 AV	54.00	-22.70	1.36 V	156	-4.10	35.40
4	7386.00	54.40 PK	74.00	-19.60	1.33 V	147	12.80	41.60
4	7386.00	41.10 AV	54.00	-12.90	1.33 V	147	-0.50	41.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. The limit value is defined as per 15.247
  6. “ \* “ : Fundamental frequency


RESTRICTED BANDEDGE (802.11g MODE, CH1, HORIZONTAL )





RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL )



RESTRICTED BANDEDGE (802.11g MODE,CH11, HORIZONTAL )



RESTRICTED BANDEDGE (802.11g MODE,CH11, VERTICAL )





### 4.3 6dB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006


**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

#### 4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




#### 4.3.6 TEST RESULTS –DSSS

##### 802.11b DSSS modulation


<b>MODULATION TYPE</b>	CCK	<b>TRANSFER RATE</b>	11Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	11.62	0.5	PASS
6	2437	11.70	0.5	PASS
11	2462	12.15	0.5	PASS


# CH1



# CH6



CH11




### 4.3.7 TEST RESULTS-OFDM

#### 802.11g OFDM modulation


<b>MODULATION TYPE</b>	BPSK	<b>TRANSFER RATE</b>	6Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	16.40	0.5	PASS
6	2437	16.35	0.5	PASS
11	2462	16.35	0.5	PASS


CH1



CH6



CH11



#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2006
TEKTRONIX OSCILLOSCOPE	TDS380	B016335	Jul. 04, 2007
NARDA DETECTOR	4503A	FSCM99899	NA


**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the peak response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

#### 4.4.4 TEST SETUP



#### 4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5



#### 4.4.6 TEST RESULTS – DSSS

##### 802.11b DSSS modulation

<b>MODULATION TYPE</b>	CCK	<b>TRANSFER RATE</b>	11Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (mW)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	86.696	19.38	30	PASS
6	2437	223.872	23.50	30	PASS
11	2462	79.433	19.00	30	PASS



#### 4.4.7 TEST RESULTS –OFDM

##### 802.11g OFDM modulation

<b>MODULATION TYPE</b>	BPSK	<b>TRANSFER RATE</b>	6Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (mW)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	115.611	20.63	30	PASS
6	2437	354.813	25.50	30	PASS
11	2462	100.00	20.00	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006


**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 TEST SETUP



#### 4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5




#### 4.5.6 TEST RESULTS –DSSS

##### 802.11b DSSS modulation


<b>MODULATION TYPE</b>	CCK	<b>TRANSFER RATE</b>	11Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-6.02	8	PASS
6	2437	-2.18	8	PASS
11	2462	-6.69	8	PASS


CH1



CH6



# CH11






#### 4.5.7 TEST RESULTS –OFDM

##### 802.11g OFDM modulation


<b>MODULATION TYPE</b>	BPSK	<b>TRANSFER RATE</b>	6Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60Hz	<b>ENVIRONMENTAL CONDITIONS</b>	26deg. C, 64%RH, 960hPa
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-8.82	8	PASS
6	2437	-3.48	8	PASS
11	2462	-10.11	8	PASS


### CH1



### CH6



# CH11



## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2006

#### NOTE:

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (RBW = VBW = 100kHz) are attached on the following pages.

### 4.6.4 EUT OPERATING CONDITION

Same as Item 4.3.5




#### 4.6.5 TEST RESULTS


The spectrum plots are attached on the following 8 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

## 802.11b DSSS MODULATION:


CH1




CH11




CH1




CH11




## 802.11g OFDM MODULATION: CH1




CH11



CH1



CH11



## 4.7 ANTENNA REQUIREMENT

### 4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antennas used in this product are as following:

No.	Antenna Type	Gain (dBi)	Cable lose(dB)	Arrester lose(dB)	Net Gain (dBi)	Antenna Connector
1	Monopole	5	0.8	0.8	3.4	RP-N Type Male
2	Dipole	4.5	0.8	0.8	2.9	RP-N plug

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

<b>USA</b>	FCC, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA, CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB, GOST-ASIA (MOU)
<b>Russia</b>	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Email:** [service@adt.com.tw](mailto:service@adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



## **APPENDIX-A**

### **MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.