

FCC Test Report

Report No.: RF180424C02

FCC ID: KA2WL8620APEA1

Test Model: DWL-8620APE

Received Date: Apr. 24, 2018

Test Date: May 28 ~ Jul. 08, 2018

Issued Date: Jul. 09, 2018

Applicant: D-Link Corporation

Address: 17595 Mt. Herrmann, Fountain Valley, California, United States, 92708

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	14
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures.....	17
4.1.4 Deviation from Test Standard	18
4.1.5 Test Set Up	18
4.1.6 EUT Operating Conditions.....	19
4.1.7 Test Results	20
4.2 Conducted Emission Measurement	38
4.2.1 Limits of Conducted Emission Measurement	38
4.2.2 Test Instruments	38
4.2.3 Test Procedures.....	39
4.2.4 Deviation from Test Standard	39
4.2.5 Test Setup.....	39
4.2.6 EUT Operating Conditions.....	39
4.2.7 Test Results	40
4.3 6dB Bandwidth Measurement.....	46
4.3.1 Limits of 6dB Bandwidth Measurement.....	46
4.3.2 Test Setup.....	46
4.3.3 Test Instruments	46
4.3.4 Test Procedure	46
4.3.5 Deviation from Test Standard	46
4.3.6 EUT Operating Conditions.....	46
4.3.7 Test Result.....	47
4.4 Conducted Output Power Measurement.....	49
4.4.1 Limits of Conducted Output Power Measurement	49
4.4.2 Test Setup.....	49
4.4.3 Test Instruments	49
4.4.4 Test Procedures.....	49
4.4.5 Deviation from Test Standard	49
4.4.6 EUT Operating Conditions.....	49
4.4.7 Test Results	50
4.5 Power Spectral Density Measurement.....	52
4.5.1 Limits of Power Spectral Density Measurement	52
4.5.2 Test Setup.....	52
4.5.3 Test Instruments	52
4.5.4 Test Procedure	52
4.5.5 Deviation from Test Standard	52
4.5.6 EUT Operating Condition	52

4.5.7 Test Results	53
4.6 Conducted Out of Band Emission Measurement.....	58
4.6.1 Limits of Conducted Out of Band Emission Measurement	58
4.6.2 Test Setup.....	58
4.6.3 Test Instruments	58
4.6.4 Test Procedure	58
4.6.5 Deviation from Test Standard	59
4.6.6 EUT Operating Condition	59
4.6.7 Test Results	59
5 Pictures of Test Arrangements.....	76
Appendix – Information on the Testing Laboratories	77

Release Control Record

Issue No.	Description	Date Issued
RF180424C02	Original release.	Jul. 09, 2018

1 Certificate of Conformity

Product: Unified AC Concurrent Dual-Band PoE Access Point

Brand: D-Link Corporation

Test Model: DWL-8620APE

Sample Status: Engineering sample

Applicant: D-Link Corporation

Test Date: May 28 ~ Jul. 08, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Sunt Lee , **Date:** Jul. 09, 2018
Sunt Lee / Specialist

Approved by : Bruce Chen , **Date:** Jul. 09, 2018
Bruce Chen / Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -6.63dB at 0.46179MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.3dB at 237.94MHz.
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	Pass	Meet the requirement of limit.
15.247(b)	Conducted power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is SMA not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.94 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.86 dB
	200MHz ~ 1000MHz	3.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Unified AC Concurrent Dual-Band PoE Access Point
Brand	D-Link Corporation
Test Model	DWL-8620APE
Sample Status	Engineering sample
Power Supply Rating	12Vdc (adapter) 52Vdc (POE)
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 600.0Mbps
Operating Frequency	2412~2462MHz
Number of Channel	11 for 802.11b, 802.11g, 802.11n (HT20) 7 for 802.11n (HT40)
Output Power	CDD Mode: 899.271mW Beamforming Mode: 630.983mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter
Data Cable Supplied	NA

Note:

1. The EUT incorporates a MIMO function. Physically, the EUT provides 4 completed transmitters and 4 receivers.

Band	Modulation Mode	Beamforming Mode	TX Function
2.4GHz	802.11b	Not Support	4TX
	802.11g	Not Support	4TX
	802.11n (HT20)	Support	4TX
	802.11n (HT40)	Support	4TX

2. The EUT uses following antennas.

Ant. No.	Type	Connector	Ant. Gain (dBi)		Beamforming Gain (dBi)	
			2.4GHz	5GHz	2.4GHz	5GHz
0, 1, 2, 3	Dipole	SMA	3	4	3.78	5.77

3. The EUT consumes power from the following Adapters.

Adapter 1	
Brand	Channel Well Technology
Model	2ABL030F NJ
Input Power	100-240Vac~, 50/60Hz 1.0A
Output Power	12.0Vdc / 2.5A
Power Cord	1.2m non-shielded power cord without core

Adapter 2	
Brand	Asian Power Devices Inc.
Model	WA-30J12R
Input Power	100-240Vac~, 50-60Hz, 0.9A Max
Output Power	12Vdc / 2.5A
Power Cord	1.2m non-shielded power cord without core

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11ac (20MHz):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11ac (40MHz):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	
A	√	√	√	√	Power from adapter 1
B	-	√	√	-	Power from adapter 2
C	-	√	√	-	Power from POE

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement
 RE<1G: Radiated Emission below 1GHz
 PLC: Power Line Conducted Emission
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.
2. "-": Means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B, C	802.11b	1 to 11	6	DSSS	DBPSK	1.0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A, B, C	802.11b	1 to 11	6	DSSS	DBPSK	1.0

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	7.2
A	802.11n (HT40)	3 to 9	3, 6, 9	OFDM	BPSK	15.0

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE $\geq$ 1G	25deg. C, 70%RH	120Vac, 60Hz	Noah Chang
RE<1G	23deg. C, 66%RH 25deg. C, 65%RH	120Vac, 60Hz	Willy Cheng
PLC	24deg. C, 62%RH 24deg. C, 65%RH 25deg. C, 66%RH	120Vac, 60Hz	Willy Cheng
APCM	25deg. C, 60%RH	120Vac, 60Hz	Alan Wu

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is $\geq 98\%$, duty factor is not required.


Duty cycle of test signal is $< 98\%$, duty factor is required.

802.11b: Duty cycle = $12.35/12.487 = 0.989$

802.11g: Duty cycle = $2.059/2.139 = 0.963$, Duty factor = $10 * \log(1/0.963) = 0.17$

802.11n (HT20): Duty cycle = $4.98/5.075 = 0.981$

802.11n (HT40): Duty cycle = $2.425/2.502 = 0.969$, Duty factor = $10 * \log(1/0.969) = 0.14$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved	-
B.	Load	NA	NA	NA	NA	-
C.	POE	PHIHONG	POE31U-1AT	NA	NA	-


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ45 cable	1	1.5	N	0	Cat5e
2.	RJ45 cable	1	5	N	0	Cat5e
3.	RJ45 to console cable	1	1.2	N	0	Cat5e
4.	RJ45, Cat5e	1	1.8	N	0	Cat5e

3.4.1 Configuration of System under Test

Mode A, B



Mode C



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 DTS Meas Guidance v04

KDB 662911 D01 Multiple Transmitter Output v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 17, 2017	Oct. 16, 2018
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Dec. 12, 2017	Dec. 11, 2018
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Dec. 11, 2017	Dec. 10, 2018
HORN Antenna SCHWARZBECK	9120D	209	Dec. 13, 2017	Dec. 12, 2018
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Dec. 01, 2017	Nov. 30, 2018
Loop Antenna EMCI	EM-6879	269	Aug. 11, 2017	Aug. 10, 2018
Preamplifier Agilent (Below 1GHz)	8447D	2944A10738	Aug. 21, 2017	Aug. 20, 2018
Preamplifier Agilent (Above 1GHz)	8449B	3008A02465	Apr. 03, 2018	Apr. 02, 2019
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (223653/4)	Aug. 21, 2017	Aug. 20, 2018
RF signal cable HUBER+SUHNER& EMCI	SUCOFLEX 104&EMC104-SM- SM-8000	Cable-CH3-03 (309224+170907)	Sep.11, 2017	Sep. 10, 2018
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
High Speed Peak Power Meter	ML2495A	0824012	Aug. 18, 2017	Aug. 17, 2018
Power Sensor	MA2411B	0738171	Aug. 18, 2017	Aug. 17, 2018

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Designation Number is TW0003. The number will be varied with the Lab location and scope as attached.
5. The IC Site Registration No. is IC 7450F-3.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10 Hz (Duty cycle $\geq 98\%$) for Peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (QRCT 3.0.239.0) to enable EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the system in full functions.

4.1.7 Test Results

Above 1GHz Worst-case Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.7 PK	74.0	-12.3	1.80 H	10	28.3	33.4
2	2390.00	52.6 AV	54.0	-1.4	1.80 H	10	19.2	33.4
3	*2412.00	121.8 PK			1.69 H	8	88.4	33.4
4	*2412.00	117.9 AV			1.69 H	8	84.5	33.4
5	4824.00	48.9 PK	74.0	-25.1	2.56 H	320	45.3	3.6
6	4824.00	35.8 AV	54.0	-18.2	2.56 H	320	32.2	3.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.7 PK	74.0	-15.3	2.55 V	110	25.3	33.4
2	2390.00	48.0 AV	54.0	-6.0	2.55 V	110	14.6	33.4
3	*2412.00	111.3 PK			2.66 V	106	77.9	33.4
4	*2412.00	107.9 AV			2.66 V	106	74.5	33.4
5	4824.00	48.2 PK	74.0	-25.8	3.02 V	222	44.6	3.6
6	4824.00	35.2 AV	54.0	-18.8	3.02 V	222	31.6	3.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	123.7 PK			2.55 H	24	90.3	33.4
2	*2437.00	119.5 AV			2.55 H	24	86.1	33.4
3	4874.00	48.3 PK	74.0	-25.7	1.75 H	280	45.0	3.3
4	4874.00	35.6 AV	54.0	-18.4	1.75 H	280	32.3	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	115.1 PK			2.65 V	115	81.7	33.4
2	*2437.00	110.9 AV			2.65 V	115	77.5	33.4
3	4874.00	47.8 PK	74.0	-26.2	1.65 V	226	44.5	3.3
4	4874.00	35.2 AV	54.0	-18.8	1.65 V	226	31.9	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	119.8 PK			3.87 H	13	86.3	33.5
2	*2462.00	115.9 AV			3.87 H	13	82.4	33.5
3	2483.50	64.0 PK	74.0	-10.0	2.41 H	22	30.5	33.5
4	2483.50	52.4 AV	54.0	-1.6	2.41 H	22	18.9	33.5
5	4924.00	47.9 PK	74.0	-26.1	1.50 H	336	44.6	3.3
6	4924.00	34.6 AV	54.0	-19.4	1.50 H	336	31.3	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.6 PK			2.66 V	107	80.1	33.5
2	*2462.00	109.8 AV			2.66 V	107	76.3	33.5
3	2483.50	60.2 PK	74.0	-13.8	2.56 V	122	26.7	33.5
4	2483.50	48.6 AV	54.0	-5.4	2.56 V	122	15.1	33.5
5	4924.00	46.4 PK	74.0	-27.6	2.88 V	222	43.1	3.3
6	4924.00	33.5 AV	54.0	-20.5	2.88 V	222	30.2	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.2 PK	74.0	-8.8	2.40 H	359	31.8	33.4
2	2390.00	52.8 AV	54.0	-1.2	2.40 H	359	19.4	33.4
3	*2412.00	118.5 PK			1.69 H	6	85.1	33.4
4	*2412.00	108.0 AV			1.69 H	6	74.6	33.4
5	4824.00	48.1 PK	74.0	-25.9	2.53 H	326	44.5	3.6
6	4824.00	35.2 AV	54.0	-18.8	2.53 H	326	31.6	3.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.5 PK	74.0	-16.5	3.20 V	86	24.1	33.4
2	2390.00	45.9 AV	54.0	-8.1	3.20 V	86	12.5	33.4
3	*2412.00	110.7 PK			3.33 V	99	77.3	33.4
4	*2412.00	99.9 AV			3.33 V	99	66.5	33.4
5	4824.00	47.9 PK	74.0	-26.1	1.57 V	256	44.3	3.6
6	4824.00	34.4 AV	54.0	-19.6	1.57 V	256	30.8	3.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.8 PK	74.0	-9.2	1.72 H	8	31.4	33.4
2	2390.00	52.5 AV	54.0	-1.5	1.72 H	8	19.1	33.4
3	*2437.00	123.4 PK			2.04 H	21	90.0	33.4
4	*2437.00	112.8 AV			2.04 H	21	79.4	33.4
5	4874.00	47.9 PK	74.0	-26.1	2.25 H	302	44.6	3.3
6	4874.00	34.8 AV	54.0	-19.2	2.25 H	302	31.5	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.6 PK	74.0	-16.4	2.85 V	105	24.2	33.4
2	2390.00	46.4 AV	54.0	-7.6	2.85 V	105	13.0	33.4
3	*2437.00	117.2 PK			2.92 V	101	83.8	33.4
4	*2437.00	105.4 AV			2.92 V	101	72.0	33.4
5	4874.00	47.8 PK	74.0	-26.2	1.50 V	229	44.5	3.3
6	4874.00	34.5 AV	54.0	-19.5	1.50 V	229	31.2	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	118.5 PK			1.68 H	12	85.0	33.5
2	*2462.00	107.3 AV			1.68 H	12	73.8	33.5
3	2483.50	67.5 PK	74.0	-6.5	1.68 H	355	34.0	33.5
4	2483.50	52.5 AV	54.0	-1.5	1.68 H	355	19.0	33.5
5	4924.00	48.1 PK	74.0	-25.9	2.22 H	205	44.8	3.3
6	4924.00	34.9 AV	54.0	-19.1	2.22 H	205	31.6	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.1 PK			2.97 V	112	76.6	33.5
2	*2462.00	99.3 AV			2.97 V	112	65.8	33.5
3	2483.50	62.1 PK	74.0	-11.9	2.96 V	122	28.6	33.5
4	2483.50	48.5 AV	54.0	-5.5	2.96 V	122	15.0	33.5
5	4924.00	47.8 PK	74.0	-26.2	1.66 V	225	44.5	3.3
6	4924.00	34.5 AV	54.0	-19.5	1.66 V	225	31.2	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.3 PK	74.0	-9.7	2.65 H	193	30.9	33.4
2	2390.00	52.7 AV	54.0	-1.3	2.65 H	193	19.3	33.4
3	*2412.00	117.0 PK			1.73 H	7	83.6	33.4
4	*2412.00	106.1 AV			1.73 H	7	72.7	33.4
5	4824.00	47.9 PK	74.0	-26.1	2.69 H	69	44.3	3.6
6	4824.00	34.6 AV	54.0	-19.4	2.69 H	69	31.0	3.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	3.26 V	88	24.4	33.4
2	2390.00	46.9 AV	54.0	-7.1	3.26 V	88	13.5	33.4
3	*2412.00	108.0 PK			3.27 V	91	74.6	33.4
4	*2412.00	97.7 AV			3.27 V	91	64.3	33.4
5	4824.00	47.8 PK	74.0	-26.2	3.05 V	255	44.2	3.6
6	4824.00	34.4 AV	54.0	-19.6	3.05 V	255	30.8	3.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.0 PK	74.0	-9.0	3.07 H	188	31.6	33.4
2	2390.00	52.5 AV	54.0	-1.5	3.07 H	188	19.1	33.4
3	*2437.00	122.6 PK			2.51 H	5	89.2	33.4
4	*2437.00	112.1 AV			2.51 H	5	78.7	33.4
5	4874.00	47.9 PK	74.0	-26.1	2.55 H	325	44.6	3.3
6	4874.00	34.8 AV	54.0	-19.2	2.55 H	325	31.5	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.5 PK	74.0	-16.5	3.25 V	66	24.1	33.4
2	2390.00	46.6 AV	54.0	-7.4	3.25 V	66	13.2	33.4
3	*2437.00	116.7 PK			3.30 V	82	83.3	33.4
4	*2437.00	105.9 AV			3.30 V	82	72.5	33.4
5	4874.00	47.8 PK	74.0	-26.2	1.05 V	311	44.5	3.3
6	4874.00	34.2 AV	54.0	-19.8	1.05 V	311	30.9	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	117.6 PK			1.69 H	12	84.1	33.5
2	*2462.00	106.4 AV			1.69 H	12	72.9	33.5
3	2483.50	63.9 PK	74.0	-10.1	1.88 H	195	30.4	33.5
4	2483.50	52.5 AV	54.0	-1.5	1.88 H	195	19.0	33.5
5	4924.00	47.9 PK	74.0	-26.1	2.58 H	33	44.6	3.3
6	4924.00	34.9 AV	54.0	-19.1	2.58 H	33	31.6	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.9 PK			3.32 V	104	76.4	33.5
2	*2462.00	98.8 AV			3.32 V	104	65.3	33.5
3	2483.50	60.4 PK	74.0	-13.6	3.30 V	88	26.9	33.5
4	2483.50	49.0 AV	54.0	-5.0	3.30 V	88	15.5	33.5
5	4924.00	47.8 PK	74.0	-26.2	1.56 V	333	44.5	3.3
6	4924.00	34.2 AV	54.0	-19.8	1.56 V	333	30.9	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.5 PK	74.0	-10.5	1.58 H	198	30.1	33.4
2	2390.00	52.6 AV	54.0	-1.4	1.58 H	198	19.2	33.4
3	*2422.00	108.4 PK			1.88 H	13	75.0	33.4
4	*2422.00	98.4 AV			1.88 H	13	65.0	33.4
5	2483.50	57.7 PK	74.0	-16.3	1.89 H	48	24.2	33.5
6	2483.50	46.1 AV	54.0	-7.9	1.89 H	48	12.6	33.5
7	4844.00	47.8 PK	74.0	-26.2	2.58 H	302	44.3	3.5
8	4844.00	34.8 AV	54.0	-19.2	2.58 H	302	31.3	3.5
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.0 PK	74.0	-16.0	3.77 V	50	24.6	33.4
2	2390.00	46.6 AV	54.0	-7.4	3.77 V	50	13.2	33.4
3	*2422.00	101.3 PK			3.78 V	61	67.9	33.4
4	*2422.00	91.2 AV			3.78 V	61	57.8	33.4
5	2483.50	57.6 PK	74.0	-16.4	3.56 V	88	24.1	33.5
6	2483.50	45.6 AV	54.0	-8.4	3.56 V	88	12.1	33.5
7	4844.00	47.7 PK	74.0	-26.3	2.55 V	105	44.2	3.5
8	4844.00	34.5 AV	54.0	-19.5	2.55 V	105	31.0	3.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.2 PK	74.0	-12.8	1.85 H	7	27.8	33.4
2	2390.00	49.5 AV	54.0	-4.5	1.85 H	7	16.1	33.4
3	*2437.00	113.1 PK			1.58 H	5	79.7	33.4
4	*2437.00	103.5 AV			1.58 H	5	70.1	33.4
5	2483.50	66.0 PK	74.0	-8.0	1.88 H	16	32.5	33.5
6	2483.50	52.5 AV	54.0	-1.5	1.88 H	16	19.0	33.5
7	4874.00	48.0 PK	74.0	-26.0	2.26 H	310	44.7	3.3
8	4874.00	34.8 AV	54.0	-19.2	2.26 H	310	31.5	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	3.92 V	65	25.9	33.4
2	2390.00	47.5 AV	54.0	-6.5	3.92 V	65	14.1	33.4
3	*2437.00	106.0 PK			3.95 V	71	72.6	33.4
4	*2437.00	95.9 AV			3.95 V	71	62.5	33.4
5	2483.50	59.7 PK	74.0	-14.3	3.99 V	95	26.2	33.5
6	2483.50	47.5 AV	54.0	-6.5	3.99 V	95	14.0	33.5
7	4874.00	47.8 PK	74.0	-26.2	1.58 V	200	44.5	3.3
8	4874.00	34.6 AV	54.0	-19.4	1.58 V	200	31.3	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.0 PK	74.0	-16.0	1.82 H	357	24.6	33.4
2	2390.00	46.0 AV	54.0	-8.0	1.82 H	357	12.6	33.4
3	*2452.00	108.7 PK			1.60 H	12	75.2	33.5
4	*2452.00	98.8 AV			1.60 H	12	65.3	33.5
5	2483.50	64.6 PK	74.0	-9.4	1.85 H	13	31.1	33.5
6	2483.50	52.7 AV	54.0	-1.3	1.85 H	13	19.2	33.5
7	4904.00	47.3 PK	74.0	-26.7	1.55 H	256	44.0	3.3
8	4904.00	34.6 AV	54.0	-19.4	1.55 H	256	31.3	3.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.5 PK	74.0	-16.5	3.88 V	75	24.1	33.4
2	2390.00	45.8 AV	54.0	-8.2	3.88 V	75	12.4	33.4
3	*2452.00	100.4 PK			1.98 V	84	66.9	33.5
4	*2452.00	91.3 AV			1.98 V	84	57.8	33.5
5	2483.50	58.2 PK	74.0	-15.8	3.86 V	55	24.7	33.5
6	2483.50	46.2 AV	54.0	-7.8	3.86 V	55	12.7	33.5
7	4904.00	47.0 PK	74.0	-27.0	2.88 V	155	43.7	3.3
8	4904.00	34.5 AV	54.0	-19.5	2.88 V	155	31.2	3.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.


Below 1GHz Worst-case Data: 802.11b

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	249.99	45.4 QP	46.0	-0.6	1.00 H	342	60.0	-14.6
2	286.03	43.7 QP	46.0	-2.3	1.00 H	7	56.7	-13.0
3	375.29	42.0 QP	46.0	-4.0	1.00 H	14	53.5	-11.5
4	625.60	40.5 QP	46.0	-5.5	1.00 H	27	47.3	-6.8
5	875.91	37.8 QP	46.0	-8.2	1.49 H	158	40.5	-2.7
6	934.13	36.6 QP	46.0	-9.4	1.49 H	56	38.7	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	A

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.66	34.6 QP	40.0	-5.4	1.00 V	99	49.9	-15.3
2	64.83	33.3 QP	40.0	-6.7	1.00 V	1	48.4	-15.1
3	276.33	38.7 QP	46.0	-7.3	1.50 V	94	52.0	-13.3
4	375.29	40.1 QP	46.0	-5.9	1.50 V	22	51.6	-11.5
5	499.48	35.5 QP	46.0	-10.5	1.00 V	80	44.9	-9.4
6	875.91	37.4 QP	46.0	-8.6	1.00 V	355	40.1	-2.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	62.95	30.7 QP	40.0	-9.3	2.00 H	180	45.8	-15.1
2	239.88	43.4 QP	46.0	-2.6	1.00 H	359	58.1	-14.7
3	251.55	44.2 QP	46.0	-1.8	1.00 H	354	58.2	-14.0
4	374.04	36.9 QP	46.0	-9.1	1.00 H	6	47.6	-10.7
5	500.42	29.3 QP	46.0	-16.7	1.49 H	199	37.3	-8.0
6	624.85	38.6 QP	46.0	-7.4	1.00 H	41	43.5	-4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	B

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	41.57	33.8 QP	40.0	-6.2	1.49 V	253	48.5	-14.7
2	57.12	33.1 QP	40.0	-6.9	1.00 V	333	47.6	-14.5
3	253.49	35.3 QP	46.0	-10.7	1.49 V	51	49.3	-14.0
4	374.04	37.2 QP	46.0	-8.8	1.49 V	57	47.9	-10.7
5	500.42	35.4 QP	46.0	-10.6	1.00 V	55	43.4	-8.0
6	624.85	34.5 QP	46.0	-11.5	1.49 V	150	39.4	-4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	C

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	146.56	40.0 QP	43.5	-3.5	2.00 H	135	53.9	-13.9
2	226.27	40.4 QP	46.0	-5.6	1.50 H	18	56.4	-16.0
3	237.94	45.7 QP	46.0	-0.3	1.50 H	18	60.6	-14.9
4	269.05	43.8 QP	46.0	-2.2	1.50 H	148	57.0	-13.2
5	374.04	40.1 QP	46.0	-5.9	2.00 H	12	50.8	-10.7
6	624.85	44.1 QP	46.0	-1.9	1.50 H	321	49.0	-4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz	TEST MODE	C

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.79	30.8 QP	40.0	-9.2	1.00 V	251	46.7	-15.9
2	146.56	39.2 QP	43.5	-4.3	1.00 V	154	53.1	-13.9
3	239.88	38.5 QP	46.0	-7.5	1.49 V	92	53.2	-14.7
4	255.44	38.8 QP	46.0	-7.2	1.99 V	132	52.7	-13.9
5	374.04	40.0 QP	46.0	-6.0	1.49 V	151	50.7	-10.7
6	624.85	44.1 QP	46.0	-1.9	1.00 V	94	49.0	-4.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 23, 2017	Nov. 22, 2018
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond1-01	Sep. 05, 2017	Sep. 04, 2018
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Mar. 06, 2018	Mar. 05, 2019
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 15, 2017	Aug. 14, 2018
Software ADT	BV ADT_Conc_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 1.
 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as item 4.3.6.

4.2.7 Test Results


Worst-case Data: 802.11b

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.16	41.01	29.66	51.17	39.82	66.00	56.00	-14.83	-16.18
2	0.18519	10.16	36.61	24.06	46.77	34.22	64.25	54.25	-17.48	-20.03
3	0.31021	10.18	38.65	32.73	48.83	42.91	59.96	49.96	-11.13	-7.05
4	0.86944	10.18	18.97	14.28	29.15	24.46	56.00	46.00	-26.85	-21.54
5	3.75130	10.33	15.07	8.95	25.40	19.28	56.00	46.00	-30.60	-26.72
6	6.99250	10.50	12.97	7.21	23.47	17.71	60.00	50.00	-36.53	-32.29

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16181	10.15	35.58	22.14	45.73	32.29	65.37	55.37	-19.64	-23.08
2	0.29043	10.18	36.25	27.91	46.43	38.09	60.51	50.51	-14.08	-12.42
3	0.31765	10.18	36.34	28.52	46.52	38.70	59.77	49.77	-13.25	-11.07
4	2.14014	10.23	17.06	11.27	27.29	21.50	56.00	46.00	-28.71	-24.50
5	4.90847	10.38	14.01	7.80	24.39	18.18	56.00	46.00	-31.61	-27.82
6	6.52330	10.44	14.35	8.05	24.79	18.49	60.00	50.00	-35.21	-31.51

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.73	36.24	25.82	45.97	35.55	65.79	55.79	-19.82	-20.24
2	0.19301	9.73	29.46	17.27	39.19	27.00	63.91	53.91	-24.72	-26.91
3	0.23993	9.73	26.70	18.00	36.43	27.73	62.10	52.10	-25.67	-24.37
4	0.34560	9.75	33.26	25.89	43.01	35.64	59.07	49.07	-16.06	-13.43
5	3.27409	9.80	16.36	9.05	26.16	18.85	56.00	46.00	-29.84	-27.15
6	22.25323	10.00	14.01	2.21	24.01	12.21	60.00	50.00	-35.99	-37.79

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.73	36.05	26.12	45.78	35.85	65.79	55.79	-20.01	-19.94
2	0.36896	9.75	31.81	25.02	41.56	34.77	58.52	48.52	-16.96	-13.75
3	1.56542	9.76	15.98	12.34	25.74	22.10	56.00	46.00	-30.26	-23.90
4	4.59176	9.84	15.33	7.99	25.17	17.83	56.00	46.00	-30.83	-28.17
5	7.76272	9.90	13.40	7.39	23.30	17.29	60.00	50.00	-36.70	-32.71
6	23.21900	10.14	12.63	4.58	22.77	14.72	60.00	50.00	-37.23	-35.28

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	C		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.67	30.40	19.74	40.07	29.41	66.00	56.00	-25.93	-26.59
2	0.19305	9.67	23.00	2.39	32.67	12.06	63.90	53.90	-31.23	-41.84
3	0.46179	9.67	36.32	30.36	45.99	40.03	56.66	46.66	-10.67	-6.63
4	0.49846	9.67	34.49	28.48	44.16	38.15	56.03	46.03	-11.87	-7.88
5	1.27217	9.69	25.82	15.90	35.51	25.59	56.00	46.00	-20.49	-20.41
6	27.34405	9.97	30.26	15.37	40.23	25.34	60.00	50.00	-19.77	-24.66

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Test Mode	C		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.68	30.15	19.02	39.83	28.70	66.00	56.00	-26.17	-27.30
2	0.17737	9.68	30.20	23.87	39.88	33.55	64.61	54.61	-24.73	-21.06
3	0.45575	9.68	31.35	23.03	41.03	32.71	56.77	46.77	-15.74	-14.06
4	2.41780	9.72	24.54	9.68	34.26	19.40	56.00	46.00	-21.74	-26.60
5	21.46732	10.06	27.42	17.05	37.48	27.11	60.00	50.00	-22.52	-22.89
6	25.81133	10.09	31.06	18.58	41.15	28.67	60.00	50.00	-18.85	-21.33

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	7.61	8.10	7.59	7.11	0.5	Pass
6	2437	8.12	8.12	8.09	8.12	0.5	Pass
11	2462	8.11	8.10	7.14	7.68	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	16.36	15.98	16.05	15.58	0.5	Pass
6	2437	16.36	16.36	15.78	15.79	0.5	Pass
11	2462	16.36	16.09	15.78	16.06	0.5	Pass

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	16.87	17.20	16.03	16.36	0.5	Pass
6	2437	17.24	16.59	16.28	16.37	0.5	Pass
11	2462	17.24	16.85	15.74	16.36	0.5	Pass

802.11n (HT40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	35.17	35.05	35.24	35.26	0.5	Pass
6	2437	35.18	35.16	35.23	35.18	0.5	Pass
9	2452	35.26	35.16	33.91	35.09	0.5	Pass

Spectrum Plot of Worst Value


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as item 4.3.6.

4.4.7 Test Results

CDD Mode

802.11b

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	21.37	21.34	21.28	21.11	536.630	27.30	30	Pass
6	2437	23.66	23.63	23.12	23.64	899.271	29.54	30	Pass
11	2462	22.04	21.78	21.03	22.73	624.881	27.96	30	Pass

802.11g

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	16.90	16.74	16.51	16.57	186.349	22.70	30	Pass
6	2437	22.76	22.64	22.73	22.61	742.342	28.71	30	Pass
11	2462	16.88	16.62	16.64	16.79	188.558	22.75	30	Pass

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	14.89	14.87	14.81	14.93	122.908	20.90	30	Pass
6	2437	22.96	22.87	22.43	22.76	755.123	28.78	30	Pass
11	2462	15.81	15.76	15.66	15.91	151.584	21.81	30	Pass

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	10.96	10.99	11.04	11.08	50.563	17.04	30	Pass
6	2437	15.52	15.14	15.71	15.49	140.943	21.49	30	Pass
9	2452	10.08	10.16	10.23	10.47	42.248	16.26	30	Pass

Beamforming Mode

802.11n (HT20)

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	14.11	14.09	14.03	14.15	102.703	20.12	30	Pass
6	2437	22.18	22.09	21.65	21.98	630.983	28.00	30	Pass
11	2462	15.03	14.98	14.88	15.13	126.664	21.03	30	Pass

Note: Beamforming gain = 3.78dBi < 6dBi, so the power limit no need to reduced.

802.11n (HT40)

Chan.	Chan. Freq. (MHz)	AVG. Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	10.18	10.21	10.26	10.30	42.250	16.26	30	Pass
6	2437	14.74	14.36	14.93	14.71	117.772	20.71	30	Pass
9	2452	9.30	9.38	9.45	9.69	35.302	15.48	30	Pass


Note: Beamforming gain = 3.78dBi < 6dBi, so the power limit no need to reduced.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

For AVG. power (duty cycle $\geq 98\%$)

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

For AVG. power (duty cycle $< 98\%$)

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as item 4.3.6.

4.5.7 Test Results

802.11b

TX chain	Channel	Freq. (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Total PSD With Duty Factor (dBm/10kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-6.02	6.02	0.00	4.98	Pass
	6	2437	-3.74	6.02	2.28	4.98	Pass
	11	2462	-5.09	6.02	0.93	4.98	Pass
1	1	2412	-5.59	6.02	0.43	4.98	Pass
	6	2437	-3.89	6.02	2.13	4.98	Pass
	11	2462	-4.95	6.02	1.07	4.98	Pass
2	1	2412	-6.19	6.02	-0.17	4.98	Pass
	6	2437	-3.84	6.02	2.18	4.98	Pass
	11	2462	-4.76	6.02	1.26	4.98	Pass
3	1	2412	-6.23	6.02	-0.21	4.98	Pass
	6	2437	-3.88	6.02	2.14	4.98	Pass
	11	2462	-4.47	6.02	1.55	4.98	Pass

Note:

1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $3\text{dBi} + 10\log(4) = 9.02\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (9.02 - 6) = 4.98\text{dBm}$.

802.11g

TX chain	Channel	Freq. (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Duty factor (dB)	Total PSD With Duty Factor (dBm/10kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-13.56	6.02	0.17	-7.37	4.98	Pass
	6	2437	-7.48	6.02	0.17	-1.29	4.98	Pass
	11	2462	-12.87	6.02	0.17	-6.68	4.98	Pass
1	1	2412	-13.67	6.02	0.17	-7.48	4.98	Pass
	6	2437	-7.68	6.02	0.17	-1.49	4.98	Pass
	11	2462	-13.33	6.02	0.17	-7.14	4.98	Pass
2	1	2412	-13.45	6.02	0.17	-7.26	4.98	Pass
	6	2437	-7.10	6.02	0.17	-0.91	4.98	Pass
	11	2462	-13.11	6.02	0.17	-6.92	4.98	Pass
3	1	2412	-12.76	6.02	0.17	-6.57	4.98	Pass
	6	2437	-7.07	6.02	0.17	-0.88	4.98	Pass
	11	2462	-12.88	6.02	0.17	-6.69	4.98	Pass

Note:

- Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $3\text{dBi} + 10\log(4) = 9.02\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (9.02 - 6) = 4.98\text{dBm}$.
- Refer to section 3.3 for duty cycle spectrum plot.

802.11n (HT20)

TX chain	Channel	Freq. (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Total PSD With Duty Factor (dBm/10kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	1	2412	-15.08	6.02	-9.06	4.98	Pass
	6	2437	-7.34	6.02	-1.32	4.98	Pass
	11	2462	-14.08	6.02	-8.06	4.98	Pass
1	1	2412	-14.76	6.02	-8.74	4.98	Pass
	6	2437	-6.93	6.02	-0.91	4.98	Pass
	11	2462	-13.57	6.02	-7.55	4.98	Pass
2	1	2412	-14.37	6.02	-8.35	4.98	Pass
	6	2437	-6.82	6.02	-0.80	4.98	Pass
	11	2462	-13.27	6.02	-7.25	4.98	Pass
3	1	2412	-14.44	6.02	-8.42	4.98	Pass
	6	2437	-6.46	6.02	-0.44	4.98	Pass
	11	2462	-13.46	6.02	-7.44	4.98	Pass

Note:

1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $3\text{dBi} + 10\log(4) = 9.02\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $8 - (9.02 - 6) = 4.98\text{dBm}$.

802.11n (HT40)


TX chain	Channel	Freq. (MHz)	PSD (dBm/10kHz)	10 log (N=4) dB	Duty factor (dB)	Total PSD With Duty Factor (dBm/10kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	3	2422	-22.25	6.02	0.14	-16.09	4.98	Pass
	6	2437	-17.26	6.02	0.14	-11.10	4.98	Pass
	9	2452	-22.71	6.02	0.14	-16.55	4.98	Pass
1	3	2422	-21.54	6.02	0.14	-15.38	4.98	Pass
	6	2437	-17.16	6.02	0.14	-11.00	4.98	Pass
	9	2452	-22.49	6.02	0.14	-16.33	4.98	Pass
2	3	2422	-21.86	6.02	0.14	-15.70	4.98	Pass
	6	2437	-16.98	6.02	0.14	-10.82	4.98	Pass
	9	2452	-22.02	6.02	0.14	-15.86	4.98	Pass
3	3	2422	-21.48	6.02	0.14	-15.32	4.98	Pass
	6	2437	-16.97	6.02	0.14	-10.81	4.98	Pass
	9	2452	-21.48	6.02	0.14	-15.32	4.98	Pass

Note:


1. Method a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = 3dBi + 10log(4) = 9.02dBi > 6dBi, so the power density limit shall be reduced to 8-(9.02-6) = 4.98dBm.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- Set the VBW $\geq$ 300 kHz.
- Detector = average.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW $\geq$ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Same as item 4.3.6.


4.6.7 Test Results

The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

802.11b_Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11b_Chain 1


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11b_Chain 2


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11b_Chain 3


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g_Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g_Chain 1


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g_Chain 2


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11g_Chain 3


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20)_Chain 0


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20)_Chain 1


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20)_Chain 2


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT20)_Chain 3


CH 1




CH 6




CH 11



CH 1 Band edge




CH 11 Band edge




802.11n (HT40)_Chain 0


CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




802.11n (HT40)_Chain 1


CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




802.11n (HT40)_Chain 2


CH 3




CH 6




CH 9



CH 3 Band edge




CH 9 Band edge




802.11n (HT40)_Chain 3


CH 3




CH 6




CH 9



CH 3 Band edge



CH 9 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---