

EAC



052



R-NZ

ERAC000113



CCXXxxYYyyyZzW

減少電磁波影響，請妥適使用

Polarity:



Input:

額定電壓電流: 12V $\equiv$ 2.5A (Adapter) or
42.5-57V $\equiv$ 0.6A (PoE)

FCC



D43032
RoHS



D-Link DWL-X8630APE
AX3600 無線網路基地台
11AX 3600M 并发双频POE无线接入点



UL
LISTED
L.T.E. 4G17
UL 2043

友讯电子设备(上海)有限公司
Made in Taiwan/台灣製造/台灣製造

A-Link DWL-X8630APE

AX3600 無線網路基地台
11AX 3600M 并发双频POE无线接入点

Complies with

IMDA Standards
DB100549


CIBF 15000447

FCC ID: KA2WL8630A0A1

[C]: 4216A-WL8630A0A1	MIN: DWL-X8630APEA1
[CA] IES3-3: R10MB-SB1B	

Default Access Point settings:
<http://10.90.90.91>
Username: admin
Password: admin



UL 2043

This device complies with Part 15 of the FCC Rules.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received,
including interference that may cause undesired
operation.

友訊電子股份有限公司
Made in Taiwan/台灣製造/台灣總經銷