

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

ELECTROMAGNETIC COMPATIBILITY

EMC TEST REPORT

FCC 47 CFR PART 15 SUBPART C

INDUSTRY CANADA RSS-210 ISSUE 5
(compliant with RSS-210 Issue 6, Sept. 2005)

FOR

ITRONIX CORPORATION

MODEL: IX325A860IWLBT

IX325 SERIES RUGGED TABLET PC

WITH

802.11b/g WLAN MINI-PCI CARD

AND

INTERNAL PIFA ANTENNA

FCC ID: KBCIX325A860IWLBT

IC: 1943A-IX325g

Test Report Serial No.

042406KBC-T743-E15W

Test Report Revision No.

Revision 1.0 (Initial Release)

Test Lab and Location

Celltech Compliance Testing & Engineering Lab
(Celltech Labs Inc.)
1955 Moss Court
Kelowna, BC
Canada
V1Y 9L3

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

DECLARATION OF COMPLIANCE

Test Lab and Location	CELLTECH LABS INCORPORATED Testing and Engineering Services 1955 Moss Court Kelowna, BC V1Y 9L3 Canada	Company Information	ITRONIX CORPORATION 12825 E. Mirabeau Parkway Spokane Valley, WA 99216 United States
Phone:	250-448-7047		
Fax:	250-448-7048		
e-mail:	info@celltechlabs.com		
web site:	www.celltechlabs.com		
Lab Registration No.(s):	FCC: 714830	IC: 3874	
Rule Part(s) Applied:	FCC: §15.247; §2.1091; §1.1310	IC: RSS-210 Issue 5 - A1. 11/30/02	
Device Classification:	FCC: Digital Transmission System (DTS)	IC: Low Power Licence-Exempt Transmitter	
Device Identification:	FCC ID: KBCIX325A860IWLBT	IC: 1943A-IX325g	
DUT Description:			
Model:	IX325A860IWLBT		
Device Description:	Rugged Tablet PC		
Internal Transmitter(s):	Intel PRO2200BG 802.11b/g 2.4 GHz DSSS WLAN Mini-PCI Card		
TX Frequency Range:	2412 - 2462 MHz		
Max. RF Output Power:	0.112 Watts - 20.49 dBm - Peak Conducted - 802.11b 0.048 Watts - 16.77 dBm - Peak Conducted - 802.11g		
Modulation Type(s):	OFDM with BPSK, QPSK, 16QAM, 64QAM, DBPSK, DQPSK, CCK		
Antenna Type(s):	Well Green Technology PIFA WLAN Dual Internal Antenna (Primary Transmit & Receive - upper right side edge of LCD Display) (Auxiliary Receive only - upper left side edge of LCD Display)		
Power Source(s):	Stationary: 75 Watt AC Power Adapter		
	11.1 V Internal Lithium-ion Battery, 3600 mAh (Model: T8M-E)		
	11.1 V External Second Lithium-ion Battery, 3600 mAh (Model: T8S-E)		

This wireless transmitting device has demonstrated compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC 47 CFR Part 15C and Industry Canada RSS-210 Issue 5.

I attest to the accuracy of the data. All measurements reported herein were performed by me or were under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This test report shall not be reproduced partially, or in full, without the prior written approval of Celltech Labs Inc. The results and statements contained in this report pertain only to the device(s) evaluated.

	Russell Pipe Senior Compliance Technologist Celltech Labs Inc.	
	Alex Yuan EMC Technologist Celltech Labs Inc.	
	Duane M. Friesen, C.E.T. EMC Manager Celltech Labs Inc.	

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 2 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

TABLE OF CONTENTS

1.0 SCOPE.....	5
2.0 REFERENCES	5
2.1 Normative References	5
TERMS AND DEFINITIONS.....	6
3.0 FACILITIES AND ACCREDITATIONS	7
4.0 GENERAL INFORMATION.....	7
4.1 Applicant Information.....	7
4.2 DUT Description.....	7
4.3 Co-Located Equipment.....	8
4.4 Cable Descriptions	8
4.5 Support Equipment.....	8
4.6 Clock Frequencies.....	9
4.7 Mode(s) of Operation Tested	9
4.8 Configuration Description	10
5.0 PASS/FAIL CRITERIA.....	10
APPENDICES	11
Appendix A - DUT Photographs.....	12
Appendix B - 6 dB Bandwidth Measurement	13
Appendix C - Peak Conducted RMS Power Measurement.....	18
Appendix D - Radiated Spurious Emissions Measurement	21
Appendix E - Restricted Band Emissions Measurement	35
Appendix F - Peak Power Spectral Density Measurement	50
Appendix G - Conducted Powerline Emissions Measurement.....	53
END OF DOCUMENT	59

FIGURES

Figure B.6-1 - Setup Drawing	14
Figure C.6-1 - Setup Drawing	19
Figure D.6-1 - Setup Drawing	22
Figure E.6-1 - Setup Drawing	37
Figure F.6-1 - Setup Drawing.....	51
Figure G.6-1 - Setup Drawing.....	54

PHOTOGRAPHS

Photograph A-1 - Front of IX325 Tablet PC.....	12
Photograph A-2 - Back of IX325 Tablet PC.....	12
Photograph A-3 - Edge of IX325 Tablet PC.....	12
Photograph A-4 - Side of IX325 Tablet PC.....	12
Photograph A-5 - WLAN Mini-PCI Card Location.....	12
Photograph A-6 - WLAN Dual Antenna Location	12
Photograph D-1 - 3115 Horn @ 3 m	23
Photograph D-2 - 3115 Horn with LNA/Filter @ 1m	23
Photograph D-3 - Waveline Horn with LNA @ 1m	23
Photograph E-1 - Loop Antenna (10kHz - 30 MHz) @ 3m.....	38
Photograph E-2 - Bilog Antenna (30 MHz - 1 GHz) @ 3m.....	38
Photograph E-3 - 3115 Horn (1G - 2G) @ 3 m	38
Photograph E-4 - 3115 Horn with LNA/Filter @ 1m.....	38
Photograph E-5 - Waveline Horn with LNA @ 1m.....	38
Photograph G-1 - AC Powerline Conducted Emission Cable Placement	55
Photograph G-2 - AC Powerline Conducted Emission Configuration	55

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 3 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

TEST SUMMARY

Appendix	Test Description	Procedure Reference	Limit Reference	Test Start Date	Test End Date	Result
Referenced Standard: FCC CFR Title 47 Part 15						
B	6 dB Bandwidth	FCC 97-114	§15.247(2)	14Jul05	14Jul05	Pass
C	Peak Conducted Output Power	FCC 97-114	§15.247 (b) (3)	14Jul05	14Jul05	Pass
D	Maximum Permissible Exposure	FCC CFR 47 § 2.1091 IEEE Std C95.1-1992	§1.1310 Table 1 (b)	15Jul05	15Jul05	Pass
E	Radiated Spurious Emissions	FCC 97-114	§15.247(c)	4Jul05	13Jul05	Pass
F	Restricted Band Emissions	FCC 97-114	§15.205 (a), (b) §15.209 (a)	4Jul05	13Jul05	Pass
G	Peak Power Spectral Density	FCC 97-114	§15.247(d)	20Jul05	20Jul05	Pass
H	Powerline Conducted Emissions	ANSI C63.4	§15.207	20Jul05	20Jul05	Pass
Referenced Standard: IC RSS-210 Issue 5						
B	6 dB Bandwidth	RSS-210 § 10	RSS-210 A1 §(l)(iv)	14Jul05	14Jul05	Pass
C	Peak Conducted Output Power	RSS-210 § 10	RSS-210 A1 §(l)(iv) RSS-210 §6.2.2 (o)(b)	14Jul05	14Jul05	Pass
D	Maximum Permissible Exposure	RSS-102	RSS-210 §14 Safety Code 6 2.2.1(a) Table 5	15Jul05	15Jul05	Pass
E	Radiated Spurious Emissions	RSS-212, ANSI C63.4	RSS-210 §6.2.2 (o)(e1)	4Jul05	13Jul05	Pass
F	Restricted Band Emissions	RSS-212, ANSI C63.4	RSS-210 §6.3	4Jul05	13Jul05	Pass
G	Peak Power Spectral Density	RSS-210 § 10	RSS-210 §6.2.2 (o)(b)	20Jul05	20Jul05	Pass
H	Powerline Conducted Emissions	RSS-212, ANSI C63.4	RSS-210 §6.6	20Jul05	20Jul05	Pass

REVISION LOG

Revision	Description	Implemented By	Implementation Date
1.0	Initial Release	Jonathan Hughes	07Nov06

SIGNATORIES

Prepared By		February 13, 2006
Name/Title	Duane M. Friesen, C.E.T. / EMC Manager	Date
Reviewed By		February 13, 2006
Name/Title	Jonathan Hughes / General Manager	Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 4 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

1.0 SCOPE

This report outlines the measurements made and results collected during the electromagnetic emissions testing of the Itronix Corporation Model: IX325A860IWLBT Rugged Tablet PC with internal Intel PRO2200BG 802.11b/g DSSS WLAN Mini-PCI Card and internal Well Green Technology PIFA WLAN antenna. The results were applied against the EMC requirements and limits outlined in the technical rules and regulations set forth in the Federal Communication Commission Code of Federal Regulations Title 47 Part 15 Subpart C and Industry Canada RSS-210 Issue 5.

2.0 REFERENCES

2.1 Normative References

ANSI/ISO 17025:1999	General Requirements for competence of testing and calibration laboratories
IEEE/ANSI C63.4-2003	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
IEEE/ANSI Std C95.1-1999	American National Standard Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields
CFR Title 47 Part 2:2004	Code of Federal Regulations Title 47: Telecommunication Part 2: Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
CFR Title 47 Part 15:2004	Code of Federal Regulations Title 47: Telecommunication Part 15: Radio Frequency Devices
FCC Public Notice DA 00-705	Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems March 30, 2000
FCC Knowledge Database Pub.	558074 (May 10, 2005)
IC Spectrum Management & Telecommunications Policy	Radio Standards Specification RSS-212 Issue 1 (Provisional) - Test Facilities & Test Methods for Radio Equipment RSS-210 Issue 5 - Low Power Licence-Exempt Radiocommunication Devices: Amendment November 30, 2002 RSS-102 Issue 1 (Provisional) - Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 5 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

TERMS AND DEFINITIONS

AVG	Average
CFR	Code of Federal Regulations
dB	decibel
dBm	dB referenced to 1 mW
dBuV	dB referenced to 1 uV
DUT	Device under Test
dBc	dB down from carrier
EBW	Emission Bandwidth
EMC	Electromagnetic Compatibility
FCC	Federal Communication Commission
HP	Hewlett Packard
HPF	High Pass Filter
Hpol	Horizontal Polarization
IC	Industry Canada
kHz	kilohertz
LNA	Low Noise Amplifier
m	meter
MHz	Megahertz
Mbps	megabits per second
na	not applicable
n/a	not available
PK	Peak
PPSD	Peak Power Spectral Density
QP	Quasi-peak
RBW	Resolution Bandwidth
R&S	Rohde & Schwarz
RSS	Radio Standard Specification
SA	Spectrum Analyzer
VBW	Video Bandwidth
Vpol	Vertical Polarization
WLAN	Wireless Local Area Network

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 6 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

3.0 FACILITIES AND ACCREDITATIONS

The facilities used in collecting the test results outlined in this report are located at 1955 Moss Court, Kelowna, British Columbia, Canada, V1Y 9L3. The radiated and conducted emissions sites conform with the requirements set forth in ANSI C63.4 and are filed and are listed with the FCC under Registration Number 714830 and Industry Canada under File Number IC 3874.

4.0 GENERAL INFORMATION

4.1 Applicant Information

Company Name:	Itronix Corporation
Address:	12825 E. Mirabeau Parkway
	Spokane Valley, WA 99216
	United States

4.2 DUT Description

The DUT consisted of the Itronix Rugged Tablet PC Model: IX325A860IWLBT with internal Intel PRO2200BG 802.11b/g DSSS WLAN Mini-PCI Card installed in the Mini-PCI slot, and internal PIFA antenna installed in the upper right side edge of the LCD display. Photographs of the DUT placement and construction are shown in Appendix A.

Device:	Rugged Tablet PC		
Model:	IX325A860IWLBT		
Serial Number:	ZZGEG5074ZZ9799		
Identifier(s):	FCC ID:	KBCIX325A860IWLBT	IC: 1943A-IX325g
Power Source(s):	Delta Electronics 75 Watt AC-DC Power Supply Model: ADP-75 FB B Rev 00 (S/N: UCT030200307)		
	Internal Lithium-ion 11.1 V 3600 mAh Battery Model: T8M-E		
	External Second Lithium-ion 11.1 V 3600 mAh Battery Model: T8S-E		

Device:	2.4GHz DSSS WLAN Mini-PCI Card (802.11b/g)		
Model:	Intel PRO2200BG		
Serial Number:	06036C074ADC54906006		
Rule Part(s):	FCC:	§15.247; §2.1091; §1.1310	IC: RSS-210 Issue 5 - A1. 11/30/02
Classification:	FCC:	Digital Transmission System (DTS)	IC: Low Power Licence-Exempt Transmitter
Power Source:	Powered from the internal PC power supply		

Device:	Internal PIFA WLAN Antenna 2 (diversity antenna for Transmit and Receive) - upper right side of LCD		
Model:	Well Green Technology WLAN Antenna		
Gain:	1.65 dBi		

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 7 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Device:	Internal PIFA WLAN Antenna 1 (diversity antenna for Receive only) - upper left side of LCD
Model:	Well Green Technology WLAN Antenna
Gain:	2.41 dBi

4.3 Co-Located Equipment

Device:	GPS Receiver Module
Model:	Leadtek Model LR9805

Device:	GPS Antenna (Receive only)
Model:	Sarantel 101401040/2004UK

4.4 Cable Descriptions

ROUTING		Length	Model	Terminations		Shield Type	Shield Termination		Suppression
From	To	m		End 1	End 2		End 1	End 2	
PC modem port	Unterminated	1.0	n/a	RJ-11	RJ-11	None	na	na	None

4.5 Support Equipment

The following equipment was used in support of the DUT.

CO-LOCATED SUPPORT EQUIPMENT LIST		
MANUFACTURER	MODEL	DESCRIPTION
D-Link	DE-809TC/	Ethernet hub
YNG YUH	YP-040	Hub power supply
MLi	699	Speakers
Polk Audio	n/a	Speaker-microphone
	K8255	Keyboard
Sanwa Supply	MA-MBUSB	Mouse

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 8 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

4.6 Clock Frequencies

4.6.1 DUT Clock Frequencies

Device:	Rugged Tablet PC
Clocks:	n/a
Name:	2.4GHz DSSS WLAN Mini-PCI Card
Clocks:	n/a
Name:	Internal PIFA Antenna (WLAN)
Clocks:	None

4.6.2 Co-Located Clock Frequencies

Device:	Peripherals
Clocks:	n/a

4.7 Mode(s) of Operation Tested

Customer supplied the software which was used to set the WLAN card in the appropriate mode, channel, and power level for the specific measurement.

TX Frequency Range:	2412 - 2462 MHz Ch. 1 (2412 MHz), Ch. 6 (2437 MHz) & Ch. 11 (2462 MHz) measured unless otherwise noted					
Software Power Gain Settings:	802.11b set to power setting of 27 802.11g set to power setting of 20					
RF Peak Conducted Output Power Tested:¹	802.11b	1 Mbps	11 Mbps	802.11g	6 Mbps	54 Mbps
	2412 MHz	18.20 dBm	19.63 dBm	2412 MHz	16.24 dBm	15.96 dBm
	2437 MHz	18.56 dBm	20.49 dBm	2437 MHz	16.67 dBm	16.30 dBm
	2462 MHz	19.04 dBm	20.41 dBm	2462 MHz	16.77 dBm	16.54 dBm
Modes / Data Rates Tested:²	802.11b (1, 5.5, 11 Mbps checked in prescan) (1 Mbps short determined to be worst-case spurious and used unless otherwise noted)					
	802.11g (6, 36, 54 Mbps checked in prescan) (6 Mbps determined to be worst-case spurious and used unless otherwise noted)					
Modulation Type(s):	OFDM with BPSK, QPSK, 16QAM, 64QAM, DBPSK, DQPSK, CCK					
Power Source(s) Tested:	All tests were performed with the AC Power Adapter powering the DUT.					

Note 1: Peak power measured and corrected per FCC Document KDB Pub. No. 558074 Power Output Option 2 Method 1

Note 2: Turbo mode available at module level but not enabled when installed in DUT

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 9 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

4.7.1 DUT Exercising Software Description

The DUT was configured and exercised using customer supplied test software that allows an operator to set the parameters of the WLAN operation. The settings used are described in each appendix. Unless otherwise noted the power gain settings were set as described in section 5.6 with the worst-case data rate as described in the same section. Software power settings were set as defined by the manufacturer for typical operation.

4.8 Configuration Description

The DUT was configured, as described by the client as being representative of what would be delivered to a final customer. This configuration included the WLAN and internal antenna as described in section 5.2 installed in a typical manner. More specific details may be included in each appendix.

4.8.1 Configuration Justification

The DUT was tested in a configuration described by the client as being worst-case but typical of normal use.

Prescan measurements were made with the WLAN in each of the two available modes (b & g), lowest and highest bit rates and each of the lowest, highest and mid-band frequencies. From this preliminary data, it was determined that Mode b Rate 1 Mbps resulted in the highest spurious emissions. When a measurement of Mode g was required, its data rate was set for a worst-case setting of 6 Mbps. Unless otherwise specified in the applicable appendices, these settings were used for the measurements described in this report.

5.0 PASS/FAIL CRITERIA

Unless otherwise noted in the Appendices, the pass/fail criteria is the limit set forth in the reference standards. A DUT is considered to have passed the requirements, if the data collected during the described measurement procedure is less than or equal to the specified limits as defined. The pass/fail statements made in this report only apply to the unit tested.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 10 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

APPENDICES

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 11 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix A - DUT Photographs

Photograph A-1 - Front of IX325 Tablet PC



Photograph A-2 - Back of IX325 Tablet PC



Photograph A-3 - Edge of IX325 Tablet PC




Photograph A-4 - Side of IX325 Tablet PC



Photograph A-5 - WLAN Mini-PCI Card Location



Photograph A-6 - WLAN Dual Antenna Location



Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 12 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix B - 6 dB Bandwidth Measurement

B.1. REFERENCES

Normative Reference Standard	FCC CFR 47 §15.247 (2)
Procedure Reference	FCC Document KDB Publication Number 558074

B.2. LIMITS

B.2.1. FCC CFR 47

FCC CFR 47 §15.247 (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

B.3. ENVIRONMENTAL CONDITIONS

Temperature	25 +/- 2 °C
Humidity	35 +/- 2 %
Barometric Pressure	96 kPa

B.4. EQUIPMENT LIST

ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
00015	Agilent	E4408B	Spectrum Analyzer	24Jan05	24Jan06
00075	Alpha Wire-J	9223	1ft. RG223/U RF Cable	na*	na
00076	Pasternack	PE7014-30	30dB 2 Watt Attenuator	na*	na

*Cable and attenuator verified with power meter prior to use

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 13 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

B.5. MEASUREMENT EQUIPMENT SETUP

Measurement Equipment Connections	The equipment was connected as shown in the setup drawing in B.6.
Measurement Equipment Settings	To evaluate the occupied bandwidth, software and a PC controller were used to set the spectrum analyzer using the following setting: RBW – 100 kHz VBW – 100kHz Span – 50 MHz Detector – Sample Average – Power Average Count – 100 Offset – appropriate for external attenuation (-31.4 dB)

B.6. SETUP DRAWING

Figure B.6-1 - Setup Drawing



B.7. DUT OPERATING DESCRIPTION




The worst-case data rate was determined from prescan investigations. Measurements were made at three channels throughout the band, Low Channel (2412 MHz), Mid Channel (2437 MHz), High Channel (2462 MHz) for both Modes b and g.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 14 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

B.8. TEST RESULTS

B.8.1. Mode b Occupied Bandwidth






Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/Fail
1	2412	9.56	0.5	PASS
6	2437	9.50	0.5	PASS
11	2462	7.75	0.5	PASS

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 15 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

B.8.2. Mode g Occupied Bandwidth



Channel	Channel Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/Fail
1	2412	16.44	0.5	PASS
6	2437	16.31	0.5	PASS
11	2462	16.44	0.5	PASS

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 16 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

B.9. PASS/FAIL

In reference to the results outlined in B.8, the DUT passes the requirements as stated in the reference standards as follows:

FCC 15.247 (2): The 6 dB bandwidth as measured meets the minimum 500 kHz bandwidth requirement.

The minimum 6 dB bandwidth measured for Mode b was 7.75 MHz and for Mode g was 16.31 MHz.

B.10. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Alex Yuan
EMC Technologist
Celltech Labs Inc.

14Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 17 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix C - Peak Conducted RMS Power Measurement

C.1. REFERENCES	
Normative Reference Standard	FCC CFR 47 §15.247(b) (3)
Procedure Reference	FCC Document KDB Publication Number 558074

C.2. LIMITS
C.2.1. FCC CFR
§15.247(b): The maximum peak output power of the intentional radiator shall not exceed the following: §15.247(b) (3) For system using digital modulation in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands: 1 Watt.

C.3. ENVIRONMENTAL CONDITIONS	
Temperature	25 +/- 2 °C
Humidity	35 +/- 2 %
Barometric Pressure	96 kPa

C.4. EQUIPMENT LIST					
ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
00015	Agilent	E4408B	Spectrum Analyzer	24Jan05	24Jan06
00075	Alpha Wire-J	9223	1ft. RG223/U RF Cable	na*	na
00076	Pasternack	PE7014-30	30dB 2 Watt Attenuator	na*	na

*Cable and attenuator verified with power meter prior to use


C.5. MEASUREMENT EQUIPMENT SETUP	
Measurement Equipment Connections	The equipment was connected as shown in the setup drawing in C.6.
Measurement Equipment Settings	To evaluate the maximum peak power, with the following spectrum analyzer settings were used: RBW – 3 MHz VBW – 3 MHz Detector – Peak Trace – Max Hold Span -25 MHz
Measurement Procedure	A PC controller was used to record the spectrum analyzer display and pick the maximum level and to determine the emission bandwidth (EBW). It then corrected the peak level recorded with a bandwidth correction factor of $10 * \log (EBW/RBW)$. The corrected peak value was recorded and reported herein.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 18 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

C.6. SETUP DRAWING

Figure C.6-1 - Setup Drawing



C.7. DUT OPERATING DESCRIPTION

The worst-case data rate was determined from prescan investigations. Measurements were made at three channels throughout the band, Low Channel (2412 MHz), Mid Channel (2437 MHz), High Channel (2462 MHz) for both Modes b and g. The measurements were made for both the lowest and highest data rate available for the mode.

C.8. TEST RESULTS

Channel	Frequency	802.11b					802.11g				
		Data Rate	Peak Conducted Power*		Limit	-26 dB EBW	Data Rate	Peak Conducted Power*		Limit	-26 dB EBW
	MHz	Mb/s	dBm	Watts	Watts	MHz	Mb/s	dBm	Watts	Watts	MHz
Low	2412	1	18.20	0.066	1	19.25	6	16.24	0.042	1	19.88
		11	19.63	0.092	1	19.25	54	15.96	0.039	1	19.75
Mid	2437	1	18.56	0.072	1	19.25	6	16.67	0.046	1	20.00
		11	20.49	0.112	1	19.38	54	16.30	0.043	1	19.88
High	2462	1	19.04	0.080	1	19.50	6	16.77	0.048	1	19.88
		11	20.41	0.110	1	19.50	54	16.54	0.045	1	19.88

*Corrected Peak Power (corrected for BW),

Peak Conducted Power (dBm) = Measured Conducted Power (dBm) + 10 * log (EBW / 3 MHz)

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 19 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

C.9. PASS/FAIL

In reference to the results outlined in C.8 the DUT passes the requirements as stated in the reference standards as follows:

FCC 15.247 (b) (3): The peak power did not exceed 1 Watt.

The maximum peak power measured for Mode b was 0.112 watts, and for Mode g was 0.048 watts.

C.10. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Alex Yuan
EMC Technologist
Celltech Labs Inc.

14Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 20 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix D - Radiated Spurious Emissions Measurement

D.1. REFERENCES	
Normative Reference Standard	FCC CFR 47 §15.247(c)
Procedure Reference	ANSI C63.4; FCC 97-114

D.2. LIMITS	
D.2.1. FCC CFR 47	
§15.247 (c): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in 15.209 (a) is not required.	
Note: Spurious emissions within the restricted bands are reported in Appendix F.	

D.3. ENVIRONMENTAL CONDITIONS	
Temperature	27 +/- 2 °C
Humidity	33 +/- 2 %
Barometric Pressure	96 +/- 0.2 kPa

D.4. EQUIPMENT LIST						
RECEIVING EQUIPMENT						
ID	ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
1	00072	EMCO	2075	Mini-mast	na	na
2	00073	EMCO	2080	Turn Table	na	na
3	00071	EMCO	2090	Multi-Device Controller	na	na
4	00035	ETS	3115	Double Ridged Guide Horn	24Mar04	24Mar06
5	00161/00166	Waveline	899/801-KF	Standard Gain Horn	na	na
6	00051	HP	8566B	Spectrum Analyzer RF Section	12Apr05	12Apr06
7	00049	HP	85650A	Quasi-Peak Adapter	13Apr05	13Apr06
8	00047	HP	85685A	RF Preselector	13Apr05	13Apr06
9	00015	Agilent	4408B	Spectrum Analyzer	24Jan05	24Jan06
10	00115	Miteq	J54-00102600-35-5A	LNA	08Jun04	08Jun06
11	00093	Microtronics	HPM50111	High Pass Filter	8Jun04	8Dec05
12	00119	INMAT	18AH-10	10dB attenuator	8Jun04	8Dec05
13	00120	Celltech	n/a	Microwave Cable (RX)	25Mar05	25Mar06
14	00121	Andrew	FSJ4-50B	Microwave Cable (RX)	25Mar05	25Mar06
15	00130	Andrew	FSJ1-50A	Microwave Cable (RX)	25Mar05	25Mar06

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 21 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.5. MEASUREMENT EQUIPMENT SETUP

MEASUREMENT EQUIPMENT CONNECTIONS	The measurement equipment was connected as shown in the E.6. A number of antennas were used to cover the applicable frequency range test. The ranges in which each antenna was used are as follows:			
	Frequency Range	Spectrum Analyzer Asset #	LNA/Filter/Attenuator Asset #	Antenna Asset #
	2 GHz – 10 GHz	00051	00093/00115	00035
	10 GHz – 20 GHz	00015	00093/00115	00161/00166
MEASUREMENT EQUIPMENT SETTINGS	20 GHz – 26 GHz	00015	00093	00161/00166
	The spectrum analyzer was set to the following settings:			
	Frequency Range	RBW	VBW	Detector
	MHz	kHz	kHz	
	> 1000	1000*	1000	Peak*
	*As a worst-case measurement, the average/QP limit was applied to measurements made with a peak detector using a RBW of 1 MHz (vs the specified 100 kHz), unless otherwise noted. Average measurements were performed with video averaging using a VBW of 30 Hz.			

D.6. SETUP DRAWING

Figure D.6-1 - Setup Drawing



Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 22 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.7. SETUP PHOTOGRAPHS

Photograph D-1 - 3115 Horn @ 3 m



Photograph D-2 - 3115 Horn with LNA/Filter @ 1m



Photograph D-3 - Waveline Horn with LNA @ 1m



Intentionally Left Blank

D.8. DUT OPERATING DESCRIPTION

The worst-case data rate was determined from prescan investigations. Measurements were made at three channels throughout the band, Low Channel (2412 MHz), Mid Channel (2437 MHz), High Channel (2462 MHz) for both Modes b and g.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 23 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9. TEST RESULTS

D.9.1. Mode b - Fundamental Field Strengths @ Specified Distance (100 kHz RBW)



Project Numb 060605KBC-T643-E15W

Company: Itronix

Product: IX325 with Intel PRO 2200BG

Standard: FCC15.247a

Test Start Date: 4-Jul-05

Test End Date: 13-Jul-05

IX325 with Intel WLAN Mode b with Setting 27, Tx = 1 Mbps Carrier Field Strengths													
Channel	Polarity	Measurement Distance	Antenna	Frequency	SA Level	Noise Floor	AF	CL	Other	Total CF	Field Strength	Detector	RBW
		m											
WLAN-CH1	H	3	Horn SN6276	2412.00	77.90		30.26	5.10	-23.13	12.23	90.13	PK	100
WLAN-CH1	H	3	Horn SN6276	2412.00	66.90		30.26	5.10	-23.13	12.23	79.13	AV	100
WLAN-CH1	V	3	Horn SN6276	2412.00	80.50		30.26	5.10	-23.13	12.23	92.73	PK	100
WLAN-CH1	V	3	Horn SN6276	2412.00	69.50		30.26	5.10	-23.13	12.23	81.73	AV	100
WLAN-CH6	H	3	Horn SN6276	2437.00	78.40		30.30	5.14	-23.12	12.31	90.71	PK	100
WLAN-CH6	H	3	Horn SN6276	2437.00	67.20		30.30	5.14	-23.12	12.31	79.51	AV	100
WLAN-CH6	V	3	Horn SN6276	2437.00	81.15		30.30	5.14	-23.12	12.31	93.46	PK	100
WLAN-CH6	V	3	Horn SN6276	2437.00	70.00		30.30	5.14	-23.12	12.31	82.31	AV	100
WLAN-CH11	H	3	Horn SN6276	2462.00	78.65		30.34	5.16	-23.12	12.38	91.03	PK	100
WLAN-CH11	H	3	Horn SN6276	2462.00	67.30		30.34	5.16	-23.12	12.38	79.68	AV	100
WLAN-CH11	V	3	Horn SN6276	2462.00	81.75		30.34	5.16	-23.12	12.38	94.13	PK	100
WLAN-CH11	V	3	Horn SN6276	2462.00	70.50		30.34	5.16	-23.12	12.38	82.88	AV	100

Formulae:

Total CF = AF + CL + Other


Field Strength = SA Level + Total CF

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 24 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9.2. Mode b - Lower Band-edge Emission Field Strengths @ Specified Distance

Channel 1 Mode b - Conducted Peak Band-edge Plots



Channel 1 Mode b - Conducted Average Band-edge Plots



Channel 1 b - Calculated Band-edge (Unrestricted) Field Strengths

IX325 with Intel WLAN Mode b with Setting 27.0, Tx = 1 Mbps

Channel	Polarity	Distance	Frequency	Carrier Radiated Field Strength	Delta Marker	Detector	Calculated Bandedge Field Strength	Duty Cycle Correction	Corrected Bandedge Field Strength	Specified Limit	Specified Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m	MHz	dBuV/m	dB		dBuV/m	dB	dBuV/m	dBuV/m	m	dB	dBuV/m	dB	
WLAN-CH1	H	3	2399.40	90.13	38.52	PK	51.61	0.00	51.61	71.03	3.00	0.00	71.03	19.42	PASS
WLAN-CH1	H	3	2399.77	79.13	38.37	AV	40.76	0.00	40.76	59.68	3.00	0.00	59.68	18.92	PASS
WLAN-CH1	V	3	2399.40	92.73	38.52	PK	54.21	0.00	54.21	74.13	3.00	0.00	74.13	19.92	PASS
WLAN-CH1	V	3	2399.77	81.73	38.37	AV	43.36	0.00	43.36	62.88	3.00	0.00	62.88	19.52	PASS

Formulae:

Calculated Bandedge Field Strength (dBuV/m) = Carrier Radiated Field Strength (dBuV/m) + Delta Marker (dB)

Duty Cycle Correction (dB) = $20 \times \log(\text{time on} / \text{total time})$

Corrected Bandedge Field Strength (dBuV/m) = Calculated Bandedge Field Strength (dBuV/m) + Duty Cycle Correction (dB)

Limit Distance Correction = $20 \times \log(\text{measurement distance} / \text{limit distance})$

Calculated Limit (dBuV/m) = Specified Limit (dBuV/m) + Limit Distance Correction (dB)

Margin (dB) = Corrected Limit (dBuV/m) - Corrected Bandedge Field Strength (dBuV/m)

Note: Measurements and calculation reference the Marker-Delta Method described in FCC Public Notice DA 00-705
Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 25 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9.3. Mode b - Out-of-Band Spurious Emission Field Strengths @ Specified Distance (not within restricted bands)

Channel 1 - Mode b

			Project Number: 060605KBC-T643-E15W		Standard: FCC15.247c												
			Company: Itronix		Test Start Date: 4-Jul-05												
			Product: IX325 with Intel PRO 2200BG		Test End Date: 13-Jul-05												
Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m											MHz	dBuV			
WLAN-CH1	H	3	Horn SN6276	5768.07	33.70		36.61	8.45	-30.96	14.09	47.79	PK*	3.00	0.00	59.68	11.89	PASS
WLAN-CH1	H	3	Horn SN6276	7236.00	33.80	x	38.22	9.72	-30.84	17.10	50.90	PK*	3.00	0.00	59.68	8.77	PASS
WLAN-CH1	H	3	Horn SN6276	9648.00	33.80	x	40.30	12.00	-30.71	21.58	55.38	PK	3.00	0.00	71.03	15.64	PASS
WLAN-CH1	H	3	Horn SN6276	9648.00	22.20	x	40.30	12.00	-30.71	21.58	43.78	AV	3.00	0.00	59.68	15.89	PASS
WLAN-CH1	H	1	Horn SN6276	16891.85	40.86	x	42.76	10.76	-32.06	21.46	62.32	PK*	3.00	9.54	69.22	6.90	PASS
WLAN-CH1	H	1	Waveline_899	21708.00	37.49		40.30	12.52	-35.58	17.25	54.74	PK*	3.00	9.54	69.22	14.48	PASS
WLAN-CH1	V	3	Horn SN6276	4441.43	32.00	x	34.70	7.17	-31.07	10.80	42.80	PK*	3.00	0.00	62.88	20.08	PASS
WLAN-CH1	V	3	Horn SN6276	5255.02	37.30		36.11	8.17	-31.00	13.27	50.57	PK*	3.00	0.00	62.88	12.30	PASS
WLAN-CH1	V	3	Horn SN6276	7236.00	34.10	x	38.22	9.72	-30.84	17.10	51.20	PK*	3.00	0.00	62.88	11.67	PASS
WLAN-CH1	V	3	Horn SN6276	9648.00	33.70	x	40.30	12.00	-30.71	21.58	55.28	PK	3.00	0.00	74.13	18.84	PASS
WLAN-CH1	V	3	Horn SN6276	9648.00	22.30	x	40.30	12.00	-30.71	21.58	43.88	AV	3.00	0.00	62.88	18.99	PASS
WLAN-CH1	V	1	Horn SN6276	14340.75	39.96	x	42.44	9.67	-30.71	21.40	61.36	PK*	3.00	9.54	72.42	11.06	PASS
WLAN-CH1	V	1	Horn SN6276	14460.40	40.07	x	42.56	9.73	-30.77	21.51	61.58	PK*	3.00	9.54	72.42	10.84	PASS
WLAN-CH1	V	1	Horn SN6276	16874.05	39.68	x	42.72	10.75	-32.05	21.42	61.10	PK*	3.00	9.54	72.42	11.32	PASS
WLAN-CH1	V	1	Horn SN6276	17677.60	39.94	x	44.93	11.05	-32.48	23.50	63.44	PK	3.00	9.54	83.67	20.23	PASS
WLAN-CH1	V	1	Horn SN6276	17677.60	34.25	x	44.93	11.05	-32.48	23.50	57.75	AV	3.00	9.54	72.42	14.67	PASS
WLAN-CH1	V	1	Waveline_899	21708.00	36.78		40.30	12.52	-35.58	17.25	54.03	PK*	3.00	9.54	72.42	18.39	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = $40 \cdot \log(d1/d2)$ for $F < 30$ MHz, $20 \cdot \log(d1/d2)$ for $F > 30$ MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 26 of 59

	Test Report Serial No.: 042406KBC-T743-E15W		Report Revision No.: Revision 1.0	
	Test Date(s): 04Jul05 - 20Jul05		Report Issue Date: November 07, 2006	
	Test Standard(s): FCC 47 CFR §15.247		Industry Canada RSS-210 Issue 5	
	Lab Registration(s): FCC Lab Reg. # 714830		Industry Canada Lab File #3874	

Channel 6 - Mode b



Project Number:

060605KBC-T643-E15W

Company:

Itronix

Product:

IX325 with Intel PRO 2200BG

Standard:

FCC15.247c

Test Start Date:

4-Jul-05

Test End Date:

13-Jul-05

Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
							dB/m	dB	dB	dB/m	dBuV/m	(PK/QP/AV)	m	dB	dBuV/m	dB	
WLAN-CH6	H	3	Horn SN6276	3249.32	34.90		32.65	5.96	-31.17	7.44	42.34	PK*	3.00	0.00	59.68	17.33	PASS
WLAN-CH6	H	3	Horn SN6276	5764.06	39.60		36.61	8.41	-30.96	14.06	53.66	PK*	3.00	0.00	59.68	6.02	PASS
WLAN-CH6	H	3	Horn SN6276	9748.00	33.40	x	40.30	12.18	-30.71	21.77	55.17	PK	3.00	0.00	71.03	15.85	PASS
WLAN-CH6	H	3	Horn SN6276	9748.00	22.30	x	40.30	12.18	-30.71	21.77	44.07	AV	3.00	0.00	59.68	15.60	PASS
WLAN-CH6	H	1	Horn SN6276	14185.20	40.24	x	42.29	9.60	-30.63	21.26	61.50	PK*	3.00	9.54	69.22	7.72	PASS
WLAN-CH6	H	1	Horn SN6276	14619.85	40.00	x	42.58	9.80	-30.86	21.52	61.52	PK*	3.00	9.54	69.22	7.70	PASS
WLAN-CH6	H	1	Horn SN6276	17061.05	39.80	x	43.17	10.82	-32.15	21.84	61.64	PK*	3.00	9.54	69.22	7.58	PASS
WLAN-CH6	H	1	Waveline_899	21933.00	38.57	x	40.30	12.61	-35.58	17.33	55.90	PK*	3.00	9.54	69.22	13.32	PASS
WLAN-CH6	V	3	Horn SN6276	3249.00	34.30		32.65	5.96	-31.17	7.44	41.74	PK*	3.00	0.00	62.88	21.13	PASS
WLAN-CH6	V	3	Horn SN6276	5254.32	36.90		36.11	8.17	-31.00	13.27	50.17	PK*	3.00	0.00	62.88	12.71	PASS
WLAN-CH6	V	3	Horn SN6276	5255.78	35.50		36.11	8.18	-31.00	13.28	48.78	PK*	3.00	0.00	62.88	14.09	PASS
WLAN-CH6	V	3	Horn SN6276	9748.00	33.30	x	40.30	12.18	-30.71	21.77	55.07	PK*	3.00	0.00	62.88	7.80	PASS
WLAN-CH6	V	1	Horn SN6276	14108.15	40.63	x	42.21	9.56	-30.59	21.18	61.81	PK*	3.00	9.54	72.42	10.60	PASS
WLAN-CH6	V	1	Horn SN6276	14622.00	38.43	x	42.58	9.80	-30.86	21.52	59.95	PK*	3.00	9.54	72.42	12.47	PASS
WLAN-CH6	V	1	Horn SN6276	17059.00	37.39	x	43.17	10.82	-32.15	21.83	59.22	PK*	3.00	9.54	72.42	13.19	PASS
WLAN-CH6	V	1	Waveline_899	21933.00	39.09	x	40.30	12.61	-35.58	17.33	56.42	PK*	3.00	9.54	72.42	16.00	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = 40*log(d1/d2) for F<30 MHz, 20*log(d1/d2) for F> 30 MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company: Itronix Corporation	Model: IX325A860IWLBT	FCC ID: KBCIX325A860IWLBT	IC ID: 1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna			
			
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.		
			Page 27 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Channel 11 - Mode b



Project Number: 060605KBC-T643-E15W
Company: Itronix
Product: IX325 with Intel PRO 2200BG

Standard: FCC15.247c
Test Start Date: 4-Jul-05
Test End Date: 13-Jul-05

Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m		MHz	dBuV		dB/m	dB	dB	dB/m	dBuV/m	(PK/QP/AV)	m	dB	dBuV/m	dB	
WLAN-CH11	H	3	Horn SN6276	5751.28	35.40		36.60	8.39	-30.96	14.02	49.42	PK*	3.00	0.00	59.68	10.25	PASS
WLAN-CH11	H	3	Horn SN6276	9848.00	33.30	x	40.30	12.42	-30.70	22.02	55.32	PK	3.00	0.00	71.03	15.70	PASS
WLAN-CH11	H	3	Horn SN6276	9848.00	22.40	x	40.30	12.42	-30.70	22.02	44.42	AV	3.00	0.00	59.68	15.25	PASS
WLAN-CH11	H	1	Horn SN6276	14772.00	38.03	x	42.55	9.87	-30.94	21.48	59.51	PK*	3.00	9.54	69.22	9.71	PASS
WLAN-CH11	H	1	Horn SN6276	17234.00	38.38	x	43.66	10.88	-32.24	22.30	60.68	PK*	3.00	9.54	69.22	8.54	PASS
WLAN-CH11	V	3	Horn SN6276	5336.43	30.40	x	36.24	8.47	-31.00	13.71	44.11	PK*	3.00	0.00	62.88	18.76	PASS
WLAN-CH11	V	3	Horn SN6276	9848.00	34.00	x	40.30	12.42	-30.70	22.02	56.02	PK*	3.00	0.00	62.88	6.85	PASS
WLAN-CH11	V	1	Horn SN6276	14772.00	38.32	x	42.55	9.87	-30.94	21.48	59.80	PK*	3.00	9.54	72.42	12.62	PASS
WLAN-CH11	V	1	Horn SN6276	17234.00	38.13	x	43.66	10.88	-32.24	22.30	60.43	PK*	3.00	9.54	72.42	11.99	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = $40 \cdot \log(d1/d2)$ for $F < 30$ MHz, $20 \cdot \log(d1/d2)$ for $F > 30$ MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 28 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9.4. Mode g - Fundamental Field Strengths @ Specified Distance (100 kHz RBW)



Project Numb

060605KBC-T643-E15W

Company:

Itronix

Product:

IX325 with Intel PRO 2200BG

Standard:

FCC15.247a

Test Start Date:

4-Jul-05

Test End Date:

13-Jul-05

IX325 with Intel WLAN Mode g with Setting 20, Tx = 6 Mbps Carrier Field Strengths													
Channel	Polarity	Measurement Distance	Antenna	Frequency	SA Level	Noise Floor	AF	CL	Other	Total CF	Field Strength	Detector	RBW
		m					MHz	dBuV	dB/m	dB	dB		dB/m
WLAN-CH1	H	3	Horn SN6276	2412.00	71.45		30.26	5.10	-23.13	12.23	83.68	PK	100
WLAN-CH1	H	3	Horn SN6276	2412.00	61.50		30.26	5.10	-23.13	12.23	73.73	AV	100
WLAN-CH1	V	3	Horn SN6276	2412.00	69.40		30.26	5.10	-23.13	12.23	81.63	PK	100
WLAN-CH1	V	3	Horn SN6276	2412.00	59.35		30.26	5.10	-23.13	12.23	71.58	AV	100
WLAN-CH6	H	3	Horn SN6276	2437.00	72.55		30.30	5.14	-23.12	12.31	84.86	PK	100
WLAN-CH6	H	3	Horn SN6276	2437.00	62.20		30.30	5.14	-23.12	12.31	74.51	AV	100
WLAN-CH6	V	3	Horn SN6276	2437.00	69.35		30.30	5.14	-23.12	12.31	81.66	PK	100
WLAN-CH6	V	3	Horn SN6276	2437.00	59.55		30.30	5.14	-23.12	12.31	71.86	AV	100
WLAN-CH11	H	3	Horn SN6276	2462.00	73.70		30.34	5.16	-23.12	12.38	86.08	PK	100
WLAN-CH11	H	3	Horn SN6276	2462.00	63.45		30.34	5.16	-23.12	12.38	75.83	AV	100
WLAN-CH11	V	3	Horn SN6276	2462.00	71.20		30.34	5.16	-23.12	12.38	83.58	PK	100
WLAN-CH11	V	3	Horn SN6276	2462.00	61.00		30.34	5.16	-23.12	12.38	73.38	AV	100

Formulae:

Total CF = AF + CL + Other


Field Strength = SA Level + Total CF

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 29 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9.5. Mode g - Lower Band-edge Emission Field Strengths @ Specified Distance

Channel 1 Mode g - Conducted Peak Band-edge Plots



Channel 1 Mode g - Conducted Average Band-edge Plots



Channel 1 g – Calculated Band-edge (Unrestricted) Field Strengths

IX325 with Intel WLAN Mode g with Setting 20, Tx = 6 Mbps

Channel	Polarity	Distance	Frequency	Carrier Radiated Field Strength	Delta Marker	Detector	Calculated Bandedge Field Strength	Duty Cycle Correction	Corrected Bandedge Field Strength	Specified Limit	Specified Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m	MHz	dBuV/m	dB		dBuV/m	dB	dBuV/m	dBuV/m	m	dB	dBuV/m	dB	
WLAN-CH1	H	3	2399.85	83.68	31.69	PK	51.99	0.00	51.99	66.08	3.00	0.00	66.08	14.09	PASS
WLAN-CH1	H	3	2400.00	73.73	32.44	AV	41.29	0.00	41.29	55.83	3.00	0.00	55.83	14.54	PASS
WLAN-CH1	V	3	2399.85	81.63	31.69	PK	49.94	0.00	49.94	63.58	3.00	0.00	63.58	13.64	PASS
WLAN-CH1	V	3	2400.00	71.58	32.44	AV	39.14	0.00	39.14	53.38	3.00	0.00	53.38	14.24	PASS

Formulae:

Calculated Bandedge Field Strength (dBuV/m) = Carrier Radiated Field Strength (dBuV/m) + Delta Marker (dB)

Duty Cycle Correction (dB) = 20 * log (time on / total time)

Corrected Bandedge Field Strength (dBuV/m) = Calculated Bandedge Field Strength (dBuV/m) + Duty Cycle Correction (dB)

Limit Distance Correction = 20 * log (measurement distance / limit distance)

Calculated Limit (dBuV/m) = Specified Limit (dBuV/m) + Limit Distance Correction (dB)

Margin (dB) = Corrected Limit (dBuV/m) – Corrected Bandedge Field Strength (dBuV/m)

Note: Measurements and calculation reference the Marker-Delta Method described in FCC Public Notice DA 00-705

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 30 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.9.6. Mode g - Out-of-Band Spurious Emission Field Strengths @ Specified Distance (not within restricted bands)

Channel 1 - Mode g

			Project Number:		060605KBC-T643-E15W		Standard:		FCC15.209								
			Company:		Itronix		Test Start Date:		4-Jul-05								
			Product:		IX325 with Intel PRO 2200BG		Test End Date:		13-Jul-05								
Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m															
WLAN-CH1	H	3	Horn SN6276	5763.87	33.40		36.61	8.41	-30.96	14.06	47.46	PK*	3.00	0.00	53.98	6.52	PASS
WLAN-CH1	H	3	Horn SN6276	7236.00	33.80	x	38.22	9.72	-30.84	17.10	50.90	PK*	3.00	0.00	53.98	3.08	PASS
WLAN-CH1	H	3	Horn SN6276	9648.00	33.00	x	40.30	12.00	-30.71	21.58	54.58	PK	3.00	0.00	73.98	19.40	PASS
WLAN-CH1	H	3	Horn SN6276	9648.00	22.00	x	40.30	12.00	-30.71	21.58	43.58	AV	3.00	0.00	53.98	10.40	PASS
WLAN-CH1	H	1	Horn SN6276	14139.50	39.67	x	42.24	9.58	-30.60	21.21	60.88	PK*	3.00	9.54	63.52	2.64	PASS
WLAN-CH1	H	1	Horn SN6276	16884.00	40.07	x	42.74	10.76	-32.06	21.44	61.51	PK*	3.00	9.54	63.52	2.01	PASS
WLAN-CH1	H	1	Waveline 899	21708.00	38.08	x	40.30	12.52	-35.58	17.25	55.33	PK*	3.00	9.54	63.52	8.20	PASS
WLAN-CH1	V	3	Horn SN6276	5786.75	30.10	x	36.61	8.53	-30.96	14.18	44.28	PK*	3.00	0.00	53.98	9.70	PASS
WLAN-CH1	V	3	Horn SN6276	7236.00	34.20	x	38.22	9.72	-30.84	17.10	51.30	PK*	3.00	0.00	53.98	2.68	PASS
WLAN-CH1	V	3	Horn SN6276	9648.00	33.60	x	40.30	12.00	-30.71	21.58	55.18	PK	3.00	0.00	73.98	18.80	PASS
WLAN-CH1	V	3	Horn SN6276	9648.00	22.30	x	40.30	12.00	-30.71	21.58	43.88	AV	3.00	0.00	53.98	10.10	PASS
WLAN-CH1	V	1	Horn SN6276	14402.80	40.17	x	42.50	9.70	-30.74	21.46	61.63	PK*	3.00	9.54	63.52	1.89	PASS
WLAN-CH1	V	1	Horn SN6276	16884.00	37.81	x	42.74	10.76	-32.06	21.44	59.25	PK*	3.00	9.54	63.52	4.27	PASS
WLAN-CH1	V	1	Waveline 899	21708.00	38.59	x	40.30	12.52	-35.58	17.25	55.84	PK*	3.00	9.54	63.52	7.69	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = $40 \cdot \log(d1/d2)$ for $F < 30$ MHz, $20 \cdot \log(d1/d2)$ for $F > 30$ MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 31 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Channel 6 - Mode g

		Project Number:		060605KBC-T643-E15W				Standard:		FCC15.209							
		Company:		Itronix				Test Start Date:		4-Jul-05							
		Product:		IX325 with Intel PRO 2200BG				Test End Date:		13-Jul-05							
Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
			m	MHz	dBuV		dB/m	dB	dB	dB/m	dBuV/m	(PK/QP/AV)	m	dB	dBuV/m	dB	
WLAN-CH6	H	3	Horn SN6276	5766.72	36.30		36.61	8.43	-30.96	14.08	50.38	PK*	3.00	0.00	53.98	3.60	PASS
WLAN-CH6	H	3	Horn SN6276	9748.00	33.50	x	40.30	12.18	-30.71	21.77	55.27	PK	3.00	0.00	73.98	18.71	PASS
WLAN-CH6	H	3	Horn SN6276	9748.00	22.10	x	40.30	12.18	-30.71	21.77	43.87	AV	3.00	0.00	53.98	10.11	PASS
WLAN-CH6	H	1	Horn SN6276	14622.00	37.80	x	42.58	9.80	-30.86	21.52	59.32	PK*	3.00	9.54	63.52	4.21	PASS
WLAN-CH6	H	1	Horn SN6276	15037.35	39.56	x	42.37	9.99	-31.08	21.28	60.84	PK*	3.00	9.54	63.52	2.68	PASS
WLAN-CH6	H	1	Horn SN6276	17059.00	39.75	x	43.17	10.82	-32.15	21.83	61.58	PK	3.00	9.54	83.52	21.94	PASS
WLAN-CH6	H	1	Waveline 899	21933.00	38.48		40.30	12.61	-35.58	17.33	55.81	PK*	3.00	9.54	63.52	7.71	PASS
WLAN-CH6	V	3	Horn SN6276	3254.00	31.30	x	32.66	5.97	-31.17	7.46	38.76	PK*	3.00	0.00	53.98	15.22	PASS
WLAN-CH6	V	3	Horn SN6276	9748.00	34.90	x	40.30	12.18	-30.71	21.77	56.67	PK	3.00	0.00	73.98	17.31	PASS
WLAN-CH6	V	3	Horn SN6276	9748.00	22.50	x	40.30	12.18	-30.71	21.77	44.27	AV	3.00	0.00	53.98	9.71	PASS
WLAN-CH6	V	1	Horn SN6276	14622.00	37.23	x	42.58	9.80	-30.86	21.52	58.75	PK*	3.00	9.54	63.52	4.78	PASS
WLAN-CH6	V	1	Horn SN6276	17059.00	36.81	x	43.17	10.82	-32.15	21.83	58.64	PK*	3.00	9.54	63.52	4.88	PASS
WLAN-CH6	V	1	Waveline 899	21933.00	37.75		40.30	12.61	-35.58	17.33	55.08	PK*	3.00	9.54	63.52	8.44	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = $40 \cdot \log(d1/d2)$ for $F < 30$ MHz, $20 \cdot \log(d1/d2)$ for $F > 30$ MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 32 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Channel 11 - Mode g



Project Number:

Company:

Product:

060605KBC-T643-E15W

Itronix

IX325 with Intel PRO 2200BG

Standard:

Test Start Date:

Test End Date:

FCC15.209

4-Jul-05

13-Jul-05

Channel	Polarity	Distance	Rx Antenna	Frequency	SA Level	Noise Floor	Rx AF	Rx CL	Other Rx	Total Rx CF	Field Strength	Detector	Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m											MHz	dBuV			
WLAN-CH11	H	3	Horn SN6276	2524.31	34.10	x	30.48	5.24	-23.12	12.60	46.70	PK*	3.00	0.00	53.98	7.28	PASS
WLAN-CH11	H	3	Horn SN6276	5750.93	33.20		36.60	8.39	-30.96	14.02	47.22	PK*	3.00	0.00	53.98	6.76	PASS
WLAN-CH11	H	3	Horn SN6276	9848.00	34.00	x	40.30	12.42	-30.70	22.02	56.02	PK	3.00	0.00	73.98	17.96	PASS
WLAN-CH11	H	3	Horn SN6276	9848.00	22.30	x	40.30	12.42	-30.70	22.02	44.32	AV	3.00	0.00	53.98	9.66	PASS
WLAN-CH11	H	1	Horn SN6276	14317.05	38.98	x	42.42	9.66	-30.70	21.38	60.36	PK*	3.00	9.54	63.52	3.16	PASS
WLAN-CH11	H	1	Horn SN6276	14772.00	37.03	x	42.55	9.87	-30.94	21.48	58.51	PK*	3.00	9.54	63.52	5.02	PASS
WLAN-CH11	H	1	Horn SN6276	17234.00	36.84	x	43.66	10.88	-32.24	22.30	59.14	PK*	3.00	9.54	63.52	4.39	PASS
WLAN-CH11	V	3	Horn SN6276	8993.84	35.90	x	40.19	10.96	-30.74	20.41	56.31	PK	3.00	0.00	73.98	17.67	PASS
WLAN-CH11	V	3	Horn SN6276	8993.84	22.00	x	40.19	10.96	-30.74	20.41	42.41	AV	3.00	0.00	53.98	11.57	PASS
WLAN-CH11	V	3	Horn SN6276	9848.00	35.50	x	40.30	12.42	-30.70	22.02	57.52	PK	3.00	0.00	73.98	16.46	PASS
WLAN-CH11	V	3	Horn SN6276	9848.00	22.70	x	40.30	12.42	-30.70	22.02	44.72	AV	3.00	0.00	53.98	9.26	PASS
WLAN-CH11	V	1	Horn SN6276	14772.00	36.79	x	42.55	9.87	-30.94	21.48	58.27	PK*	3.00	9.54	63.52	5.26	PASS
WLAN-CH11	V	1	Horn SN6276	17234.00	37.45	x	43.66	10.88	-32.24	22.30	59.75	PK*	3.00	9.54	63.52	3.78	PASS

Notes:

*PK denotes QP or Average limits applied to emissions measured with a peak detector

BOLD signifies the highest signal measured near a carrier harmonic frequency

No EUT emissions levels were measured above those reported

Formulae:

Total CF = Antenna Factor + Cable Factor + Other Factor (Amplifier Gain, filter loss, etc)

Field Strength = SA Reading + Total CF

Limit Distance Correction = 40*log(d1/d2) for F<30 MHz, 20*log(d1/d2) for F> 30 MHz:

where d1 is the measurement distance, d2 is the published limit distance

Limit = Specified Limit + Limit Distance Correction

Margin = Limit - Field Strength

Limit based on highest radiated carrier

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 33 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

D.10. PASS/FAIL

In reference to the results outlined in E.9, the DUT passes the requirements as stated in the reference standards as follows:

FCC 15.247 (c): All emissions within any 100 kHz bandwidth outside the operating frequency band are greater than 20 dB below the maximum 100 kHz bandwidth signal within the operating band.

D.11. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.

13Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 34 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix E - Restricted Band Emissions Measurement

E.1. REFERENCES

Normative Reference Standard	FCC CFR 47 §15.205 (a) (b), FCC CFR 47 §15.209 (a)
Procedure Reference	FCC 97-114

E.2. LIMITS

FCC CFR 47 §15.205	(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:																																																																											
	<table><tr><th>MHz</th><th>MHz</th><th>MHz</th><th>GHz</th></tr><tr><td>0.090–0.110</td><td>16.42–16.423</td><td>399.9–410</td><td>4.5–5.15</td></tr><tr><td>10.495–0.505</td><td>16.69475–16.69525</td><td>608–614</td><td>5.35–5.46</td></tr><tr><td>2.1735–2.1905</td><td>16.80425–16.80475</td><td>960–1240</td><td>7.25–7.75</td></tr><tr><td>4.125–4.128</td><td>25.5–25.67</td><td>1300–1427</td><td>8.025–8.5</td></tr><tr><td>4.17725–4.17775</td><td>37.5–38.25</td><td>1435–1626.5</td><td>9.0–9.2</td></tr><tr><td>4.20725–4.20775</td><td>73–74.6</td><td>1645.5–1646.5</td><td>9.3–9.5</td></tr><tr><td>6.215–6.218</td><td>74.8–75.2</td><td>1660–1710</td><td>10.6–12.7</td></tr><tr><td>6.26775–6.26825</td><td>108–121.94</td><td>1718.8–1722.2</td><td>13.25–13.4</td></tr><tr><td>6.31175–6.31225</td><td>123–138</td><td>2200–2300</td><td>14.47–14.5</td></tr><tr><td>8.291–8.294</td><td>149.9–150.05</td><td>2310–2390</td><td>15.35–16.2</td></tr><tr><td>8.362–8.366</td><td>156.52475–156.52525</td><td>2483.5–2500</td><td>17.7–21.4</td></tr><tr><td>8.37625–8.38675</td><td>156.7–156.9</td><td>2655–2900</td><td>22.01–23.12</td></tr><tr><td>8.41425–8.41475</td><td>162.0125–167.17</td><td>3260–3267</td><td>23.6–24.0</td></tr><tr><td>12.29–12.293</td><td>167.72–173.2</td><td>3332–3339</td><td>31.2–31.8</td></tr><tr><td>12.51975–12.52025</td><td>240–285</td><td>3345.8–3358</td><td>36.43–36.5</td></tr><tr><td>12.57675–12.57725</td><td>322–335.4</td><td>3600–4400</td><td>(²)</td></tr><tr><td>13.36–13.41</td><td></td><td></td><td></td></tr></table>	MHz	MHz	MHz	GHz	0.090–0.110	16.42–16.423	399.9–410	4.5–5.15	10.495–0.505	16.69475–16.69525	608–614	5.35–5.46	2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75	4.125–4.128	25.5–25.67	1300–1427	8.025–8.5	4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2	4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5	6.215–6.218	74.8–75.2	1660–1710	10.6–12.7	6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4	6.31175–6.31225	123–138	2200–2300	14.47–14.5	8.291–8.294	149.9–150.05	2310–2390	15.35–16.2	8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4	8.37625–8.38675	156.7–156.9	2655–2900	22.01–23.12	8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0	12.29–12.293	167.72–173.2	3332–3339	31.2–31.8	12.51975–12.52025	240–285	3345.8–3358	36.43–36.5	12.57675–12.57725	322–335.4	3600–4400	(²)	13.36–13.41						
MHz	MHz	MHz	GHz																																																																									
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15																																																																									
10.495–0.505	16.69475–16.69525	608–614	5.35–5.46																																																																									
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75																																																																									
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5																																																																									
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2																																																																									
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5																																																																									
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7																																																																									
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4																																																																									
6.31175–6.31225	123–138	2200–2300	14.47–14.5																																																																									
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2																																																																									
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4																																																																									
8.37625–8.38675	156.7–156.9	2655–2900	22.01–23.12																																																																									
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0																																																																									
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8																																																																									
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5																																																																									
12.57675–12.57725	322–335.4	3600–4400	(²)																																																																									
13.36–13.41																																																																												
	¹ Until February 1, 1999, this restricted band shall be 0.490–0.510 MHz. ² Above 38.6																																																																											
	(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions of 15.35 apply to these measurements.																																																																											
FCC CFR 47 §15.209	(a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:																																																																											
	<table><tr><th>Frequency</th><th colspan="2">Field Strength</th><th>Measurement Distance</th></tr><tr><th>MHz</th><th>uV/m</th><th>dBuV/m</th><th>Meters</th></tr><tr><td>.009 – 0.490</td><td>2400/F(kHz)</td><td>48.52 – 13.80</td><td>300</td></tr><tr><td>0.490 – 1.705</td><td>24000/F(kHz)</td><td>33.80 – 22.97</td><td>30</td></tr><tr><td>1.705 – 30.0</td><td>30</td><td>29.54</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td><td>40.00</td><td>3</td></tr><tr><td>88 – 216</td><td>150</td><td>43.52</td><td>3</td></tr><tr><td>216 – 960</td><td>200</td><td>46.02</td><td>3</td></tr><tr><td>Above 960</td><td>500</td><td>53.98</td><td>3</td></tr></table>	Frequency	Field Strength		Measurement Distance	MHz	uV/m	dBuV/m	Meters	.009 – 0.490	2400/F(kHz)	48.52 – 13.80	300	0.490 – 1.705	24000/F(kHz)	33.80 – 22.97	30	1.705 – 30.0	30	29.54	30	30 – 88	100	40.00	3	88 – 216	150	43.52	3	216 – 960	200	46.02	3	Above 960	500	53.98	3																																							
Frequency	Field Strength		Measurement Distance																																																																									
MHz	uV/m	dBuV/m	Meters																																																																									
.009 – 0.490	2400/F(kHz)	48.52 – 13.80	300																																																																									
0.490 – 1.705	24000/F(kHz)	33.80 – 22.97	30																																																																									
1.705 – 30.0	30	29.54	30																																																																									
30 – 88	100	40.00	3																																																																									
88 – 216	150	43.52	3																																																																									
216 – 960	200	46.02	3																																																																									
Above 960	500	53.98	3																																																																									
	(b) In the emission table above, the tighter limit applies at the band edges.																																																																											

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 35 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.3. ENVIRONMENTAL CONDITIONS

Temperature	274 +/- 2 °C
Humidity	33 +/- 2 %
Barometric Pressure	96 +/- 0.2 kPa

E.4. EQUIPMENT LIST

RECEIVING EQUIPMENT						
ID	ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
1	00072	EMCO	2075	Mini-mast	na	na
2	00073	EMCO	2080	Turn Table	na	na
3	00071	EMCO	2090	Multi-Device Controller	na	na
4	00085	EMCO	6502	Loop Antenna	10Aug04	10Aug05
5	00050	Chase	CBL-6111A	Bilog Antenna	08Feb05	08Feb06
6	00035	ETS	3115	Double Ridged Guide Horn	24Mar04	24Mar06
7	00161/00166	Waveline	899/801-KF	Standard Gain Horn	na	na
8	00051	HP	8566B	Spectrum Analyzer RF Section	12Apr05	12Apr06
9	00049	HP	85650A	Quasi-Peak Adapter	13Apr05	13Apr06
10	00047	HP	85685A	RF Preselector	13Apr05	13Apr06
11	00015	Agilent	4408B	Spectrum Analyzer	24Jan05	24Jan06
12	00115	Miteq	J54-00102600-35-5A	LNA	08Jun04	08Jun06
13	00093	Microtronics	HPM50111	High Pass Filter	8Jun04	8Dec05
14	00119	INMAT	18AH-10	10dB attenuator	8Jun04	8Dec05
15	00120	Celltech	n/a	Microwave Cable (RX)	25Mar05	25Mar06
16	00121	Andrew	FSJ4-50B	Microwave Cable (RX)	25Mar05	25Mar06
17	00130	Andrew	FSJ1-50A	Microwave Cable (RX)	25Mar05	25Mar06

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 36 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.5. MEASUREMENT EQUIPMENT SETUP

MEASUREMENT EQUIPMENT CONNECTIONS	The measurement equipment was connected as shown in the F.6. A number of antennas were used to cover the applicable frequency range test. The ranges in which each antenna was used are as follows:			
	Frequency Range	Spectrum Analyzer Asset #	LNA/Filter/Attenuator Asset #	Antenna Asset #
	10kHz - 30 MHz	00051/00049/00047	none	00085
	30 MHz – 1 GHz	00051/00049/00047	none	00050
	1 GHz – 2 GHz	00051/00047	00119/00115	00035
	1 GHz – 18 GHz	00051	00093/00115	00035
	18 GHz – 22 GHz	00051	00093/00115	00161/00166
	22 GHz – 26 GHz	00015	00093/00115	00161/00166
MEASUREMENT EQUIPMENT SETTINGS	The spectrum analyzer was set to the following settings:			
	Frequency Range	RBW	VBW	Detector
	MHz	kHz	kHz	
	0.009 – 0.150	0.200	10	Peak*
	0.150 – 30	9	30	Peak*
	30 – 1000	100	300	Peak*
	> 1000	1000*	1000	Peak*
	*As a worst-case measurement, the average/QP limit was applied to measurements made with a peak detector, unless otherwise noted.			

E.6. SETUP DRAWING

Figure E.6-1 - Setup Drawing



Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 37 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.7. SETUP PHOTOGRAPHS

Photograph E-1 - Loop Antenna (10kHz - 30 MHz) @ 3m



Photograph E-2 - Bilog Antenna (30 MHz - 1 GHz) @ 3m



Photograph E-3 - 3115 Horn (1G - 2G) @ 3 m



Photograph E-4 - 3115 Horn with LNA/Filter @ 1m



Photograph E-5 - Waveline Horn with LNA @ 1m



Left Intentionally Blank

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 38 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	


E.8. DUT OPERATING DESCRIPTION

The worst-case data rate was determined from prescan investigations. Measurements were made at three channels throughout the band, Low Channel (2412 MHz), Mid Channel (2437 MHz), High Channel (2462 MHz) and both Modes b and g.


E.9. TEST RESULTS

E.9.1. Mode b - Lower Band-edge Emission Field Strengths @ Specified Distance

Channel 1 Mode b - Conducted Peak Band-edge Plots



Channel 1 Mode b - Conducted Average Band-edge Plots



Channel 1 b - Calculated Band-edge (Restricted) Field Strengths

IX325 with Intel WLAN Mode b with Setting 27.0, Tx = 1 Mbps

Channel	Polarity	Distance	Frequency	Carrier Radiated Field Strength	Delta Marker	Detector	Calculated Bandedge Field Strength	Duty Cycle Correction	Corrected Bandedge Field Strength	Specified Limit	Specified Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m	MHz	dBuV/m	dB		dBuV/m	dB	dBuV/m	dBuV/m	m	dB	dBuV/m	dB	
WLAN-CH1	H	3	2385.30	93.33	54.15	PK	39.18	0.00	39.18	73.98	3.00	0.00	73.98	34.80	PASS
WLAN-CH1	H	3	2385.15	89.13	54.11	AV	35.02	0.00	35.02	53.98	3.00	0.00	53.98	18.96	PASS
WLAN-CH1	V	3	2385.30	96.03	54.15	PK	41.88	0.00	41.88	73.98	3.00	0.00	73.98	32.10	PASS
WLAN-CH1	V	3	2385.15	91.53	54.11	AV	37.42	0.00	37.42	53.98	3.00	0.00	53.98	16.56	PASS

Formulae:

Calculated Bandedge Field Strength (dBuV/m) = Carrier Radiated Field Strength (dBuV/m) + Delta Marker (dB)

Duty Cycle Correction (dB) = 20 * log (time on / total time)

Corrected Bandedge Field Strength (dBuV/m) = Calculated Bandedge Field Strength (dBuV/m) + Duty Cycle Correction (dB)

Limit Distance Correction = 20 * log (measurement distance / limit distance)

Calculated Limit (dBuV/m) = Specified Limit (dBuV/m) + Limit Distance Correction (dB)

Margin (dB) = Corrected Limit (dBuV/m) - Corrected Bandedge Field Strength (dBuV/m)


Note: Measurements and calculation reference the Marker-Delta Method described in FCC Public Notice DA 00-705

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 39 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.9.2. Mode b - Upper Band-edge Emission Field Strengths @ Specified Distance

Channel 11 Mode b - Conducted Peak Band-edge Plots



Channel 11 Mode b - Conducted Average Band-edge Plots



Channel 11 b - Calculated Band-edge (Restricted) Field Strengths

IX325 with Intel WLAN Mode b with Setting 27.0, Tx = 1 Mbps

Channel	Polarity	Distance	Frequency	Carrier Radiated Field Strength	Delta Marker	Detector	Calculated Bandedge Field Strength	Duty Cycle Correction	Corrected Bandedge Field Strength	Specified Limit	Specified Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m	MHz	dBuV/m	dB		dBuV/m	dB	dBuV/m	dBuV/m	m	dB	dBuV/m	dB	
WLAN-CH11	H	3	2486.70	93.98	51.36	PK	42.62	0.00	42.62	73.98	3.00	0.00	73.98	31.36	PASS
WLAN-CH11	H	3	2487.97	89.73	48.87	AV	40.86	0.00	40.86	53.98	3.00	0.00	53.98	13.12	PASS
WLAN-CH11	V	3	2486.70	97.58	51.36	PK	46.22	0.00	46.22	73.98	3.00	0.00	73.98	27.76	PASS
WLAN-CH11	V	3	2487.97	93.13	48.87	AV	44.26	0.00	44.26	53.98	3.00	0.00	53.98	9.72	PASS

Formulae:

Calculated Bandedge Field Strength (dBuV/m) = Carrier Radiated Field Strength (dBuV/m) + Delta Marker (dB)

Duty Cycle Correction (dB) = $20 \cdot \log(\text{time on} / \text{total time})$

Corrected Bandedge Field Strength (dBuV/m) = Calculated Bandedge Field Strength (dBuV/m) + Duty Cycle Correction (dB)

Limit Distance Correction = $20 \cdot \log(\text{measurement distance} / \text{limit distance})$

Calculated Limit (dBuV/m) = Specified Limit (dBuV/m) + Limit Distance Correction (dB)

Margin (dB) = Corrected Limit (dBuV/m) - Corrected Bandedge Field Strength (dBuV/m)

Note: Measurements and calculation reference the Marker-Delta Method described in FCC Public Notice DA 00-705

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 40 of 59

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Antenna PIFA Antenna							 A GENERAL DYNAMIC'S COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 41 of 59


Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 42 of 59

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green External PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 43 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.9.7. Mode g - Upper Band-edge Emission Field Strengths @ Specified Distance

Channel 11 Mode g - Conducted Peak Band-edge Plots



Channel 11 Mode g - Conducted Average Band-edge Plots



Channel 11 g - Calculated Band-edge (Restricted) Field Strengths

IX325 with Intel WLAN Mode g with Setting 20, Tx = 6 Mbps															
Channel	Polarity	Distance	Frequency	Carrier Radiated Field Strength	Delta Marker	Detector	Calculated Bandedge Field Strength	Duty Cycle Correction	Corrected Bandedge Field Strength	Specified Limit	Specified Limit Distance	Limit Distance Correction	Calculated Limit	Margin	Pass/Fail
		m	MHz	dBuV/m	dB		dBuV/m	dB	dBuV/m	dBuV/m	m	dB	dBuV/m	dB	
WLAN-CH11	H	3	2486.70	95.18	42.72	PK	52.46	0.00	52.46	73.98	3.00	0.00	73.98	21.52	PASS
WLAN-CH11	H	3	2486.62	82.53	40.56	AV	41.97	0.00	41.97	53.98	3.00	0.00	53.98	12.01	PASS
WLAN-CH11	V	3	2486.70	92.98	42.72	PK	50.26	0.00	50.26	73.98	3.00	0.00	73.98	23.72	PASS
WLAN-CH11	V	3	2486.62	80.43	40.56	AV	39.87	0.00	39.87	53.98	3.00	0.00	53.98	14.11	PASS

Formulae:

Calculated Bandedge Field Strength (dBuV/m) = Carrier Radiated Field Strength (dBuV/m) + Delta Marker (dB)

Duty Cycle Correction (dB) = 20 * log (time on / total time)

Corrected Bandedge Field Strength (dBuV/m) = Calculated Bandedge Field Strength (dBuV/m) + Duty Cycle Correction (dB)

Limit Distance Correction = 20 * log (measurement distance / limit distance)

Calculated Limit (dBuV/m) = Specified Limit (dBuV/m) + Limit Distance Correction (dB)

Margin (dB) = Corrected Limit (dBuV/m) - Corrected Bandedge Field Strength (dBuV/m)

Note: Measurements and calculation reference the Marker-Delta Method described in FCC Public Notice DA 00-705

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 45 of 59

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 46 of 59

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 47 of 59

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 48 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

E.10. PASS/FAIL

In reference to the results outlined in F.9, the DUT passes the requirements as stated in the reference standards as follows:

FCC 15.205 (a) (b) and 15.209 (a): No emissions were measured within the restricted bands as outlined in 15.205 that exceeded the limits stated in 15.209.

E.11. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.

13Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 49 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix F - Peak Power Spectral Density Measurement

F.1. REFERENCES

Normative Reference Standard	FCC CFR 47 §15.247(d)
Procedure Reference	FCC Bulletin KDB Publication No 558074

F.2. LIMITS

F.2.1. FCC CFR

§15.247(d): For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission.

F.3. ENVIRONMENTAL CONDITIONS

Temperature	25 +/- 2 °C
Humidity	35 +/- 2 %
Barometric Pressure	96 kPa

F.4. EQUIPMENT LIST

ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
00015	Agilent	E4408B	Spectrum Analyzer	24Jan05	24Jan06
00075	Alpha Wire-J	9223	1ft. RG223/U RF Cable	na*	na
00076	Pasternack	PE7014-30	30dB 2 Watt Attenuator	na*	na

*Cable and attenuator verified with power meter prior to use

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 50 of 59


	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

F.5. MEASUREMENT EQUIPMENT SETUP

Measurement Equipment Connections	The equipment was connected as shown in the setup drawing in G.6.
Measurement Equipment Settings	To evaluate the occupied bandwidth, software and a PC controller were used to set the spectrum analyzer using the following setting: RBW – 3 kHz VBW – 30 kHz Detector – Sample Average – Power Trace Average – 100 Offset – appropriate for external attenuation (-31.4 dB)
Measurement Procedure	The power spectral density measurement was performed using the PSD Option 2 method described in the FCC document KDB Publication No. 558074.

F.6. SETUP DRAWING

Figure F.6-1 - Setup Drawing



Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 51 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

F.7. TEST RESULTS

Channel	802.11b			802.11g		
	Frequency (GHz)	PPSD (dBm)	Data Rate Mb/s	Frequency (GHz)	PPSD (dBm)	Data Rate Mb/s
Low	2.412	-11.97	1	2.412	-18.35	6
Mid	2.437	-10.54	1	2.437	-18.02	6
High	2.462	-11.37	1	2.462	-17.06	6

F.8. PASS/FAIL

In reference to the results outlined in G.5, the DUT passes the requirements as stated in the reference standards as follows:

FCC 15.247 (d): The peak power spectral density did not exceed +8 dBm in any 3 kHz band.

F.9. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Alex Yuan
EMC Technologist
Celltech Labs Inc.

17Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 52 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

Appendix G - Conducted Powerline Emissions Measurement

G.1. REFERENCES

Normative Reference Standard	CFR 47 FCC Part 15 §15.207
Procedure Reference	ANSI C63.4

G.2. LIMITS

§15.207: Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each powerline and ground at the power terminal.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.50 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases logarithmically with frequency.

G.3. ENVIRONMENTAL CONDITIONS

Temperature	+26 ± 5 °C
Humidity	31 % ± 10% RH
Barometric Pressure	101.4 kpa

G.4. EQUIPMENT LIST

ASSET NUMBER	MANUFACTURER	MODEL	DESCRIPTION	LAST CAL	CAL DUE
00049	HP	85650A	Quasi-Peak Adapter	13Apr05	13Apr06
00047	HP	85685A	RF Preselector	13Apr05	13Apr06
00051	HP	8566B	Spectrum Analyzer RF Section	12Apr05	12Apr06
00083	EMCO	3825/2	Line Impedance Stabilization Network	26Apr05	26Apr06
00084	EMCO	3825/2	Line Impedance Stabilization Network	26Apr05	26Apr06

G.5. MEASUREMENT EQUIPMENT SETUP


MEASUREMENT EQUIPMENT CONNECTIONS	The conducted emissions were measured on each of the two AC powerline leads connected to the DUT's power supply brick. A two line LISN was used to make this measurement. A drawing of the equipment setup is shown in H.7
MEASUREMENT EQUIPMENT SETTINGS	Each of the monitor ports from the 2-line LISN was connected in turn to the spectrum analyzer. The port not connected to the analyzer was terminated in a 50-ohm load. A prescan of the peak emission levels was made of the 150 kHz – 30 MHz range split into 4 equal frequency bands. The following were the spectrum analyzer settings: Start Frequency and Stop Frequency set by software for each of the four bands RBW: 100 kHz VBW: 300 kHz Sweep: 500 mS The resulting data from each band was corrected and collected by software and presented in the graphical representations shown in H.9 for the two leads. The frequency points with the highest 10 levels on each lead were used by software to optimize a set of 20 readings for each type of detector (peak, quasi-peak and average). This data was corrected by the software is presented in the tables shown in section H.9.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 53 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

G.6. SETUP DRAWING

Figure G.6-1 - Setup Drawing




Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 54 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

G.7. SETUP PHOTOS

Photograph G-1 - AC Powerline Conducted Emission Cable Placement



Photograph G-2 - AC Powerline Conducted Emission Configuration



G.8. DUT OPERATING DESCRIPTION


WLAN:	The WLAN was set to transmit at full power on Channel 1, Mode b 1 Mb/s
PC:	Other than operating the WLAN software and running MS windows, no PC exercising was performed.
Peripherals:	All peripherals were active, but no specific traffic was initiated.

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 55 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

G.9. TEST RESULTS

G.9.1. Line 1 Conducted Emissions



Project Number: 060605KBC-T643-E15W
Company: Itronix
Product: IX325 with INTEL PRO2200BG WLAN

Standard: FCC 15.207
Test Start Date: 20-Jul-05
Test End Date: 20-Jul-05

Line 1 Conducted Emissions												
Frequency MHz	Uncorrected Reading			Correction Factor dB	Corrected Emission Level			Quasi-Peak Limit dBuV	Quasi-Peak Margin dB	Average Limit dBuV	Average Margin dB	Pass/Fail
	Peak dBuV	Quasi-Peak dBuV	Average dBuV		Peak dBuV	Quasi-Peak dBuV	Average dBuV					
0.151	64.20	55.89	32.34	-2.13	62.07	53.76	30.21	65.96	12.20	55.96	25.75	Pass
0.165	63.20	52.62	27.98	-1.88	61.32	50.74	26.10	65.19	14.45	55.19	29.09	Pass
0.201	58.50	48.70	28.60	-1.43	57.07	47.27	27.17	63.59	16.31	53.59	26.41	Pass
0.210	58.10	47.70	21.27	-1.34	56.76	46.36	19.93	63.22	16.86	53.22	33.29	Pass
0.239	55.10	44.81	19.03	-1.12	53.98	43.69	17.91	62.15	18.46	52.15	34.24	Pass
0.247	54.00	42.69	19.23	-1.07	52.93	41.62	18.16	61.85	20.23	51.85	33.69	Pass
0.255	52.30	42.32	16.90	-1.02	51.28	41.30	15.88	61.58	20.28	51.58	35.70	Pass
0.261	52.80	41.93	17.17	-0.98	51.82	40.95	16.19	61.39	20.44	51.39	35.20	Pass
0.274	51.20	41.79	18.52	-0.93	50.27	40.86	17.59	60.99	20.12	50.99	33.40	Pass
0.406	45.80	40.18	38.22	-0.58	45.22	39.60	37.64	57.72	18.12	47.72	10.08	Pass
3.443	41.70	39.99	38.40	-0.30	41.40	39.69	38.10	56.00	16.31	46.00	7.90	Pass
3.579	42.40	39.93	38.72	-0.31	42.10	39.63	38.41	56.00	16.38	46.00	7.59	Pass
4.992	34.60	30.32	27.34	-0.31	34.29	30.01	27.03	56.00	25.99	46.00	18.97	Pass
24.000	35.00	33.39	31.98	-0.45	34.55	32.94	31.53	60.00	27.06	50.00	18.47	Pass

Corrected Emission Level (dBuV) = Uncorrected Reading (dBuV) + Correction Factor (dB)
Margin (dB) = Limit (dBuV) - Corrected Emission Level (dBuV)


Calculations

CF = Correction Factor
Emission Level = Measured Level + correction factor
Margin = Limit - Emission Level

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 56 of 59

	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

G.9.2. Line 2 Conducted Emissions



Project Number: 060605KBC-T643-E15W
Company: Itronix
Product: IX325 with INTEL PRO2200BG WLAN

Standard: FCC 15.207
Test Start Date: 20-Jul-05
Test End Date: 20-Jul-05

Line 2 Conducted Emissions

Frequency MHz	Uncorrected Reading			Correction Factor dB	Corrected Emission Level			Quasi-Peak Limit dBuV	Quasi-Peak Margin dB	Average Limit dBuV	Average Margin dB	Pass/Fail
	Peak dBuV	Quasi-Peak dBuV	Average dBuV		Peak dBuV	Quasi-Peak dBuV	Average dBuV					
0.150	64.80	55.57	33.03	-2.14	62.66	53.43	30.88	65.98	12.55	55.98	25.10	Pass
0.165	63.20	54.10	29.12	-1.88	61.32	52.22	27.23	65.18	12.97	55.18	27.95	Pass
0.172	61.70	53.85	27.48	-1.79	59.91	52.06	25.69	64.88	12.81	54.88	29.18	Pass
0.181	61.60	51.27	24.59	-1.67	59.93	49.60	22.92	64.46	14.86	54.46	31.54	Pass
0.194	58.80	49.58	22.96	-1.50	57.30	48.08	21.45	63.86	15.78	53.86	32.40	Pass
0.263	54.60	42.73	20.67	-0.99	53.61	41.74	19.68	61.34	19.60	51.34	31.67	Pass
0.331	48.50	38.38	28.81	-0.73	47.78	37.66	28.08	59.41	21.76	49.41	21.33	Pass
0.335	50.50	40.79	37.43	-0.72	49.78	40.07	36.71	59.32	19.25	49.32	12.61	Pass
3.501	38.80	35.67	34.20	-0.30	38.50	35.37	33.91	56.00	20.63	46.00	12.09	Pass
23.998	34.40	32.50	30.83	-0.43	33.97	32.07	30.40	60.00	27.93	50.00	19.60	Pass

Corrected Emission Level (dBuV) = Uncorrected Reading (dBuV) + Correction Factor (dB)

Margin (dB) = Limit (dBuV) - Corrected Emission Level (dBuV)

Calculations

CF = Correction Factor

Emission Level = Measured Level + correction factor

Margin = Limit - Emission Level

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							ITRONIX A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 57 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

G.10. PASS/FAIL

In reference to the results outlined in H.9 the DUT passes the requirements as stated in the reference standards as follows:

The RF voltage measured in reference to ground on each of the power line conductors does not exceed the limits as outline in FCC 15.207.

The emission measured on Line 1 with the least margin to the limit measured with an AV detector at 3.579 MHz and a margin of 7.59 dB. The emission measured on Line 2 with the least margin to the limit was measured with a QP detector at 150 kHz with a margin of 12.55 dB.

G.11. SIGN-OFF

I attest to the accuracy of the data. All measurements reported herein were performed by me and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements.



Russell Pipe
Senior Compliance Technologist
Celltech Labs Inc.

20Jul05

Date

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 58 of 59

 Testing and Engineering Services Lab	Test Report Serial No.:	042406KBC-T743-E15W	Report Revision No.:	Revision 1.0
	Test Date(s):	04Jul05 - 20Jul05	Report Issue Date:	November 07, 2006
	Test Standard(s):	FCC 47 CFR §15.247	Industry Canada RSS-210 Issue 5	
	Lab Registration(s):	FCC Lab Reg. # 714830	Industry Canada Lab File #3874	

END OF DOCUMENT

Company:	Itronix Corporation	Model:	IX325A860IWLBT	FCC ID:	KBCIX325A860IWLBT	IC ID:	1943A-IX325g
Rugged Tablet PC with Intel PRO2200BG 802.11b/g WLAN Mini-PCI Card & Well Green Internal PIFA Antenna							 A GENERAL DYNAMICS COMPANY
2006 Celltech Labs Inc.	This document is not to be reproduced in whole or in part without the prior written permission of Celltech Labs Inc.						Page 59 of 59