

**Environmental evaluation and exposure limit according to FCC CFR 47part 1,
§1.1307, §1.1310**

The Wireless PIR Detector, model PMD3M are classified as a mobile device. The Wireless PIR Detector includes transmitter operating according to FCC part 15 subpart C section 15.247 (FHSS)

The FCC limit for power density for general population/uncontrolled exposure is $f/1500 \text{ mW/cm}^2$ for 300 – 1500 MHz frequency range:

$$P = 902.25/1500 = 0.6 \text{ mW/cm}^2$$

The power density $P \text{ (mW/cm}^2\text{)} = P_T / 4\pi r^2$

P_T is the transmitted power, which is equal to the peak transmitter output power 10.88 dBm plus maximum antenna gain 0 dBi, the maximum equivalent isotropically radiated power EIRP is

$$P_T = 10.88 \text{ dBm} + 0 \text{ dBi} = 10.88 \text{ dBm} = 12.24 \text{ mW}.$$

The power density at 20 cm (minimum safe distance, required for mobile devices), calculated as follows:

$$\text{Compliance with FCC limit: } 12.24 \text{ mW} / 4\pi (20 \text{ cm})^2 = 0.0024 \text{ mW/cm}^2 \ll 0.6 \text{ mW/cm}^2$$

General public cannot be exposed to dangerous RF level.

Mrs. S. Peysahov Sheynin,
certification specialist, EMC & Radio



EXPERTS IN GLOBAL COMPLIANCE SOLUTIONS



EMC



Radio



Telecom



Environmental



Product
Safety



International
Approvals

Hermon Laboratories Ltd.

POB 23, Binyamina 3055001 Israel

Phone: +972 4 628 8001, Fax: +972 4 628 8277

Email: mail@hermonlabs.com, www.hermonlabs.com