

14 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

14.1 Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

* = Plane-wave equipment power density

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

14.2 Maximum Permissible Exposure (MPE) Evaluation

802.11b Power Table

Frequency (MHz)	Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	18.83	18.83	0.07638	1
2437.00	19.70	19.70	0.09333	1
2462.00	18.64	18.64	0.07311	1

MPE Prediction (802.11b)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	19.70	(dBm)
Maximum peak output power at antenna input terminal:	93.32543008	(mW)
Duty cycle:	100	(%)
Maximum Pav :	93.32543008	(mW)
Antenna gain (typical):	2.98	(dBi)
Maximum antenna gain:	1.986094917	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2437	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.036894	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.036894mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2437MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

802.11g Power Table

Frequency (MHz)	Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	15.44	15.44	0.03500	1
2437.00	18.52	18.52	0.07112	1
2462.00	16.47	16.47	0.04436	1

MPE Prediction (802.11g)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	18.52	(dBm)
Maximum peak output power at antenna input terminal:	71.12135137	(mW)
Duty cycle:	100	(%)
Maximum Pav :	71.12135137	(mW)
Antenna gain (typical):	2.98	(dBi)
Maximum antenna gain:	1.986094917	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2437	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.028116	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.028116mW/cm². This is below the uncontrolled exposure limit of 1mW/cm² at 2437MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

802.11a Power Table

Frequency (MHz)	Reading Power (dBm)	Output Power (dBm)	Output Power (W)	Limit (W)
5745.00	18.58	18.58	0.07211	1
5785.00	18.18	18.18	0.06577	1
5825.00	18.10	18.10	0.06457	1

MPE Prediction (802.11a)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	18.58	(dBm)
Maximum peak output power at antenna input terminal:	72.11074792	(mW)
Duty cycle:	100	(%)
Maximum Pav :	72.11074792	(mW)
Antenna gain (typical):	4.97	(dBi)
Maximum antenna gain:	3.140508694	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5745	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm ²)
Power density at predication frequency at 20 (cm)	0.045077	(mW/cm ²)

Measurement Result

The predicted power density level at 20 cm is 0.045077mW/cm². This is below the uncontrolled exposure limit of 1 mW/cm² at 5745MHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Collocated MPE analysis:

As per KDB447498 D01, if the radio application is composed of the multiple transmitters confining in the host platform, and placing nearby, the simultaneous transmission due to impact of accumulation of individual MPE shall be evaluated if or not given application could conditionally qualify for MPE test exclusion.

Location of the transmitting antennas where they distribute:



Scenario of operation when simultaneous transmission occurs:

Scenario 1:

External Antenna:

Wifi b or g + Bluetooth

Scenario 2:

External Antenna:

Wifi a + Bluetooth

Scenario 3:

Internal Antenna:

Wifi b or g + Bluetooth

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



FCC ID: KDZVM2C01
IC: 1693B-VM2C01

Report No.: EH/2012/A0023

Issue Date: Jan. 21, 2013

Scenario 4:

Internal Antenna:

Wifi a + Bluetooth

Exclusion of test condition:

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 .

MPE ratio1 + MPE ratio2+MPE ratio3 <=1.0

The spreadsheet as FCC deduces, and releases is employed to conduct the measurement:

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Scenario 1:

External Antenna:
Wifi b or g + Bluetooth

Antenna No.		Total	1	2
Tx Status			On	On
Frequency	MHz		2437	2402
MPE Limit	mW/cm ²		1.00	1.00
Max % MPE	%	2.2	2.2	0.0
Power	(W)	0.057	0.055	0.002
Antenna Gain	dBi		2.98	1.20
EIRP	(W)	0.11	0.109	0.002
X	(cm)		6.0	11.5
Y	(cm)		10.0	-1.0
Sector			FALSE	FALSE
Arc			FALSE	FALSE
θ ₁	degs	input	-120	-120
θ ₂			60	60
θ ₁		actual	-120	-120
θ ₂			60	60

MPE = 2.2/100 = 0.022 < 1.0, and therefore maximum MPE generated from individual transmitter can be excluded.

Scenario 2:

External Antenna:
Wifi a + Bluetooth

Antenna No.		Total	1	2
Tx Status			On	On
Frequency	MHz		5260	2402
MPE Limit	mW/cm ²		1.00	1.00
Max % MPE	%	2.1	2.0	0.0
Power	(W)	0.036	0.034	0.002
Antenna Gain	dBi		4.85	1.20
EIRP	(W)	0.10	0.103	0.002
X	(cm)		6.0	11.5
Y	(cm)		10.0	-1.0
Sector			FALSE	FALSE
Arc			FALSE	FALSE
θ ₁	degs	input	-120	-120
θ ₂			60	60
θ ₁		actual	-120	-120
θ ₂			60	60

MPE = 2.1/100 = 0.021 < 1.0, and therefore maximum MPE generated from individual transmitter can be excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Scenario 3:

Internal Antenna:
Wifi b or g + Bluetooth

Antenna No.		Total	1	2
Tx Status			On	On
Frequency	MHz		2437	2402
MPE Limit	mW/cm ²		1.00	1.00
Max % MPE	%	1.7	1.7	0.0
Power	(W)	0.057	0.055	0.002
Antenna Gain	dBi		1.80	1.20
EIRP	(W)	0.08	0.083	0.002
X	(cm)		3.0	11.5
Y	(cm)		8.0	-1.0
Sector			FALSE	FALSE
Arc			FALSE	FALSE
θ_1	degs	input	-120	-120
θ_2			60	60
θ_1		actual	-120	-120
θ_2			60	60

MPE = 1.7/100 = 0.017 < 1.0, and therefore maximum MPE generated from individual transmitter can be excluded.

Scenario 4:

Internal Antenna:
Wifi a + Bluetooth

Antenna No.		Total	1	2
Tx Status			On	On
Frequency	MHz		5260	2402
MPE Limit	mW/cm ²		1.00	1.00
Max % MPE	%	2.1	2.1	0.0
Power	(W)	0.036	0.034	0.002
Antenna Gain	dBi		4.97	1.20
EIRP	(W)	0.11	0.106	0.002
X	(cm)		3.0	11.5
Y	(cm)		8.0	-1.0
Sector			FALSE	FALSE
Arc			FALSE	FALSE
θ_1	degs	input	-120	-120
θ_2			60	60
θ_1		actual	-120	-120
θ_2			60	60

MPE = 2.1/100 = 0.021 < 1.0, and therefore maximum MPE generated from individual transmitter can be excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.