

4 FCC §2.1091 - RF Exposure Information

4.1 Applicable Standards

FCC §2.1091, (a) Requirements of this section are a consequence of Commission responsibilities under the National Environmental Policy Act to evaluate the environmental significance of its actions. See subpart I of part 1 of this chapter, in particular §1.1307(b).

Limits for Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	842/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1	30

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal (dBm):	45.64
Maximum peak output power at antenna input terminal (mW):	36643.75746
Prediction distance (cm):	120
Prediction frequency (MHz):	390.15
Maximum Antenna Gain, typical (dBi):	0
Maximum Antenna Gain (numeric):	1
Power density of prediction frequency at 120 cm (mW/cm ²):	0.2025
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm ²):	0.2601

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>45.38</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>34514.37</u>
<u>Prediction distance (cm):</u>	<u>120</u>
<u>Prediction frequency (MHz):</u>	<u>429.85</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>0</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>1</u>
<u>Power density of prediction frequency at 120 cm (mW/cm²):</u>	<u>0.191</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>0.287</u>

4.3 Conclusion

The device complies with the MPE requirements by providing a safe separation distance of at least 120 cm between the antenna with maximum 0 dBi gain, including any radiating structure, and any persons when normally operated.