

TEST DATA

Test Mode	Battery status	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Probe Position E (V/m)	Probe Position F (V/m)	Limits (V/m)
Mode 1	<1% Battery status	0.15	0.13	0.14	0.10	0.12	0.13	614
Mode 2	50% Battery status	0.12	0.12	0.14	0.10	0.17	0.13	614
Mode 3	99% Battery status	0.13	0.15	0.10	0.21	0.14	0.11	614

E-Field Strength

Test Mode	Battery status	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Probe Position E (A/m)	Probe Position F (A/m)	Limits (A/m)
Mode 1	<1% Battery status	0.389	0.297	0.333	0.186	0.351	0.248	1.63
Mode 2	50% Battery status	0.363	0.299	0.324	0.190	0.345	0.248	1.63
Mode 3	99% Battery status	0.384	0.280	0.343	0.197	0.374	0.325	1.63

H-Field Strength

Remark:

The device meets the mobile RF exposure limit at a 15cm and 20cm separation distance as specified in §2.1091 of the FCC Rules.

All simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

