

EXHIBIT 3

TEST REPORT

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



**FCC PART 15, SUB-PART B
(CLASS II CHANGE)
TEST REPORT**

On
VGA CARD

model
**Gloria Synergy-4
(FCC ID: KJGP2EASY)**

provided for tests by
**ELSA GmbH
Sonnenweg 11
Aachen, 5100 Germany**

tests performed by
**Rockford Engineering Services, Inc.
4750 Williams Wharf Road
St. Leonard, MD 20685-9611
Tel: (301) 855-1375
Fax: (410) 586-1460
Email: documentation@resemc.com**



NVLAP Accredited (Code 200075-0)



FCC PART 15 SUB-PART B (CLASS II CHANGE) TEST REPORT

on

**Gloria Synergy-4
(FCC ID: KJGP2EASY)**

provided for evaluation by

**ELSA GmbH
Sonnenweg 11
Aachen, 5100 Germany**

This report contains 27 pages

All services undertaken are subject to the following general policy: Reports are submitted for exclusive use of the client to whom they are addressed.

Their significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations or surveys made. No quotations in part from reports or use of the RES or NvLAP or VCCI name is permitted except as expressly authorized by RES and/or NvLAP and/or VCCI in writing. It is agreed between RES and the client that no partial distribution of any test data herein or of this report or analysis shall be made to any third party without the prior written consent of all parties. The content of all reports, analysis and tests is strictly confidential. This report is not valid unless copied in full. All parties acknowledge that this report must not be used to claim product endorsement by RES and/or NvLAP and/or VCCI. Reports are maintained on file for a period of five years. Additional copies of reports are available at a nominal fee. In correspondence concerning this report please refer to the date, manufacturer's name and the report number.

**Accepted by the Federal Communications Commission (FCC)
for Declaration of Conformity Testing (Ref: NVLAP Lab Code 200075-0)**

**Certified by the Voluntary Control Council for Interference by
Information Technology Equipment (VCCI) for EMC testing, in accordance with
the Regulations for Voluntary Control Measures, Article 8,
Registration Number R-436 and C-447**

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VCCI Accredited Laboratory



NVLAP Accredited (code 200075-0)

DECLARATION OF CONFORMANCE

(FCC Part 15, SubPart B)

I hereby certify that the measurements taken as referenced by the test number below were made in accordance with the procedures indicated and that the energy emitted by this equipment was found to comply with the FCC Class B limits

I further certify that on the basis of the measurements taken at the Rockford Engineering Services facilities, 4750 Williams Wharf Road, St. Leonard, Maryland 20685-9611, USA ; the equipment tested is capable of operation in compliance with the conditions set forth in the **FCC Rules and Regulations Part 15, SubPart B**. The measurement results are deemed satisfactory evidence of compliance with the technical EMC requirements of the Radio Interference Regulations of the Industry Canada.

Rockford Engineering Services, Incorporated, hereby certifies verification of compliance to applicable FCC/ANSI C63.4-1992 Requirements, both Radiated and Line Conducted.


Manufacturer's Name: ELSA GmbH
Manufacturer's Address: Sonnenweg 11
Aachen, 5100 Germany, USA
Tel: 49(0)241-606-0
Fax: 49(0)241-606-1199


Type of Equipment: VGA Card
Model Number: Gloria Synergy-4

Installed Components: N/a

Test Number: 9803RM012
Test Date(s): March 30 and 31, 1998

Director:


Mr. Bandele Adepoju


Date

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VCEI Accredited Laboratory

TABLE OF CONTENTS

Part 1 General.....	1
1.1 Test Methodology	1
1.1.1 Test Facility	1
1.1.2 Accuracy of Test Data.....	1
1.2 Summary	2
1.2.1 Description of EUT	2
1.2.2 Support Equipment Included in Tests.....	2
1.2.3 Data Justification	3
 Part 2 Powerline Conducted Emissions.....	 4
2.1 Configuration and Procedure	4
2.1.1 EUT Configuration	4
2.1.2 Test Procedure	4
2.1.3 Spectrum Analyzer Configuration	4
2.1.4 Data Table Legend	4
2.2 Powerline Conducted Emissions.....	5
2.2.1 Administrative Details	5
2.2.2 EUT Configuration Summary.....	5
2.2.3 Test Result	5
 Part 3 Open Field Radiated Emissions.....	 6
3.1 Configuration and Procedure.....	6
3.1.1 EUT Configuration.....	6
3.1.2 Test Procedure.....	6
3.1.3 Spectrum Analyzer Configuration	6
3.1.4 Data Table Legend and Field Strength Calculation	7
3.2 Open Field Radiated Emissions.....	8
3.2.1 Administrative Detail.....	8
3.2.2 EUT Configuration Summary	8
3.2.3 Test Result	8

TABLES

1.2.1 Resolution Modes	3
2.2.1 Powerline Conducted Emissions	4
3.2.1 Open Field Radiated Emissions	8

TABLE OF CONTENTS CONTD.

APPENDICES

A:	Measurement Uncertainty.....	10
B:	Measurement Procedures.....	12
C:	Description of Open Field Test Site.....	14
D:	Test Equipment.....	16
E:	Description of Support Equipment.....	18
F:	EUT Specifications.....	22

PART 1 - GENERAL

1.1. TEST METHODOLOGY

The electromagnetic interference tests which this report describes were performed by an independent electromagnetic compatibility consultant, Rockford Engineering Services Inc., in accordance with the FCC test procedure ANSI C63.4-1992.

1.1.1 Test Facility

The open area test site, the conducted measurement facility, and the test equipment used to collect the emissions data is located in St. Leonard, Maryland and is fully described in a report submitted to the FCC Equipment Evaluation Division office in November 1995 and accepted in a letter dated February 15, 1996 (31040/SIT).

1.1.2 Accuracy of Test Data

The test results contained in this report accurately represent the radiated and powerline conducted electromagnetic emissions generated by the sample equipment under test.

Equipment Tested: VGA card

Model(s): Gloria Synergy-4

Date(s) of Test: March 30 and 31, 1998

Test Performed:

1. Powerline conducted emissions in a shielded room utilizing two LISN's in accordance with the FCC test procedure ANSI C63.4-1992. See Part 2 of this report for full details.
2. Radiated emissions in a 3 meter open area site. See Part 3 of this report for full details.

The result show that the sample equipment tested as described in this report is in compliance with the Class B conducted and radiated emission limits of FCC Rules Part 15, SubPart B.

GENERAL CONTD.

1.2. SUMMARY

1.2.1 Description of Equipment Under Test (EUT)

Description: VGA card

Model Name(s): Gloria Synergy-4

Applicant: ELSA GmbH

Address: Sonnenweg 11
Aachen, 5100 Germany
Tel: 49(0)241-606-0
Fax: 49(0)241-606-1199
Email: kd@elsa.de

Client Contact: Mr. Karl-Heinz Dorfler

Test Engineer: Liming Xu

Test Number: 9803RM014

1.2.2 Support Equipment Included in Tests

The VGA Card was installed in a computer that was supported with the following peripherals:

1. Team Technologies Modem, model 103/212A
2. Team Technologies Modem, model 1200AT
3. Hewlett Packard Printer, model 2225C
4. Mitsumi Keyboard, model KPQEA4EA
5. Microsoft Mouse, model IntelliMouse

The VGA card, model Gloria Synergy-4, was supported with the following peripherals:

6. Micron Personal Computer, model KPV-M6PI-MT
7. 3D-Labs Monitor, model GDM-90W01T

A more detailed list is provided in Appendix E.

GENERAL CONTD.

1.2. SUMMARY

1.2.3 Test Data Justification

The card was investigated connected to a monitor via a video cable with no torroid. The following resolution modes were tested:

Resolution	Clock Frequency	Horizontal Frequency	Vertical Frequency	Comments
1920 x 1200	230MHz	94.6KHz	110.0Hz	Non- Interlaced
1600 x 1280	170MHz	93.3KHz	76.0Hz	Non- Interlaced
1280 x 1024	110MHz	48.3KHz	87.1Hz	Interlaced
1024 x 768	68MHz	35.2KHz	87.3Hz	Interlaced
800 x 600	30MHz	35.3KHz	56.4Hz	Non- Interlaced
640 x 480	26.3MHz	31.4KHz	59.0Hz	Non- Interlaced
640 x 200	10MHz	21.3KHz	68.9Hz	Non- Interlaced

Table 1.2.1. Resolution Modes

Please note that additional modes may have been tested but not necessary listed. The 1920 x 1200 resolution mode is representative of the worst case for the tests and is used to provide the recorded radiated data in the tables of this report.

PART 2 - POWERLINE CONDUCTED EMISSIONS

per FCC PART 15 SUB-PART B

2.1. CONFIGURATION AND PROCEDURE

2.1.1 EUT Configuration

The EUT was arranged in a way to maximize emissions within the constraints set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992. The measurement instrumentation used was an IFR A-7550 Receiver with bandwidth parameters as stipulated in ANSI C63.4-1992. The Any excess power cord of the host computer was folded back and forth, on top of a LISN, to form a 30-cm by 40-cm bundle.

2.1.2 Test Procedure

The system was set up as described above, with EMI diagnostic software running the host system in a mode that printed "H"s to the monitor, and sent "H"s to the serial and parallel devices.

2.1.3 Spectrum Analyzer Configuration (during Swept frequency Scans)

Start Frequency	450 KHz
Stop Frequency	30MHz
Sweep Speed	Manual
IF Frequency	30MHz
Video Band Width	30MHz
Quasi Peak Adapter Mode	Normal
Quasi Peak Adapter Bandwidth	9KHz

2.1.4 Data Table Legend And Field Strength Calculation

'Margin' indicates the degree of compliance with the applicable limit. For example, a margin of -8 dB means that the emissions is 8 dB below the limit (in compliance); a margin of +4 dB means that the emission is 4 dB over the limit (out of compliance). The margin is calculated as follows:

Margin = Corrected Amplitude - Limit

where Corrected Amplitude = Amplitude + Cable Loss - Distance Factor


p	=	Peak
q	=	Quasi Peak
a	=	Average

2.2. POWERLINE CONDUCTED EMISSIONS per FCC PART 15 SUB-PART B

2.2.1 Administrative Details

Date(s) of Test: March 30, 1998
Emission Limits: Class B
Test Engineer(s): Liming Xu

Engineer's Signature:



2.2.2 EUT Configuration Summary

The system was set up as described above. The powerline conducted EMI tests were run on all the current carrying conductors of the host computer power cord and also on the peripherals to confirm compliance to FCC limits. Only the results of the host computer are recorded in the following tables. The highest emissions were also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables were moved around to maximize the emissions, and the position of the peripheral devices were interchanged to check for any changes in emissions.

2.2.3 Test Results

The table below shows a summary of the highest conducted emissions on both the hot and neutral current carrying conductors of the computer power cord compared to FCC Class B limits.

CONDUCTOR PHASE	GND	FREQ. (MHz)	AMPL. (dBuV)	LIMIT (dBuV)	MARGIN (dBuV)
Hot	Con	0.45	p 39.00	47.96	-8.96
Hot	Con	1.20	p 37.00	47.96	-10.96
Hot	Con	10.00	p 37.00	47.96	-10.96
Hot	Con	18.00	p 36.00	47.96	-11.96
Hot	Con	23.00	p 36.00	47.96	-11.96
Hot	Con	29.00	p 36.00	47.96	-11.96
Neutral	Con	0.45	p 38.00	47.96	-9.96
Neutral	Con	11.00	p 36.00	47.96	-11.96
Neutral	Con	16.00	p 37.00	47.96	-10.96
Neutral	Con	24.00	p 36.00	47.96	-11.96
Neutral	Con	28.00	p 36.00	47.96	-11.96

Table 2.2.1 Powerline Conducted Emissions

No emissions of significant levels were observed between 450 KHz and the lowest frequencies shown in the above data. No emissions of significant levels were observed between the highest frequencies shown in the above data and 30 MHz.

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



Accredited Laboratory

PART 3 - OPEN FIELD RADIATED EMISSIONS

per FCC PART 15 SUB-PART B

3.1. CONFIGURATION AND PROCEDURE

3.1.1 EUT Configuration

The EUT was arranged in a way to maximize emissions within the constraints set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992. The measurement instrumentation used was a Hewlett Packard 8566B Spectrum Analyzer with detector and bandwidth parameters as stipulated in C63.4-1992. At frequencies above 1GHz, measurements were made using the video filter method. Quasi peak detector and preselector functions were disabled.

3.1.2 Test Procedure

The system was set up as described above, with EMI diagnostic software running the host system in a mode that printed "H"s to the monitor, and sent "H"s to the serial and parallel devices. Unless stated otherwise the following the antenna to EUT distance was 3 meters. For any measurements of frequencies above 1GHz, tests were performed at a distance of one meter at an indoor site.

3.1.3 Spectrum Analyzer Configuration (during Swept frequency Scans)

Start Frequency 30MHz
 Stop Frequency 2000MHz
 Sweep Speed Manual

Measurements Below 1GHz

RES Bandwidth..... 100KHz
 Video Band Width 100KHz
 Quasi Peak Adapter Mode Normal
 Quasi Peak Adapter Bandwidth..... 120KHz

Measurements Above 1GHz (unless otherwise stated)

Analyzer mode Video Filter
 RES Bandwidth..... 1MHz
 Video Band Width 10Hz
 Frequency Span..... 7MHz
 Offset..... 0dB
 Sweep Time Auto
 Quasi Peak Adapter Bandwidth..... Disabled

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



3.1. CONFIGURATION AND PROCEDURE CONTD.

3.1.4 Data Table Legend and Field Strength Calculation

'Margin' indicates the degree of compliance with the applicable limit. For example, a margin of -8 dB means that the emissions is 8 dB below the limit (in compliance); a margin of +4 dB means that the emission is 4 dB over the limit (out of compliance). The margin calculated as follows:

Margin = Corrected Amplitude - Limit

where Corrected Amplitude = Amplitude + Antenna Correction Factor + Cable Loss - Distance Factor

p = Peak

q = Quasi Peak


a = Average

3.2. OPEN FIELD RADIATED EMISSIONS per FCC PART 15 SUB-PART B

3.2.1 Administrative Details

Date(s) of Test: March 31, 1998
Emission Limits: Class B
Test Engineer(s): Liming Xu
Antenna Used: Biconical Antenna, EMCO, model # 3104, S/N 8901-3885,
 Log Periodic Antenna, model # 3146, S/N 2261 and
 Horn Antenna, model # 3115, S/N. 8812-3050.
 (All calibrated July 3, 1997)

Engineer's Signature:



3.2.2 EUT Configuration Summary

The highest emissions were analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables were moved around to maximize the emissions, and the position of the peripheral devices were interchanged to check for any changes in emissions.

3.2.3 Test Results

The table below shows a summary of the highest amplitudes of the radiated emissions from the equipment under test at various antenna heights, antenna polarizations, and EUT orientations.

ANTENNA		FREQ.	AMPL.	CORRECTION		FACT.	CORR	FCC-A	FCC-B	
TYPE	POLAR	(MHz)	(dBuV)	ANT	CBL	DIST.	AMPL	LIMIT	MARG	LIMIT
							(dBuV)	(dBuV)	dB	(dBuV)
Bicon	Horiz	191.30	13.20	p	16.91	5.20	0.00	35.31	-18.67	43.52
Bicon	Horiz	192.00	15.20	p	17.08	5.20	0.00	37.48	-16.50	43.52
Log P	Horiz	213.80	21.10	p	12.15	5.06	0.00	38.31	-15.67	43.52
Log P	Horiz	225.00	21.40	p	11.95	4.95	0.00	38.30	-18.60	46.00
Log P	Horiz	236.30	12.80	p	12.25	4.84	0.00	29.89	-27.01	46.00
Log P	Horiz	325.90	19.30	p	15.08	3.94	0.00	38.32	-18.58	46.00
Log P	Horiz	364.30	18.00	p	15.54	3.56	0.00	37.10	-19.80	46.00
Log P	Vert	213.80	21.90	p	11.79	5.06	0.00	38.75	-15.23	43.52
Log P	Vert	225.00	20.70	p	11.80	4.95	0.00	37.45	-19.45	46.00
Log P	Vert	325.90	15.20	p	14.90	3.94	0.00	34.04	-22.86	46.00
Log P	Vert	364.30	14.00	p	15.54	3.56	0.00	33.10	-23.80	46.00

Table 3.2.1 Open Field Radiated Emissions

No emissions of significant levels were observed between 30 MHz and the lowest frequencies shown in the above data. No emissions of significant levels were observed between the highest frequency shown in the above data and 2000MHz.

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VCEI Accredited Laboratory

APPENDIX A

MEASUREMENT UNCERTAINTY

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



Accredited Laboratory

MEASUREMENT UNCERTAINTY

Verification of test results and tests for accuracy of measurements may be performed if:

- The tests results are marginal to the specific limit
- The tests results are inconsistent with the results obtained from another location
- The test results are inconsistent with the test results from an earlier test

$$\bar{x} - kS_n \leq L$$

Compliance is achieved when the following relationship is met:

$$\text{Measurement Uncertainty Number} = (\bar{x} - kS_n) \div 2$$

Compliance is maintained when the measured quantity maintains a tolerance less than the square root of the measurement acceptance number:

$$\text{Measurement Acceptance Number} = L - (\bar{x} - kS_n)$$

$\bar{X}$ = the arithmetic mean of the measured value of n measurements at the measurement of concern.

S_n = the standard deviation of test, where:

$$S_n^2 = \frac{1}{n-1} * \sum (x - \bar{x})^2$$

x = the disturbance level of a single measurement at the frequency of concern.

L = the appropriate limit

K = factor derived from the tables of the non-central t-distribution chart in ETR028 which ensures with 95% confidence that 95% or more of the total measurement value exceeds the minimum value of insertion loss. The value of k depends on the sample measurement size n and is stated below.

(The quantities x , $\bar{x}$, S_n and L are expressed logarithmically [dB].)

$$n = 3$$

$$k = 2.04$$

APPENDIX B

MEASUREMENT PROCEDURES

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



APPENDIX C

DESCRIPTION OF OPEN FIELD TEST SITE

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VEI Accredited Laboratory

DESCRIPTION OF OPEN FIELD TEST SITE

The tests were conducted at the Maryland facility of Rockford Engineering Services, located on a 25 acre parcel, in the agriculturally zoned section of the city of St. Leonard, Maryland. The site is located west of William's Wharf Road. The west, north and south ends of the site are bordered by farm land.

Supporting structures used to support device being measured and test instrumentation include the following:

- a. Test Platform measuring 17.5 ft by 26 ft. The platform is provided with ground screen, to enhance a homogenous reflective surface.
- b. Test Site building measures approx. 1200 Sq. ft. This building houses the test laboratory, the shielded room, for performing Line Conducted test, test personnel and other support staff. The test building is an all wooden building, constructed using 2 by 4 inch studs. It also contains all necessary electrical wiring and utilities.

The Rockford Engineering Services RFI test site described above is primarily used for conducting contract work for client companies following the procedures stated in FCC/OST MP-4 (1987) or ANSI C63.4-1992, and other regulatory agencies. The site attenuation characteristics are routinely measured and recorded every three months.

Complete description and measurement data are on file at the test laboratory and are available for review by request.

APPENDIX D

TEST EQUIPMENT

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



APPENDIX E

DESCRIPTION OF SUPPORT EQUIPMENT

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VEI Accredited Laboratory

DETAILS/DESCRIPTION OF SUPPORT EQUIPMENT CONTD.**SUPPORT EQUIPMENT #4**

Description	Modem #2
Manufacturer	Team Technologies, Inc.
Model	1200AT
Trade Name	SmartTeam
Part Number	Not Provided
Serial Number	AT123014
Power Supply Type	AC-to-AC Xfmr. (2-prong. wall mounting type), model # DV1215A
Power Cord	Non-Shielded (Detachable)
Data Cable	Shielded with Metal Hood Connector
	Detachable, 1m long
FCC ID	EF56A51200AT

SUPPORT EQUIPMENT #5

Description	Printer
Manufacturer	Hewlett Packard
Model Name	2225C
Trade Name	Not Provided
Part Number	Not Provided
Serial Number	2712540435
Power Supply Type	Linear Adapter
Power Cord	Not Shielded, Non-Detachable
Data Cable	Shielded with Metal Hood Connector
	Detachable, 1m long
FCC ID	DSI6XU2225

SUPPORT EQUIPMENT #6

Description	Keyboard
Grantee Name	Mitsumi Elec. Co., LTD
Trade Name	Not Provided
Model Name	KPQEA4EA
Part Number	Not Provided
Serial Number	Not Provided
Power Supply Type	From Computer
Power Cord	N/A
Data Cable	Shielded with Metal Hood Connector, Non-Detachable
FCC ID	CMYKPQ6987

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



DETAILS/DESCRIPTION OF SUPPORT EQUIPMENT CONTD.**SUPPORT EQUIPMENT #7**

Description	Mouse
Manufacturer	Microsoft
Model Name	IntelliMouse
Trade Name	IntelliMouse 1.1A
Part Number	92658
Serial Number	00715394
Power Supply Type	From Computer
Power Cord	N/A
Data Cable	Non-Shielded, but with Metal Hood Connector
	Non-Detachable
FCC ID	C3KKMP5

Tested and Evaluated by Rockford Engineering Services, Incorporated

NVLAP Accredited (Code 200075-0)



APPENDIX F

EUT TECHNICAL DESCRIPTION

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)



EUT TECHNICAL DESCRIPTION

Description	Video Card
Manufacturer	ELSA, GmbH
Model/Trade Name	Gloria Synergy-4
Serial Number	6166300011
Compatibility	PCI/VGA
Number of Layers	Multi-Layer
Dimensions	120mm x 180mm
Proprietary Slots	None
Processor Type	Texas Instruments, Permedia 2, Model P4020GFN
Co-Processor Type	N/a
Crystal(s)	14.318MHz
Oscillator(s)	None
Headers/Connectors	1) 15-pin D-Sub Connector 2) PCI Card-Edge Connector 3) 40-pin Connector (Feature) 4) 26-pin Connector (Feature) 5) One SGRAM Socket for Memory
Power Supply	From Host Computer
Power Supply Type	N/a
Power Cord(s)	N/a
Data Cable(s)	Shielded with metal connector hoods. No Ferrite Core on Cable. (1 meter length used during tests)

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VEI Accredited Laboratory

TEST EQUIPMENT

Some or all of the following test equipment is currently used to measure the conducted and/or radiated emissions from the equipment under test:

TEST EQUIPMENT	MODEL	S/N
Spectrum Analyzer	IFR A-7550	2469
Spectrum Analyzer	H/P 8590A	310761
Spectrum Analyzer	H/P 8568B	2841A04315
Spectrum Analyzer	H/P 8566B0	218A02909
Quasi Peak Adapter	H/P 85650A	2811A01169
Preselector	H/P 85685A	2724A00536
Pre-Amp. (OPT H64)	H/P 8447F	2805A02491
Sniffer Probe	H/P 11940A	N/A
Close Field Probe	EMCO 7405	N/A
Signal Generator	H/P 8656b	262A04271
Antenna Cable (OPTK45)	H/P 85685A	N/A
Biconical Antenna (<200 MHz)	EMCO 3104	8901-3885
Log Periodic Antenna (200 MHz - 1 GHz)	EMCO 3146	2261
Adj. Element Dipole Antenna (28 MHz - 1GHz)	EMCO 3120	140
Active Loop Antenna	EMCO 6502	1071-1001
Double Rigid Guide (Horn: 1 GHz - 18 GHz)	EMCO 3115	8812-3050
LISN (25 Amp.)	EMCO 38825/2	8901-1447
Remote Controlled	RES RT6	N/A
Rotating Table	RES RT7	N/A
Remote Controlled	RES AM8	N/A
Antenna Mast	RES AM9	N/A

All measurement instrumentation calibration is traceable to the United States National Institute of Standards and Technology (NIST). Supporting documentation relative is on file and is available for examination upon request.

The Hewlett Packard (H/P) 8566B spectrum analyzer system are self-calibrated before use every day calibrated to NIST standards annually. They are scheduled for the next annual calibration to NIST standards in July of 1998. All other EMI equipment is calibrated on a monthly basis using the spectrum analyzer as standard.

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VEI Accredited Laboratory

MEASUREMENT PROCEDURES

POWERLINE CONDUCTED EMISSIONS

The measurements are performed in a 21' x 14' x 9' shielded room. A wooden bench 80 cm in height is located at the center of the shielded room; desktop EUT are placed on top of this bench. The rear of the EUT and bench are placed 40 cm from the shielded room wall. All items on the table (or test-table) are placed at least 10 cm apart. Excess EUT power cord is folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately in the middle between the ground plane and table. The EUT power cord is plugged into a LISN 80 cm away, while all other devices are plugged into a second LISN, also 80 cm away from the closest part of the EUT.

The highest emissions are also analyzed in detail by operating the spectrum analyzer in fixed tuned mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables are moved around to maximize the emissions, and the position of the peripheral devices are interchanged to check for any changes in emissions.

RADIATED EMISSIONS

The EUT is set up in accordance with the suggested configuration given in FCC Measurement Procedure ANSI C63.4-1992.

The EUT is set up on the turntable of an open field site. Desktop EUT are set up on a wooden stand (test table), 80 cm above the ground plane. All items on the table are placed at least 10 cm apart. Interconnecting cables which hang closer than 40 cm to the ground plane are folded back and forth to form a 30 cm by 40 cm long bundle, hanging approximately between the ground plane and table.

The highest emissions are also analyzed, in detail, by operating the spectrum analyzer in fixed tuned quasi-peak mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables are moved around and at the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings. The position of the peripheral devices are interchanged to check for any changes in emissions.

DETAILS/DESCRIPTION OF SUPPORT EQUIPMENT**SUPPORT EQUIPMENT #1**

Description	Mini Tower Personal Computer
Manufacturer	Micron Electronics, Inc.
Model	KPV-M6PI-MT
Trade Name	Not Provided
Part Number	Not Provided
Serial Number	Not Provided
Power Supply Type	200W, Closed Frame, Switching
Power Cord	Non-Shielded, Detachable
Data Cable	Shielded with Metal Hood Connector, 1m long
FCC ID	KPV-M6PI-MT

SUPPORT EQUIPMENT #2

Description	Monitor
Manufacturer	3D-Labs
Model	GDM-90W01T
Trade Name	Professional 3D
Part Number	Not Provided
Serial Number	2000799
Power Supply Type	Switching
Power Cord	Shielded, Detachable
Data Cable	Shielded with Metal Hood Connectors. Detachable, 1m long. NO FERRITE CORE ON CABLE. (Cable was replaced with one without ferrite core for tests.)
FCC ID	AK8GDMW900TC

SUPPORT EQUIPMENT #3

Description	Modem #1
Manufacturer	Team Technologies, Inc.
Model	103/212A
Trade Name	SmartTeam
Part Number	Not Provided
Serial Number	A038610
Power Supply Type	AC-to-AC Xfmr. (2-prong. wall mounting type), model DV1215A
Power Cord	Non-Shielded (Detachable)
Data Cable	Shielded with Metal Hood Connector Detachable, 1m long
FCC ID	EF56A5103/212A

Tested and Evaluated by Rockford Engineering Services, Incorporated



NVLAP Accredited (Code 200075-0)

VCEI Accredited Laboratory