

INSTRUCTIONS / NOTES		
1	DIMENSION	3.00" (W) X 1.50" (H); SHARP RADIUS
2	MATERIAL	GE: 8B35, LEXAN, 7 MIL THICK, TEXTURED SURFACE
3	ADHESIVE	3M: 468 MP, 5 MIL ADHESIVE, APPLY TO BACK SIDE
4	BKGND FLOOD	COLOR: WHITE
5	LOGO/TEXT	COLOR: BLACK



TT – TensiTrak

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



2.7 - 4.8V \equiv 300mA Max

ARBN
090 007 962

IC: 2213A-2020

FCC ID: KKG2020


Complies with IEC 61010-1
12kHz Frequency



800-288-3610 or 425-251-0559
www.digitrak.com
450-0055-00-A





TITLEBLOCK: SIZE 8.5X11 (LETTER)	MD		11-02-11		INITIAL RELEASE FOR PRODUCTION					A					
	BY		DATE		DESCRIPTION							REV			
THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON THE UNDERSTANDING THAT IT IS NOT SHOWN TO OTHER PERSONS OR COMPANIES WITHOUT WRITTEN CONSENT OF DIGITAL CONTROL INCORPORATED	APPROVAL		AH		TOLERANCES (STANDARD UNITS UNLESS OTHERWISE SPECIFIED)				 DIGITAL CONTROL INCORPORATED			TITLE DIGITRAK TT, ECLIPSE TRANSMITTER LABEL		SHEET 1 / 1	
	APPROVAL		JP									REV			
	DRAFTER		MD		DECIMAL .X ±.030 FRACTIONS ±1/32 .XX ±.010 .XXX ±.005 ANGLES ± 1°				19625 62ND AVE SOUTH, SUITE B103 KENT, WA 98032, WWW.DIGITRAK.COM 425-251-0701 · 425-251-0702 FAX			DRAWING NO. 450-0055-00		REV A	
	ENGINEER		MD									REV			